


# Freefem++

Third Edition, Version 3.11-1

<http://www.freefem.org/ff++>

F. Hecht



Laboratoire Jacques-Louis Lions, Université Pierre et Marie Curie, Paris



# FreeFem++

Third Edition, Version 3.11-1

<http://www.freefem.org/ff++>

Frédéric Hecht<sup>1,4</sup>

<mailto:frederic.hecht@upmc.fr>

<http://www.ann.jussieu.fr/~hecht>

In collaboration with:

- **Olivier Pironneau**, <mailto:olivier.pironneau@upmc.fr>, <http://www.ann.jussieu.fr/pironneau> Olivier Pironneau is a professor of numerical analysis at the university of Paris VI and at LJLL. His scientific contributions are in numerical methods for fluids. He is a member of the Institut Universitaire de France and of the French Academy of Sciences
- **Jacques Morice**, <mailto:morice@ann.jussieu.fr>. Jacques Morice is a Post-Doct at LJLL. His doing is Thesis in University of Bordeaux I on fast multipole method (FMM). In this version, he do all three dimensions mesh generation and coupling with medit software.
- **Antoine Le Hyaric**, <mailto:lehyaric@ann.jussieu.fr>, <http://www.ann.jussieu.fr/~lehyaric/> Antoine Le Hyaric is a research engineer from the "Centre National de la Recherche Scientifique" (CNRS) at LJLL . He is an expert in software engineering for scientific applications. He has applied his skills mainly to electromagnetics simulation, parallel computing and three-dimensional visualization.
- **Kohji Ohtsuka**, <mailto:ohtsuka@hkg.ac.jp>, <http://www.comfos.org/> Kohji Ohtsuka is a professor at the Hiroshima Kokusai Gakuin University, Japan and chairman of the World Scientific and Engineering academy and Society, Japan chapter. His research is in fracture dynamics, modeling and computing.



**Acknowledgments** We are very grateful to l'École Polytechnique (Palaiseau, France) for printing the second edition of this manual (<http://www.polytechnique.fr> ), and to l'Agence Nationale de la Recherche (Paris, France) for funding of the extension of FreeFem++ to a parallel tridimensional version (<http://www.agence-nationale-recherche.fr>) Référence : ANR-07-CIS7-002-01.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Installation . . . . .	2
1.1.1	For everyone: . . . . .	2
1.1.2	For the pros: Installation from sources . . . . .	3
1.2	How to use FreeFem++ . . . . .	8
1.3	Environment variables, and the init file . . . . .	8
1.4	History . . . . .	9
<b>2</b>	<b>Getting Started</b>	<b>11</b>
2.0.1	FEM by FreeFem++ : how does it work? . . . . .	12
2.0.2	Some Features of FreeFem++ . . . . .	16
2.1	The Development Cycle: Edit–Run/Visualize–Revise . . . . .	16
<b>3</b>	<b>Learning by Examples</b>	<b>19</b>
3.1	Membranes . . . . .	19
3.2	Heat Exchanger . . . . .	24
3.3	Acoustics . . . . .	26
3.4	Thermal Conduction . . . . .	28
3.4.1	Axisymmetry: 3D Rod with circular section . . . . .	29
3.4.2	A Nonlinear Problem : Radiation . . . . .	30
3.5	Irrotational Fan Blade Flow and Thermal effects . . . . .	30
3.5.1	Heat Convection around the airfoil . . . . .	32
3.6	Pure Convection : The Rotating Hill . . . . .	33
3.7	A Projection Algorithm for the Navier-Stokes equations . . . . .	37
3.8	The System of elasticity . . . . .	39
3.9	The System of Stokes for Fluids . . . . .	41
3.10	A Large Fluid Problem . . . . .	43
3.11	An Example with Complex Numbers . . . . .	46
3.12	Optimal Control . . . . .	47
3.13	A Flow with Shocks . . . . .	49
3.14	Classification of the equations . . . . .	51
<b>4</b>	<b>Syntax</b>	<b>55</b>
4.1	Data Types . . . . .	55
4.2	List of major types . . . . .	56
4.3	Global Variables . . . . .	57
4.4	System Commands . . . . .	58

4.5	Arithmetics . . . . .	58
4.6	Functions of one Variable . . . . .	61
4.7	Functions of two Variables . . . . .	63
4.7.1	Formula . . . . .	63
4.7.2	FE-functions . . . . .	63
4.8	Arrays . . . . .	64
4.8.1	Arrays with two integer indices versus matrices . . . . .	70
4.8.2	Matrix construction and setting . . . . .	71
4.8.3	Matrix Operations . . . . .	72
4.8.4	Other arrays . . . . .	76
4.9	Loops . . . . .	77
4.10	Input/Output . . . . .	78
4.10.1	Script arguments . . . . .	79
4.11	preprocessor . . . . .	79
4.12	Exception handling . . . . .	81
<b>5</b>	<b>Mesh Generation</b>	<b>85</b>
5.1	Commands for Mesh Generation . . . . .	85
5.1.1	Square . . . . .	85
5.1.2	Border . . . . .	86
5.1.3	Data Structures and Read/Write Statements for a Mesh . . . . .	89
5.1.4	Mesh Connectivity . . . . .	91
5.1.5	The keyword "triangulate" . . . . .	94
5.2	Boundary FEM Spaces Built as Empty Meshes . . . . .	95
5.3	Remeshing . . . . .	96
5.3.1	Movemesh . . . . .	96
5.4	Regular Triangulation: hTriangle . . . . .	98
5.5	Adaptmesh . . . . .	98
5.6	Trunc . . . . .	103
5.7	Splitmesh . . . . .	104
5.8	Meshing Examples . . . . .	104
5.9	How to change the label of elements and border elements of a mesh in FreeFem++ ?	110
5.10	Mesh in three dimensions . . . . .	111
5.10.1	Read/Write Statements for a Mesh in 3D . . . . .	111
5.10.2	TeGen: A tetrahedral mesh generator . . . . .	111
5.10.3	Reconstruct/Refine a three dimensional mesh with TetGen . . . . .	115
5.10.4	Moving mesh in three dimensions . . . . .	117
5.10.5	Layer mesh . . . . .	117
5.11	Meshing examples . . . . .	122
5.11.1	Build a 3d mesh of a cube with a balloon . . . . .	124
5.12	The output solution formats .sol and .solb . . . . .	125
5.13	medit . . . . .	127
5.14	Mshmet . . . . .	130
5.15	FreeYams . . . . .	132
5.16	mmg3d . . . . .	134
5.17	A first 3d isotope mesh adaptation process . . . . .	137

<b>6</b>	<b>Finite Elements</b>	<b>139</b>
6.1	Use of “fespace” in 2d . . . . .	141
6.2	Use of fespace in 3d . . . . .	142
6.3	Lagrangian Finite Elements . . . . .	143
6.3.1	P0-element . . . . .	143
6.3.2	P1-element . . . . .	143
6.3.3	P2-element . . . . .	144
6.4	P1 Nonconforming Element . . . . .	145
6.5	Other FE-space . . . . .	146
6.6	Vector valued FE-function . . . . .	147
6.6.1	Raviart-Thomas element . . . . .	147
6.7	A Fast Finite Element Interpolator . . . . .	149
6.8	Keywords: Problem and Solve . . . . .	151
6.8.1	Weak form and Boundary Condition . . . . .	151
6.9	Parameters affecting solve and problem . . . . .	153
6.10	Problem definition . . . . .	154
6.11	Numerical Integration . . . . .	155
6.12	Variational Form, Sparse Matrix, PDE Data Vector . . . . .	158
6.13	Interpolation matrix . . . . .	162
6.14	Finite elements connectivity . . . . .	163
<b>7</b>	<b>Visualization</b>	<b>165</b>
7.1	Plot . . . . .	165
7.2	link with gnuplot . . . . .	169
7.3	link with medit . . . . .	169
<b>8</b>	<b>Algorithms</b>	<b>171</b>
8.1	conjugate Gradient/GMRES . . . . .	171
8.2	Optimization . . . . .	174
<b>9</b>	<b>Mathematical Models</b>	<b>175</b>
9.1	Static Problems . . . . .	175
9.1.1	Soap Film . . . . .	175
9.1.2	Electrostatics . . . . .	177
9.1.3	Aerodynamics . . . . .	179
9.1.4	Error estimation . . . . .	181
9.1.5	Periodic Boundary Conditions . . . . .	182
9.1.6	Poisson Problems with mixed boundary condition . . . . .	185
9.1.7	Poisson with mixte finite element . . . . .	187
9.1.8	Metric Adaptation and residual error indicator . . . . .	188
9.1.9	Adaptation using residual error indicator . . . . .	190
9.2	Elasticity . . . . .	192
9.2.1	Fracture Mechanics . . . . .	195
9.3	Nonlinear Static Problems . . . . .	199
9.3.1	Newton-Raphson algorithm . . . . .	200
9.4	Eigenvalue Problems . . . . .	201
9.5	Evolution Problems . . . . .	204

9.5.1	Mathematical Theory on Time Difference Approximations. . . . .	206
9.5.2	Convection . . . . .	208
9.5.3	2D Black-Scholes equation for an European Put option . . . . .	210
9.6	Navier-Stokes Equation . . . . .	211
9.6.1	Stokes and Navier-Stokes . . . . .	211
9.6.2	Uzawa Algorithm and Conjugate Gradients . . . . .	216
9.6.3	NSUzawaCahouetChabart.edp . . . . .	217
9.7	Variational inequality . . . . .	219
9.8	Domain decomposition . . . . .	221
9.8.1	Schwarz Overlap Scheme . . . . .	221
9.8.2	Schwarz non Overlap Scheme . . . . .	223
9.8.3	Schwarz-gc.edp . . . . .	225
9.9	Fluid/Structures Coupled Problem . . . . .	227
9.10	Transmission Problem . . . . .	229
9.11	Free Boundary Problem . . . . .	233
9.12	Non linear Elasticity (nolinear-elas.edp) . . . . .	235
9.13	Compressible Neo-Hookean Materials: Computational Solutions . . . . .	239
9.13.1	Notation . . . . .	239
9.13.2	A Neo-Hookean Compressible Material . . . . .	239
9.13.3	An Approach to Implementation in FreeFem++ . . . . .	240
<b>10</b>	<b>MPI Parallel version</b>	<b>243</b>
10.1	MPI keywords . . . . .	243
10.2	MPI constants . . . . .	243
10.3	MPI Constructor . . . . .	243
10.4	MPI functions . . . . .	244
10.5	MPI communicator operator . . . . .	244
10.6	Schwarz example in parallel . . . . .	245
10.6.1	True parallel Schwarz example . . . . .	247
<b>11</b>	<b>Parallel sparse solvers</b>	<b>253</b>
11.1	Using parallel sparse solvers in FreeFem++ . . . . .	253
11.2	Sparse direct solver . . . . .	256
11.2.1	MUMPS solver . . . . .	256
11.2.2	SuperLU distributed solver . . . . .	259
11.2.3	Pastix solver . . . . .	261
11.3	Parallel sparse iterative solver . . . . .	262
11.3.1	pARMS solver . . . . .	263
11.3.2	Interfacing with HIPS . . . . .	265
11.3.3	Interfacing with HYPRE . . . . .	269
11.3.4	Conclusion . . . . .	272
11.4	Domain decomposition . . . . .	272
11.4.1	Communicators and groups . . . . .	275
11.4.2	Process . . . . .	276
11.4.3	Points to Points communicators . . . . .	276
11.4.4	Global operations . . . . .	276



<b>12 Mesh Files</b>	<b>281</b>
12.1 File mesh data structure . . . . .	281
12.2 bb File type for Store Solutions . . . . .	282
12.3 BB File Type for Store Solutions . . . . .	282
12.4 Metric File . . . . .	283
12.5 List of AM.FMT, AMDBA Meshes . . . . .	283
<b>13 Addition of a new finite element</b>	<b>287</b>
13.1 Some notations . . . . .	287
13.2 Which class to add? . . . . .	288
<b>A Table of Notations</b>	<b>293</b>
A.1 Generalities . . . . .	293
A.2 Sets, Mappings, Matrices, Vectors . . . . .	293
A.3 Numbers . . . . .	294
A.4 Differential Calculus . . . . .	294
A.5 Meshes . . . . .	295
A.6 Finite Element Spaces . . . . .	295
<b>B Grammar</b>	<b>297</b>
B.1 The bison grammar . . . . .	297
B.2 The Types of the languages, and cast . . . . .	301
B.3 All the operators . . . . .	301
<b>C Dynamical link</b>	<b>307</b>
C.1 A first example myfunction.cpp . . . . .	307
C.2 Example: Discrete Fast Fourier Transform . . . . .	310
C.3 Load Module for Dervieux' P0-P1 Finite Volume Method . . . . .	312
C.4 More on Adding a new finite element . . . . .	315
C.5 Add a new sparse solver . . . . .	318
<b>D Keywords</b>	<b>329</b>



# Preface

ॐ पूर्णमदः पूर्णमिदं पूर्णात् पूर्णमुदच्यते ।  
पूर्णस्य पूर्णमादाय पूर्णमेवावशिष्यते ॥  
ॐ शान्तिः शान्तिः शान्तिः ॥

Fruit of a long maturing process, freefem, in its last avatar, FreeFem++, is a high level integrated development environment (IDE) for numerically solving partial differential equations (PDE). It is the ideal tool for teaching the finite element method but it is also perfect for research to quickly test new ideas or multi-physics and complex applications.

FreeFem++ has an advanced automatic mesh generator, capable of a posteriori mesh adaptation; it has a general purpose elliptic solver interfaced with fast algorithms such as the multi-frontal method UMFPACK, SuperLU . Hyperbolic and parabolic problems are solved by iterative algorithms prescribed by the user with the high level language of FreeFem++. It has several triangular finite elements, including discontinuous elements. Finally everything is there in FreeFem++ to prepare research quality reports: color display online with zooming and other features and postscript printouts.

This manual is meant for students at Master level, for researchers at any level, and for engineers (including financial engineering) with some understanding of variational methods for partial differential equations.



# Chapter 1

## Introduction

A partial differential equation is a relation between a function of several variables and its (partial) derivatives. Many problems in physics, engineering, mathematics and even banking are modeled by one or several partial differential equations.

**FreeFem++** is a software to solve these equations numerically. As its name implies, it is a free software (see the copyrights for full detail) based on the Finite Element Method; it is not a package, it is an integrated product with its own high level programming language. This software runs on all UNIX OS (with g++ 3.3 or later, and X11R6) , on Window 2000, NT, XP, Vista and 7 and on MacOS 10 (powerpc, intel)

Moreover **FreeFem++** is highly adaptive. Many phenomena involve several coupled systems, for example: fluid-structure interactions, Lorentz forces for aluminium casting and ocean-atmosphere problems are three such systems. These require different finite element approximations and polynomial degrees, possibly on different meshes. Some algorithms like Schwarz' domain decomposition method also require data interpolation on multiple meshes within one program. **FreeFem++** can handle these difficulties, i.e. *arbitrary finite element spaces on arbitrary unstructured and adapted bi-dimensional meshes*.

The characteristics of **FreeFem++** are:

- Problem description (real or complex valued) by their variational formulations, with access to the internal vectors and matrices if needed.
- Multi-variables, multi-equations, bi-dimensional and three-dimensional static or time dependent, linear or nonlinear coupled systems; however the user is required to describe the iterative procedures which reduce the problem to a set of linear problems.
- Easy geometric input by analytic description of boundaries by pieces; however this part is not a CAD system; for instance when two boundaries intersect, the user must specify the intersection points.
- Automatic mesh generator, based on the Delaunay-Voronoi algorithm; the inner point density is proportional to the density of points on the boundaries [7].

- Metric-based anisotropic mesh adaptation. The metric can be computed automatically from the Hessian of any FreeFem++ function [9].
- High level user friendly typed input language with an algebra of analytic and finite element functions.
- Multiple finite element meshes within one application with automatic interpolation of data on different meshes and possible storage of the interpolation matrices.
- A large variety of triangular finite elements : linear, quadratic Lagrangian elements and more, discontinuous P1 and Raviart-Thomas elements, elements of a non-scalar type, the mini-element,... (but no quadrangles).
- Tools to define discontinuous Galerkin finite element formulations P0, P1dc, P2dc and keywords: `jump`, `mean`, `intalledges`.
- A large variety of linear direct and iterative solvers (LU, Cholesky, Crout, CG, GMRES, UMFPACK) and eigenvalue and eigenvector solvers.
- Near optimal execution speed (compared with compiled C++ implementations programmed directly).
- Online graphics, generation of `.txt`, `.eps`, `.gnu`, `mesh` files for further manipulations of input and output data.
- Many examples and tutorials: elliptic, parabolic and hyperbolic problems, Navier-Stokes flows, elasticity, Fluid structure interactions, Schwarz's domain decomposition method, eigenvalue problem, residual error indicator, ...
- A parallel version using `mpi`

## 1.1 Installation

### 1.1.1 For everyone:

First open the following web page

<http://www.freefem.org/ff++/>

And choose your platform: Linux, Windows, MacOS X, or go to the end of the page to get the full list of downloads.

**Remark 1** : *Binaries are available for Microsoft Windows, Apple Mac OS X and some Linux systems.*

Install by double click on the appropriate file.

**Windows binaries install** First download the windows installation executable, then double click it. to install FreeFem++. In most cases just answer yes (or typr return) to all questions. Otherwise in the Additional Task windows, check the box "Add application directory to your system path your system path." This is required otherwise the program `ffglut.exe` will not be found. By now you should have two new icons on your desktop:

- FreeFem++ (VERSION).exe the FreeFem++ application.
- FreeFem++ (VERSION) Examples a link to the FreeFem++ folder of examples.

where (VERSION) is the version of the files (for example 3.3-0-P4).

By default, the installed files are in

`C:\Programs Files\FreeFem++`

In this directory, you have all the .dll files and other applications: `FreeFem++-nw.exe`, `ffglut.exe`, ... the FreeFem++ application without graphic windows.

The syntax for the command-line tools are the same as those of FreeFem.exe.

**MacOS X binaries install** Download the MacOS X binary version file, extract all the files with a double click on the icon of the file, go the the directory and put the `FreeFem+.app` application in the /Applications directory. If you want a terminal access to FreeFem++ just copy the file FreeFem++ in a directory of your \$PATH shell environment variable.

If you want to automatically launch the `FreeFem+.app`, double click on a .edp file icon. Under the finder pick a .edp in directory `examples++-tutorial` for example, select menu File -> Get Info an change Open with: (choose `FreeFem++.app`) and click on button change All....

**Where to go from here** An integrated environment called `FreeFem++-cs`, written by Antoine Le Hyaric, is provided with FreeFem++ . Unless you wish to profile now your own development environment, you may proceed to the next paragraph "How to use FreeFem++".

## 1.1.2 For the pros: Installation from sources

This section is for those who for some reason do not wish to use the binaries and hence need to recompile FreeFem++ or install it from the source code:

**The documentation archive** : The documentation is also open source; to regenerate it you need a  $\text{\LaTeX}$  environment capable of compiling a CVS archive; under MS-Windows you will have to use cygwin

<http://www.cygwin.com>

and under MacOS X we have used Apple's Developer Tools "Xcode" and  $\text{\LaTeX}$  from <http://www.ctan.org/system/mac/texmac>.

**The C++ archive** : FreeFem++ must be compiled from the source archive, as indicated in

<http://www.freefem.org/ff++/index.htm>

To extract files from the compressed archive `freefem++-(VERSION).tar.gz` to a directory called

`freefem++-(VERSION)`

enter the following commands in a shell window :

```
tar zxvf freefem++-(VERSION).tar.gz
cd freefem++-(VERSION)
```

To compile and install FreeFem++ , just follow the INSTALL and README files. The following programs are produced, depending on the system you are running :

1. FreeFem++, standard version, with a graphical interface based on GLUT/OpenGL (use `ffglut` visualization tool) or not just add `-nw` parameter.
2. `ffglut` the visualization tools through a pipe of `freefem++` (remark: *if `ffglut` is not in the system path, you will have no plot*)
3. FreeFem++-nw, postscript plot output only (batch version, no graphics windows via `ffglut` )
4. FreeFem++-mpi, parallel version, postscript output only
5. /Applications/FreeFem++.app, the Drag and Drop CoCoa MacOSX Application
6. `bamg` , the `bamg` mesh generator
7. `cvms2` , a mesh file convertor
8. `drawbdmesh` , a mesh file viewer
9. `ffmedit` the `freefem++` version of `medit` software (thanks to P. Frey)

The FreeFem++ parameter command:

Brochet-2:~ hecht\$ FreeFem++

Syntaxe:

```
FreeFem++ [ -v verbosity ] [ -fglut filepath ] [ -glut command ] [ -nw ] [ -f ] filename
  -v      verbosity : 0 -- 1000000 level of freefem output
  -fglut  filepath  : the file name of save all plots (replot with ffglut command )
  -glut   command   : change the command ffglut
  -gff    command   : change the command ffglut with space quotting
  -nowait                : nowait at the end on window
  -wait                 : wait at the end on window
  -nw                  : no ffglut (=> no graphics windows)
  -ne                  : no edp script output
  -cd                  : Change directory to script dir
```

with default `ffglut` : `ffglut`



**Remark 2** *In most cases you can set the level of output (verbosity) to value `nn` by adding the parameters `-v nn` on the command line.*

As an installation test, under unix: go into the directory `examples+-tutorial` and run `FreeFem++` on the example script `LaplaceP1.edp` with the command :

```
FreeFem++ LaplaceP1.edp
```

If you are using `nedit` as your text editor, do one time `nedit -import edp.nedit` to have coloring syntax for your `.edp` files.

The syntax of tools `FreeFem++`, `FreeFem++-nw` on the command-line are

- `FreeFem++ [-?] [-vnn] [-fglut file1] [-glut file2] [-f] edppath` where the
  - or `FreeFem++-nw -? [-vnn] [-fglut file1] [-glut file2] [-f] edppath` where the
- ? show the usage.
  - fglut filename to store all the data for graphic in file filename, and to replay do `ffglut filename`.
  - glut ffglutprogram to change the visualisator program's.
  - nw no call to ffglut
  - v nn set the level of verbosity to nn before execution of the script.
- if no file path then you get a dialog box to choose the edp file on windows systeme.

The notation `[]` means "optional".

### Link with other text editors

**notepad++** at <http://notepad-plus.sourceforge.net/uk/site.htm>

- Open Notepad++ and Enter F5
  - In the new window enter the command `FreeFem++ "$(FULL_CURRENT_PATH)"`
  - Click on Save, and enter `FreeFem++` in the box "Name", now choose the short cut key to launch directly `FreeFem++` (for example `alt+shift+R`)
  - To add Color Syntax Compatible with `FreeFem++` In Notepad++,
    - In Menu "Parameters"->"Configuration of the Color Syntax" proceed as follows:
    - In the list "Language" select C++
    - Add "edp" in the field "add ext"
    - Select "INSTRUCTION WORD" in the list "Description" and in the field "supplementary key word", cut and past the following list:
- `P0 P1 P2 P3 P4 P5 P1dc P2dc P3dc P4dc P5dc RT0 RT1 RT2 RT3 RT4 RT5`  
`macro plot int1d int2d solve movemesh adaptmesh trunc checkmovemesh on func`  
`buildmesh square Eigenvalue min max imag exec LinearCG NLCG Newton BFGS`  
`LinearGMRES catch try intalldges jump average mean load savemesh convect`  
`abs sin cos tan atan asin acos cotan sinh cosh tanh cotanh atanh asinh acosh pow`  
`exp log log10 sqrt dx dy endl cout`

- Select "TYPE WORD" in the list "Description" and ... " "supplementary key word", cut and past the following list  
`mesh real fespace varf matrix problem string border complex ifstream ofstream`
- Click on Save & Close. Now nodepad++ is configured.

**Crimson Editor** available at <http://www.crimsoneditor.com/> and adapted as follows:

- Go to the Tools/Preferences/File association menu and add the .edp extension set
- In the same panel in Tools/User Tools, add a FreeFem++ item (1st line) with the path to `freefem++.exe` on the second line and `$(FilePath)` and `$(FileDir)` on third and fourth lines. Tick the 8.3 box.
- for color syntax, extract file from `crimson-freefem.zip` and put files in the corresponding sub-folder of Crimson folder (`C:\Program Files\Crimson Editor`).

**winedt** for Windows : this is the best but it could be tricky to set up. Download it from

<http://www.winedt.com>

this is a multipurpose text editor with advanced features such as syntax coloring; a macro is available on [www.freefem.org](http://www.freefem.org) to localize winedt to FreeFem++ without disturbing the winedt functional mode for LaTeX, TeX, C, etc. However winedt is not free after the trial period.

**TeXnicCenter** for Windows: this is the easiest and will be the best once we find a volunteer to program the color syntax. Download it from

<http://www.texniccenter.org/>

It is also an editor for TeX/LaTeX. It has a "tool" menu which can be configured to launch FreeFem++ programs as in:

- Select the Tools/Customize item which will bring up a dialog box.
- Select the Tools tab and create a new item: call it `freefem`.
- in the 3 lines below,
  1. search for `FreeFem++.exe`
  2. select Main file with further option then Full path and click also on the 8.3 box
  3. select main file full directory path with 8.3

**nedit** on the Mac OS, Cygwin/Xfree and linux, to import the color syntax do

```
nedit -import edp.nedit
```

**Smultron** on the Mac, available at <http://smultron.sourceforge.net>. It comes ready with color syntax for .edp file. To teach it to launch FreeFem++ files, do a "command B" (i.e. the menu Tools/Handle Command/new command) and create a command which does

```
/usr/local/bin/FreeFem++-CoCoa %p
```




Figure 1.1: Integrated environment for FreeFem++ development with Windows

## 1.2 How to use FreeFem++

**Under MacOS X with Graphic Interfaces** To test an .edp file, just drag and drop the file icon on the MacOS application icon FreeFem++.app. You can also launch this application and use the menu: File → Open.

One of the best ways however on the Mac is to use a text editor like Smultron.app (see above).




Figure 1.2: The 3 panels of the integrated environment built with the Smultron Editor with FreeFem++ in action. The Tools menu has an item to launch FreeFem++ by a Ctrl+I command.

**In Terminal mode** Choose the type of application from FreeFem++, FreeFem++-nw, FreeFem++-mpi, ... according to your needs. Add at least the path name; for example

```
FreeFem++ your-edp-file-path
```

## 1.3 Environment variables, and the init file

FreeFem++ reads a user's init file named `freefem++.pref` to initialize global variables: verbosity, includepath, loadpath.

**Remark 3** The variable `verbosity` changes the level of internal printing (0, nothing (unless there are syntax errors), 1 few, 10 lots, etc. ...), the default value is 2.

The include files are searched from the `includepath` list and the load files are searched from `loadpath` list.

The syntax of the file is:

```

verbosity= 5
loadpath += "/Library/FreeFem++/lib"
loadpath += "/Users/hecht/Library/FreeFem++/lib"
includepath += "/Library/FreeFem++/edp"
includepath += "/Users/hecht/Library/FreeFem++/edp"
# comment
load += "funcTemplate"
load += "myfunction"

```

The possible paths for this file are

- under unix and MacOS

```

/etc/freefem++.pref
$(HOME)/.freefem++.pref
freefem++.pref

```

- under windows

```

freefem++.pref

```

We can also use shell environment variable to change verbosity and the search rule before the init files.

```

export FF_VERBOSITY=50
export FF_INCLUDEPATH="dir;;dir2"
export FF_LOADPATH="dir;;dir3"

```

Remark: the separator between directories must be ";" and not ":" because ":" is used under Windows.

Remark, to show the list of init of freefem++, do

```

export FF_VERBOSITY=100; ./FreeFem++-nw
-- verbosity is set to 100
insert init-files /etc/freefem++.pref $
...

```

## 1.4 History

The project has evolved from MacFem, PCfem, written in Pascal. The first C version lead to freefem 3.4; it offered mesh adaptativity on a single mesh only.

A thorough rewriting in C++ led to freefem+ (freefem+ 1.2.10 was its last release), which included interpolation over multiple meshes (functions defined on one mesh can be used on any other mesh); this software is no longer maintained but still in use because it handles a problem

description using the strong form of the PDEs. Implementing the interpolation from one unstructured mesh to another was not easy because it had to be fast and non-diffusive; for each point, one had to find the containing triangle. This is one of the basic problems of computational geometry (see Preparata & Shamos[18] for example). Doing it in a minimum number of operations was the challenge. Our implementation is  $O(n \log n)$  and based on a quadtree. This version also grew out of hand because of the evolution of the template syntax in C++.

We have been working for a few years now on `FreeFem++` , entirely re-written again in C++ with a thorough usage of `template` and generic programming for coupled systems of unknown size at compile time. Like all versions of `freefem` it has a high level user friendly input language which is not too far from the mathematical writing of the problems.

The `freefem` language allows for a quick specification of any partial differential system of equations. The language syntax of `FreeFem++` is the result of a new design which makes use of the STL [26], templates and `bison` for its implementation; more detail can be found in [12]. The outcome is a versatile software in which any new finite element can be included in a few hours; but a recompilation is then necessary. Therefore the library of finite elements available in `FreeFem++` will grow with the version number and with the number of users who program more new elements. So far we have discontinuous  $P_0$  elements, linear  $P_1$  and quadratic  $P_2$  Lagrangian elements, discontinuous  $P_1$  and Raviart-Thomas elements and a few others like bubble elements.

# Chapter 2

## Getting Started

To illustrate with an example, let us explain how FreeFem++ solves **Poisson's** equation: *for a given function  $f(x, y)$ , find a function  $u(x, y)$  satisfying*

$$-\Delta u(x, y) = f(x, y) \quad \text{for all } (x, y) \in \Omega, \quad (2.1)$$

$$u(x, y) = 0 \quad \text{for all } (x, y) \text{ on } \partial\Omega, . \quad (2.2)$$

Here  $\partial\Omega$  is the boundary of the bounded open set  $\Omega \subset \mathbb{R}^2$  and  $\Delta u = \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2}$ .

The following is a FreeFem++ program which computes  $u$  when  $f(x, y) = xy$  and  $\Omega$  is the unit disk. The boundary  $C = \partial\Omega$  is

$$C = \{(x, y) \mid x = \cos(t), y = \sin(t), 0 \leq t \leq 2\pi\}$$

Note that in FreeFem++ the domain  $\Omega$  is assumed to be described by its boundary that is on the left side of its boundary oriented by the parameter. As illustrated in Fig. 2.2, we can see the isovalue of  $u$  by using `plot` (see line 13 below).




Figure 2.1: mesh Th by `build(C(50))`




Figure 2.2: isovalue by `plot(u)`

### Example 2.1

```
// defining the boundary
1: border C(t=0,2*pi){x=cos(t); y=sin(t);}
```



```

// the triangulated domain Th is on the left side of its boundary
2: mesh Th = buildmesh (C(50));
// the finite element space defined over Th is called here Vh
3: fespace Vh(Th,P1);
4: Vh u,v; // defines u and v as piecewise-P1 continuous functions
5: func f= x*y; // definition of a called f function
6: real cpu=clock(); // get the clock in second
7: solve Poisson(u,v,solver=LU) = // defines the PDE
8:   int2d(Th)(dx(u)*dx(v) + dy(u)*dy(v)) // bilinear part
9:   - int2d(Th)( f*v) // right hand side
10:   + on(C,u=0) ; // Dirichlet boundary condition
11: plot(u);
12: cout << " CPU time = " << clock()-cpu << endl;

```

Note that the qualifier `solver=LU` is not required and by default a multi-frontal LU would have been used. Note also that the lines containing `clock` are equally not required. Finally note how close to the mathematics FreeFem++ input language is. Line 8 and 9 correspond to the mathematical variational equation

$$\int_{T_h} \left( \frac{\partial u}{\partial x} \frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \frac{\partial v}{\partial y} \right) dx dy = \int_{T_h} f v dx dy$$

for all  $v$  which are in the finite element space  $V_h$  and zero on the boundary  $C$ .

**Exercise** : Change P1 into P2 and run the program.

### 2.0.1 FEM by FreeFem++ : how does it work?

This first example shows how FreeFem++ executes with no effort all the usual steps required by the finite element method (FEM). Let us go through them one by one.

**1st line:** the boundary  $\Gamma$  is described analytically by a parametric equation for  $x$  and for  $y$ . When  $\Gamma = \sum_{j=0}^J \Gamma_j$  then each curve  $\Gamma_j$ , must be specified and crossings of  $\Gamma_j$  are not allowed except at end points .

The keyword “label” can be added to define a group of boundaries for later use (boundary conditions for instance). Hence the circle could also have been described as two half circle with the same label:

```

border Gamma1(t=0,pi) {x=cos(t); y=sin(t); label=C}
border Gamma2(t=pi,2*pi){x=cos(t); y=sin(t); label=C}

```

Boundaries can be referred to either by name ( Gamma1 for example) or by label ( C here) or even by its internal number here 1 for the first half circle and 2 for the second (more examples are in Section 5.8).

**2nd line:** the triangulation  $\mathcal{T}_h$  of  $\Omega$  is automatically generated by `buildmesh(C(50))` using 50 points on  $C$  as in Fig. 2.1.

The domain is assumed to be on the left side of the boundary which is implicitly oriented by the parametrization. So an elliptic hole can be added by



```
border C(t=2*pi,0){x=0.1+0.3*cos(t); y=0.5*sin(t);}
```

If by mistake one had written

```
border C(t=0,2*pi){x=0.1+0.3*cos(t); y=0.5*sin(t);}
```

then the inside of the ellipse would be triangulated as well as the outside.

Automatic mesh generation is based on the Delaunay-Voronoi algorithm. Refinement of the mesh are done by increasing the number of points on  $\Gamma$ , for example, `buildmesh(C(100))`, because inner vertices are determined by the density of points on the boundary. Mesh adaptation can be performed also against a given function  $f$  by calling `adaptmesh(Th,f)`.

Now the name  $\mathcal{T}_h$  (Th in FreeFem++) refers to the family  $\{T_k\}_{k=1,\dots,n_t}$  of triangles shown in figure 2.1. Traditionally  $h$  refers to the mesh size,  $n_t$  to the number of triangles in  $\mathcal{T}_h$  and  $n_v$  to the number of vertices, but it is seldom that we will have to use them explicitly. If  $\Omega$  is not a polygonal domain, a “skin” remains between the exact domain  $\Omega$  and its approximation  $\Omega_h = \cup_{k=1}^{n_t} T_k$ . However, we notice that all corners of  $\Gamma_h = \partial\Omega_h$  are on  $\Gamma$ .

**3rd line:** A finite element space is, usually, a space of polynomial functions on elements, triangles here only, with certain matching properties at edges, vertices etc. Here `fespace Vh(Th,P1)` defines  $V_h$  to be the space of continuous functions which are affine in  $x, y$  on each triangle of  $\mathcal{T}_h$ . As it is a linear vector space of finite dimension, basis can be found. The canonical basis is made of functions, called the *hat functions*  $\phi_k$  which are continuous piecewise affine and are equal to 1 on one vertex and 0 on all others. A typical hat function is shown on figure 2.4<sup>1</sup>. Then

$$V_h(\mathcal{T}_h, P_1) = \left\{ w(x, y) \left| w(x, y) = \sum_{k=1}^M w_k \phi_k(x, y), w_k \text{ are real numbers} \right. \right\} \quad (2.3)$$

where  $M$  is the dimension of  $V_h$ , i.e. the number of vertices. The  $w_k$  are called the *degree of freedom* of  $w$  and  $M$  the number of the degree of freedom.

It is said also that the *nodes* of this finite element method are the vertices.

Currently FreeFem++ implements the following elements in 2d, (see section 6 for the full description)



- P0 piecewise constant,
- P1 continuous piecewise linear,
- P2 continuous piecewise quadratic,
- RT0 Raviart-Thomas piecewise constant,
- P1nc piecewise linear non-conforming,
- P1dc piecewise linear discontinuous,
- P2dc piecewise quadratic discontinuous,
- P1b piecewise linear continuous plus bubble,

---

<sup>1</sup> The easiest way to define  $\phi_k$  is by making use of the *barycentric coordinates*  $\lambda_i(x, y)$ ,  $i = 1, 2, 3$  of a point  $q = (x, y) \in T$ , defined by

$$\sum_i \lambda_i = 1, \quad \sum_i \lambda_i q^i = q$$

where  $q^i$ ,  $i = 1, 2, 3$  are the 3 vertices of  $T$ . Then it is easy to see that the restriction of  $\phi_k$  on  $T$  is precisely  $\lambda_k$ .

Figure 2.3: mesh  $\mathcal{T}_h$ Figure 2.4: Graph of  $\phi_1$  (left) and  $\phi_6$ 

P2b piecewise quadratic continuous plus bubble.

...

Currently FreeFem++ implements the following elements in 3d, (see section 6 for the full description)

P03d piecewise constant,

P13d continuous piecewise linear,

P23d continuous piecewise quadratic,

RT03d Raviart-Thomas piecewise constant,

Edge03d The Nedelec Edge element

P1b3d piecewise linear continuous plus bubble,

...

To get the full list, in a unix terminal, in directory `examples++-tutorial` do

```
FreeFem++ dumptable.edp
grep TypeOfFE lestables
```

Note that other elements can be added fairly easily.

### Step3: Setting the problem

**4th line:** `Vh u, v` declares that  $u$  and  $v$  are approximated as above, namely

$$u(x, y) \simeq u_h(x, y) = \sum_{k=0}^{M-1} u_k \phi_k(x, y) \quad (2.4)$$

**5th line:** the right hand side  $f$  is defined analytically using the keyword `func`.

**7th–9th lines:** defines the bilinear form of equation (2.1) and its Dirichlet boundary conditions (2.2).

This *variational formulation* is derived by multiplying (2.1) by  $v(x, y)$  and integrating the result over  $\Omega$ :

$$-\int_{\Omega} v \Delta u \, dx dy = \int_{\Omega} v f \, dx dy$$

Then, by Green's formula, the problem is converted into finding  $u$  such that

$$a(u, v) - \ell(f, v) = 0 \quad \forall v \text{ satisfying } v = 0 \text{ on } \partial\Omega. \quad (2.5)$$

$$\text{with } a(u, v) = \int_{\Omega} \nabla u \cdot \nabla v \, dx dy, \quad \ell(f, v) = \int_{\Omega} f v \, dx dy \quad (2.6)$$

In FreeFem++ the **Poisson** problem can be declared only as in

```
Vh u,v; problem Poisson(u,v) =
```

and solved later as in

```
...
  Poisson;                                     // the problem is solved here
...
```

or declared and solved at the same time as in

```
Vh u,v; solve Poisson(u,v) =int(...
```

and (2.5) is written with  $\mathbf{dx}(u) = \partial u / \partial x$ ,  $\mathbf{dy}(u) = \partial u / \partial y$  and

$$\begin{aligned} \int_{\Omega} \nabla u \cdot \nabla v \, dx dy &\longrightarrow \mathbf{int2d}(\text{Th}) ( \mathbf{dx}(u) * \mathbf{dx}(v) + \mathbf{dy}(u) * \mathbf{dy}(v) ) \\ \int_{\Omega} f v \, dx dy &\longrightarrow \mathbf{int2d}(\text{Th}) ( f * v ) \quad (\text{Notice here, } u \text{ is unused}) \end{aligned}$$

In FreeFem++ **bilinear terms and linear terms should not be under the same integral**; indeed to construct the linear systems FreeFem++ finds out which integral contributes to the bilinear form by checking if both terms, the unknown (here  $u$ ) and test functions (here  $v$ ) are present.

#### Step4: Solution and visualization

**6th line:** The current time in seconds is stored into the real-valued variable `cpu`.

**7th line** The problem is solved.

**11th line:** The visualization is done as illustrated in Fig. 2.2 (see Section 7.1 for zoom, postscript and other commands).

**12th line:** The computing time (not counting graphics) is written on the console Notice the C++-like syntax; the user needs not study C++ for using FreeFem++, but it helps to guess what is allowed in the language.

#### Access to matrices and vectors

Internally FreeFem++ will solve a linear system of the type

$$\sum_{j=0}^{M-1} A_{ij} u_j - F_i = 0, \quad i = 0, \dots, M-1; \quad F_i = \int_{\Omega} f \phi_i \, dx dy \quad (2.7)$$

which is found by using (2.4) and replacing  $v$  by  $\phi_i$  in (2.5). And the Dirichlet conditions are implemented by penalty, namely by setting  $A_{ii} = 10^{30}$  and  $F_i = 10^{30} * 0$  if  $i$  is a boundary degree of freedom. Note, that the number  $10^{30}$  is called `tg`*v* (*très grande valeur*) and it is generally possible to change this value, see the index item `solve!tg`*v*.

The matrix  $A = (A_{ij})$  is called *stiffness matrix*.

If the user wants to access  $A$  directly he can do so by using (see section 6.12 page 159 for details)

```
varf a(u,v) = int2d(Th) ( dx(u)*dx(v) + dy(u)*dy(v))
```

```

+ on(C,u=0) ;
matrix A=a(Vh,Vh); // stiffness matrix,

```

The vector  $F$  in (2.7) can also be constructed manually

```

varf l(UNUSED,v) = int2d(Th)(f*v)+on(C,u=0);
Vh F; F[] = l(0,Vh); // F[] is the vector associated to the function F

```

The problem can then be solved by

```

u[]=A^-1*F[]; // u[] is the vector associated to the function u

```

**Note 2.1** Here  $u$  and  $F$  are finite element function, and  $u[]$  and  $F[]$  give the array of value associated ( $u[] \equiv (u_i)_{i=0,\dots,M-1}$  and  $F[] \equiv (F_i)_{i=0,\dots,M-1}$ ). So we have

$$u(x, y) = \sum_{i=0}^{M-1} u[i] \phi_i(x, y), \quad F(x, y) = \sum_{i=0}^{M-1} F[i] \phi_i(x, y)$$

where  $\phi_i, i = 0, \dots, M-1$  are the basis functions of  $V_h$  like in equation (2.3), and  $M = V_h.\text{ndof}$  is the number of degree of freedom (i.e. the dimension of the space  $V_h$ ).

The linear system (2.7) is solved by UMFPACK unless another option is mentioned specifically as in

```

Vh u,v; problem Poisson(u,v,solver=CG) = int2d(...

```

meaning that `Poisson` is declared only here and when it is called (by simply writing `Poisson;`) then (2.7) will be solved by the Conjugate Gradient method.

## 2.0.2 Some Features of FreeFem++

The language of FreeFem++ is typed, polymorphic and reentrant with macro generation (see 9.12). Every variable must be typed and declared in a statement each statement separated from the next by a semicolon “;”. The syntax is that of C++ by default augmented with something that is more akin to  $\text{\TeX}$ . For the specialist, one key guideline is that FreeFem++ rarely generates an internal finite element array; this was adopted for speed and consequently FreeFem++ could be hard to beat in terms of execution speed, except for the time lost in the interpretation of the language (which can be reduced by a systematic usage of `varf` and matrices instead of `problem`).

## 2.1 The Development Cycle: Edit–Run/Visualize–Revise

An integrated environment is provided with FreeFem++ by A. Le Hyaric; Many examples and tutorials are also given along with this documentation and it is best to study them and learn by example. Explanations for some of these examples are given in this documentation in the next chapter. If you are a FEM beginner, you may also have to read a book on variational formulations. The development cycle will have the following steps:

**Modeling:** From strong forms of PDE to weak forms, one must know the variational formulation to use FreeFem++ ; one should also have an eye on the reusability of the variational formulation so as to keep the same internal matrices; a typical example is the time dependent heat equation with an implicit time scheme: the internal matrix can be factorized only once and FreeFem++ can be taught to do so.

**Programming:** Write the code in FreeFem++ language using a text editor such as the one provided in the integrated environment.

**Run:** Run the code (here written in file mycode.edp). note that this can also be done in terminal mode by :

```
% FreeFem++ mycode.edp
```

**Visualization:** Use the keyword `plot` to display functions while FreeFem++ is running. Use the plot-parameter `wait=1` to stop the program at each plot. Use the plot-parameter `ps="toto.eps"` to generate a postscript file to archive the results.

**Debugging:** A global variable "debug" (for example) can help as in `wait=true` to `wait=false`.

```
bool debug = true;
border a(t=0,2*pi){ x=cos(t); y=sin(t);label=1;}
border b(t=0,2*pi){ x=0.8+0.3*cos(t); y=0.3*sin(t);label=2;}
plot(a(50)+b(-30),wait=debug);           // plot the borders to see the intersection
                                           // (so change (0.8 in 0.3 in b) then needs a mouse click
mesh Th = buildmesh(a(50)+b(-30));
plot(Th,wait=debug);                     // plot Th then needs a mouse click
fespace Vh(Th,P2);
Vh f = sin(pi*x)*cos(pi*y);
plot(f,wait=debug);                     // plot the function f
Vh g = sin(pi*x + cos(pi*y));
plot(g,wait=debug);                     // plot the function g
```

Changing debug to false will make the plots flow continuously; watching the flow of graphs on the screen (while drinking coffee) can then become a pleasant experience.

Error messages are displayed in the console window. They are not always very explicit because of the template structure of the C++ code, (we did our best)! Nevertheless they are displayed at the right place. For example, if you forget parenthesis as in

```
bool debug = true;
mesh Th = square(10,10;
plot(Th);
```

then you will get the following message from FreeFem++,

```
2 : mesh Th = square(10,10;
Error line number 2, in file bb.edp, before token ;
parse error
current line = 2
Compile error : parse error
line number :2, ;
error Compile error : parse error
line number :2, ;
code = 1
```

If you use the same symbol twice as in

```
real aaa =1;
real aaa;
```

then you will get the message

```
2 : real aaa; The identifier aaa exists
    the existing type is <Pd>
    the new type is <Pd>
```

If you find that the program isn't doing what you want you may also use `cout` to display in text format on the console window the value of variables, just as you would do in C++.

The following example works:

```
...;
fespace Vh...; Vh u;...
cout<<u;...
matrix A=a(Vh,Vh);...
cout<<A;
```

Another trick is to *comment in and out* by using the“ `//`” as in C++. For example

```
real aaa =1;
// real aaa;
```

# Chapter 3

## Learning by Examples

This chapter is for those, like us, who don't like to read manuals. A number of simple examples cover a good deal of the capacity of FreeFem++ and are self-explanatory. For the modeling part this chapter continues at Chapter 9 where some PDEs of physics, engineering and finance are studied in greater depth.

### 3.1 Membranes

**Summary** *Here we shall learn how to solve a Dirichlet and/or mixed Dirichlet Neumann problem for the Laplace operator with application to the equilibrium of a membrane under load. We shall also check the accuracy of the method and interface with other graphics packages.*

An elastic membrane  $\Omega$  is attached to a planar rigid support  $\Gamma$ , and a force  $f(x)dx$  is exerted on each surface element  $dx = dx_1 dx_2$ . The vertical membrane displacement,  $\varphi(x)$ , is obtained by solving Laplace's equation:

$$-\Delta\varphi = f \text{ in } \Omega.$$

As the membrane is fixed to its planar support, one has:

$$\varphi|_{\Gamma} = 0.$$

If the support wasn't planar but at an elevation  $z(x_1, x_2)$  then the boundary conditions would be of non-homogeneous Dirichlet type.

$$\varphi|_{\Gamma} = z.$$

If a part  $\Gamma_2$  of the membrane border  $\Gamma$  is not fixed to the support but is left hanging, then due to the membrane's rigidity the angle with the normal vector  $n$  is zero; thus the boundary conditions are

$$\varphi|_{\Gamma_1} = z, \quad \frac{\partial\varphi}{\partial n}|_{\Gamma_2} = 0$$

where  $\Gamma_1 = \Gamma - \Gamma_2$ ; recall that  $\frac{\partial\varphi}{\partial n} = \nabla\varphi \cdot n$ . Let us recall also that the Laplace operator  $\Delta$  is defined by:

$$\Delta\varphi = \frac{\partial^2\varphi}{\partial x_1^2} + \frac{\partial^2\varphi}{\partial x_2^2}.$$

With such "mixed boundary conditions" the problem has a unique solution (see (1987), Dautray-Lions (1988), Strang (1986) and Raviart-Thomas (1983)); the easiest proof is to notice that  $\varphi$  is the state of least energy, i.e.

$$E(\phi) = \min_{\varphi-z \in V} E(v), \quad \text{with} \quad E(v) = \int_{\Omega} \left( \frac{1}{2} |\nabla v|^2 - f v \right)$$

and where  $V$  is the subspace of the Sobolev space  $H^1(\Omega)$  of functions which have zero trace on  $\Gamma_1$ . Recall that ( $x \in \mathbb{R}^d$ ,  $d = 2$  here)

$$H^1(\Omega) = \{u \in L^2(\Omega) : \nabla u \in (L^2(\Omega))^d\}$$

Calculus of variation shows that the minimum must satisfy, what is known as the weak form of the PDE or its variational formulation (also known here as the theorem of virtual work)

$$\int_{\Omega} \nabla \varphi \cdot \nabla w = \int_{\Omega} f w \quad \forall w \in V$$

Next an integration by parts (Green's formula) will show that this is equivalent to the PDE when second derivatives exist.

**WARNING** Unlike `freefem+` which had both weak and strong forms, `FreeFem++` implements only weak formulations. It is not possible to go further in using this software if you don't know the weak form (i.e. variational formulation) of your problem: either you read a book, or ask help from a colleague or drop the matter. Now if you want to solve a system of PDE like  $A(u, v) = 0$ ,  $B(u, v) = 0$  don't close this manual, because in weak form it is

$$\int_{\Omega} (A(u, v) w_1 + B(u, v) w_2) = 0 \quad \forall w_1, w_2 \dots$$

**Example** Let an ellipse have the length of the semimajor axis  $a = 2$ , and unitary the semiminor axis. Let the surface force be  $f = 1$ . Programming this case with `FreeFem++` gives:

### Example 3.1 (membrane.edp)

*// file membrane.edp*

```

real theta=4.*pi/3.;
real a=2.,b=1.;           // the length of the semimajor axis and semiminor axis
func z=x;

border Gamma1(t=0,theta) { x = a * cos(t); y = b*sin(t); }
border Gamma2(t=theta,2*pi) { x = a * cos(t); y = b*sin(t); }
mesh Th=buildmesh(Gamma1(100)+Gamma2(50));

fespace Vh(Th,P2);           // P2 conforming triangular FEM
Vh phi,w, f=1;

solve Laplace(phi,w)=int2d(Th)(dx(phi)*dx(w) + dy(phi)*dy(w))
- int2d(Th)(f*w) + on(Gamma1,phi=z);
plot(phi,wait=true, ps="membrane.eps");           // Plot phi
plot(Th,wait=true, ps="membraneTh.eps");         // Plot Th

savemesh(Th, "Th.msh");
```






Figure 3.1: Mesh and level lines of the membrane deformation. Below: the same in 3D drawn by gnuplot from a file generated by FreeFem++ .

A triangulation is built by the keyword `buildmesh`. This keyword calls a triangulation subroutine based on the Delaunay test, which first triangulates with only the boundary points, then adds internal points by subdividing the edges. How fine the triangulation becomes is controlled by the size of the closest boundary edges.

The PDE is then discretized using the triangular second order finite element method on the triangulation; as was briefly indicated in the previous chapter, a linear system is derived from the discrete formulation whose size is the number of vertices plus the number of mid-edges in the triangulation. The system is solved by a multi-frontal Gauss LU factorization implemented in the package `UMFPACK`. The keyword `plot` will display both  $\mathbb{T}_h$  and  $\varphi$  (remove `Th` if  $\varphi$  only is desired) and the qualifier `fill=true` replaces the default option (colored level lines) by a full color display. Results are on figure 3.1.

```
plot(phi,wait=true,fill=true); // Plot phi with full color display
```

Next we would like to check the results!

One simple way is to adjust the parameters so as to know the solutions. For instance on the unit circle  $a=1$ ,  $\varphi_e = \sin(x^2 + y^2 - 1)$  solves the problem when

$$z = 0, \quad f = -4(\cos(x^2 + y^2 - 1) - (x^2 + y^2) \sin(x^2 + y^2 - 1))$$

except that on  $\Gamma_2$   $\partial_n \varphi = 2$  instead of zero. So we will consider a non-homogeneous Neumann condition and solve

$$\int_{\Omega} (\nabla \varphi \cdot \nabla w) = \int_{\Omega} f w + \int_{\Gamma_2} 2 w \quad \forall w \in V$$

We will do that with two triangulations, compute the  $L^2$  error:

$$\epsilon = \int_{\Omega} |\varphi - \varphi_e|^2$$

and print the error in both cases as well as the log of their ratio an indication of the rate of convergence.

### Example 3.2 (membranerror.edp)

```
// file membranerror.edp
verbosity =0; // to remove all default output
real theta=4.*pi/3.;
real a=1.,b=1.; // the length of the semimajor axis and semiminor axis
border Gamma1(t=0,theta) { x = a * cos(t); y = b*sin(t); }
border Gamma2(t=theta,2*pi) { x = a * cos(t); y = b*sin(t); }

func f=-4*(cos(x^2+y^2-1) -(x^2+y^2)*sin(x^2+y^2-1));
func phiexact=sin(x^2+y^2-1);

real[int] L2error(2); // an array two values
for(int n=0;n<2;n++)
{
  mesh Th=buildmesh(Gamma1(20*(n+1))+Gamma2(10*(n+1)));
  fespace Vh(Th,P2);
  Vh phi,w;

  solve laplace(phi,w)=int2d(Th)(dx(phi)*dx(w) + dy(phi)*dy(w))
    - int2d(Th)(f*w) - int1d(Th,Gamma2)(2*w)+ on(Gamma1,phi=0);
```

```

plot(Th,phi,wait=true,ps="membrane.eps");           // Plot Th and phi

L2error[n]= sqrt(int2d(Th)((phi-phiexact)^2));
}

for(int n=0;n<2;n++)
  cout << " L2error " << n << " = "<< L2error[n] <<endl;

cout <<" convergence rate = "<< log(L2error[0]/L2error[1])/log(2.) <<endl;

```

the output is

```

L2error 0 = 0.00462991
L2error 1 = 0.00117128
convergence rate = 1.9829
times: compile 0.02s, execution 6.94s

```

We find a rate of 1.93591, which is not close enough to the 3 predicted by the theory. The Geometry is always a polygon so we lose one order due to the geometry approximation in  $O(h^2)$

Now if you are not satisfied with the .eps plot generated by FreeFem++ and you want to use other graphic facilities, then you must store the solution in a file very much like in C++. It will be useless if you don't save the triangulation as well, consequently you must do

```

{
  ofstream ff("phi.txt");
  ff << phi[];
}
savemesh(Th,"Th.msh");

```

For the triangulation the name is important: it is the extension that determines the format. Still that may not take you where you want. Here is an interface with gnuplot to produce the right part of figure 3.2.

```

// to build a gnuplot data file
{ ofstream ff("graph.txt");
  for (int i=0;i<Th.nt;i++)
  { for (int j=0; j <3; j++)
    ff<<Th[i][j].x << " " << Th[i][j].y<< " " <<phi[][Vh(i,j)]<<endl;
    ff<<Th[i][0].x << " " << Th[i][0].y<< " " <<phi[][Vh(i,0)]<<"\n\n"
  }
}

```

We use the finite element numbering, where  $Vh(i, j)$  is the global index of  $j^{th}$  degrees of freedom of triangle number  $i$ .

Then open gnuplot and do

```

set palette rgbformulae 30,31,32
splot "graph.txt" w l pal

```

This works with P2 and P1, but not with P1nc because the 3 first degrees of freedom of P2 or P2 are on vertices and not with P1nc.

## 3.2 Heat Exchanger

**Summary** Here we shall learn more about geometry input and triangulation files, as well as read and write operations.

**The problem** Let  $\{C_i\}_{1,2}$ , be 2 thermal conductors within an enclosure  $C_0$ . The first one is held at a constant temperature  $u_1$  the other one has a given thermal conductivity  $\kappa_2$  5 times larger than the one of  $C_0$ . We assume that the border of enclosure  $C_0$  is held at temperature  $20^\circ\text{C}$  and that we have waited long enough for thermal equilibrium.

In order to know  $u(x)$  at any point  $x$  of the domain  $\Omega$ , we must solve

$$\nabla \cdot (\kappa \nabla u) = 0 \quad \text{in } \Omega, \quad u|_\Gamma = g$$

where  $\Omega$  is the interior of  $C_0$  minus the conductors  $C_1$  and  $\Gamma$  is the boundary of  $\Omega$ , that is  $C_0 \cup C_1$ . Here  $g$  is any function of  $x$  equal to  $u_i$  on  $C_i$ . The second equation is a reduced form for:

$$u = u_i \text{ on } C_i, \quad i = 0, 1.$$

The variational formulation for this problem is in the subspace  $H_0^1(\Omega) \subset H^1(\Omega)$  of functions which have zero traces on  $\Gamma$ .

$$u - g \in H_0^1(\Omega) : \int_{\Omega} \nabla u \nabla v = 0 \quad \forall v \in H_0^1(\Omega)$$

Let us assume that  $C_0$  is a circle of radius 5 centered at the origin,  $C_i$  are rectangles,  $C_1$  being at the constant temperature  $u_1 = 60^\circ\text{C}$ .

### Example 3.3 (heatex.edp)

```

// file heatex.edp
int C1=99, C2=98; // could be anything such that ≠ 0 and C1 ≠ C2
border C0(t=0,2*pi){x=5*cos(t); y=5*sin(t);}

border C11(t=0,1){ x=1+t; y=3; label=C1;}
border C12(t=0,1){ x=2; y=3-6*t; label=C1;}
border C13(t=0,1){ x=2-t; y=-3; label=C1;}
border C14(t=0,1){ x=1; y=-3+6*t; label=C1;}

border C21(t=0,1){ x=-2+t; y=3; label=C2;}
border C22(t=0,1){ x=-1; y=3-6*t; label=C2;}
border C23(t=0,1){ x=-1-t; y=-3; label=C2;}
border C24(t=0,1){ x=-2; y=-3+6*t; label=C2;}

plot( C0(50) // to see the border of the domain
      + C11(5)+C12(20)+C13(5)+C14(20)
      + C21(-5)+C22(-20)+C23(-5)+C24(-20),
      wait=true, ps="heatexb.eps");

mesh Th=buildmesh( C0(50)
                   + C11(5)+C12(20)+C13(5)+C14(20)
                   + C21(-5)+C22(-20)+C23(-5)+C24(-20));

plot(Th,wait=1);

fespace Vh(Th,P1); Vh u,v;
```

```
Vh kappa=1+2*(x<-1)*(x>-2)*(y<3)*(y>-3);
solve a(u,v)= int2d(Th)(kappa*(dx(u)*dx(v)+dy(u)*dy(v)))
      +on(C0,u=20)+on(C1,u=60);
plot(u,wait=true, value=true, fill=true, ps="heatex.eps");
```

Note the following:

- $C0$  is oriented counterclockwise by  $t$ , while  $C1$  is oriented clockwise and  $C2$  is oriented counterclockwise. This is why  $C1$  is viewed as a hole by `buildmesh`.
- $C1$  and  $C2$  are built by joining pieces of straight lines. To group them in the same logical unit to input the boundary conditions in a readable way we assigned a label on the boundaries. As said earlier, borders have an internal number corresponding to their order in the program (check it by adding a `cout<<C22;` above). This is essential to understand how a mesh can be output to a file and re-read (see below).
- As usual the mesh density is controlled by the number of vertices assigned to each boundary. It is not possible to change the (uniform) distribution of vertices but a piece of boundary can always be cut in two or more parts, for instance  $C12$  could be replaced by  $C121+C122$ :

```
// border C12(t=0,1) x=2; y=3-6*t; label=C1;
border C121(t=0,0.7){ x=2; y=3-6*t; label=C1;}
border C122(t=0.7,1){ x=2; y=3-6*t; label=C1;}
... buildmesh(.../* C12(20) */ + C121(12)+C122(8)+...);
```




Figure 3.2: The heat exchanger

**Exercise** Use the symmetry of the problem with respect to the axes; triangulate only one half of the domain, and set Dirichlet conditions on the vertical axis, and Neumann conditions on the horizontal axis.

**Writing and reading triangulation files** Suppose that at the end of the previous program we added the line

```
savemesh(Th, "condensor.msh");
```

and then later on we write a similar program but we wish to read the mesh from that file. Then this is how the condenser should be computed:

```
mesh Sh=readmesh("condensor.msh");
fespace Wh(Sh,P1); Wh us,vs;
solve b(us,vs)= int2d(Sh)(dx(us)*dx(vs)+dy(us)*dy(vs))
+on(1,us=0)+on(99,us=1)+on(98,us=-1);
plot(us);
```

Note that the names of the boundaries are lost but either their internal number (in the case of C0) or their label number (for C1 and C2) are kept.

### 3.3 Acoustics

**Summary** *Here we go to grip with ill posed problems and eigenvalue problems*

Pressure variations in air at rest are governed by the wave equation:

$$\frac{\partial^2 u}{\partial t^2} - c^2 \Delta u = 0.$$

When the solution wave is monochromatic (and that depend on the boundary and initial conditions),  $u$  is of the form  $u(x, t) = \text{Re}(v(x)e^{ikt})$  where  $v$  is a solution of Helmholtz's equation:

$$\begin{aligned} k^2 v + c^2 \Delta v &= 0 \quad \text{in } \Omega, \\ \frac{\partial v}{\partial n} \Big|_{\Gamma} &= g. \end{aligned} \tag{3.1}$$

where  $g$  is the source. Note the “+” sign in front of the Laplace operator and that  $k > 0$  is real. This sign may make the problem ill posed for some values of  $\frac{c}{k}$ , a phenomenon called “resonance”. At resonance there are non-zero solutions even when  $g = 0$ . So the following program may or may not work:

#### Example 3.4 (sound.edp)

// file sound.edp

```
real kc2=1;
func g=y*(1-y);

border a0(t=0,1) { x= 5; y= 1+2*t ;}
border a1(t=0,1) { x=5-2*t; y= 3 ;}
border a2(t=0,1) { x= 3-2*t; y=3-2*t ;}
border a3(t=0,1) { x= 1-t; y= 1 ;}
border a4(t=0,1) { x= 0; y= 1-t ;}
border a5(t=0,1) { x= t; y= 0 ;}
border a6(t=0,1) { x= 1+4*t; y= t ;}

mesh Th=buildmesh( a0(20) + a1(20) + a2(20)
+ a3(20) + a4(20) + a5(20) + a6(20));
fespace Vh(Th,P1);
```

Vh u,v;

```
solve sound(u,v)=int2d(Th)(u*v * kc2 - dx(u)*dx(v) - dy(u)*dy(v))
          - int1d(Th,a4)(g*v);
plot(u, wait=1, ps="sound.eps");
```

Results are on Figure 3.3. But when  $kc2$  is an eigenvalue of the problem, then the solution is not unique: if  $u_e \neq 0$  is an eigen state, then for any given solution  $u + u_e$  is another a solution. To find all the  $u_e$  one can do the following

```
real sigma = 20; // value of the shift
// OP = A - sigma B ; // the shifted matrix
varf op(u1,u2)= int2d(Th)( dx(u1)*dx(u2) + dy(u1)*dy(u2) - sigma* u1*u2 );
varf b([u1],[u2]) = int2d(Th)( u1*u2 ); // no Boundary condition see note 9.1

matrix OP= op(Vh,Vh,solver=CROUT,factorize=1);
matrix B= b(Vh,Vh,solver=CG,eps=1e-20);

int nev=2; // number of requested eigenvalues near sigma

real[int] ev(nev); // to store the nev eigenvalue
Vh[int] eV(nev); // to store the nev eigenvector

int k=EigenValue(OP,B,sym=true,sigma=sigma,value=ev,vector=eV,
                 tol=1e-10,maxit=0,ncv=0);
cout<<ev(0)<<" 2 eigen values "<<ev(1)<<endl;
v=eV[0];
plot(v,wait=1,ps="eigen.eps");
```




Figure 3.3: Left:Amplitude of an acoustic signal coming from the left vertical wall. Right: first eigen state ( $\lambda = (k/c)^2 = 19.4256$ ) close to 20 of eigenvalue problem :  $-\Delta\varphi = \lambda\varphi$  and  $\frac{\partial\varphi}{\partial n} = 0$  on  $\Gamma$

### 3.4 Thermal Conduction

**Summary** Here we shall learn how to deal with a time dependent parabolic problem. We shall also show how to treat an axisymmetric problem and show also how to deal with a nonlinear problem.

**How air cools a plate** We seek the temperature distribution in a plate  $(0, Lx) \times (0, Ly) \times (0, Lz)$  of rectangular cross section  $\Omega = (0, 6) \times (0, 1)$ ; the plate is surrounded by air at temperature  $u_e$  and initially at temperature  $u = u_0 + \frac{x}{L}u_1$ . In the plane perpendicular to the plate at  $z = Lz/2$ , the temperature varies little with the coordinate  $z$ ; as a first approximation the problem is 2D.

We must solve the temperature equation in  $\Omega$  in a time interval  $(0, T)$ .

$$\begin{aligned} \partial_t u - \nabla \cdot (\kappa \nabla u) &= 0 \text{ in } \Omega \times (0, T), \\ u(x, y, 0) &= u_0 + xu_1 \\ \kappa \frac{\partial u}{\partial n} + \alpha(u - u_e) &= 0 \text{ on } \Gamma \times (0, T). \end{aligned} \quad (3.2)$$

Here the diffusion  $\kappa$  will take two values, one below the middle horizontal line and ten times less above, so as to simulate a thermostat. The term  $\alpha(u - u_e)$  accounts for the loss of temperature by convection in air. Mathematically this boundary condition is of Fourier (or Robin, or mixed) type.

The variational formulation is in  $L^2(0, T; H^1(\Omega))$ ; in loose terms and after applying an implicit Euler finite difference approximation in time; we shall seek  $u^n(x, y)$  satisfying for all  $w \in H^1(\Omega)$ :

$$\int_{\Omega} \left( \frac{u^n - u^{n-1}}{\delta t} w + \kappa \nabla u^n \nabla w \right) + \int_{\Gamma} \alpha(u^n - u_e) w = 0$$

```
func u0 = 10 + 90 * x / 6;
func k = 1.8 * (y < 0.5) + 0.2;
real ue = 25, alpha = 0.25, T = 5, dt = 0.1;

mesh Th = square(30, 5, [6 * x, y]);
fespace Vh(Th, P1);
Vh u = u0, v, uold;

problem thermic(u, v) = int2d(Th)(u * v / dt + k * (dx(u) * dx(v) + dy(u) * dy(v)))
+ int1d(Th, 1, 3)(alpha * u * v)
- int1d(Th, 1, 3)(alpha * ue * v)
- int2d(Th)(uold * v / dt) + on(2, 4, u = u0);

ofstream ff("thermic.dat");
for(real t = 0; t < T; t += dt){
    uold = u; // uold ≡ u^{n-1} = u^n ≡ u
    thermic; // here solve the thermic problem
    ff << u(3, 0.5) << endl;
    plot(u);
}
```

Notice that we must separate by hand the bilinear part from the linear one.



Notice also that the way we store the temperature at point (3,0.5) for all times in file `thermic.dat`. Should a one dimensional plot be required, the same procedure can be used. For instance to print  $x \mapsto \frac{\partial u}{\partial y}(x, 0.9)$  one would do

```
for(int i=0;i<20;i++) cout<<dy(u)(6.0*i/20.0,0.9)<<endl;
```

Results are shown on Figure 3.4.




Figure 3.4: Temperature at  $T=4.9$ . Right: decay of temperature versus time at  $x=3, y=0.5$

### 3.4.1 Axisymmetry: 3D Rod with circular section

Let us now deal with a cylindrical rod instead of a flat plate. For simplicity we take  $\kappa = 1$ . In cylindrical coordinates, the Laplace operator becomes ( $r$  is the distance to the axis,  $z$  is the distance along the axis,  $\theta$  polar angle in a fixed plane perpendicular to the axis):

$$\Delta u = \frac{1}{r} \partial_r(r \partial_r u) + \frac{1}{r^2} \partial_{\theta\theta}^2 u + \partial_{zz}^2.$$

Symmetry implies that we loose the dependence with respect to  $\theta$ ; so the domain  $\Omega$  is again a rectangle  $]0, R[ \times ]0, L[$ . We take the convention of numbering of the edges as in `square()` (1 for the bottom horizontal ...); the problem is now:

$$\begin{aligned} r \partial_r u - \partial_r(r \partial_r u) - \partial_z(r \partial_z u) &= 0 \text{ in } \Omega, \\ u(t=0) &= u_0 + \frac{z}{L_z}(u_1 - u_0) \\ u|_{\Gamma_4} &= u_0, \quad u|_{\Gamma_2} = u_1, \quad \alpha(u - u_e) + \frac{\partial u}{\partial n}|_{\Gamma_1 \cup \Gamma_3} = 0. \end{aligned} \quad (3.3)$$

Note that the PDE has been multiplied by  $r$ .

After discretization in time with an implicit scheme, with time steps  $dt$ , in the FreeFem++ syntax  $r$  becomes  $x$  and  $z$  becomes  $y$  and the problem is:

```
problem thermaxi(u,v)=int2d(Th)((u*v/dt + dx(u)*dx(v) + dy(u)*dy(v))*x)
+ int1d(Th,3)(alpha*x*u*v) - int1d(Th,3)(alpha*x*ue*v)
- int2d(Th)(uold*v*x/dt) + on(2,4,u=u0);
```

Notice that the bilinear form degenerates at  $x = 0$ . Still one can prove existence and uniqueness for  $u$  and because of this degeneracy no boundary conditions need to be imposed on  $\Gamma_1$ .

### 3.4.2 A Nonlinear Problem : Radiation

Heat loss through radiation is a loss proportional to the absolute temperature to the fourth power (Stefan's Law). This adds to the loss by convection and gives the following boundary condition:

$$\kappa \frac{\partial u}{\partial n} + \alpha(u - u_e) + c[(u + 273)^4 - (u_e + 273)^4] = 0$$

The problem is nonlinear, and must be solved iteratively. If  $m$  denotes the iteration index, a semi-linearization of the radiation condition gives

$$\frac{\partial u^{m+1}}{\partial n} + \alpha(u^{m+1} - u_e) + c(u^{m+1} - u_e)(u^m + u_e + 546)((u^m + 273)^2 + (u_e + 273)^2) = 0,$$

because we have the identity  $a^4 - b^4 = (a - b)(a + b)(a^2 + b^2)$ . The iterative process will work with  $v = u - u_e$ .

```
...
fespace Vh(Th,P1);
real rad=1e-8, uek=ue+273; // finite element space
Vh vold,w,v=u0-ue,b; // def of the physical constants
problem thermradia(v,w)
= int2d(Th)(v*w/dt + k*(dx(v) * dx(w) + dy(v) * dy(w)))
+ int1d(Th,1,3)(b*v*w)
- int2d(Th)(vold*w/dt) + on(2,4,v=u0-ue);

for(real t=0;t<T;t+=dt){
  vold=v;
  for(int m=0;m<5;m++){
    b= alpha + rad * (v + 2*uek) * ((v+uek)^2 + uek^2);
    thermradia;
  }
}
vold=v+ue; plot(vold);
```

## 3.5 Irrotational Fan Blade Flow and Thermal effects

**Summary** Here we will learn how to deal with a multi-physics system of PDEs on a Complex geometry, with multiple meshes within one problem. We also learn how to manipulate the region indicator and see how smooth is the projection operator from one mesh to another.

**Incompressible flow** Without viscosity and vorticity incompressible flows have a velocity given by:

$$u = \begin{pmatrix} \frac{\partial \psi}{\partial x_2} \\ -\frac{\partial \psi}{\partial x_1} \end{pmatrix}, \quad \text{where } \psi \text{ is solution of } \Delta \psi = 0$$

This equation expresses both incompressibility ( $\nabla \cdot u = 0$ ) and absence of vortex ( $\nabla \times u = 0$ ). As the fluid slips along the walls, normal velocity is zero, which means that  $\psi$  satisfies:

$$\psi \text{ constant on the walls.}$$

One can also prescribe the normal velocity at an artificial boundary, and this translates into non constant Dirichlet data for  $\psi$ .

**Airfoil** Let us consider a wing profile  $S$  in a uniform flow. Infinity will be represented by a large circle  $C$  where the flow is assumed to be of uniform velocity; one way to model this problem is to write

$$\Delta \psi = 0 \text{ in } \Omega, \quad \psi|_S = 0, \quad \psi|_C = u_\infty y, \quad (3.4)$$

where  $\partial\Omega = C \cup S$

**The NACA0012 Airfoil** An equation for the upper surface of a NACA0012 (this is a classical wing profile in aerodynamics) is:

$$y = 0.17735 \sqrt{x} - 0.075597x - 0.212836x^2 + 0.17363x^3 - 0.06254x^4.$$

### Example 3.5 (potential.edp)

// file potential.edp

```
real S=99;
border C(t=0,2*pi) { x=5*cos(t); y=5*sin(t);}
border Splus(t=0,1){ x = t; y = 0.17735*sqrt(t)-0.075597*t
- 0.212836*(t^2)+0.17363*(t^3)-0.06254*(t^4); label=S;}
border Sminus(t=1,0){ x =t; y= -(0.17735*sqrt(t)-0.075597*t
-0.212836*(t^2)+0.17363*(t^3)-0.06254*(t^4)); label=S;}
mesh Th= buildmesh(C(50)+Splus(70)+Sminus(70));
fespace Vh(Th,P2); Vh psi,w;

solve potential(psi,w)=int2d(Th)(dx(psi)*dx(w)+dy(psi)*dy(w))+
on(C,psi = y) + on(S,psi=0);

plot(psi,wait=1);
```

A zoom of the streamlines are shown on Figure 3.5.




Figure 3.5: Zoom around the NACA0012 airfoil showing the streamlines (curve  $\psi = \text{constant}$ ). To obtain such a plot use the interactive graphic command: “+” and p. Right: temperature distribution at time  $T=25$  (now the maximum is at 90 instead of 120). Note that an incidence angle has been added here (see Chapter 9).

### 3.5.1 Heat Convection around the airfoil

Now let us assume that the airfoil is hot and that air is there to cool it. Much like in the previous section the heat equation for the temperature  $u$  is

$$\partial_t v - \nabla \cdot (\kappa \nabla v) + u \cdot \nabla v = 0, \quad v(t=0) = v_0, \quad \frac{\partial v}{\partial n}|_C = 0$$

But now the domain is outside AND inside  $S$  and  $\kappa$  takes a different value in air and in steel. Furthermore there is convection of heat by the flow, hence the term  $u \cdot \nabla v$  above. Consider the following, to be plugged at the end of the previous program:

```
...
border D(t=0,2){x=1+t;y=0;} // added to have a fine mesh at trail
mesh Sh = buildmesh(C(25)+Splus(-90)+Sminus(-90)+D(200));
fespace Wh(Sh,P1); Wh v,vv;
int steel=Sh(0.5,0).region, air=Sh(-1,0).region;
fespace W0(Sh,P0);
W0 k=0.01*(region==air)+0.1*(region==steel);
W0 u1=dy(psi)*(region==air), u2=-dx(psi)*(region==air);
Wh vold = 120*(region==steel);
real dt=0.05, nbT=50;
int i;
problem thermic(v,vv,init=i,solver=LU)= int2d(Sh)(v*vv/dt
+ k*(dx(v) * dx(vv) + dy(v) * dy(vv))
+ 10*(u1*dx(v)+u2*dy(v))*vv)- int2d(Sh)(vold*vv/dt);
for(i=0;i<nbT;i++){
v=vold; thermic;
```

```
plot(v);
}
```

Notice here

- how steel and air are identified by the mesh parameter region which is defined when buildmesh is called and takes an integer value corresponding to each connected component of  $\Omega$ ;
- how the convection terms are added without upwinding. Upwinding is necessary when the Pecley number  $|u|L/\kappa$  is large (here is a typical length scale), The factor 10 in front of the convection terms is a quick way of multiplying the velocity by 10 (else it is too slow to see something).
- The solver is Gauss' LU factorization and when `init`  $\neq 0$  the LU decomposition is reused so it is much faster after the first iteration.

## 3.6 Pure Convection : The Rotating Hill

**Summary** *Here we will present two methods for upwinding for the simplest convection problem. We will learn about Characteristics-Galerkin and Discontinuous-Galerkin Finite Element Methods.*

Let  $\Omega$  be the unit disk centered at 0; consider the rotation vector field

$$\mathbf{u} = [u_1, u_2], \quad u_1 = y, \quad u_2 = -x.$$

Pure convection by  $\mathbf{u}$  is

$$\partial_t c + \mathbf{u} \cdot \nabla c = 0 \quad \text{in } \Omega \times (0, T) \quad c(t=0) = c^0 \quad \text{in } \Omega.$$

The exact solution  $c(x_t, t)$  at time  $t$  en point  $x_t$  is given by

$$c(x_t, t) = c^0(x, 0)$$

where  $x_t$  is the particle path in the flow starting at point  $x$  at time 0. So  $x_t$  are solutions of

$$\dot{x}_t = \mathbf{u}(x_t), \quad , \quad x_{t=0} = x, \quad \text{where} \quad \dot{x}_t = \frac{d(t \mapsto x_t)}{dt}$$

The ODE are reversible and we want the solution at point  $x$  at time  $t$  ( not at point  $x_t$ ) the initial point is  $x_{-t}$ , and we have

$$c(x, t) = c^0(x_{-t}, 0)$$

The game consists in solving the equation until  $T = 2\pi$ , that is for a full revolution and to compare the final solution with the initial one; they should be equal.

**Solution by a Characteristics-Galerkin Method** In FreeFem++ there is an operator called `convect([u1,u2],dt,c)` which compute  $c \circ X$  with  $X$  is the convect field defined by  $X(x) = x_{dt}$  and where  $x_\tau$  is particule path in the steady state velocity field  $\mathbf{u} = [u1, u2]$  starting at point  $x$  at time  $\tau = 0$ , so  $x_\tau$  is solution of the following ODE:

$$\dot{x}_\tau = u(x_\tau), \quad x_{\tau=0} = x.$$

When  $\mathbf{u}$  is piecewise constant; this is possible because  $x_\tau$  is then a polygonal curve which can be computed exactly and the solution exists always when  $\mathbf{u}$  is divergence free; `convect` returns  $c(x_{df}) = C \circ X$ .

### Example 3.6 (convects.edp)

// file convects.edp

```
border C(t=0, 2*pi) { x=cos(t); y=sin(t); };
mesh Th = buildmesh(C(100));
fespace Uh(Th,P1);
Uh cold, c = exp(-10*((x-0.3)^2 +(y-0.3)^2));

real dt = 0.17, t=0;
Uh u1 = y, u2 = -x;
for (int m=0; m<2*pi/dt ; m++) {
  t += dt;      cold=c;
  c=convect([u1,u2],-dt,cold);
  plot(c,cmm=" t="+t + ", min=" + c[].min + ", max=" + c[].max);
}
```

**Remark 4** 3D plots can be done by adding the qualifier "dim=3" to the plot instruction.

The method is very powerful but has two limitations: a/ it is not conservative, b/ it may diverge in rare cases when  $|\mathbf{u}|$  is too small due to quadrature error.

**Solution by Discontinuous-Galerkin FEM** Discontinuous Galerkin methods take advantage of the discontinuities of  $c$  at the edges to build upwinding. There are many formulations possible. We shall implement here the so-called dual- $P_1^{DC}$  formulation (see Ern[11]):

$$\int_{\Omega} \left( \frac{c^{n+1} - c^n}{\delta t} + \mathbf{u} \cdot \nabla c \right) w + \int_E (\alpha |n \cdot \mathbf{u}| - \frac{1}{2} n \cdot \mathbf{u}) [c] w = \int_{E_T^-} |n \cdot \mathbf{u}| c w \quad \forall w$$

where  $E$  is the set of inner edges and  $E_T^-$  is the set of boundary edges where  $\mathbf{u} \cdot \mathbf{n} < 0$  (in our case there is no such edges). Finally  $[c]$  is the jump of  $c$  across an edge with the convention that  $c^+$  refers to the value on the right of the oriented edge.

### Example 3.7 (convects\_end.edp)

// file convects.edp

```
...
fespace Vh(Th,P1dc);

Vh w, ccold, v1 = y, v2 = -x, cc = exp(-10*((x-0.3)^2 +(y-0.3)^2));
real u, al=0.5; dt = 0.05;
```

```

macro n() (N.x*v1+N.y*v2) // Macro without parameter
problem Aduall(cc,w) =
int2d(Th)((cc/dt+(v1*dx(cc)+v2*dy(cc)))*w)
+ intalledges(Th)((1-nTonEdge)*w*(al*abs(n)-n/2)*jump(cc))
// - int1d(Th,C)((n<0)*abs(n)*cc*w) // unused because cc=0 on ∂Ω⁻
- int2d(Th)(ccold*w/dt);

for ( t=0; t< 2*pi ; t+=dt)
{
ccold=cc; Aduall;
plot(cc,fill=1,cmm="t="+t + " , min=" + cc[].min + " , max=" + cc[].max);
};
real [int] viso=[-0.2,-0.1,0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9,1,1.1];
plot(c,wait=1,fill=1,ps="convectCG.eps",viso=viso);
plot(c,wait=1,fill=1,ps="convectDG.eps",viso=viso);

```

Notice the new keywords, `intalledges` to integrate on all edges of all triangles

$$\text{intalledges}(\text{Th}) \equiv \sum_{T \in \text{Th}} \int_{\partial T} \quad (3.5)$$

(so all internal edges are seen two times), `nTonEdge` which is one if the triangle has a boundary edge and zero otherwise, `jump` to implement  $[c]$ . Results of both methods are shown on Figure 3.6 with identical levels for the level line; this is done with the plot-modifier `viso`.

Notice also the macro where the parameter  $u$  is not used (but the syntax needs one) and which ends with a `//`; it simply replaces the name  $n$  by  $(N.x*v1+N.y*v2)$ . As easily guessed  $N.x, N.y$  is the normal to the edge.




Figure 3.6: The rotated hill after one revolution, left with Characteristics-Galerkin, on the right with Discontinuous  $P_1$  Galerkin FEM.

Now if you think that DG is too slow try this

```

// the same DG very much faster
varf aadual(cc,w) = int2d(Th)((cc/dt+(v1*dx(cc)+v2*dy(cc))*w)
    + intalldedges(Th)((1-nTonEdge)*w*(al*abs(n)-n/2)*jump(cc));
varf bbdual(ccold,w) = - int2d(Th)(ccold*w/dt);
matrix AA= aadual(Vh,Vh);
matrix BB = bbdual(Vh,Vh);
set (AA,init=t,solver=sparsesolver);
Vh rhs=0;
for ( t=0; t< 2*pi ; t+=dt)
{
    ccold=cc;
    rhs[] = BB* ccold[];
    cc[] = AA^-1*rhs[];
    plot(cc,fill=0,cmm="t="+t + ", min=" + cc[].min + ", max=" + cc[].max);
};

```

Notice the new keyword `set` to specify a solver in this framework; the modifier `init` is used to tell the solver that the matrix has not changed (`init=true`), and the name parameter are the same that in problem definition (see. 6.9) .

**Finite Volume Methods** can also be handled with `FreeFem++` but it requires programming. For instance the  $P_0 - P_1$  Finite Volume Method of Dervieux et al associates to each  $P_0$  function  $c^1$  a  $P_0$  function  $c^0$  with constant value around each vertex  $q^i$  equal to  $c^1(q^i)$  on the cell  $\sigma_i$  made by all the medians of all triangles having  $q^i$  as vertex. Then upwinding is done by taking left or right values at the median:

$$\int_{\sigma_i} \frac{1}{\delta t} (c^{1^{n+1}} - c^{1^n}) + \int_{\partial\sigma_i} u \cdot nc^- = 0 \quad \forall i$$

It can be programmed as

```

load "mat_dervieux"; // external module in C++ must be loaded
border a(t=0, 2*pi){ x = cos(t); y = sin(t); }
mesh th = buildmesh(a(100));
fespace Vh(th,P1);

Vh vh,vold,u1 = y, u2 = -x;
Vh v = exp(-10*((x-0.3)^2 +(y-0.3)^2)), vWall=0, rhs =0;

real dt = 0.025;

// qf1pTlump means mass lumping is used
problem FVM(v,vh) = int2d(th,qft=qf1pTlump)(v*vh/dt)
    - int2d(th,qft=qf1pTlump)(vold*vh/dt)
    + int1d(th,a)((u1*N.x+u2*N.y)<0)*(u1*N.x+u2*N.y)*vWall*vh
+ rhs[] ;

matrix A;
MatUpWind0(A,th,vold,[u1,u2]);

for ( int t=0; t< 2*pi ; t+=dt){
    vold=v;
    rhs[] = A * vold[] ; FVM;
    plot(v,wait=0);
};

```



the mass lumping parameter forces a quadrature formula with Gauss points at the vertices so as to make the mass matrix diagonal; the linear system solved by a conjugate gradient method for instance will then converge in one or two iterations.

The right hand side rhs is computed by an external C++ function `MatUpWind0(...)` which is programmed as

```

// computes matrix a on a triangle for the Dervieux FVM
int fvmP1P0(double q[3][2], // the 3 vertices of a triangle T
            double u[2], // convection velocity on T
            double c[3], // the P1 function on T
            double a[3][3], // output matrix
            double where[3] ) // where>0 means we're on the boundary
{
    for(int i=0;i<3;i++) for(int j=0;j<3;j++) a[i][j]=0;

    for(int i=0;i<3;i++){
        int ip = (i+1)%3, ipp = (ip+1)%3;
        double unL = -((q[ip][1]+q[i][1]-2*q[ipp][1])*u[0]
                       -(q[ip][0]+q[i][0]-2*q[ipp][0])*u[1])/6;
        if(unL>0) { a[i][i] += unL; a[ip][i]-=unL;}
        else{ a[i][ip] += unL; a[ip][ip]-=unL;}
        if(where[i]&&where[ip]){ // this is a boundary edge
            unL=((q[ip][1]-q[i][1])*u[0] -(q[ip][0]-q[i][0])*u[1])/2;
            if(unL>0) { a[i][i]+=unL; a[ip][ip]+=unL;}
        }
    }
    return 1;
}

```

It must be inserted into a larger .cpp file, shown in Appendix A, which is the load module linked to FreeFem++ .

### 3.7 A Projection Algorithm for the Navier-Stokes equations

**Summary** *Fluid flows require good algorithms and good triangulations. We show here an example of a complex algorithm and our first example of mesh adaptation.*

An incompressible viscous fluid satisfies:

$$\partial_t u + u \cdot \nabla u + \nabla p - \nu \Delta u = 0, \quad \nabla \cdot u = 0 \quad \text{in } \Omega \times ]0, T[,$$

$$u|_{t=0} = u^0, \quad u|_{\Gamma} = u_{\Gamma}.$$

A possible algorithm, proposed by Chorin, is

$$\frac{1}{\delta t} [u^{m+1} - u^m \circ X^m] + \nabla p^m - \nu \Delta u^m = 0, \quad u|_{\Gamma} = u_{\Gamma},$$

$$-\Delta p^{m+1} = -\nabla \cdot u^m \circ X^m, \quad \partial_n p^{m+1} = 0,$$

where  $u \circ X(x) = u(x - u(x)\delta t)$  since  $\partial_t u + u \cdot \nabla u$  is approximated by the method of characteristics, as in the previous section.

An improvement over Chorin's algorithm, given by Rannacher, is to compute a correction,  $q$ , to the pressure (the overline denotes the mean over  $\Omega$ )

$$-\Delta q = \nabla \cdot \mathbf{u} - \overline{\nabla \cdot \mathbf{u}}$$

and define

$$\mathbf{u}^{m+1} = \tilde{\mathbf{u}} + \nabla q \delta t, \quad p^{m+1} = p^m - q - \overline{p^m - q}$$

where  $\tilde{\mathbf{u}}$  is the  $(\mathbf{u}^{m+1}, \mathbf{v}^{m+1})$  of Chorin's algorithm.

**The backward facing step** The geometry is that of a channel with a backward facing step so that the inflow section is smaller than the outflow section. This geometry produces a fluid recirculation zone that must be captured correctly.

This can only be done if the triangulation is sufficiently fine, or well adapted to the flow.

### Example 3.8 (NSprojection.edp)

// file NSprojection.edp

```
border a0(t=1,0){ x=0;      y=t;      label=1;}
border a1(t=0,1){ x=2*t;    y=0;      label=2;}
border a2(t=0,1){ x=2;      y=-t/2;   label=2;}
border a3(t=0,1){ x=2+18*t^1.2; y=-0.5; label=2;}
border a4(t=0,1){ x=20;     y=-0.5+1.5*t; label=3;}
border a5(t=1,0){ x=20*t;   y=1;     label=4;}
int n=1;
mesh Th= buildmesh(a0(3*n)+a1(20*n)+a2(10*n)+a3(150*n)+a4(5*n)+a5(100*n));
plot(Th);
fespace Vh(Th,P1);
real nu = 0.0025, dt = 0.2;
Vh w,u = 4*y*(1-y)*(y>0)*(x<2), v = 0, p = 0, q=0;
real area= int2d(Th)(1.);

for(int n=0;n<100;n++){
  Vh uold = u, vold = v, pold=p;
  Vh f=convect([u,v],-dt,uold), g=convect([u,v],-dt,vold);

  solve pb4u(u,w,init=n,solver=LU)
    =int2d(Th)(u*w/dt +nu*(dx(u)*dx(w)+dy(u)*dy(w)))
    -int2d(Th)((f/dt-dx(p))*w)
    + on(1,u = 4*y*(1-y)) + on(2,4,u = 0) + on(3,u=f);
  plot(u);

  solve pb4v(v,w,init=n,solver=LU)
    = int2d(Th)(v*w/dt +nu*(dx(v)*dx(w)+dy(v)*dy(w)))
    -int2d(Th)((g/dt-dy(p))*w)
    +on(1,2,3,4,v = 0);

  real meandiv = int2d(Th)(dx(u)+dy(v))/area;

  solve pb4p(q,w,init=n,solver=LU)= int2d(Th)(dx(q)*dx(w)+dy(q)*dy(w))
    - int2d(Th)((dx(u)+ dy(v)-meandiv)*w/dt)+ on(3,q=0);

  real meanpq = int2d(Th)(pold - q)/area;
  if(n==50){
```

// Reynolds=400

```

    Th = adaptmesh(Th,u,v,q); plot(Th, wait=true);
}
p = pold-q-meanpq;
u = u + dx(q)*dt;
v = v + dy(q)*dt;
}

```




Figure 3.7: Rannacher's projection algorithm: result on an adapted mesh (top) showing the pressure (middle) and the horizontal velocity  $u$  at Reynolds 400.

We show in figure 3.7 the numerical results obtained for a Reynolds number of 400 where mesh adaptation is done after 50 iterations on the first mesh.

### 3.8 The System of elasticity

**Elasticity** Solid objects deform under the action of applied forces: a point in the solid, originally at  $(x, y, z)$  will come to  $(X, Y, Z)$  after some time; the vector  $\mathbf{u} = (u_1, u_2, u_3) = (X - x, Y - y, Z - z)$  is called the displacement. When the displacement is small and the solid is elastic, Hooke's law gives a relationship between the stress tensor  $\sigma(u) = (\sigma_{ij}(u))$  and the strain tensor  $\epsilon(u) = \epsilon_{ij}(u)$

$$\sigma_{ij}(u) = \lambda \delta_{ij} \nabla \cdot \mathbf{u} + 2\mu \epsilon_{ij}(u),$$

where the Kronecker symbol  $\delta_{ij} = 1$  if  $i = j$ , 0 otherwise, with

$$\epsilon_{ij}(u) = \frac{1}{2} \left( \frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right),$$

and where  $\lambda, \mu$  are two constants that describe the mechanical properties of the solid, and are themselves related to the better known constants  $E$ , Young's modulus, and  $\nu$ , Poisson's ratio:

$$\mu = \frac{E}{2(1 + \nu)}, \quad \lambda = \frac{E\nu}{(1 + \nu)(1 - 2\nu)}.$$

**Lamé's system** Let us consider a beam with axis  $Oz$  and with perpendicular section  $\Omega$ . The components along  $x$  and  $y$  of the strain  $\mathbf{u}(x)$  in a section  $\Omega$  subject to forces  $\mathbf{f}$  perpendicular to the axis are governed by

$$-\mu \Delta \mathbf{u} - (\mu + \lambda) \nabla(\nabla \cdot \mathbf{u}) = \mathbf{f} \text{ in } \Omega,$$

where  $\lambda, \mu$  are the Lamé coefficients introduced above.

Remark, we do not use this equation because the associated variational form does not give the right boundary condition, we simply use

$$-\text{div}(\sigma) = \mathbf{f} \text{ in } \Omega$$

where the corresponding variational form is:

$$\int_{\Omega} \sigma(u) : \epsilon(v) dx - \int_{\Omega} v f dx = 0;$$

where  $:$  denote the tensor scalar product, i.e.  $a : b = \sum_{i,j} a_{ij} b_{ij}$ .

So the variational form can be written as :

$$\int_{\Omega} \lambda \nabla \cdot u \nabla \cdot v + 2\mu \epsilon(u) : \epsilon(v) dx - \int_{\Omega} v f dx = 0;$$

**Example** Consider elastic plate with the undeformed rectangle shape  $[0, 20] \times [-1, 1]$ . The body force is the gravity force  $\mathbf{f}$  and the boundary force  $\mathbf{g}$  is zero on lower, upper and right sides. The left vertical sides of the beam is fixed. The boundary conditions are

$$\begin{aligned} \sigma \cdot \mathbf{n} &= \mathbf{g} = 0 \text{ on } \Gamma_1, \Gamma_4, \Gamma_3, \\ \mathbf{u} &= \mathbf{0} \text{ on } \Gamma_2 \end{aligned}$$

Here  $\mathbf{u} = (u, v)$  has two components.

The above two equations are strongly coupled by their mixed derivatives, and thus any iterative solution on each of the components is risky. One should rather use FreeFem++'s system approach and write:

### Example 3.9 (lame.edp)

```

// file lame.edp
mesh Th=square(10,10,[20*x,2*y-1]);
fespace Vh(Th,P2);
Vh u,v,uu,vv;
real sqrt2=sqrt(2.);
macro epsilon(u1,u2) [dx(u1),dy(u2),(dy(u1)+dx(u2))/sqrt2] // EOM
// the sqrt2 is because we want: epsilon(u1,u2)'* epsilon(v1,v2) == epsilon(u):epsilon(v)
macro div(u,v) ( dx(u)+dy(v) ) // EOM

real E = 21e5, nu = 0.28, mu= E/(2*(1+nu));
real lambda = E*nu/((1+nu)*(1-2*nu)), f = -1; //

solve lame([u,v],[uu,vv])= int2d(Th)(
    lambda*div(u,v)*div(uu,vv)
```

```

+2.*mu*( epsilon(u,v)'*epsilon(uu,vv) ) )
- int2d(Th)(f*vv)
+ on(4,u=0,v=0);
real coef=100;
plot([u,v],wait=1,ps="lamevect.eps",coef=coef);

mesh th1 = movemesh(Th, [x+u*coef, y+v*coef]);
plot(th1,wait=1,ps="lamedeform.eps");
real dxmin = u[].min;
real dymin = v[].min;

cout << " - dep. max x = "<< dxmin<< " y=" << dymin << endl;
cout << " dep. (20,0) = "<< u(20,0) << " " << v(20,0) << endl;

```

The numerical results are shown on figure 3.8 and the output is:

```

-- square mesh : nb vertices =121 , nb triangles = 200 , nb boundary edges 40
-- Solve : min -0.00174137 max 0.00174105
min -0.0263154 max 1.47016e-29
- dep. max x = -0.00174137 y=-0.0263154
dep. (20,0) = -1.8096e-07 -0.0263154
times: compile 0.010219s, execution 1.5827s

```




Figure 3.8: Solution of Lamé's equations for elasticity for a 2D beam deflected by its own weight and clamped by its left vertical side; result are shown with a amplification factor equal to 100. *Remark: the size of the arrow is automatically bound, but the color gives the real length*

## 3.9 The System of Stokes for Fluids

In the case of a flow invariant with respect to the third coordinate (two-dimensional flow), flows at low Reynolds number (for instance micro-organisms) satisfy,

$$\begin{aligned} -\Delta \mathbf{u} + \nabla p &= 0 \\ \nabla \cdot \mathbf{u} &= 0 \end{aligned}$$

where  $\mathbf{u} = (u_1, u_2)$  is the fluid velocity and  $p$  its pressure.

The driven cavity is a standard test. It is a box full of liquid with its lid moving horizontally at speed one. The pressure and the velocity must be discretized in compatible finite element spaces for the LBB conditions to be satisfied:

$$\sup_{p \in P_h} \frac{(\mathbf{u}, \nabla p)}{|p|} \geq \beta |\mathbf{u}| \quad \forall \mathbf{u} \in U_h$$

```

// file stokes.edp

int n=3;
mesh Th=square(10*n,10*n);
fespace Uh(Th,P1b); Uh u,v,uu,vv;
fespace Ph(Th,P1); Ph p,pp;

solve stokes([u,v,p],[uu,vv,pp]) =
  int2d(Th)(dx(u)*dx(uu)+dy(u)*dy(uu) + dx(v)*dx(vv)+ dy(v)*dy(vv)
    + dx(p)*uu + dy(p)*vv + pp*(dx(u)+dy(v))
    - 1e-10*p*pp)
  + on(1,2,4,u=0,v=0) + on(3,u=1,v=0);
plot([u,v],p,wait=1);

```

Remark, we add a stabilization term  $-10e-10*p*pp$  to fix the constant part of the pressure.




Figure 3.9: Solution of Stokes' equations for the driven cavity problem, showing the velocity field and the pressure level lines.

Results are shown on figure 3.9

### 3.10 A Large Fluid Problem

A friend of one of us in Auroville-India was building a ramp to access an air conditioned room. As I was visiting the construction site he told me that he expected to cool air escaping by the door to the room to slide down the ramp and refrigerate the feet of the coming visitors. I told him "no way" and decided to check numerically. The results are on the front page of this book.

The fluid velocity and pressure are solution of the Navier-Stokes equations with varying density function of the temperature.

The geometry is trapezoidal with prescribed inflow made of cool air at the bottom and warm air above and so are the initial conditions; there is free outflow, slip velocity at the top (artificial) boundary and no-slip at the bottom. However the Navier-Stokes cum temperature equations have a RANS  $k - \epsilon$  model and a Boussinesq approximation for the buoyancy. This comes to

$$\begin{aligned}
 \partial_t \theta + u \nabla \theta - \nabla \cdot (\kappa_T^m \nabla \theta) &= 0 \\
 \partial_t u + u \nabla u - \nabla \cdot (\mu_T \nabla u) + \nabla p + e(\theta - \theta_0) \mathbf{e}_2, \quad \nabla \cdot u &= 0 \\
 \mu_T = c_\mu \frac{k^2}{\epsilon}, \quad \kappa_T = \kappa \mu_T \\
 \partial_t k + u \nabla k + \epsilon - \nabla \cdot (\mu_T \nabla k) &= \frac{\mu_T}{2} |\nabla u + \nabla u^T|^2 \\
 \partial_t \epsilon + u \nabla \epsilon + c_2 \frac{\epsilon^2}{k} - \frac{c_\epsilon}{c_\mu} \nabla \cdot (\mu_T \nabla \epsilon) &= \frac{c_1}{2} k |\nabla u + \nabla u^T|^2 = 0
 \end{aligned} \tag{3.6}$$

We use a time discretization which preserves positivity and uses the method of characteristics ( $X^m(x) \approx x - u^m(x) \delta t$ )

$$\begin{aligned}
 \frac{1}{\delta t} (\theta^{m+1} - \theta^m \circ X^m) - \nabla \cdot (\kappa_T^m \nabla \theta^{m+1}) &= 0 \\
 \frac{1}{\delta t} (u^{m+1} - u^m \circ X^m) - \nabla \cdot (\mu_T^m \nabla u^{m+1}) + \nabla p^{m+1} + e(\theta^{m+1} - \theta_0) \mathbf{e}_2, \quad \nabla \cdot u^{m+1} &= 0 \\
 \frac{1}{\delta t} (k^{m+1} - k^m \circ X^m) + k^{m+1} \frac{\epsilon^m}{k^m} - \nabla \cdot (\mu_T^m \nabla k^{m+1}) &= \frac{\mu_T^m}{2} |\nabla u^m + \nabla u^{mT}|^2 \\
 \frac{1}{\delta t} (\epsilon^{m+1} - \epsilon^m \circ X^m) + c_2 \epsilon^{m+1} \frac{\epsilon^m}{k^m} - \frac{c_\epsilon}{c_\mu} \nabla \cdot (\mu_T^m \nabla \epsilon^{m+1}) &= \frac{c_1}{2} k^m |\nabla u^m + \nabla u^{mT}|^2 \\
 \mu_T^{m+1} = c_\mu \frac{k^{m+12}}{\epsilon^{m+1}}, \quad \kappa_T^{m+1} = \kappa \mu_T^{m+1}
 \end{aligned} \tag{3.7}$$

In variational form and with appropriated boundary conditions the problem is:

```

real L=6;
border aa(t=0,1){x=t; y=0 ;}
border bb(t=0,14){x=1+t; y= - 0.1*t ;}
border cc(t=-1.4,L){x=15; y=t ;}
border dd(t=15,0){x= t ; y = L;}
border ee(t=L,0.5){ x=0; y=t ;}
border ff(t=0.5,0){ x=0; y=t ;}
int n=8;
mesh Th=buildmesh(aa(n)+bb(9*n) + cc(4*n) + dd(10*n)+ee(6*n) + ff(n));
real s0=clock();

fespace Vh2(Th,P1b); // velocity space
fespace Vh(Th,P1); // pressure space
fespace V0h(Th,P0); // for gradients

```

```

Vh2 u2,v2,up1=0,up2=0;
Vh2 u1,v1;
Vh u1x=0,u1y,u2x,u2y, vv;

real reynods=500;
// cout << " Enter the reynolds number :"; cin >> reynods;
assert(reynods>1 && reynods < 100000);
up1=0;
up2=0;
func g=(x)*(1-x)*4; // inflow
Vh p=0,q, temp1,temp=35, k=0.001,k1,ep=0.0001,ep1;
V0h muT=1,prodk,prode, kappa=0.25e-4, stress;
real alpha=0, eee=9.81/303, c1m = 1.3/0.09 ;
real nu=1, numu=nu/sqrt( 0.09), nuep=pow(nu,1.5)/4.1;
int i=0,iter=0;
real dt=0;
problem TEMPER(temp,q) = // temperature equation
    int2d(Th)(
        alpha*temp*q + kappa * ( dx(temp)*dx(q) + dy(temp)*dy(q) ))
        // + int1d(Th,aa,bb)(temp*q* 0.1)
    + int2d(Th) ( -alpha*convect([up1,up2],-dt,temp1)*q )
    + on(ff,temp=25)
    + on(aa,bb,temp=35) ;

problem kine(k,q)= // get the kinetic turbulent energy
    int2d(Th)(
        (ep1/k1+alpha)*k*q + muT * ( dx(k)*dx(q) + dy(k)*dy(q) ))
        // + int1d(Th,aa,bb)(temp*q*0.1)
    + int2d(Th) ( prodk*q-alpha*convect([up1,up2],-dt,k1)*q )
    + on(ff,k=0.0001) + on(aa,bb,k=numu*stress) ;

problem viscturb(ep,q)= // get the rate of turbulent viscous energy
    int2d(Th)(
        (1.92*ep1/k1+alpha)*ep*q + c1m*muT * ( dx(ep)*dx(q) + dy(ep)*dy(q) ))
        // + int1d(Th,aa,bb)(temp*q*0.1)
    + int2d(Th) ( prode*q-alpha*convect([up1,up2],-dt,ep1)*q )
    + on(ff,ep= 0.0001) + on(aa,bb,ep=nuep*pow(stress,1.5)) ;

solve NS ([u1,u2,p],[v1,v2,q]) = // Navier-Stokes k-epsilon and Boussinesq
    int2d(Th)(
        alpha*( u1*v1 + u2*v2)
        + muT * (dx(u1)*dx(v1)+dy(u1)*dy(v1)+dx(u2)*dx(v2)+dy(u2)*dy(v2))
        // ( 2*dx(u1)*dx(v1) + 2*dy(u2)*dy(v2)+(dy(u1)+dx(u2))*(dy(v1)+dx(v2)))
        + p*q*(0.000001)
        - p*dx(v1) - p*dy(v2)
        - dx(u1)*q - dy(u2)*q
    )
    + int1d(Th,aa,bb,dd)(u1*v1* 0.1)
    + int2d(Th) (eee*(temp-35)*v1 -alpha*convect([up1,up2],-dt,up1)*v1
        -alpha*convect([up1,up2],-dt,up2)*v2 )
    + on(ff,u1=3,u2=0)
    + on(ee,u1=0,u2=0)
    + on(aa,dd,u2=0)
    + on(bb,u2= -up1*N.x/N.y)
    + on(cc,u2=0) ;

```



```

plot(coef=0.2,cmm=" [u1,u2] et p ",p,[u1,u2],ps="StokesP2P1.eps",value=1,wait=1);
{
  real[int] xx(21),yy(21),pp(21);
  for (int i=0;i<21;i++)
  {
    yy[i]=i/20.;
    xx[i]=u1(0.5,i/20.);
    pp[i]=p(i/20.,0.999);
  }
  cout << " " << yy << endl;
                                     //      plot([xx,yy],wait=1,cmm="u1 x=0.5 cup");
                                     //      plot([yy,pp],wait=1,cmm="pressure y=0.999 cup");
}

dt = 0.05;
int nbiter = 3;
real coefdt = 0.25^(1./nbiter);
real coefcut = 0.25^(1./nbiter) , cut=0.01;
real tol=0.5,coeftol = 0.5^(1./nbiter);
nu=1./reynolds;

for (iter=1;iter<=nbiter;iter++)
{
  cout << " dt = " << dt << " ----- " << endl;
  alpha=1/dt;
  for (i=0;i<=500;i++)
  {
    up1=u1;
    up2=u2;
    temp1=max(temp,25);
    temp1=min(temp1,35);
    k1=k; ep1=ep;
    muT=0.09*k*k/ep;
    NS; plot([u1,u2],wait=1); //      Solves Navier-Stokes
    prode =0.126*k*(pow(2*dx(u1),2)+pow(2*dy(u2),2)+2*pow(dx(u2)+dy(u1),2))/2;
    prodk= prode*k/ep*0.09/0.126;
    kappa=muT/0.41;
    stress=abs(dy(u1));
    kine; plot(k,wait=1);
    viscturb; plot(ep,wait=1);
    TEMPER; //      solves temperature equation
    if ( !(i % 5)){
      plot(temp,value=1,fill=true,ps="temp_"+iter+"_"+i+".ps");
      plot(coef=0.2,cmm=" [u1,u2] et p ",p,[u1,u2],ps="plotNS_"+iter+"_"+i+".ps");
    }
    cout << "CPU " << clock()-s0 << "s " << endl;
  }

  if (iter>= nbiter) break;
  Th=adaptmesh(Th,[dx(u1),dy(u1),dx(u1),dy(u2)],splitpbedge=1,
    absserror=0,cutoff=cut,err=tol, inquire=0,ratio=1.5,hmin=1./1000);
  plot(Th,ps="ThNS.eps");
  dt = dt*coefdt;
  tol = tol *coeftol;
  cut = cut *coefcut;
}

```

```
cout << "CPU " << clock()-s0 << "s " << endl;
```

### 3.11 An Example with Complex Numbers

In a microwave oven heat comes from molecular excitation by an electromagnetic field. For a plane monochromatic wave, amplitude is given by Helmholtz's equation:

$$\beta v + \Delta v = 0.$$

We consider a rectangular oven where the wave is emitted by part of the upper wall. So the boundary of the domain is made up of a part  $\Gamma_1$  where  $v = 0$  and of another part  $\Gamma_2 = [c, d]$  where for instance  $v = \sin(\pi \frac{y-c}{c-d})$ .

Within an object to be cooked, denoted by  $B$ , the heat source is proportional to  $v^2$ . At equilibrium, one has

$$-\Delta \theta = v^2 I_B, \quad \theta_\Gamma = 0$$

where  $I_B$  is 1 in the object and 0 elsewhere.




Figure 3.10: A microwave oven: real (left) and imaginary (middle) parts of wave and temperature (right).

Results are shown on figure 3.10

In the program below  $\beta = 1/(1 - I/2)$  in the air and  $2/(1 - I/2)$  in the object ( $i = \sqrt{-1}$ ):

#### Example 3.10 (muwave.edp)

```
real a=20, b=20, c=15, d=8, e=2, l=12, f=2, g=2;
border a0(t=0,1) {x=a*t; y=0;label=1;}
border a1(t=1,2) {x=a; y= b*(t-1);label=1;}
border a2(t=2,3) { x=a*(3-t);y=b;label=1;}
border a3(t=3,4){x=0;y=b-(b-c)*(t-3);label=1;}
border a4(t=4,5){x=0;y=c-(c-d)*(t-4);label=2;}
border a5(t=5,6){ x=0; y= d*(6-t);label=1;}

border b0(t=0,1) {x=a-f+e*(t-1);y=g; label=3;}
```

// file muwave.edp

```

border b1(t=1,4) {x=a-f; y=g+l*(t-1)/3; label=3;}
border b2(t=4,5) {x=a-f-e*(t-4); y=l+g; label=3;}
border b3(t=5,8) {x=a-e-f; y= l+g-l*(t-5)/3; label=3;}
int n=2;
mesh Th = buildmesh(a0(10*n)+a1(10*n)+a2(10*n)+a3(10*n)
+a4(10*n)+a5(10*n)+b0(5*n)+b1(10*n)+b2(5*n)+b3(10*n));
plot(Th,wait=1);
fespace Vh(Th,P1);
real meat = Th(a-f-e/2,g+l/2).region, air= Th(0.01,0.01).region;
Vh R=(region-air)/(meat-air);

Vh<complex> v,w;
solve muwave(v,w) = int2d(Th)(v*w*(1+R)
-(dx(v)*dx(w)+dy(v)*dy(w))*(1-0.5i))
+ on(1,v=0) + on(2, v=sin(pi*(y-c)/(c-d)));
Vh vr=real(v), vi=imag(v);
plot(vr,wait=1,ps="rmuonde.ps", fill=true);
plot(vi,wait=1,ps="imuonde.ps", fill=true);

fespace Uh(Th,P1); Uh u,uu, ff=1e5*(vr^2 + vi^2)*R;

solve temperature(u,uu)= int2d(Th)(dx(u)* dx(uu)+ dy(u)* dy(uu))
- int2d(Th)(ff*uu) + on(1,2,u=0);
plot(u,wait=1,ps="tempmuonde.ps", fill=true);

```

## 3.12 Optimal Control

Thanks to the function BFGS it is possible to solve complex nonlinear optimization problem within FreeFem++. For example consider the following inverse problem

$$\min_{b,c,d \in R} J = \int_E (u - u_d)^2 : -\nabla(\kappa(b, c, d) \cdot \nabla u) = 0, \quad u|_{\Gamma} = u_{\Gamma}$$

where the desired state  $u_d$ , the boundary data  $u_{\Gamma}$  and the observation set  $E \subset \Omega$  are all given. Furthermore let us assume that

$$\kappa(x) = 1 + bI_B(x) + cI_C(x) + dI_D(x) \quad \forall x \in \Omega$$

where  $B, C, D$  are separated subsets of  $\Omega$ .

To solve this problem by the quasi-Newton BFGS method we need the derivatives of  $J$  with respect to  $b, c, d$ . We self explanatory notations, if  $\delta b, \delta c, \delta d$  are variations of  $b, c, d$  we have

$$\delta J \approx 2 \int_E (u - u_d) \delta u, \quad -\nabla(\kappa \cdot \nabla \delta u) \approx \nabla(\delta \kappa \cdot \nabla u) \quad \delta u|_{\Gamma} = 0$$

Obviously  $J'_b$  is equal to  $\delta J$  when  $\delta b = 1, \delta c = 0, \delta d = 0$ , and so on for  $J'_c$  and  $J'_d$ .

All this is implemented in the following program

// file optimcontrol.edp

```

border aa(t=0, 2*pi) {    x = 5*cos(t);    y = 5*sin(t);  };
border bb(t=0, 2*pi) {    x = cos(t);     y = sin(t);   };
border cc(t=0, 2*pi) {    x = -3*cos(t);    y = sin(t);   };
border dd(t=0, 2*pi) {    x = cos(t);     y = -3*sin(t); };
mesh th = buildmesh(aa(70)+bb(35)+cc(35)+dd(35));
fespace Vh(th,P1);
Vh Ib=((x^2+y^2)<1.0001),
    Ic=((x+3)^2+ y^2)<1.0001),
    Id=((x^2+(y+3)^2)<1.0001),
    Ie=((x-1)^2+ y^2)<=4),
    ud,u,uH,du;
real[int] z(3);
problem A(u,uH) =int2d(th)((1+z[0]*Ib+z[1]*Ic+z[2]*Id)*(dx(u)*dx(uH)
                        +dy(u)*dy(uH))) + on(aa,u=x^3-y^3);
z[0]=2; z[1]=3; z[2]=4;
A; ud=u;
ofstream f("J.txt");
func real J(real[int] & Z)
{
    for (int i=0;i<z.n;i++)z[i]=Z[i];
    A; real s= int2d(th)(Ie*(u-ud)^2);
    f<<s<<" "; return s;
}

real[int] dz(3), dJdz(3);

problem B(du,uH)
= int2d(th)((1+z[0]*Ib+z[1]*Ic+z[2]*Id)*(dx(du)*dx(uH)+dy(du)*dy(uH)))
+ int2d(th)((dz[0]*Ib+dz[1]*Ic+dz[2]*Id)*(dx(u)*dx(uH)+dy(u)*dy(uH)))
+ on(aa,du=0);

func real[int] DJ(real[int] &Z)
{
    for(int i=0;i<z.n;i++)
        { for(int j=0;j<dz.n;j++) dz[j]=0;
          dz[i]=1; B;
          dJdz[i]= 2*int2d(th)(Ie*(u-ud)*du);
        }
    return dJdz;
}

real[int] Z(3);
for(int j=0;j<z.n;j++) Z[j]=1;
BFGS(J,DJ,Z,eps=1.e-6,nbiter=15,nbiterline=20);
cout << "BFGS: J(z) = " << J(Z) << endl;
for(int j=0;j<z.n;j++) cout<<z[j]<<endl;
plot(ud,value=1,ps="u.eps");

```

In this example the sets  $B, C, D, E$  are circles of boundaries  $bb, cc, dd, ee$  are the domain  $\Omega$  is the circle of boundary  $aa$ . The desired state  $u_d$  is the solution of the PDE for  $b = 2, c = 3, d = 4$ . The unknowns are packed into array  $z$ . Notice that it is necessary to recopy  $Z$  into  $z$  because one is a local variable while the other one is global. The program found  $b = 2.00125, c = 3.00109, d = 4.00551$ . Figure 3.11 shows  $u$  at convergence and the successive function evaluations of  $J$ . Note that an *adjoint state* could have been used. Define  $p$  by

$$-\nabla \cdot (\kappa \nabla p) = 2I_E(u - u_d), \quad p|_{\Gamma} = 0$$




Figure 3.11: On the left the level lines of  $u$ . On the right the successive evaluations of  $J$  by BFGS (5 values above 500 have been removed for readability)

Consequently

$$\begin{aligned}\delta J &= - \int_{\Omega} (\nabla \cdot (\kappa \nabla p)) \delta u \\ &= \int_{\Omega} (\kappa \nabla p \cdot \nabla \delta u) = - \int_{\Omega} (\delta \kappa \nabla p \cdot \nabla u)\end{aligned}\quad (3.8)$$

Then the derivatives are found by setting  $\delta b = 1, \delta c = \delta d = 0$  and so on:

$$J'_b = - \int_B \nabla p \cdot \nabla u, \quad J'_c = - \int_C \nabla p \cdot \nabla u, \quad J'_d = - \int_D \nabla p \cdot \nabla u$$

**Remark** As BFGS stores an  $M \times M$  matrix where  $M$  is the number of unknowns, it is dangerously expensive to use this method when the unknown  $x$  is a Finite Element Function. One should use another optimizer such as the NonLinear Conjugate Gradient NLCG (also a key word of FreeFem++). See the file algo.edp in the examples folder.

### 3.13 A Flow with Shocks

Compressible Euler equations should be discretized with Finite Volumes or FEM with flux upwinding scheme but these are not implemented in FreeFem++ . Nevertheless acceptable results can be obtained with the method of characteristics provided that the mean values  $\bar{f} = \frac{1}{2}(f^+ + f^-)$  are used at shocks in the scheme, and finally mesh adaptation .

$$\begin{aligned}\partial_t \rho + \bar{u} \nabla \rho + \bar{\rho} \nabla \cdot u &= 0 \\ \bar{\rho} (\partial_t u + \frac{\bar{\rho} u}{\bar{\rho}} \nabla u + \nabla p) &= 0 \\ \partial_t p + \bar{u} \nabla p + (\gamma - 1) \bar{p} \nabla \cdot u &= 0\end{aligned}\quad (3.9)$$

One possibility is to couple  $u, p$  and then update  $\rho$ , i.e.

$$\frac{1}{(\gamma - 1) \delta t \bar{p}^m} (p^{m+1} - p^m \circ X^m) + \nabla \cdot u^{m+1} = 0$$

$$\begin{aligned} \frac{\bar{\rho}^m}{\delta t}(u^{m+1} - u^m \circ \tilde{X}^m) + \nabla p^{m+1} &= 0 \\ \rho^{m+1} &= \rho^m \circ X^m + \frac{\bar{\rho}^m}{(\gamma - 1)\bar{p}^m}(p^{m+1} - p^m \circ X^m) \end{aligned} \quad (3.10)$$

A numerical result is given on Figure 3.12 and the FreeFem++ script is




Figure 3.12: Pressure for a Euler flow around a disk at Mach 2 computed by (3.10)

```

verbosity=1;
int anew=1;
real x0=0.5,y0=0, rr=0.2;
border ccc(t=0,2){x=2-t;y=1;};
border ddd(t=0,1){x=0;y=1-t;};
border aaal(t=0,x0-rr){x=t;y=0;};
border cercle(t=pi,0){ x=x0+rr*cos(t);y=y0+rr*sin(t);}
border aaa2(t=x0+rr,2){x=t;y=0;};
border bbb(t=0,1){x=2;y=t;};

int m=5; mesh Th;
if(anew) Th = buildmesh (ccc(5*m) +ddd(3*m) + aaal(2*m) + cercle(5*m)
+ aaa2(5*m) + bbb(2*m) );
else Th = readmesh("Th_circle.mesh"); plot(Th,wait=0);

real dt=0.01, u0=2, err0=0.00625, pena=2;
fespace Wh(Th,P1);
fespace Vh(Th,P1);
Wh u,v,u1,v1,u1,v1;
Vh r,rh,r1;

```

```

macro dn(u) (N.x*dx(u)+N.y*dy(u) ) // def the normal derivative

if(anew){ u1= u0; v1= 0; r1 = 1;}
else {
    ifstream g("u.txt");g>>u1[];
    ifstream gg("v.txt");gg>>v1[];
    ifstream ggg("r.txt");ggg>>r1[];
    plot(u1,ps="eta.eps", value=1,wait=1);
    err0=err0/10; dt = dt/10;
}

problem eul(u,v,r,u1,v1,rh)
= int2d(Th)( (u*u1+v*v1+r*rh)/dt
+ ((dx(r)*u1+ dy(r)*v1) - (dx(rh)*u + dy(rh)*v))
)
+ int2d(Th)(-(rh*convect([u1,v1],-dt,r1) + u1*convect([u1,v1],-dt,u1)
+ v1*convect([u1,v1],-dt,v1))/dt)
+int1d(Th,6)(rh*u) // +int1d(Th,1)(rh*v)
+ on(2,r=0) + on(2,u=u0) + on(2,v=0);

int j=80;
for(int k=0;k<3;k++)
{
    if(k==20){ err0=err0/10; dt = dt/10; j=5;}
    for(int i=0;i<j;i++){
        eul; u1=u; v1=v; r1=abs(r);
        cout<<"k="<<k<<" E="<<int2d(Th)(u^2+v^2+r)<<endl;
        plot(r,wait=0,value=1);
    }
}
Th = adaptmesh (Th,r, nbvx=40000,err=err0,
    absserror=1,nbjacoby=2, omega=1.8,ratio=1.8, nbsmooth=3,
    splitpbedge=1, maxsubdiv=5,rescaling=1) ;
plot(Th,wait=0);
u=u;v=v;r=r;

savemesh(Th,"Th_circle.mesh");
ofstream f("u.txt");f<<u[];
ofstream ff("v.txt");ff<<v[];
ofstream fff("r.txt");fff<<r[];
r1 = sqrt(u*u+v*v);
plot(r1,ps="mach.eps", value=1);
r1=r;
}

```

## 3.14 Classification of the equations

**Summary** *It is usually not easy to determine the type of a system. Yet the approximations and algorithms suited to the problem depend on its type:*

- *Finite Elements compatible (LBB conditions) for elliptic systems*
- *Finite difference on the parabolic variable and a time loop on each elliptic subsystem of parabolic systems; better stability diagrams when the schemes are implicit in time.*

- Upwinding, Petrov-Galerkin, Characteristics-Galerkin, Discontinuous-Galerkin, Finite Volumes for hyperbolic systems plus, possibly, a time loop.

When the system changes type, then expect difficulties (like shock discontinuities)!

**Elliptic, parabolic and hyperbolic equations** A partial differential equation (PDE) is a relation between a function of several variables and its derivatives.

$$F(\varphi(x), \frac{\partial \varphi}{\partial x_1}(x), \dots, \frac{\partial \varphi}{\partial x_d}(x), \frac{\partial^2 \varphi}{\partial x_1^2}(x), \dots, \frac{\partial^m \varphi}{\partial x_d^m}(x)) = 0 \quad \forall x \in \Omega \subset \mathcal{R}^d.$$

The range of  $x$  over which the equation is taken, here  $\Omega$ , is called the *domain* of the PDE. The highest derivation index, here  $m$ , is called the *order*. If  $F$  and  $\varphi$  are vector valued functions, then the PDE is actually a *system* of PDEs.

Unless indicated otherwise, here by convention *one* PDE corresponds to one scalar valued  $F$  and  $\varphi$ . If  $F$  is linear with respect to its arguments, then the PDE is said to be *linear*.

The general form of a second order, linear scalar PDE is  $\frac{\partial^2 \varphi}{\partial x_i \partial x_j}$  and  $A : B$  means  $\sum_{i,j=1}^d a_{ij} b_{ij}$ .

$$\alpha \varphi + a \cdot \nabla \varphi + B : \nabla(\nabla \varphi) = f \quad \text{in } \Omega \subset \mathcal{R}^d,$$

where  $f(x), \alpha(x) \in \mathcal{R}, a(x) \in \mathcal{R}^d, B(x) \in \mathcal{R}^{d \times d}$  are the PDE *coefficients*. If the coefficients are independent of  $x$ , the PDE is said to have *constant coefficients*.

To a PDE we associate a quadratic form, by replacing  $\varphi$  by 1,  $\partial \varphi / \partial x_i$  by  $z_i$  and  $\partial^2 \varphi / \partial x_i \partial x_j$  by  $z_i z_j$ , where  $z$  is a vector in  $\mathcal{R}^d$ :

$$\alpha + a \cdot z + z^T B z = f.$$

If it is the equation of an ellipse (ellipsoid if  $d \geq 2$ ), the PDE is said to be *elliptic*; if it is the equation of a parabola or a hyperbola, the PDE is said to be *parabolic* or *hyperbolic*. If  $A \equiv 0$ , the degree is no longer 2 but 1, and for reasons that will appear more clearly later, the PDE is still said to be hyperbolic.

These concepts can be generalized to systems, by studying whether or not the polynomial system  $P(z)$  associated with the PDE system has branches at infinity (ellipsoids have no branches at infinity, paraboloids have one, and hyperboloids have several).

If the PDE is not linear, it is said to be *non linear*. Those are said to be locally elliptic, parabolic, or hyperbolic according to the type of the linearized equation.

For example, for the non linear equation

$$\frac{\partial^2 \varphi}{\partial r^2} - \frac{\partial \varphi}{\partial x} \frac{\partial^2 \varphi}{\partial x^2} = 1,$$

we have  $d = 2, x_1 = t, x_2 = x$  and its linearized form is:

$$\frac{\partial^2 u}{\partial r^2} - \frac{\partial u}{\partial x} \frac{\partial^2 \varphi}{\partial x^2} - \frac{\partial \varphi}{\partial x} \frac{\partial^2 u}{\partial x^2} = 0,$$

which for the unknown  $u$  is locally elliptic if  $\frac{\partial \varphi}{\partial x} < 0$  and locally hyperbolic if  $\frac{\partial \varphi}{\partial x} > 0$ .



**Examples** Laplace's equation is elliptic:

$$\Delta\varphi \equiv \frac{\partial^2\varphi}{\partial x_1^2} + \frac{\partial^2\varphi}{\partial x_2^2} + \cdots + \frac{\partial^2\varphi}{\partial x_d^2} = f, \quad \forall x \in \Omega \subset \mathcal{R}^d.$$

The *heat* equation is parabolic in  $Q = \Omega \times ]0, T[ \subset \mathcal{R}^{d+1}$ :

$$\frac{\partial\varphi}{\partial t} - \mu\Delta\varphi = f \quad \forall x \in \Omega \subset \mathcal{R}^d, \quad \forall t \in ]0, T[.$$

If  $\mu > 0$ , the *wave* equation is hyperbolic:

$$\frac{\partial^2\varphi}{\partial t^2} - \mu\Delta\varphi = f \quad \text{in } Q.$$

The *convection diffusion* equation is parabolic if  $\mu \neq 0$  and hyperbolic otherwise:

$$\frac{\partial\varphi}{\partial t} + a\nabla\varphi - \mu\Delta\varphi = f.$$

The *biharmonic* equation is elliptic:

$$\Delta(\Delta\varphi) = f \quad \text{in } \Omega.$$

**Boundary conditions** A relation between a function and its derivatives is not sufficient to define the function. Additional information on the boundary  $\Gamma = \partial\Omega$  of  $\Omega$ , or on part of  $\Gamma$  is necessary. Such information is called a *boundary condition*. For example,

$$\varphi(x) \text{ given, } \forall x \in \Gamma,$$

is called a *Dirichlet boundary condition*. The *Neumann* condition is

$$\frac{\partial\varphi}{\partial n}(x) \text{ given on } \Gamma \quad (\text{or } n \cdot B\nabla\varphi, \text{ given on } \Gamma \text{ for a general second order PDE})$$

where  $n$  is the normal at  $x \in \Gamma$  directed towards the exterior of  $\Omega$  (by definition  $\frac{\partial\varphi}{\partial n} = \nabla\varphi \cdot n$ ). Another classical condition, called a *Robin* (or *Fourier*) condition is written as:

$$\varphi(x) + \beta(x)\frac{\partial\varphi}{\partial n}(x) \text{ given on } \Gamma.$$

Finding a set of boundary conditions that defines a unique  $\varphi$  is a difficult art.

In general, an elliptic equation is well posed (*i.e.*  $\varphi$  is unique) with one Dirichlet, Neumann or Robin conditions on the whole boundary.

Thus, Laplace's equations is well posed with a Dirichlet or Neumann condition but also with

$$\varphi \text{ given on } \Gamma_1, \quad \frac{\partial\varphi}{\partial n} \text{ given on } \Gamma_2, \quad \Gamma_1 \cup \Gamma_2 = \Gamma, \quad \Gamma_1 \cap \Gamma_2 = \emptyset.$$

Parabolic and hyperbolic equations rarely require boundary conditions on all of  $\Gamma \times ]0, T[$ . For instance, the heat equation is well posed with

$$\varphi \text{ given at } t = 0 \text{ and Dirichlet or Neumann or mixed conditions on } \partial\Omega.$$

Here  $t$  is time so the first condition is called an initial condition. The whole set of conditions are also called Cauchy conditions.

The wave equation is well posed with

$$\varphi \text{ and } \frac{\partial\varphi}{\partial t} \text{ given at } t = 0 \text{ and Dirichlet or Neumann or mixed conditions on } \partial\Omega.$$



# Chapter 4

## Syntax

### 4.1 Data Types

In essence FreeFem++ is a compiler: its language is typed, polymorphic, with exception and reentrant. Every variable must be declared of a certain type, in a declarative statement; each statement are separated from the next by a semicolon ‘;’. The language allows the manipulation of basic types integers (`int`), reals (`real`), strings (`string`), arrays (example: `real[int]`), bidimensional (2D) finite element meshes (`mesh`), 2D finite element spaces (`fespace`), analytical functions (`func`), arrays of finite element functions (`func[basic_type]`), linear and bilinear operators, sparse matrices, vectors, etc. For instance

```
int i,n=20;                                // i,n are integer.
real[int] xx(n),yy(n);                     // two array of size n
for (i=0;i<=20;i++)                        // which can be used in statements such as
{ xx[i]= cos(i*pi/10); yy[i]= sin(i*pi/10); }
```

The life of a variable is the current block {...}, except the `fespace` variable, and the variables local to a block are destroyed at the end of the block as follows.

#### Example 4.1

```
real r= 0.01;
mesh Th=square(10,10);                     // unit square mesh
fespace Vh(Th,P1);                         // P1 lagrange finite element space
Vh u = x+ exp(y);
func f = z * x + r * log(y);
plot(u,wait=true);
{
    real r = 2;                             // new block
    fespace Vh(Th,P1);                       // not the same r
}                                             // error because Vh is a global name
                                             // end of block
                                             // here r back to 0.01
```

The type declarations are compulsory in FreeFem++ ; in the end this feature is an asset because it is easy to make bugs in a language with many implicit types. The variable name is just an alphanumeric string, the underscore character “\_” is not allowed, because it will be used as an operator in the future.

## 4.2 List of major types

**bool** is used for logical expression and flow-control. The result of a comparison is a boolean type as in

```
bool fool=(1<2);
```

which makes fool to be true. Similar examples can be built with ==, <=, >=, <, >, !=.

**int** declares an integer.

**string** declare the variable to store a text enclosed within double quotes, such as:

```
"This is a string in double quotes."
```

**real** declares the variable to store a number such as "12.345".

**complex** Complex numbers, such as  $1 + 2i$ , FreeFem++ understand that  $i = \sqrt{-1}$ .

```
complex a = 1i, b = 2 + 3i;
cout << "a + b = " << a + b << endl;
cout << "a - b = " << a - b << endl;
cout << "a * b = " << a * b << endl;
cout << "a / b = " << a / b << endl;
```

Here's the output;

```
a + b = (2,4)
a - b = (-2,-2)
a * b = (-3,2)
a / b = (0.230769,0.153846)
```

**ofstream** to declare an output file .

**ifstream** to declare an input file .

**real[int ]** declares a variable that stores multiple real numbers with integer index.

```
real[int] a(5);
a[0] = 1; a[1] = 2; a[2] = 3.3333333; a[3] = 4; a[4] = 5;
cout << "a = " << a << endl;
```

This produces the output;

```
a = 5      :
  1         2         3.33333  4         5
```

**real[string ]** declares a variable that store multiple real numbers with string index.

**string[string ]** declares a variable that store multiple strings with string index.

**func** defines a function without argument, if independent variables are  $x$ ,  $y$ . For example

```
func f=cos(x)+sin(y) ;
```

Remark that the function's type is given by the expression's type. Raising functions to a numerical power is done, for instance, by  $x^1$ ,  $y^{0.23}$ .

**mesh** creates the triangulation, see Section 5.

**fespace** defines a new type of finite element space, see Section Section 6.

**problem** declares the weak form of a partial differential problem without solving it.

**solve** declares a problem and solves it.

**varf** defines a full variational form.

**matrix** defines a sparse matrix.

## 4.3 Global Variables

The names  $x, y, z, label, region, P, N, nu\_triangle \dots$  are reserved words used to link the language to the finite element tools:

**x** is the  $x$  coordinate of the current point (real value)

**y** is the  $y$  coordinate of the current point (real value)

**z** is the  $z$  coordinate of the current point (real value) , but is reserved for future use.

**label** contains the label number of a boundary if the current point is on a boundary, 0 otherwise (int value).

**region** returns the region number of the current point ( $x, y$ ) (int value).

**P** gives the current point ( $\mathbb{R}^2$  value. ). By  $P.x$ ,  $P.y$ , we can get the  $x$ ,  $y$  components of  $P$  . Also  $P.z$  is reserved and can be used in 3D.

**N** gives the outward unit normal vector at the current point if it is on a curve defined by border ( $\mathbb{R}^3$  value).  $N.x$  and  $N.y$  are  $x$  and  $y$  components of the normal vector.  $N.z$  is reserved. .

**lenEdge** gives the length of the current edge

$$\text{lenEdge} = |q^i - q^j| \quad \text{if the current edge is } [q^i, q^j]$$

**hTriangle** gives the size of the current triangle

**nuTriangle** gives the index of the current triangle (int value).

**nuEdge** gives the index of the current edge in the triangle (int value).

**nTonEdge** gives the number of adjacent triangle of the current edge (integer ).

**area** give the area of the current triangle (real value).

**volume** give the volume of the current tetrahedra (real value).

**cout** is the standard output device (default is console). On MS-Windows, the standard output is only the console, at this time. **ostream**

**cin** is the standard input device (default is keyboard). (**istreamvalue**).

**endl** adds an "end of line" to the input/output flow.

**true** means "true" in **bool** value.

**false** means "false" in **bool** value.

**pi** is the **realvalue** approximation value of  $\pi$ .

## 4.4 System Commands

Here is how to show all the types, and all the operator and functions of a **FreeFem++** program:

```
dumptable(cout);
```

To execute a system command in the string (not implemented on Carbon MacOS)

```
exec("shell command");
```

This is useful to launch another executable from within **FreeFem++** . On MS-Windows, the full path of the executable. For example, if there is the command "ls.exe" in the subdirectory "c:\cygwin\bin\", then we must write

```
exec("c:\\cygwin\\bin\\ls.exe");
```

Another useful system command is **assert()** to make sure something is true.

```
assert(version>=1.40);
```

## 4.5 Arithmetics

**On integers** , +, −, \* are the usual arithmetic summation (plus), subtraction (minus) and multiplication (times), respectively, The operators / and % yield the quotient and the remainder from the division of the first expression by the second. If the second number of / or % is zero the behavior is undefined. The *maximum* or *minimum* of two integers  $a$ ,  $b$  are obtained by  $\max(a, b)$  or  $\min(a, b)$ . The power  $a^b$  of two integers  $a$ ,  $b$  is calculated by writing  $a^b$ . The classical C++ "arithmetical if" expression  $a ? b : c$  is equal to the value of expression  $b$  if the value of expression  $a$  is true otherwise is equal to value of expression  $c$ .

**Example 4.2** *Computations with the integers*

```

int a = 12, b = 5;
cout <<"plus, minus of "<<a<<" and "<<b<<" are "<<a+b<<" , "<<a-b<<endl;
cout <<"multiplication, quotient of them are "<<a*b<<" , "<<a/b<<endl;
cout <<"remainder from division of "<<a<<" by "<<b<<" is "<<a%b<<endl;
cout <<"the minus of "<<a<<" is "<< -a << endl;
cout <<a<<" plus -"<<b<<" need bracket:"<<a<<"+"(-"<<b<<"")="<<a+(-b)<<endl;
cout <<"max and min of "<<a<<" and "<<b<<" is "<<max(a,b)<<" , "<<min(a,b)<< endl;
cout <<b<<"th power of "<<a<<" is "<<a^b<< endl;
cout << " min == (a < b ? a : b ) is " << (a < b ? a : b) << endl;

b=0;
cout <<a<<"/0"<<" is "<< a/b << endl;
cout <<a<<"%0"<<" is "<< a%b << endl;

```

produce the following result:

```

plus, minus of 12 and 5 are 17, 7
multiplication, quotient of them are 60, 2
remainder from division of 12 by 5 is 2
the minus of 12 is -12
12 plus -5 need bracket :12+(-5)=7
max and min of 12 and 5 is 12,5
5th power of 12 is 248832
min == (a < b ? a : b) is 5
12/0 : long long long
Fatal error : ExecError Div by 0 at exec line 9
Exec error : exit

```

By the relation  $integer \subset real$ , the operators “+ , − , \* , / , %” and “**max** , **min** , ^” are extended to real numbers or variables. However, % calculates the remainder of the integer parts of two real numbers.

The following are examples similar to Example 4.2

```

real a=sqrt(2.), b = pi;
cout <<"plus, minus of "<<a<<" and "<<pi<<" are "<< a+b <<" , "<< a-b << endl;
cout <<"multiplication, quotient of them are "<<a*b<<" , "<<a/b<< endl;
cout <<"remainder from division of "<<a<<" by "<<b<<" is "<< a%b << endl;
cout <<"the minus of "<<a<<" is "<< -a << endl;
cout <<a<<" plus -"<<b<<" need bracket : "<<a<<"+"(-"<<b<<"")="<<a + (-b) << endl;

```

It gives the following output:

```

plus, minus of 1.41421 and 3.14159 are 4.55581, -1.72738
multiplication, quotient of them are 4.44288, 0.450158
remainder from division of 1.41421 by 3.14159 is 1
the minus of 1.41421 is -1.41421
1.41421 plus -3.14159 need bracket :1.41421+(-3.14159)=-1.72738

```

By the relation

$$bool \subset int \subset real \subset complex,$$

the operators “+”, “-”, “\*”, “/” and “^” are also applicable on complex-typed variables, but “%”, “max”, “min” cannot be used. Complex numbers such as  $5+9i$ ,  $i = \sqrt{-1}$ , are valid expressions. With real variables  $a=2.45$ ,  $b=5.33$ , complex numbers like  $a + ib$  and  $a + i\sqrt{2.0}$  must be declared by

```
complex z1 = a+b*1i, z2=a+sqrt(2.0)*1i;
```

The imaginary and real parts of a complex number  $z$  can be obtained with `imag` and `real`. The conjugate of  $a+bi$  ( $a, b$  are reals) is defined by  $a-bi$ , which can also be computed with the operator “conj”, by `conj(a+b*1i)` in FreeFem++ .

Internally the complex number  $z = a + ib$  is considered as the pair  $(a, b)$  of real numbers  $a, b$ . We can attach to it the point  $(a, b)$  in the Cartesian plane where the  $x$ -axis is for the real part and the  $y$ -axis for the imaginary part. The same point  $(a, b)$  has a representation with polar coordinate  $(r, \phi)$ , So  $z$  is also  $z = r(\cos \phi + i \sin \phi)$ ,  $r = \sqrt{a^2 + b^2}$  and  $\phi = \tan^{-1}(b/a)$ ;  $r$  is called the *modulus* and  $\phi$  the *argument* of  $z$ . In the following example, we shall show them using FreeFem++ programming, and *de Moivre's formula*  $z^n = r^n(\cos n\phi + i \sin n\phi)$ .

### Example 4.3

```
real a=2.45, b=5.33;
complex z1=a+b*1i, z2 = a+sqrt(2.)*1i;
func string pc(complex z) // printout complex to (real)+i(imaginary)
{
    string r = "("+real(z);
    if (imag(z)>=0) r = r+" ";
    return r+imag(z)+"i)";
}

// printout complex to |z|*(cos(arg(z))+i*sin(arg(z)))
func string toPolar(complex z)
{
    return abs(z)+"*(cos("+arg(z)+")+i*sin("+arg(z)+"))";
}

cout <<"Standard output of the complex "<<pc(z1)<<" is the pair "
    <<z1<<endl;
cout <<"Plus, minus of "<<pc(z1)<<" and "<<pc(z2)<<" are "<< pc(z1+z2)
    <<" "<< pc(z1-z2) << endl;
cout <<"Multiplication, quotient of them are "<<pc(z1*z2)<<" "<<
    <<pc(z1/z2)<< endl;
cout <<"Real/imaginary part of "<<pc(z1)<<" is "<<real(z1)<<" "<<
    <<imag(z1)<<endl;
cout <<"Absolute of "<<pc(z1)<<" is "<<abs(z1)<<endl;
cout <<pc(z2)<<" = "<<toPolar(z2)<<endl;
cout <<" and polar("<<abs(z2)<<" "<<arg(z2)<<") = "
    << pc(polar(abs(z2),arg(z2)))<<endl;
cout <<"de Moivre's formula: "<<pc(z2)<<"^3 = "<<toPolar(z2^3)<<endl;
cout <<"conjugate of "<<pc(z2)<<" is "<<pc(conj(z2))<<endl;
cout <<pc(z1)<<"^"<<pc(z2)<<" is "<< pc(z1^z2) << endl;
```

Here's the output from Example 4.3

```
Standard output of the complex (2.45+5.33i) is the pair (2.45,5.33)
Plus, minus of (2.45+5.33i) and (2.45+1.41421i) are (4.9+6.74421i), (0+3.91579i)
Multiplication, quotient of them are (-1.53526+16.5233i), (1.692+1.19883i)
Real/imaginary part of (2.45+5.33i) is 2.45, 5.33
Absolute of (2.45+5.33i) is 5.86612
```



```
(2.45+1.41421i) = 2.82887*(cos(0.523509)+i*sin(0.523509))
and polar(2.82887,0.523509) = (2.45+1.41421i)
de Moivre's formula: (2.45+1.41421i)^3
                     = 22.638*(cos(1.57053)+i*sin(1.57053))
conjugate of (2.45+1.41421i) is (2.45-1.41421i)
(2.45+5.33i)^(2.45+1.41421i) is (8.37072-12.7078i)
```

## 4.6 Functions of one Variable

**Fundamental functions** are built into FreeFem++ as well as The power function  $x^y = \text{pow}(x,y)$ ; the exponent function  $\exp(x) (= e^x)$ , the logarithmic function  $\log(x) (= \ln x)$  or  $\log10(x) (= \log_{10} x)$ ; the trigonometric functions  $\sin(x)$ ,  $\cos(x)$ ,  $\tan(x)$  assume angles measured in *radians*; the inverse of  $\sin x$ ,  $\cos x$ ,  $\tan x$  (called *circular function* or *inverse trigonometric function*)  $\text{asin}(x) (= \arcsin x)$ ,  $\text{acos}(x) (= \arccos x)$ ,  $\text{atan}(x) (= \arctan x)$  are also implemented; the  $\text{atan2}(x,y)$  function computes the principal value of the arc tangent of  $y/x$ , using the signs of both arguments to determine the quadrant of the return value; the *hyperbolic functions*,

$$\sinh x = (e^x - e^{-x})/2, \quad \cosh x = (e^x + e^{-x})/2.$$

and  $\tanh x = \sinh x / \cosh x$  called by  $\sinh(x)$ ,  $\cosh(x)$ ,  $\tanh(x)$ ,  $\text{asinh}(x)$ ,  $\text{acosh}(x)$  and  $\text{atanh}(x)$ .

$$\sinh^{-1} x = \ln \left[ x + \sqrt{x^2 + 1} \right], \quad \cosh^{-1} x = \ln \left[ x + \sqrt{x^2 - 1} \right].$$

The real function which rounds a real to an integer  $\text{floor}(x)$  rounds to largest integral value not greater than  $x$ ,  $\text{ceil}(x)$  round to smallest integral value not less than  $x$ ; similarly  $\text{rint}(x)$  returns the integral value nearest to  $x$  (according to the prevailing rounding mode) in floating-point format).

**Elementary Functions** denotes for us the class of functions presented above (polynomials, exponential, logarithmic, trigonometric, circular) and the functions obtained from those by the four arithmetic operations

$$f(x) + g(x), f(x) - g(x), f(x)g(x), f(x)/g(x)$$

and by composition  $f(g(x))$ , each applied a finite number of times. In FreeFem++ , all elementary functions can thus be created. The derivative of an elementary function is also an elementary function; however, the indefinite integral of an elementary function cannot always be expressed in terms of elementary functions.

**Example 4.4** The following is an example where an elementary function is used to build the border of a domain. Cardioid

```
real b = 1.;
real a = b;
func real phix(real t)
{
```

```

    return (a+b)*cos(t)-b*cos(t*(a+b)/b);
}
func real phiy(real t)
{
    return (a+b)*sin(t)-b*sin(t*(a+b)/b);
}
border C(t=0,2*pi) { x=phix(t); y=phiy(t); }
mesh Th = buildmesh(C(50));

```

Taking the principal value, we can define  $\log z$  for  $z \neq 0$  by

$$\ln z = \ln |z| + i \arg z.$$

Using FreeFem++ , we calculated `exp(1+4i)`, `sin(pi+1i)`, `cos(pi/2-1i)` and `log(1+2i)`, we then have

$$\begin{array}{ll} -1.77679 - 2.0572i, & 1.8896710^{-16} - 1.1752i, \\ 9.4483310^{-17} + 1.1752i, & 0.804719 + 1.10715i. \end{array}$$

**Random Functions** can be define as FreeFem++ has a Mersenne Twister function (see page <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html> for full detail). It is a very fast and accurate random number generator Of period  $2^{219937} - 1$ , and the functions which calls it are:

- `randint32()` generates unsigned 32-bit integers.
- `randint31()` generates unsigned 31-bit integers.
- `randreal1()` generates uniform real in  $[0, 1]$  (32-bit resolution).
- `randreal2()` generates uniform real in  $[0, 1]$  (32-bit resolution).
- `randreal3()` generates uniform real in  $(0, 1)$  (32-bit resolution).
- `randres53()` generates uniform real in  $[0, 1]$  with 53-bit resolution.
- `randinit(seed )` initializes the state vector by using one 32-bit integer "seed", which may be zero.

**Library Functions** form the mathematical library (version 2.17).

- the functions `j0(x)`, `j1(x)`, `jn(n,x)`, `y0(x)`, `y1(x)`, `yn(n,x)` are the Bessel functions of first and second kind.

The functions `j0(x)` and `j1(x)` compute the Bessel function of the first kind of the order 0 and the order 1, respectively; the function `jn(n, x)` computes the Bessel function of the first kind of the integer order  $n$ .

The functions `y0(x)` and `y1(x)` compute the linearly independent Bessel function of the second kind of the order 0 and the order 1, respectively, for the positive integer value  $x$  (expressed as a real); the function `yn(n, x)` computes the Bessel function of the second kind for the integer order  $n$  for the positive integer value  $x$  (expressed as a real).

- the function `tgamma(x)` calculates the  $\Gamma$  function of  $x$ . `lgamma(x)` calculates the natural logarithm of the absolute value of the  $\Gamma$  function of  $x$ .
- The `erf(x)` function calculates the error function, where  $\text{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x \exp(-t^2) dt$ . The `erfc(x)` function calculates the complementary error function of  $x$ , i.e.  $\text{erfc}(x) = 1 - \text{erf}(x)$ .

## 4.7 Functions of two Variables

### 4.7.1 Formula

The general form of real functions of two independent variables  $a, b$  is usually written as  $c = f(a, b)$ . In FreeFem++ , `x`, `y` and `z` are reserved word as explained in in Section 4.3. So when the two variables of the function are `x` and `y`, we may define the function without its argument, for example

```
func f=cos(x)+sin(y) ;
```

Remark that the function type is given by the expression type. The power operator can be used in functions such as `x^1`, `y^0.23`. In `func`, we can write an elementary function as follows

```
func f = sin(x)*cos(y);
func g = (x^2+3*y^2)*exp(1-x^2-y^2);
func h = max(-0.5, 0.1*log(f^2+g^2));
```

Complex valued function create functions with 2 variables `x`, `y` as follows,

```
mesh Th=square(20,20,[-pi+2*pi*x,-pi+2*pi*y]); //      ] - pi, pi[2
fespace Vh(Th,P2);
func z=x+y*1i; //      z = x + iy
func f=imag(sqrt(z)); //      f =  $\Im \sqrt{z}$ 
func g=abs( sin(z/10)*exp(z^2/10) ); //      g =  $|\sin z/10 \exp z^2/10|$ 
Vh fh = f; plot(fh); //      contour lines of f
Vh gh = g; plot(gh); //      contour lines of g
```

We call also construct *elementary functions of two variables* from elementary functions  $f(x)$  or  $g(y)$  by the four arithmetic operations plus composition applied a finite number of times.

### 4.7.2 FE-functions

Finite element functions are also constructed like elementary functions by an arithmetic formula involving elementary functions. The difference is that they are evaluated at declaration time and FreeFem++ stores the array of its values at the places associated with the degree of freedom of the finite element type. By opposition elementary functions are evaluated only when needed. Hence FE-functions are not defined only by their formula but also by the mesh and the finite element which enter in their definitions. If the value of a FE-function is requested at a point which is not a degree of freedom, an interpolation is used, leading to an interpolation error, while by contrast, an elementary function can be evaluated at any point exactly.

```

func f=x^2*(1+y)^3+y^2;
mesh Th = square(20,20,[-2+2*x,-2+2*y]); // square ]-2,2]^2
fespace Vh(Th,P1);
Vh fh=f; // fh is the projection of f to Vh (real value)
func zf=(x^2*(1+y)^3+y^2)*exp(x+1i*y);
Vh<complex> zh = zf; // zh is the projection of zf
// to complex value Vh space

```

The construction of  $\text{fh}$  ( $=f_h$ ) is explained in Section 6.

**Note 4.1** The command `plot` applies only for real or complex FE-functions (2d or 3d) and not to elementary functions.

Complex valued functions create functions with 2 variables  $x, y$  as follows,

```

mesh Th=square(20,20,[-pi+2*pi*x,-pi+2*pi*y]); // ]-pi,pi]^2
fespace Vh(Th,P2);
func z=x+y*1i; // z = x + iy
func f=imag(sqrt(z)); // f =  $\Im \sqrt{z}$ 
func g=abs( sin(z/10)*exp(z^2/10) ); // g =  $|\sin z/10 \exp z^2/10|$ 
Vh fh = f; plot(fh); // Fig. 4.1 isovalue of f
Vh gh = g; plot(gh); // Fig. 4.2 isovalue of g

```




Figure 4.1:  $\Im \sqrt{z}$  has branch




Figure 4.2:  $|\sin(z/10) \exp(z^2/10)|$

## 4.8 Arrays

An *array* stores multiple objects, and there are 2 kinds of arrays: The first is similar to *vector*, i.e. arrays with *integer indices* and the second type is arrays with *string indices*.

In the first case, the size of the array must be known at execution time, and implementation is done with the `KN<>` class and all the vector operator of `KN<>` are implemented. For instance

```

real [int] tab(10), tab1(10); // 2 array of 10 real
real [int] tab2; // bug array with no size
tab = 1.03; // set all the array to 1.03
tab[1]=2.15;

```

```

cout << tab[1] << " " << tab[9] << " size of tab = "
    << tab.n << " min: " << tab.min << " max:" << tab.max
    << " sum : " << tab.sum << endl;
tab.resize(12);
tab(10:11)=3.14;
cout << " resize tab: " << tab << endl;
real [string] tt;
tt["+"]=1.5;
cout<<tt["a"]<<" " <<tt["+"]<<endl;
real[int] a(5),b(5),c(5),d(5);
a = 1;
b = 2;
c = 3;
a[2]=0;
d = ( a ? b : c );
cout << " d = ( a ? b : c ) is " << d << endl;
d = ( a ? 1 : c );
d = ( a ? b : 0 );
d = ( a ? 1 : 0 );
tab.sort ;
cout << " tab (after sort) " << tab << endl;
int[int] ii(0:d.n-1);
d=-1:-5;
sort(d,ii);
cout << " d " << d << "\n ii = " << ii << endl;

```

produces the output

```

2.15 1.03 size of tab = 10 min: 1.03 max:2.15 sum : 11.42
resize tab: 12
    1.03    2.15    1.03    1.03    1.03
    1.03    1.03    1.03    1.03    1.03
    3.14    3.14
0  1.5
d = ( a ? b : c ) is 5
    3      3      2      3      3
tab (after sort) 12
1.03 1.03 1.03 1.03 1.03
1.03 1.03 1.03 1.03 2.15
3.14 3.14
d 5
-5 -4 -3 -2 -1

ii = 5
 4  3  2  1  0

```

Arrays can be set like in matlab or scilab with the operator `::`, the array generator of `a:c` is equivalent to `a:1:c`, and the array set by `a:b:c` is set to size  $\lfloor (b-a)/c \rfloor + 1$  and the value  $i$  is set by  $a + i(b-a)/c$ .

There are `int`, `real`, `complex` arrays with, in the third case, two operators (`.in`, `.re`) to generate the real and imaginary real array from the complex array (without copy) :

*// version 3.2 mai 2009*

```

// like matlab. and scilab
{
int[int] tt(2:10); // 2,3,4,5,6,7,8,9,10
int[int] t1(2:3:10); // 2,5,8,
cout << " tt(2:10)= " << tt << endl;
cout << " t1(2:3:10)= " << t1 << endl;
tt=1:2:5;
cout << " 1.:2:5 => " << tt << endl;
}

{
real[int] tt(2:10); // 2,3,4,5,6,7,8,9,10
real[int] t1(2.:3:10.); // 2,5,8,
cout << " tt(2:10)= " << tt << endl;
cout << " t1(2:3:10)= " << t1 << endl;
tt=1.:0.5:3.999;
cout << " 1.:0.5:3.999 => " << tt << endl;
}

{
complex[int] tt(2.+0i:10.+0i); // 2,3,4,5,6,7,8,9,10
complex[int] t1(2.:3.:10.); // 2,5,8,
cout << " tt(2.+0i:10.+0i)= " << tt << endl;
cout << " t1(2.:3.:10.)= " << t1 << endl;
cout << " tt.re real part array " << tt.re << endl ;
// the real part array of the complex array
cout << " tt.im imag part array " << tt.im << endl ;
// the imag part array of the complex array
}

```

The output is :

```

tt(2:10)= 9
 2  3  4  5  6
 7  8  9 10
t1(2:3:10)= 3
 2  5  8
1.:2:5 => 3
 1  3  5
tt(2:10) = = 9
 2  3  4  5  6
 7  8  9 10
t1(2.:3:10.)= 3
 2  5  8
1.:0.5:3.999 => 6
 1 1.5  2 2.5  3
3.5
tt(2.+0i:10.+0i)= 9
(2,0) (3,0) (4,0) (5,0) (6,0)
(7,0) (8,0) (9,0) (10,0)
t1(2.:3.:10.);= 3
(2,0) (5,0) (8,0)

tt.re real part array 9
 2  3  4  5  6
 7  8  9 10

```

```

tt.im imag part array 9
0 0 0 0 0
0 0 0 0
2

```

the all integer array operators are :

```

{
int N=5;
real[int] a(N),b(N),c(N);
a =1;
a(0:4:2) = 2;
a(3:4) = 4;
cout <<" a = " << a << endl;
b = a+ a;
cout <<" b = a+a : " << b << endl;
b += a;
cout <<" b += a : " << b << endl;
b += 2*a;
cout <<" b += 2*a : " << b << endl;
b /= 2;
cout <<" b /= 2 : " << b << endl;
b *= a;
cout << "b*=a; b =" << b << endl;
b /= a;
cout << "b/=a; b =" << b << endl;
c = a+b;
cout << " c =a+b : c=" << c << endl;
c = 2*a+4*b;
cout << " c =2*a+4b : c=" << c << endl;
c = a+4*b;
cout << " c =a+4b : c=" << c << endl;
c = -a+4*b;
cout << " c =-a+4b : c=" << c << endl;
c = -a-4*b;
cout << " c =-a-4b : c=" << c << endl;
c = -a-b;
cout << " c =-a-b : c=" << c << endl;

c = a .* b;
cout << " c =a.*b : c=" << c << endl;
c = a ./ b;
cout << " c =a./b : c=" << c << endl;
c = 2 * b;
cout << " c =2*b : c=" << c << endl;
c = b*2 ;
cout << " c =b*2 : c=" << c << endl;

/* this operator do not exist
c = b/2 ;
cout << " c =b/2 : c=" << c << endl;
*/

cout << " ||a|_1 = " << a.l1 << endl;

```

// same b = b .\* a  
// same b = b ./ a  
  
// ---- the methods --  
//

```

cout << " ||a||_2      = " << a.l2      << endl;      //
cout << " ||a||_infty = " << a.linfty << endl;      //
cout << " sum a_i      = " << a.sum      << endl;      //
cout << " max a_i      = " << a.max      << endl;      //
cout << " min a_i      = " << a.min      << endl;      //
cout << " a'*a          = " << (a'*a)    << endl;      //
cout << " a quantile 0.2 = " << a.quantile(0.2) << endl; //
}

```

produce the output

```

5
      3      3      2      3      3
==  3      3      2      3      3
a = 5
      2      1      2      4      4
b = a+a : 5
      4      2      4      8      8
b += a : 5
      6      3      6      12     12
b += 2*a : 5
      10     5      10     20     20
b /= 2 : 5
      5      2.5    5      10     10
b*=a; b =5
      10     2.5    10     40     40
b/=a; b =5
      5      2.5    5      10     10
c =a+b : c=5
      7      3.5    7      14     14
c =2*a+4b : c= 5
      24     12     24     48     48
c =a+4b : c= 5
      22     11     22     44     44
c =-a+4b : c= 5
      18      9      18     36     36
c =-a-4b : c= 5
      -22    -11    -22    -44    -44
c =-a-b : c= 5
      -7     -3.5   -7     -14    -14
c =a.*b : c= 5
      10     2.5    10     40     40

```



```

c =a./b   : c= 5
    0.4    0.4    0.4    0.4    0.4

c =2*b    : c= 5
    10     5     10     20     20

c =b*2    : c= 5
    10     5     10     20     20

||a||_1    = 13
||a||_2    = 6.403124237
||a||_infty = 4
sum a_i    = 13
max a_i    = 4
min a_i    = 1
a'*a       = 41
a quantile 0.2 = 2

```

**Note 4.2** *Quantiles are points taken at regular intervals from the cumulative distribution function of a random variable. Here the array values are random.*

*This statistical function `a.quantile(q)` computes  $v$  from an array  $a$  of size  $n$  for a given number  $q \in ]0, 1[$  such that*

$$\#\{i/a[i] < v\} \sim q * n$$

*; it is equivalent to  $v = a[q * n]$  when the array  $a$  is sorted.*

**Example of array with renumbering** (version 2.3 or better) . The renumbering is always given by an integer array, and if a value in the array is negative, the mapping is not imaged, so the value is not set.

```

int[int] I=[2,3,4,-1,0];           // the integer mapping to set the renumbering
b=c=-3;
b= a(I);                           // for( i=0;i<b.n;i++) if(I[i] >=0) b[i]=a[I[i]];
c(I)= a;                            // for( i=0;i<I.n;i++) if(I[i] >=0) C(I[i])=a[i];
cout << " b = a(I) : " << b << "\n" c(I) = a " << c << endl;

```

The output is

```

b = a(I) : 5
    2      4      4     -3      2

c(I) = a 5
    4     -3      2      1      2

```

### 4.8.1 Arrays with two integer indices versus matrices

Some example are given below to transform full matrices into sparse matrices.

```

int N=3,M=4;

real[int,int] A(N,M);
real[int] b(N),c(M);
b=[1,2,3];
c=[4,5,6,7];

complex[int,int] C(N,M);
complex[int] cb=[1,2,3],cc=[10i,20i,30i,40i];

b=[1,2,3];

int [int] I=[2,0,1];
int [int] J=[2,0,1,3];

A=1; // set the all matrix
A(2,:) = 4; // the full line 2
A(:,1) = 5; // the full column 1
A(0:N-1,2) = 2; // set the column 2
A(1,0:2) = 3; // set the line 1 from 0 to 2

cout << " A = " << A << endl;

C = cb*cc'; // outer product
C += 3*cb*cc';
C -= 5i*cb*cc';
cout << " C = " << C << endl; // this transforms an array into a sparse matrix

matrix B;
B = A;
B=A(I,J); // B(i,j)= A(I(i),J(j))
B=A(I^-1,J^-1); // B(I(i),J(j))= A(i,j)

A = 2.*b*c'; // outer product
cout << " A = " << A << endl;
B = b*c'; // outer product B(i,j) = b(i)*c(j)
B = b*c'; // outer product B(i,j) = b(i)*c(j)
B = (2*b*c')(I,J); // outer product B(i,j) = b(I(i))*c(J(j))
B = (3.*b*c')(I^-1,J^-1); // outer product B(I(i),J(j)) = b(i)*c(j)
cout << "B = (3.*b*c')(I^-1,J^-1) = " << B << endl;

```

the output is

```

b = a(I) : 5
           2       4       4       -3       2

c(I) = a 5
          4       -3       2       1       2

```

A = 3 4

```
1  5  2  1
3  3  3  1
4  5  2  4
```

C = 3 4

```
(-50,-40) (-100,-80) (-150,-120) (-200,-160)
(-100,-80) (-200,-160) (-300,-240) (-400,-320)
(-150,-120) (-300,-240) (-450,-360) (-600,-480)
```

A = 3 4

```
8 10 12 14
16 20 24 28
24 30 36 42
```

## 4.8.2 Matrix construction and setting

- To change the linear system solver associated to a matrix do

```
set(M,solver=sparsesolver);
```

The default solver is GMRES.

- from a variational form: (see section 6.12 page 159 for details)

```
varf vDD(u,v) = int2d(Thm)(u*v*1e-10);
matrix DD=vDD(Lh,Lh);
```

- To set from a constant matrix

```
matrix A =
    [ 0, 1, 0, 10],
    [ 0, 0, 2, 0],
    [ 0, 0, 0, 3],
    [ 4,0 , 0, 0]];
```

- To set from a block matrix

```
matrix M=[
    [ Asd[0] ,0      ,0      ,0      ,Csd[0] ],
    [ 0      ,Asd[1] ,0      ,0      ,Csd[1] ],
    [ 0      ,0      ,Asd[2] ,0      ,Csd[2] ],
    [ 0      ,0      ,0      ,Asd[3] ,Csd[3] ],
    [ Csd[0]',Csd[1]',Csd[2]',Csd[3]',DD      ]
];

// to now to pack the right hand side
real[int] bb =[rhssd[0][], rhssd[1][],rhssd[2][],rhssd[3][],rhs1[] ];
set(M,solver=sparsesolver);
xx = M^-1 * bb;
[usd[0][],usd[1][],usd[2][],usd[3][],lh[]] = xx;
// to dispatch the solution on each part.
```

where `Asd` and `Csd` are arrays of matrices (from example `mortar-DN-4.edp` of `examples++-tutorial`)

- To set or get all the indices and coefficients of the sparse matrix  $A$ , let  $I, J, C$  be respectively two `int[int]` arrays and a `real[int]` array. The three arrays define the matrix as follows

$$A = \sum_k C[k] M_{I[k], J[k]} \quad \text{where} \quad M_{ab} = (\delta_{ia} \delta_{jb})_{ij}$$

one has:  $M_{ab}$  a basic matrix with the only non zero term  $m_{ab} = 1$ .

One can write `[I, J, C]=A` ; to get all the term of the matrix  $A$  (the arrays are automatically resized), and `A=[I, J, C]` ; to change all the term matrices. Note that the size of the matrix is with `n= I.max` and `m=J.max`. Remark that `I, J` is forgotten to build a diagonal matrix, and similarly for the  $n, m$  of the matrix.

- matrix renumbering

```
int[int] I(15),J(15);                                     // two array for renumbering
                                                         //
                                                         // the aim is to transform a matrix into a sparse matrix
matrix B;
B = A;                                                     // copie matrix A
B=A(I,J);                                                  // B(i,j) = A(I(i),J(j))
B=A(I^-1,J^-1);                                           // B(I(i),J(j))= A(i,j)
B.resize(10,20);     // resize the sparse matrix and remove out of bound terms
```

where  $A$  is a given matrix.

### 4.8.3 Matrix Operations

The multiplicative operators `*`, `/`, and `%` group left to right.

- `'` is the (unary) right transposition for arrays, the matrix in real cases and Hermitian transpose in complex cases.
- `.*` is the term to term multiply operator.
- `./` is the term to term divide operator.

there are some compound operators also:

- `^-1` is for solving the linear system (example: `b = A^-1 x`)
- `' *` is the compound of transposition and matrix product, so it is the dot product (example `real DotProduct=a'*b`), in complex case you get the Hermitian product, so mathematically we have  $a' * b = \bar{a}^T b$ .
- `a*b'` is the outer product (example `matrix B=a'*b`)

**Example 4.5**

```

mesh Th = square(2,1);
fespace Vh(Th,P1);
Vh f,g;
f = x*y;
g = sin(pi*x);
Vh<complex> ff,gg; // a complex valued finite element function
ff= x*(y+1i);
gg = exp(pi*x*1i);
varf mat(u,v) =
    int2d(Th)(1*dx(u)*dx(v)+2*dx(u)*dy(v)+3*dy(u)*dx(v)+4*dy(u)*dy(v))
    + on(1,2,3,4,u=1);
varf mati(u,v) =
    int2d(Th)(1*dx(u)*dx(v)+2i*dx(u)*dy(v)+3*dy(u)*dx(v)+4*dy(u)*dy(v))
    + on(1,2,3,4,u=1);
matrix A = mat(Vh,Vh); matrix<complex> AA = mati(Vh,Vh); // a complex sparse matrix

Vh m0; m0[] = A*f[];
Vh m01; m01[] = A'*f[];
Vh m1; m1[] = f[].*g[];
Vh m2; m2[] = f[]./g[];
cout << "f = " << f[] << endl;
cout << "g = " << g[] << endl;
cout << "A = " << A << endl;
cout << "m0 = " << m0[] << endl;
cout << "m01 = " << m01[] << endl;
cout << "m1 = " << m1[] << endl;
cout << "m2 = " << m2[] << endl;
cout << "dot Product = " << f[]'*g[] << endl;
cout << "hermitien Product = " << ff[]'*gg[] << endl;
cout << "outer Product = " << (A=ff[]*gg[]) << endl;
cout << "hermitien outer Product = " << (AA=ff[]*gg[]) << endl;
real[int] diagofA(A.n);
    diagofA = A.diag; // get the diagonal of the matrix
    A.diag = diagofA; // set the diagonal of the matrix
                        // version 2.17 or better ---

int[int] I(1),J(1); real[int] C(1);
[I,J,C]=A; // get of the sparse term of the matrix A (the array are resized)
cout << " I= " << I << endl;
cout << " J= " << J << endl;
cout << " C= " << C << endl;
A=[I,J,C]; // set a new matrix
matrix D=[diagofA] ; // set a diagonal matrix D from the array diagofA.
cout << " D = " << D << endl;

```

The resizing of a sparse matrix A is also allowed:

```
A.resize(10,100);
```

Note that the new size can be greater or smaller than the previous size; all new term are set to zero.

On the triangulation of Figure 2.4 this produces the following:

$$\begin{aligned}
 A &= \begin{bmatrix} 10^{30} & 0.5 & 0. & 30. & -2.5 & 0. \\ 0. & 10^{30} & 0.5 & 0. & 0.5 & -2.5 \\ 0. & 0. & 10^{30} & 0. & 0. & 0.5 \\ 0.5 & 0. & 0. & 10^{30} & 0. & 0. \\ -2.5 & 0.5 & 0. & 0.5 & 10^{30} & 0. \\ 0. & -2.5 & 0. & 0. & 0.5 & 10^{30} \end{bmatrix} \\
 \{v\} = f[] &= \begin{pmatrix} 0 & 0 & 0 & 0 & 0.5 & 1 \end{pmatrix}^T \\
 \{w\} = g[] &= \begin{pmatrix} 0 & 1 & 1.2 \times 10^{-16} & 0 & 1 & 1.2 \times 10^{-16} \end{pmatrix} \\
 A * f[] &= \begin{pmatrix} -1.25 & -2.25 & 0.5 & 0 & 5 \times 10^{29} & 10^{30} \end{pmatrix}^T (= A\{v\}) \\
 A' * f[] &= \begin{pmatrix} -1.25 & -2.25 & 0 & 0.25 & 5 \times 10^{29} & 10^{30} \end{pmatrix}^T (= A^T\{v\}) \\
 f[] .* g[] &= \begin{pmatrix} 0 & 0 & 0 & 0 & 0.5 & 1.2 \times 10^{-16} \end{pmatrix}^T = (v_1 w_1 \quad \cdots \quad v_M w_M)^T \\
 f[] ./ g[] &= \begin{pmatrix} -\text{NaN} & 0 & 0 & -\text{NaN} & 0.5 & 8.1 \times 10^{15} \end{pmatrix}^T = (v_1/w_1 \quad \cdots \quad v_M/w_M)^T \\
 f[] ' * g[] &= 0.5 \quad (= \{v\}^T \{w\} = \{v\} \cdot \{w\})
 \end{aligned}$$

The output of the I, J, C array:

```

I= 18
    0      0      0      1      1
    1      1      2      2      3
    3      4      4      4      4
    5      5      5
J= 18
    0      1      4      1      2
    4      5      2      5      0
    3      0      1      3      4
    1      4      5
C= 18
1e+30  0.5    -2.5    1e+30  0.5
0.5    -2.5    1e+30  0.5    0.5
1e+30  -2.5    0.5    0.5    1e+30
-2.5    0.5    1e+30

```

The output of a diagonal sparse matrix *D* (Warning du to fortran interface the indices start on the output at one, but in **FreeFem++** in index as in *C* begin at zero);

```

D = # Sparse Matrix (Morse)
# first line: n m (is symmetric) nbcoef
# after for each nonzero coefficient: i j a_ij where (i,j) \in {1,...,n}x{1,...,m}
6 6 1 6
1      1 1.0000000000000000199e+30
2      2 1.0000000000000000199e+30
3      3 1.0000000000000000199e+30
4      4 1.0000000000000000199e+30
5      5 1.0000000000000000199e+30
6      6 1.0000000000000000199e+30

```

**Note 4.3** The operators  $^{-1}$  cannot be used to create a matrix; the following gives an error

```
matrix AAA = A-1;
```

In examples++-load/lapack.edp a full matrix is inverted using the lapack library and this small dynamic link interface (see for more detail section C page 307).

```
load "lapack"
load "fflapack"
int n=5;
real[int,int] A(n,n),A1(n,n),B(n,n);
for(int i=0;i<n;++i)
for(int j=0;j<n;++j)
  A(i,j)= (i==j) ? n+1 : 1;
cout << A << endl;
A1=A-1; // def in load "lapack"
cout << A1 << endl;

B=0;
for(int i=0;i<n;++i)
  for(int j=0;j<n;++j)
    for(int k=0;k<n;++k)
      B(i,j) +=A(i,k)*A1(k,j);
cout << B << endl; // A1+A-1; attention ne marche pas

inv(A1); // def in load "fflapack"
cout << A1 << endl;
```

and the output is:

```
5 5
 6  1  1  1  1
 1  6  1  1  1
 1  1  6  1  1
 1  1  1  6  1
 1  1  1  1  6

error: dgesv_ 0
5 5
0.18 -0.02 -0.02 -0.02 -0.02
-0.02 0.18 -0.02 -0.02 -0.02
-0.02 -0.02 0.18 -0.02 -0.02
-0.02 -0.02 -0.02 0.18 -0.02
-0.02 -0.02 -0.02 -0.02 0.18

5 5
 1 -1.387778781e-17 -1.040834086e-17 3.469446952e-17  0
-1.040834086e-17  1 -1.040834086e-17 -2.081668171e-17  0
3.469446952e-18 -5.551115123e-17  1 -2.081668171e-17 -2.775557562e-17
1.387778781e-17 -4.510281038e-17 -4.857225733e-17  1 -2.775557562e-17
-1.387778781e-17 -9.714451465e-17 -5.551115123e-17 -4.163336342e-17  1

5 5
 6  1  1  1  1
 1  6  1  1  1
```

```

1   1   6   1   1
1   1   1   6   1
1   1   1   1   6

```

to compile `lapack.cpp` or `fblas.cpp` you must have the library `lapack` on your system and try in directory `examples++-load`

```

ff-c++ lapack.cpp -llapack
ff-c++ fblas.cpp -llapack

```

#### 4.8.4 Other arrays

It is also possible to make an array of FE functions, with the same syntax, and we can treat them as *vector valued function* if we need them.

**Example 4.6** In the following example, Poisson's equation is solved for 3 different given functions  $f = 1, \sin(\pi x) \cos(\pi y), |x - 1||y - 1|$ , whose solutions are stored in an array of FE function.

```

mesh Th=square(20,20,[2*x,2*y]);
fespace Vh(Th,P1);
Vh u, v, f;
problem Poisson(u,v) =
    int2d(Th)( dx(u)*dx(v) + dy(u)*dy(v))
    + int2d(Th)( -f*v ) + on(1,2,3,4,u=0) ;
Vh[int] uu(3);                                     // an array of FE function
f=1;                                                 // problem1
Poisson; uu[0] = u;
f=sin(pi*x)*cos(pi*y);                             // problem2
Poisson; uu[1] = u;
f=abs(x-1)*abs(y-1);                                // problem3
Poisson; uu[2] = u;
for (int i=0; i<3; i++)                             // plots all solutions
    plot(uu[i], wait=true);

```

For the second case, it is just a map of the STL<sup>1</sup>[26] so no operations on vector are allowed, except the selection of an item .

The transpose or Hermitian conjugation operator is ' as in Matlab or Scilab, so the way to compute the dot product of two array `a,b` is `real ab= a'*b`.

```

int i;
real [int] tab(10), tab1(10);                       // 2 array of 10 real
    real [int] tab2;                                 // Error: array with no size
tab = 1;                                              // set all the array to 1
tab[1]=2;
cout << tab[1] << " " << tab[9] << " size of tab = "
    << tab.n << " " << tab.min << " " << tab.max << " " << endl;
tab1=tab; tab=tab+tab1; tab=2*tab+tab1*5; tab1=2*tab-tab1*5;
tab+=tab; cout << " dot product " << tab'*tab << endl; // 'tab tab
cout << tab << endl; cout << tab[1] << " "

```

<sup>1</sup>Standard template Library, now part of standard C++



```

<< tab[9] << endl; real[string] map; // a dynamic array
for (i=0;i<10;i=i+1)
{
    tab[i] = i*i;
    cout << i << " " << tab[i] << "\n";
};

map["1"]=2.0;
map[2]=3.0; // 2 is automatically cast to the string "2"

cout << " map[\\"1\\" ] = " << map["1"] << "; "<< endl;
cout << " map[2] = " << map[2] << "; "<< endl;

```

## 4.9 Loops

The for and while loops are implemented in FreeFem++ together with break and continue keywords.

In for-loop, there are three parameters; the INITIALIZATION of a control variable, the CONDITION to continue, the CHANGE of the control variable. While CONDITION is true, for-loop continue.

```

for (INITIALIZATION; CONDITION; CHANGE)
{ BLOCK of calculations }

```

An example below shows a sum from 1 to 10 with result is in sum,

```

int sum=0;
for (int i=1; i<=10; i++)
    sum += i;

```

The while-loop

```

while (CONDITION) {
    BLOCK of calculations or change of control variables
}

```

is executed repeatedly until CONDITION become false. The sum from 1 to 10 can also be computed by while as follows,

```

int i=1, sum=0;
while (i<=10) {
    sum += i; i++;
}

```

We can exit from a loop in midstream by break. The continue statement will pass the part from continue to the end of the loop.

### Example 4.7

```

for (int i=0;i<10;i=i+1)
    cout << i << "\n";
real eps=1;
while (eps>1e-5)

```

```

{ eps = eps/2;
  if( i++ <100) break;
  cout << eps << endl;}

for (int j=0; j<20; j++) {
  if (j<10) continue;
  cout << "j = " << j << endl;
}

```

## 4.10 Input/Output

The syntax of input/output statements is similar to C++ syntax. It uses `cout`, `cin`, `endl`, `<<`, `>>`. To write to (resp. read from) a file, declare a new variable `ofstream ofile("filename");` or `ofstream ofile("filename",append);` (resp. `ifstream ifile("filename");`) and use `ofile` (resp. `ifile`) as `cout` (resp. `cin`).

The word `append` in `ofstream ofile("filename",append);` means opening a file in `append` mode.

**Note 4.4** *The file is closed at the exit of the enclosing block,*

### Example 4.8

```

int i;
cout << " std-out" << endl;
cout << " enter i= ? ";
cin >> i ;
{
  ofstream f("toto.txt");
  f << i << "coucou'\n";
};                                     // close the file f because the variable f is delete

{
  ifstream f("toto.txt");
  f >> i;
}
{
  ofstream f("toto.txt",append);
                                     // to append to the existing file "toto.txt"
  f << i << "coucou'\n";
};                                     // close the file f because the variable f is delete

cout << i << endl;

```

Some functions are available to format the output.

- `int nold=f.precision(n)` Sets the number of digits printed to the right of the decimal point. This applies to all subsequent floating point numbers written to that output stream. However, this won't make floating-point "integers" print with a decimal point. It's necessary to use `fixed` for that effect.
- `f.scientific` Formats floating-point numbers in scientific notation ( `d.dddEdd` )

- **f.fixed** Used fixed point notation ( `d.ddd` ) for floating-point numbers. Opposite of scientific.
- **f.showbase** Converts insertions to an external form that can be read according to the C++ lexical conventions for integral constants. By default, showbase is not set.
- **f.noshowbase** unset showbase flags
- **f.showpos** inserts a plus sign (+) into a decimal conversion of a positive integral value.
- **f.noshowpos** unset showpos flags
- **f.default** reset all the previous flags (`fmtflags`) to the default expect precision.

Where *f* is output stream descriptor, for example `cout`.

Remark, all these methods except the first return the stream `£`, so they can be chained as in

```
cout.scientific.showpos << 3 << endl;
```

### 4.10.1 Script arguments

There is a very useful predefined array in Freefem++ `ARGV` that contains all the arguments of the script used in the command line. The following code prints out the first three of these arguments:

```

// version 3.8-1
for(int i=0;i<ARGV.n;++i)
{
    cout << ARGV[i] << endl;
}
```

And to get argument unused in `getARGV.idp` include script file,

```

getARGV(n,defaultvalue) // get the nth parameter unused if exist (n = 1, ...)
getARGV(after,defaultvalue) // get the arg after the string after if exist
```

The type of default value can be `int`, `real`, `string`,

## 4.11 preprocessor

The preprocessor handles directives for source file inclusion (`include "script-name.idp"`), macro definitions.

There are two types of macros, object-like and function-like. Object-like macros do not take parameters; function-like macros do. The generic syntax for declaring an identifier as a macro of each type is, respectively,

```

macro <identifier>() <replacement token list> // EOM a // comment to end the macro
macro <identifier>(<parameter list>) <replacement token list> // EOM
```

An example of macro without parameter

```
macro xxx() {real i=0;int j=0;cout << i << " " << j << endl;} //
xxx /* replace xxx by the <replacement token list> */
```

The freemem++ code associated:

```
1 : // macro without parameter
2 : macro xxx {real i=0;int j=0;cout << i << " " << j << endl;}//
3 :
4 : {real i=0;int j=0;cout << i << " " << j << endl;}
```

An example of macro parameter

```
macro toto(i) i //
toto({real i=0;int j=0;cout << i << " " << j << endl;}) // quoting parameter the {} are remove
toto({{real i=0;int j=0;cout << i << " " << j << endl;}}) // and only one level of {} are remove
```

The freemem++ code created :

```
6 : macro toto(i ) i //
8 : // quoting parameter the {\} are remove
9 : real i=0;int j=0;cout << i << " " << j << endl;
10 : // and only one level of {\} are remove
11 : {real i=0;int j=0;cout << i << " " << j << endl;}
```

Use a macro as parameter of macro to transforme full matrix in formal array like in :

```
real[int,int] CC(7,7),EE(6,3),EEps(4,4);

macro VIL6(v,i) [ v(1,i), v(2,i),v(4,i), v(5,i),v(6,i) ] // EOM
macro VIL3(v,i) [ v(1,i), v(2,i) ] // EOM
// apply v on array element :
macro VV6(v,vv) [ v(vv,1), v(vv,2),
v(vv,4), v(vv,5), v(vv,6) ] // EOM
macro VV3(v,vv) [ v(vv,1), v(vv,2) ] // EOM
// so formal matrix to build problem..

func C5x5 = VV6(VIL6,CC);
func E5x2 = VV6(VIL3,EE);
func Eps = VV3(VIL3,EEps);
```

The freemem++ code created :

```
16 : real[int,int] CC(7,7),EE(6,3),EEps(4,4);
17 :
18 : macro VIL6(v,i ) [ v(1,i), v(2,i),v(4,i), v(5,i),v(6,i) ] // EOM
19 : macro VIL3(v,i ) [ v(1,i), v(2,i) ] // EOM
20 : // apply v on array element :
21 : macro VV6(v,vv ) [ v(vv,1), v(vv,2),
22 : v(vv,4), v(vv,5), v(vv,6) ] // EOM
23 : macro VV3(v,vv ) [ v(vv,1), v(vv,2) ] // EOM
24 : // so formal matrix to build problem..
25 : func C5x5 =
```

```

1 :      [      [ CC(1,1), CC(2,1),CC(4,1), CC(5,1),CC(6,1) ] ,
              [ CC(1,2), CC(2,2),CC(4,2), CC(5,2),CC(6,2) ] ,
1 :      [ CC(1,4), CC(2,4),CC(4,4), CC(5,4),CC(6,4) ] ,
              [ CC(1,5), CC(2,5),CC(4,5), CC(5,5),CC(6,5) ] ,
              [ CC(1,6), CC(2,6),CC(4,6), CC(5,6),CC(6,6) ] ] ;
26 : func E5x2 =
1 :      [      [ EE(1,1), EE(2,1) ] ,      [ EE(1,2), EE(2,2) ] ,
1 :      [ EE(1,4), EE(2,4) ] ,      [ EE(1,5), EE(2,5) ] ,
              [ EE(1,6), EE(2,6) ] ] ;
27 : func Eps =      [      [ EEps(1,1), EEps(2,1) ] ,
              [ EEps(1,2), EEps(2,2) ] ] ;
28 :

```

finally the operator # to do concatenation of parameter: to build vectorial operation, like in

```

macro div(u) (dx(u#1)+ dy(u#2))                                     // EOM
mesh Th=square(2,2); fespace Vh(Th,P1);
Vh v1=x,v2=y;
cout << int2d(Th)(div(v)) << endl;

```

The freefem++ code created :

```

31 : macro div(u ) (dx(u#1)+ dy(u#2)) //EOM
32 : mesh Th=square(2,2); fespace Vh(Th,P1);
33 : Vh v1=x,v2=y;
34 : cout << int2d(Th)( (dx(v1)+ dy(v2)) ) << endl;

```

And to finish a amazing test to verified the quoting :

```

macro foo(i,j,k) i j k                                           // EOM
foo(,,)                                                           // empty line
foo( {int [], {int] a(10},{})});

```

the result:

```

36 : macro foo(i,j,k ) i j k//EOM
37 :      // empty line
38 :      int [ int] a(10 );

```

## 4.12 Exception handling

In the version 2.3 of FreeFem++, exception handing was added as in C++. But today only the C++ exceptions are caught. Note that in C++ all the errors attached to `ExecError`, `assert`, `exit`, ... call exceptions too so it may be hard to find the cause of the error. The exceptions handle all `ExecError`:

**Example 4.9** *A simple example: catch a division by zero:*

```
real a;
try {
    a=1./0.;
}
catch (...) // in versions > 2.3 all exceptions can be caught
{
    cout << " Catch an ExecError " << endl;
    a =0;
}
```

The output is

```
1/0 : d d d
    current line = 3
Exec error : Div by 0
    -- number :1
Try:: catch (...) exception
Catch an ExecError
```

**Example 4.10** : *a more realistic example with a none invertible matrix:*

```
int nn=5 ;
mesh Th=square(nn,nn);
verbosity=5;
fespace Vh(Th,P1); // P1 FE space
Vh uh,vh; // unkown and test function.
func f=1; // right hand side function
func g=0; // boundary condition function
real cpu=clock();
problem laplace(uh,vh,solver=Cholesky,tolpivot=1e-6) = // definion
of the problem
    int2d(Th)( dx(uh)*dx(vh) + dy(uh)*dy(vh) ) // bilinear form
    + int2d(Th)( -f*vh ) // linear form
;

try {
    cout << " Try Cholesky \n";
    laplace; // solve the problem
    plot(uh); // to see the result
    cout << "-- lap Cholesky " << nn << "x" << nn << " : " << -cpu+clock()
        << " s, max =" << uh[].max << endl;
}
catch(...) { // catch all
    cout << " Catch cholesky PB " << endl;
}
```

The output is

```

-- square mesh : nb vertices =36 , nb triangles = 50 ...
Nb of edges on Mortars = 0
Nb of edges on Boundary = 20, neb = 20
Nb Mortars 0
number of real boundary edges 20
  Number of Edges          = 85
  Number of Boundary Edges = 20 neb = 20
  Number of Mortars Edges  = 0
  Nb Of Mortars with Paper Def = 0 Nb Of Mortars = 0 ...
Nb Of Nodes = 36
Nb of DF = 36
Try Cholesky
  -- Change of Mesh 0 0x312e9e8
  Problem(): initmat 1 VF (discontinuous Galerkin) = 0
  -- SizeOfSkyline =210
  -- size of Matrix 196 Bytes skyline =1
  -- discontinuous Galerkin =0 size of Mat =196 Bytes
  -- int in Optimized = 1, ...
all
  -- boundary int Optimized = 1, all
ERREUR choleskypivot (35)= -1.23124e-13 < 1e-06
  current line = 28
Exec error : FATAL ERREUR dans ../femlib/MatriceCreuse_tpl.hpp
cholesky line:
  -- number :545
  catch an erreur in solve => set sol = 0 !!!!!!!
Try:: catch (...) exception
  Catch cholesky PB

```





# Chapter 5

## Mesh Generation

### 5.1 Commands for Mesh Generation

Let us begin with the two important keywords **border** and **buildmesh**

All examples in this section come from the files `mesh.edp` and `tablefunction.edp`.

#### 5.1.1 Square

The command “**square**” triangulates the unit square. The following

```
mesh Th = square(4,5);
```

generates a  $4 \times 5$  grid in the unit square  $[0, 1]^2$ . The labels of the boundaries are shown in Fig. 5.1. To construct a  $n \times m$  grid in the rectangle  $[x_0, x_1] \times [y_0, y_1]$ , proceeds as follows: write




Figure 5.1: Boundary labels of the mesh by `square(10,10)`

```
real x0=1.2, x1=1.8;  
real y0=0, y1=1;  
int n=5, m=20;  
mesh Th=square(n, m, [x0+(x1-x0)*x, y0+(y1-y0)*y]);
```

**Note 5.1** Adding the named parameter *flags=icase* with *icase*:

**0** will produce a mesh where all quads are split with diagonal  $x - y = cte$

**1** will produce Union Jack flag type of mesh.

**2** will produce a mesh where all quads are split with diagonal  $x + y = cte$  (v 3.8)

**3** same as case 0 except in two corners such that no triangle with 3 vertices on boundary (v 3.8)

**4** same as case 2 except in two corners such that no triangle with 3 vertices on boundary (v 3.8)

```
mesh Th=square(n,m,[x0+(x1-x0)*x,y0+(y1-y0)*y],flags=icase);
```

Adding the named parameter *label=labs* will change the 4 default label numbers to *labs[i-1]*, for example `int[int] labs=[11,12,13,14]`, and adding the named parameter *region=10* will change the region number to 10, for instance (v 3.8).

To see all these fags at work, try the file `examples++/square-mesh.edp`:

```
for (int i=0;i<5;++i)
{
    int[int] labs=[11,12,13,14];
    mesh Th=square(3,3,flags=i,label=labs,region=10);
    plot(Th,wait=1,cmm=" square flags = "+i );
}
```

## 5.1.2 Border

Boundaries are defined piecewise by parametrized curves. The pieces can only intersect at their endpoints, but it is possible to join more than two endpoints. This can be used to structure the mesh if an area thouches a border and create new regions by dividing larger ones:

```
int upper = 1;
int others = 2;
int inner = 3;

border C01(t=0,1){x = 0;          y = -1+t;          label = upper;}
border C02(t=0,1){x = 1.5-1.5*t; y = -1;             label = upper;}
border C03(t=0,1){x = 1.5;        y = -t;             label = upper;}
border C04(t=0,1){x = 1+0.5*t;    y = 0;              label = others;}
border C05(t=0,1){x = 0.5+0.5*t;  y = 0;              label = others;}
border C06(t=0,1){x = 0.5*t;      y = 0;              label = others;}
border C11(t=0,1){x = 0.5;        y = -0.5*t;         label = inner;}
border C12(t=0,1){x = 0.5+0.5*t;  y = -0.5;           label = inner;}
border C13(t=0,1){x = 1;          y = -0.5+0.5*t;     label = inner;}

int n = 10;
plot(C01(-n)+C02(-n)+C03(-n)+C04(-n)+C05(-n)+C06(-n)+
     C11(n)+C12(n)+C13(n), wait=true);

mesh Th = buildmesh(C01(-n)+C02(-n)+C03(-n)+C04(-n)+C05(-n)+C06(-n)+
```

```

C11(n)+C12(n)+C13(n));

plot(Th, wait=true); // figure 5.3

cout << "Part 1 has region number " << Th(0.75, -0.25).region << endl;
cout << "Part 2 has region number " << Th(0.25, -0.25).region << endl;

```




Figure 5.2: Multiple border ends intersect





Figure 5.3: Generated mesh

Triangulation keywords assume that the domain is defined as being on the *left* (resp *right*) of its oriented parameterized boundary

$$\Gamma_j = \{(x, y) \mid x = \varphi_x(t), y = \varphi_y(t), a_j \leq t \leq b_j\}$$

To check the orientation plot  $t \mapsto (\varphi_x(t), \varphi_y(t))$ ,  $t_0 \leq t \leq t_1$ . If it is as in Fig. 5.4, then the domain lies on the shaded area, otherwise it lies on the opposite side

Figure 5.4: Orientation of the boundary defined by  $(\phi_x(t), \phi_y(t))$ 

The general expression to define a triangulation with `buildmesh` is

```

mesh    Mesh_Name = buildmesh( $\Gamma_1(m_1) + \dots + \Gamma_J(m_J)$  OptionalParameter);

```

where  $m_j$  are positive or negative numbers to indicate how many vertices should be on  $\Gamma_j$ ,  $\Gamma = \cup_{j=1}^J \Gamma_j$ , and the optional parameter (separated with comma) can be

**nbvx=<int value>** , to set the maximal number of vertices in the mesh.

**fixeborder=<bool value>** , to say if the mesh generator can change the boundary mesh or not (by default the boundary mesh can change; beware that with periodic boundary conditions (see. 6), it can be dangerous .

The orientation of boundaries can be changed by changing the sign of  $m_j$ . The following example shows how to change the orientation. The example generates the unit disk with a small circular hole, and assign “1” to the unit disk (“2” to the circle inside). The boundary label must be non-zero, but it can also be omitted.

```
1: border a(t=0,2*pi){ x=cos(t); y=sin(t);label=1;}
2: border b(t=0,2*pi){ x=0.3+0.3*cos(t); y=0.3*sin(t);label=2;}
3: plot(a(50)+b(+30)) ; // to see a plot of the border mesh
4: mesh Thwithouthole= buildmesh(a(50)+b(+30));
5: mesh Thwithhole = buildmesh(a(50)+b(-30));
6: plot(Thwithouthole,wait=1,ps="Thwithouthole.eps"); // figure 5.5
7: plot(Thwithhole,wait=1,ps="Thwithhole.eps"); // figure 5.6
```

**Note 5.2** Notice that the orientation is changed by “b(-30)” in 5th line. In 7th line, ps=“fileName” is used to generate a postscript file with identification shown on the figure.




Figure 5.5: mesh without hole




Figure 5.6: mesh with hole

**Note 5.3** Borders are evaluated only at the time plot or buildmesh is called so the global variable are defined at this time and here since  $r$  is changed between the two border calls the following code will not work because the first border will be computed with  $r=0.3$ :

```
real r=1; border a(t=0,2*pi){ x=r*cos(t); y=r*sin(t);label=1;}
r=0.3 ; border b(t=0,2*pi){ x=r*cos(t); y=r*sin(t);label=1;}
mesh Thwithhole = buildmesh(a(50)+b(-30)); // bug (a trap) because
// the two circle have the same radius = 0.3
```

### 5.1.3 Data Structures and Read/Write Statements for a Mesh

Users who want to read a triangulation made elsewhere should see the structure of the file generated below:

```
border C(t=0,2*pi) { x=cos(t); y=sin(t); }
mesh Th = buildmesh(C(10));
savemesh("mesh_sample.msh");
```

the mesh is shown on Fig. 5.7.

The informations about Th are saved in the file “mesh\_sample.msh”. whose structure is shown on Table 5.1.

There  $n_v$  denotes the number of vertices,  $n_t$  number of triangles and  $n_s$  the number of edges on boundary.

For each vertex  $q^i$ ,  $i = 1, \dots, n_v$ , denote by  $(q_x^i, q_y^i)$  the  $x$ -coordinate and  $y$ -coordinate.

Each triangle  $T_k$ ,  $k = 1, \dots, 10$  has three vertices  $q^{k_1}, q^{k_2}, q^{k_3}$  that are oriented counterclockwise. The boundary consists of 10 lines  $L_i$ ,  $i = 1, \dots, 10$  whose end points are  $q^{i_1}, q^{i_2}$ .




Figure 5.7: mesh by buildmesh(C(10))

In the left figure, we have the following.

$$n_v = 14, n_t = 16, n_s = 10$$

$$q^1 = (-0.309016994375, 0.951056516295)$$

$$\vdots \quad \vdots \quad \vdots$$

$$q^{14} = (-0.309016994375, -0.951056516295)$$

The vertices of  $T_1$  are  $q^9, q^{12}, q^{10}$ .

$$\vdots \quad \vdots \quad \vdots$$

The vertices of  $T_{16}$  are  $q^9, q^{10}, q^6$ .

The edge of 1st side  $L_1$  are  $q^6, q^5$ .

$$\vdots \quad \vdots \quad \vdots$$

The edge of 10th side  $L_{10}$  are  $q^{10}, q^6$ .

In FreeFem++ there are many mesh file formats available for communication with other tools such as emc2, modulef.. (see Section 12), The extension of a file implies its format. More details can be found on the file format .msh in the article by F. Hecht “bamg : a bidimensional anisotropic mesh generator” (downloadable from the FreeFem web site. )

A mesh file can be read into FreeFem++ except that the names of the borders are lost and only their reference numbers are kept. So these borders have to be referenced by the number which corresponds to their order of appearance in the program, unless this number is overwritten by the keyword “label”. Here are some examples:

```
border floor(t=0,1){ x=t; y=0; label=1;};
border right(t=0,1){ x=1; y=t; label=5;};
```

// the unit square

Content of the file	Explanation
14 16 10	$n_v$ $n_t$ $n_e$
-0.309016994375 0.951056516295 1	$q_x^1$ $q_y^1$ boundary label=1
0.309016994375 0.951056516295 1	$q_x^2$ $q_y^2$ boundary label=1
... .. :	
-0.309016994375 -0.951056516295 1	$q_x^{14}$ $q_y^{14}$ boundary label=1
9 12 10 0	$1_1$ $1_2$ $1_3$ region label=0
5 9 6 0	$2_1$ $2_2$ $2_3$ region label=0
...	
9 10 6 0	$16_1$ $16_2$ $16_3$ region label=0
6 5 1	$1_1$ $1_2$ boundary label=1
5 2 1	$2_1$ $2_2$ boundary label=1
...	
10 6 1	$10_1$ $10_2$ boundary label=1

Table 5.1: The structure of “mesh\_sample.msh”

```

border ceiling(t=1,0){ x=t; y=1; label=5;};
border left(t=1,0){ x=0; y=t; label=5;};
int n=10;
mesh th= buildmesh(floor(n)+right(n)+ceiling(n)+left(n));
savemesh(th,"toto.am_fmt");           // "formatted Marrocco" format
savemesh(th,"toto.Th");               // "bamg"-type mesh
savemesh(th,"toto.msh");              // freefem format
savemesh(th,"toto.nopo");             // modulef format see [10]
mesh th2 = readmesh("toto.msh");      // read the mesh

```

**Example 5.1 (Readmesh.edp)**

```

border floor(t=0,1){ x=t; y=0; label=1;}; // the unit
square
border right(t=0,1){ x=1; y=t; label=5;};
border ceiling(t=1,0){ x=t; y=1; label=5;};
border left(t=1,0){ x=0; y=t; label=5;};
int n=10;
mesh th= buildmesh(floor(n)+right(n)+ceiling(n)+left(n));
savemesh(th,"toto.am_fmt");           // format "formatted Marrocco"
savemesh(th,"toto.Th");               // format database db mesh "bamg"
savemesh(th,"toto.msh");              // format freefem
savemesh(th,"toto.nopo");             // modulef format see [10]
mesh th2 = readmesh("toto.msh");
fespace femp1(th,P1);
femp1 f = sin(x)*cos(y),g;
{                                     // save solution
ofstream file("f.txt");
file << f[] << endl;
}                                     // close the file (end block)
{                                     // read
ifstream file("f.txt");
file >> g[] ;

```

```

} // close reading file (end block)
fespace Vh2(th2,P1);
Vh2 u,v;
plot(g);
// find u such that
//  $u + \Delta u = g$  in  $\Omega$  ,
//  $u = 0$  on  $\Gamma_1$  and  $\frac{\partial u}{\partial n} = g$  on  $\Gamma_2$ 
solve pb(u,v) =
    int2d(th)( u*v - dx(u)*dx(v)-dy(u)*dy(v) )
+ int2d(th)(-g*v)
+ int1d(th,5)( g*v) //  $\frac{\partial u}{\partial n} = g$  on  $\Gamma_2$ 
+ on(1,u=0) ;
plot (th2,u);

```

### 5.1.4 Mesh Connectivity

The following example explains methods to obtain mesh information.

```

{ // get mesh information (version 1.37)
mesh Th=square(2,2); // get data of the mesh

int nbtriangles=Th.nt;
cout << " nb of Triangles = " << nbtriangles << endl;
for (int i=0;i<nbtriangles;i++)
    for (int j=0; j <3; j++)
        cout << i << " " << j << " Th[i][j] = "
            << Th[i][j] << " x = "<< Th[i][j].x << " , y= "<< Th[i][j].y
            << " , label=" << Th[i][j].label << endl;

// Th(i) return the vertex i of Th
// Th[k] return the triangle k of Th

fespace femp1(Th,P1);
femp1 Thx=x,Thy=y; // hack of get vertex coordinates
// get vertices information :

int nbvertices=Th.nv;
cout << " nb of vertices = " << nbvertices << endl;
for (int i=0;i<nbvertices;i++)
    cout << "Th(" <<i << ") : " // << endl;
    << Th(i).x << " " << Th(i).y << " " << Th(i).label // v 2.19
    << " old method: " << Thx[][i] << " " << Thy[][i] << endl;

// method to find information of point (0.55,0.6)

int it00 = Th(0.55,0.6).nuTriangle; // then triangle number
int nr00 = Th(0.55,0.6).region; //

// info of a triangle
real area00 = Th[it00].area; // new in version 2.19
real nrr00 = Th[it00].region; // new in version 2.19
real nll00 = Th[it00].label; // same as region in this case.

// Hack to get a triangle containing point x,y

```

```

// or region number (old method)
// -----
fespace femp0(Th,P0);
femp0 nuT; // a P0 function to get triangle numbering
for (int i=0;i<Th.nt;i++)
    nuT[i]=i;
femp0 nuReg=region; // a P0 function to get the region number
// inquire
int it0=nuT(0.55,0.6); // number of triangle Th's containing (0.55,0,6);
int nr0=nuReg(0.55,0.6); // number of region of Th's containing (0.55,0,6);

// dump
// -----

cout << " point (0.55,0,6) :triangle number " << it00 << " " << it00
    << ", region = " << nr0 << " == " << nr00 << ", area K " << area00 << endl;

// new method to get boundary information and mesh adjacent

int k=0,l=1,e=1;
Th.nbe ; // return the number of boundary element
Th.be(k); // return the boundary element  $k \in \{0, \dots, Th.nbe - 1\}$ 
Th.be(k)[1]; // return the vertices  $l \in \{0,1\}$  of boundary elmt k
Th.be(k).Element ; // return the triangle containing the boundary elmt k
Th.be(k).whoinElement ; // return the edge number of triangle containing
// the boundary elmt k
Th[k].adj(e) ; // return adjacent triangle to k by edge e, and change
// the value of e to the corresponding edge in the adjacent triangle
Th[k] == Th[k].adj(e) // non adjacent triangle return the same
Th[k] != Th[k].adj(e) // true adjacent triangle

cout << " print mesh connectivity " << endl;
int nbelement = Th.nt;
for (int k=0;k<nbelement;++k)
    cout << k << " : " << int(Th[k][0]) << " " << int(Th[k][1])
        << " " << int(Th[k][2])
        << " , label " << Th[k].label << endl;
//

for (int k=0;k<nbelement;++k)
    for (int e=0,ee;e<3;++e)
        // remark FH hack: set ee to e, and ee is change by method adj,
        // in () to make difference with named parameters.
        cout << k << " " << e << " <=> " << int(Th[k].adj((ee=e))) << " " << ee
            << " adj: " << ( Th[k].adj((ee=e)) != Th[k]) << endl;
        // note : if k == int(Th[k].adj(ee=e)) not adjacent element

int nbboundaryelement = Th.nbe;

for (int k=0;k<nbboundaryelement;++k)
    cout << k << " : " << Th.be(k)[0] << " " << Th.be(k)[1] << " , label "
        << Th.be(k).label << " tria " << int(Th.be(k).Element)
        << " " << Th.be(k).whoinElement << endl;

```



```
}
```

the output is:

```
-- square mesh : nb vertices =9 , nb triangles = 8 , nb boundary edges 8
  Nb of Vertices 9 , Nb of Triangles 8
  Nb of edge on user boundary 8 , Nb of edges on true boundary 8
number of real boundary edges 8
nb of Triangles = 8
0 0 Th[i][j] = 0 x = 0 , y= 0, label=4
0 1 Th[i][j] = 1 x = 0.5 , y= 0, label=1
0 2 Th[i][j] = 4 x = 0.5 , y= 0.5, label=0
...
6 0 Th[i][j] = 4 x = 0.5 , y= 0.5, label=0
6 1 Th[i][j] = 5 x = 1 , y= 0.5, label=2
6 2 Th[i][j] = 8 x = 1 , y= 1, label=3
7 0 Th[i][j] = 4 x = 0.5 , y= 0.5, label=0
7 1 Th[i][j] = 8 x = 1 , y= 1, label=3
7 2 Th[i][j] = 7 x = 0.5 , y= 1, label=3
Nb Of Nodes = 9
Nb of DF = 9
-- vector function's bound 0 1
-- vector function's bound 0 1
nb of vertices = 9
Th(0) : 0 0 4 old method: 0 0
Th(1) : 0.5 0 1 old method: 0.5 0
...
Th(7) : 0.5 1 3 old method: 0.5 1
Th(8) : 1 1 3 old method: 1 1
Nb Of Nodes = 8
Nb of DF = 8

print mesh connectivity
0 : 0 1 4 , label 0
1 : 0 4 3 , label 0
...
6 : 4 5 8 , label 0
7 : 4 8 7 , label 0
0 0 <=> 3 1 adj: 1
0 1 <=> 1 2 adj: 1
0 2 <=> 0 2 adj: 0
...
6 2 <=> 3 0 adj: 1
7 0 <=> 7 0 adj: 0
7 1 <=> 4 0 adj: 1
7 2 <=> 6 1 adj: 1
0 : 0 1 , label 1 tria 0 2
1 : 1 2 , label 1 tria 2 2
...
6 : 0 3 , label 4 tria 1 1
7 : 3 6 , label 4 tria 5 1
```

### 5.1.5 The keyword "triangulate"

FreeFem++ is able to build a triangulation from a set of points. This triangulation is a Delaunay mesh of the convex hull of the set of points. It can be useful to build a mesh from a table function. The coordinates of the points and the value of the table function are defined separately with rows of the form:  $x \ y \ f(x,y)$  in a file such as:

```
0.51387 0.175741 0.636237
0.308652 0.534534 0.746765
0.947628 0.171736 0.899823
0.702231 0.226431 0.800819
0.494773 0.12472 0.580623
0.0838988 0.389647 0.456045
.....
```




Figure 5.8: Delaunay mesh of the convex hull of point set in file xyf




Figure 5.9: Isovalue of table function

The third column of each line is left untouched by the `triangulate` command. But you can use this third value to define a table function with rows of the form:  $x \ y \ f(x,y)$ .

The following example shows how to make a mesh from the file "xyf" with the format stated just above. The command `triangulate` command use only use 1st and 2nd rows.

```
mesh Thxy=triangulate("xyf");           // build the Delaunay mesh of the convex hull
// points are defined by the first 2 columns of file xyf
plot(Thxy,ps="Thxyf.ps");               // (see figure 5.8)

fespace Vhxy(Thxy,P1);                  // create a P1 interpolation
Vhxy fxy;                                // the function

// reading the 3rd row to define the function
{ ifstream file("xyf");
  real xx,yy;
  for(int i=0;i<fxy.n;i++)
    file >> xx >>yy >> fxy[i][i];
}
// to read third row only.
// xx and yy are just skipped
plot(fxu,ps="xyf.eps");                  // plot the function (see figure 5.9)
```

One new way to build a mesh is to have two arrays one the  $x$  values and the other for the  $y$  values (version 2.23-2):

```
Vhxy xx=x,yy=y; // to set two arrays for the x's and y's
mesh Th=triangulate(xx[],yy[]);
```

## 5.2 Boundary FEM Spaces Built as Empty Meshes

To define a Finite Element space on a boundary, we came up with the idea of a mesh with no internal points (call empty mesh). It can be useful to handle Lagrange multipliers in mixed and mortar methods.

So the function `emptymesh` remove all the internal points of a mesh except points on internal boundaries.

```
{ // new stuff 2004 emptymesh (version 1.40)
// -- useful to build Multiplier space
// build a mesh without internal point
// with the same boundary
// -----

assert(version>=1.40);
border a(t=0,2*pi){ x=cos(t); y=sin(t);label=1;}
mesh Th=buildmesh(a(20));
Th=emptymesh(Th);
plot(Th,wait=1,ps="emptymesh-1.eps"); // see figure 5.10
}
```

It is also possible to build an empty mesh of a pseudo subregion with `emptymesh(Th,ssd)` using the set of edges of the mesh `Th`; a edge  $e$  is in this set if with the two adjacent triangles  $e = t1 \cap t2$  and  $ssd[T1] \neq ssd[T2]$  where `ssd` refers to the pseudo region numbering of triangles, when they are stored in an `int[int]` array of size the number of triangles.

```
{ // new stuff 2004 emptymesh (version 1.40)
// -- useful to build Multiplier space
// build a mesh without internal point
// of pseudo sub domain
// -----

assert(version>=1.40);
mesh Th=square(10,10);
int[int] ssd(Th.nt);
for(int i=0;i<ssd.n;i++) // build the pseudo region numbering
{ int iq=i/2; // because 2 triangle per quad
int ix=iq%10; //
int iy=iq/10; //
ssd[i]= 1 + (ix>=5) + (iy>=5)*2;
}
Th=emptymesh(Th,ssd); // build empty with
// all edge e = T1 ∩ T2 and ssd[T1] ≠ ssd[T2]

plot(Th,wait=1,ps="emptymesh-2.eps"); // see figure 5.11
savemesh(Th,"emptymesh-2.msh");
}
```




Figure 5.10: The empty mesh with boundary




Figure 5.11: An empty mesh defined from a pseudo region numbering of triangle

## 5.3 Remeshing

### 5.3.1 Movemesh

Meshes can be translated, rotated and deformed by `movemesh`; this is useful for elasticity to watch the deformation due to the displacement  $\Phi(x, y) = (\Phi_1(x, y), \Phi_2(x, y))$  of shape. It is also useful to handle free boundary problems or optimal shape problems.

If  $\Omega$  is triangulated as  $T_h(\Omega)$ , and  $\Phi$  is a displacement vector then  $\Phi(T_h)$  is obtained by

```
mesh Th=movemesh(Th,[Phi1,Phi2]);
```

Sometimes the transformed mesh is invalid because some triangle have flip over (now has negative area). To spot such problems one may check the minimum triangle area in the transformed mesh with `checkmovemesh` before any real transformation.

**Example 5.2**  $\Phi_1(x, y) = x + k * \sin(y * \pi)/10$ ,  $\Phi_2(x, y) = y + k * \cos(y\pi)/10$  for a big number  $k > 1$ .

```

verbosity=4;
border a(t=0,1){x=t;y=0;label=1;};
border b(t=0,0.5){x=1;y=t;label=1;};
border c(t=0,0.5){x=1-t;y=0.5;label=1;};
border d(t=0.5,1){x=0.5;y=t;label=1;};
border e(t=0.5,1){x=1-t;y=1;label=1;};
border f(t=0,1){x=0;y=1-t;label=1;};
func uu= sin(y*pi)/10;
func vv= cos(x*pi)/10;

mesh Th = buildmesh ( a(6) + b(4) + c(4) +d(4) + e(4) + f(6));
plot(Th,wait=1,fill=1,ps="Lshape.eps"); // see figure 5.12
real coef=1;
real minT0= checkmovemesh(Th,[x,y]); // the min triangle area
```

```

while(1) // find a correct move mesh
{
    real minT=checkmovemesh(Th,[x+coef*uu,y+coef*vv]); // the min triangle area
    if (minT > minT0/5) break ; // if big enough
    coef=1.5;
}

Th=movemesh(Th,[x+coef*uu,y+coef*vv]);
plot(Th,wait=1,fill=1,ps="movemesh.eps"); // see figure 5.13

```




Figure 5.12: L-shape




Figure 5.13: moved L-shape

**Note 5.4** Consider a function  $u$  defined on a mesh  $Th$ . A statement like  $Th=movemesh(Th\dots)$  does not change  $u$  and so the old mesh still exists. It will be destroyed when no function use it. A statement like  $u = u$  redefines  $u$  on the new mesh  $Th$  with interpolation and therefore destroys the old  $Th$  if  $u$  was the only function using it.

**Example 5.3 (movemesh.edp)** Now, we given an example of moving mesh with a lagrangian function  $u$  defined on the moving mesh.

```

// simple movemesh example

mesh Th=square(10,10);
fespace Vh(Th,P1);
real t=0;

// ---
// the problem is how to build data without interpolation
// so the data u is moving with the mesh as you can see in the plot
// ---

Vh u=y;
for (int i=0;i<4;i++)
{
    t=i*0.1;
    Vh f= x*t;
    real minarea=checkmovemesh(Th,[x,y+f]);
    if (minarea >0 ) // movemesh will be ok

```

```

    Th=movemesh(Th,[x,y+f]);

cout << " Min area  " << minarea << endl;

real[int] tmp(u[].n);
tmp=u[];
u=0; // to change the FEsace and mesh associated with u
u[]=tmp; // set the value of u without any mesh update
plot(Th,u,wait=1);
};
// In this program, since u is only defined on the last mesh, all the
// previous meshes are deleted from memory.
// -----

```

## 5.4 Regular Triangulation: hTriangle

For a set  $S$ , we define the diameter of  $S$  by

$$\text{diam}(S) = \sup\{|x - y|; x, y \in S\}$$

The sequence  $\{\mathcal{T}_h\}_{h \downarrow 0}$  of  $\Omega$  is called *regular* if they satisfy the following:

1.

$$\lim_{h \downarrow 0} \max\{\text{diam}(T_k) | T_k \in \mathcal{T}_h\} = 0$$

2. There is a number  $\sigma > 0$  independent of  $h$  such that

$$\frac{\rho(T_k)}{\text{diam}(T_k)} \geq \sigma \quad \text{for all } T_k \in \mathcal{T}_h$$

where  $\rho(T_k)$  are the diameter of the inscribed circle of  $T_k$ .

We put  $h(\mathcal{T}_h) = \max\{\text{diam}(T_k) | T_k \in \mathcal{T}_h\}$ , which is obtained by

```

mesh Th = .....;
fespace Ph(Th,P0);
Ph h = hTriangle;
cout << "size of mesh = " << h[].max << endl;

```

## 5.5 Adaptmesh

The function

$$f(x, y) = 10.0x^3 + y^3 + \tan^{-1}[\varepsilon/(\sin(5.0y) - 2.0x)] \quad \varepsilon = 0.0001$$

sharply varies in value and the initial mesh given by one of the commands of Section 5.1 cannot reflect its sharp variations.

**Example 5.4**

```

real eps = 0.0001;
real h=1;
real hmin=0.05;
func f = 10.0*x^3+y^3+h*atan2(eps,sin(5.0*y)-2.0*x);

mesh Th=square(5,5,[-1+2*x,-1+2*y]);
fespace Vh(Th,P1);
Vh fh=f;
plot(fh);
for (int i=0;i<2;i++)
{
  Th=adaptmesh(Th, fh);
  fh=f;
  plot(Th, fh, wait=1);
}

```

// old mesh is deleted




Figure 5.14: 3D graphs for the initial mesh and 1st and 2nd mesh adaptation

FreeFem++ uses a variable metric/Delaunay automatic meshing algorithm. The command

```
mesh ATh = adaptmesh(Th, f);
```

create the new mesh ATh adapted to the Hessian

$$D^2 f = (\partial^2 f / \partial x^2, \partial^2 f / \partial x \partial y, \partial^2 f / \partial y^2)$$

of a function (formula or FE-function). Mesh adaptation is a very powerful tool when the solution of a problem varies locally and sharply.

Here we solve the problem (2.1)-(2.2), when  $f = 1$  and  $\Omega$  is a L-shape domain.




Figure 5.15: L-shape domain and its boundary name




Figure 5.16: Final solution after 4-times adaptation

**Example 5.5 (Adapt.edp)** *The solution has the singularity  $r^{3/2}$ ,  $r = |x - \gamma|$  at the point  $\gamma$  of the intersection of two lines  $bc$  and  $bd$  (see Fig. 5.15).*

```

border ba(t=0,1.0){x=t; y=0; label=1;};
border bb(t=0,0.5){x=1; y=t; label=1;};
border bc(t=0,0.5){x=1-t; y=0.5;label=1;};
border bd(t=0.5,1){x=0.5; y=t; label=1;};
border be(t=0.5,1){x=1-t; y=1; label=1;};
border bf(t=0.0,1){x=0; y=1-t;label=1;};
mesh Th = buildmesh ( ba(6)+bb(4)+bc(4)+bd(4)+be(4)+bf(6) );
fespace Vh(Th,P1);
Vh u,v;
func f = 1;
real error=0.1;
problem Poisson(u,v,solver=CG,eps=1.0e-6) =
    int2d(Th)( dx(u)*dx(v) + dy(u)*dy(v))
    - int2d(Th) ( f*v )
    + on(1,u=0) ;
for (int i=0;i< 4;i++)
{
    Poisson;
    Th=adaptmesh(Th,u,err=error);
    error = error/2;
} ;
plot(u);

```

// set FE space  
// set unknown and test function  
// level of error

To speed up the adaptation the default parameter `err` of `adaptmesh` is changed by hand; it specifies the required precision, so as to make the new mesh finer or coarser.

The problem is coercive and symmetric, so the linear system can be solved with the conjugate gradient method (parameter `solver=CG` with the stopping criteria on the residual, here `eps=1.0e-6`).



By `adaptmesh`, the slope of the final solution is correctly computed near the point of intersection of  $bc$  and  $bd$  as in Fig. 5.16.

This method is described in detail in [9]. It has a number of default parameters which can be modified :

Si  $f1, f2$  sont des fonctions et `thold`, `Thnew` des maillages.

```
Thnew = adaptmesh(Thold, f1 ... );
Thnew = adaptmesh(Thold, f1,f2 ... ];
Thnew = adaptmesh(Thold, [f1,f2] ... );
```

The additional paramters of `adaptmesh` not written here, hence the "..."

**hmin**= Minimum edge size. (`val` is a real. Its default is related to the size of the domain to be meshed and the precision of the mesh generator).

**hmax**= Maximum edge size. (`val` is a real. It defaults to the diameter of the domain to be meshed)

**err**=  $P_1$  interpolation error level (0.01 is the default).

**errg**= Relative geometrical error. By default this error is 0.01, and in any case it must be lower than  $1/\sqrt{2}$ . Meshes created with this option may have some edges smaller than the `-hmin` due to geometrical constraints.

**nbvx**= Maximum number of vertices generated by the mesh generator (9000 is the default).

**nbsmooth**= number of iterations of the smoothing procedure (5 is the default).

**nbjacoby**= number of iterations in a smoothing procedure during the metric construction, 0 means no smoothing (6 is the default).

**ratio**= ratio for a prescribed smoothing on the metric. If the value is 0 or less than 1.1 no smoothing is done on the metric (1.8 is the default).

If  $\text{ratio} > 1.1$ , the speed of mesh size variations is bounded by  $\log(\text{ratio})$ . Note: As  $\text{ratio}$  gets closer to 1, the number of generated vertices increases. This may be useful to control the thickness of refined regions near shocks or boundary layers .

**omega**= relaxation parameter for the smoothing procedure (1.0 is the default).

**iso**= If true, forces the metric to be isotropic (false is the default).

**abserror**= If false, the metric is evaluated using the criterium of equi-repartition of relative error (false is the default). In this case the metric is defined by

$$\mathcal{M} = \left( \frac{1}{\text{err coef}^2} \frac{|\mathcal{H}|}{\max(\text{CutOff}, |\eta|)} \right)^p \quad (5.1)$$

otherwise, the metric is evaluated using the criterium of equi-distribution of errors. In this case the metric is defined by

$$\mathcal{M} = \left( \frac{1}{\text{err coef}^2} \frac{|\mathcal{H}|}{\sup(\eta) - \inf(\eta)} \right)^p. \quad (5.2)$$

**cutoff=** lower limit for the relative error evaluation (1.0e-6 is the default).

**verbosity=** informational messages level (can be chosen between 0 and  $\infty$ ). Also changes the value of the global variable verbosity (obsolete).

**inquire=** To inquire graphically about the mesh (false is the default).

**splitpbedge=** If true, splits all internal edges in half with two boundary vertices (true is the default).

**maxsubdiv=** Changes the metric such that the maximum subdivision of a background edge is bound by val (always limited by 10, and 10 is also the default).

**rescaling=** if true, the function with respect to which the mesh is adapted is rescaled to be between 0 and 1 (true is the default).

**keepbackvertices=** if true, tries to keep as many vertices from the original mesh as possible (true is the default).

**isMetric=** if true, the metric is defined explicitly (false is the default). If the 3 functions  $m_{11}, m_{12}, m_{22}$  are given, they directly define a symmetric matrix field whose Hessian is computed to define a metric. If only one function is given, then it represents the isotropic mesh size at every point.

For example, if the partial derivatives  $f_{xx} (= \partial^2 f / \partial x^2)$ ,  $f_{xy} (= \partial^2 f / \partial x \partial y)$ ,  $f_{yy} (= \partial^2 f / \partial y^2)$  are given, we can set

```
Th=adaptmesh(Th, fxx, fxy, fyy, IsMetric=1, nbvx=10000, hmin=hmin);
```

**power=** exponent power of the Hessian used to compute the metric (1 is the default).

**thetamax=** minimum corner angle in degrees (default is 0).

**splitin2=** boolean value. If true, splits all triangles of the final mesh into 4 sub-triangles.

**metric=** an array of 3 real arrays to set or get metric data information. The size of these three arrays must be the number of vertices. So if  $m_{11}, m_{12}, m_{22}$  are three P1 finite elements related to the mesh to adapt, you can write: `metric=[m11[], m12[], m22[]]` (see file `convect-apt.edp` for a full example)

**nomeshgeneration=** If true, no adapted mesh is generated (useful to compute only a metric).

**periodic=** Writing `periodic=[[4,y], [2,y], [1,x], [3,x]]`; builds an adapted periodic mesh. The sample build a bi-periodic mesh of a square. (see periodic finite element spaces 6, and see `sphere.edp` for a full example)

### Example 5.6 *uniformmesh.edp*

We can use the command `adaptmesh` to build uniform mesh with a constant mesh size.

So to build a mesh with a constant mesh size equal to  $\frac{1}{30}$  do

```
mesh Th=square(2,2); // to have initial mesh
```

```

plot(Th,wait=1,ps="square-0.eps");
Th= adaptmesh(Th,1./30,IsMetric=1,nbv=10000);
plot(Th,wait=1,ps="square-1.eps");
Th= adaptmesh(Th,1./30.,IsMetric=1,nbv=10000);
Th= adaptmesh(Th,1./30.,IsMetric=1,nbv=10000);
plot(Th,wait=1,ps="square-2.eps");

```

//  
// more the one time du to  
// adaptation bound maxsubdiv=




Figure 5.17: Initial mesh




Figure 5.18: first iteration




Figure 5.19: last iteration

## 5.6 Trunc

Two operators have been introduced to remove triangles from a mesh or to divide them. Operator `trunc` has two parameters

**label=** sets the label number of new boundary item (one by default)

**split=** sets the level  $n$  of triangle splitting. each triangle is splitted in  $n \times n$  ( one by default).

To create the mesh `Th3` where all triangles of a mesh `Th` are splitted in  $3 \times 3$  , just write:

```
mesh Th3 = trunc(Th,1,split=3);
```

The `truncmesh.edp` example constructs all "trunc" mesh to the support of the basic function of the space  $V_h$  (cf. `abs(u)>0`), split all the triangles in  $5 \times 5$ , and put a label number to 2 on new boundary.

```

mesh Th=square(3,3);
fespace Vh(Th,P1);
Vh u;
int i,n=u.n;
u=0;
for (i=0;i<n;i++)
{
  u[i]=1;
  plot(u,wait=1);
}

```

// all degree of freedom  
// the basic function i

```

mesh Sh1=trunc(Th,abs(u)>1.e-10,split=5,label=2);
plot(Th,Sh1,wait=1,ps="trunc"+i+".eps");

u[][i]=0;
}

```

*// plot the mesh of  
 // the function's support  
 // reset*




Figure 5.20: mesh of support the function P1 number 0, splitted in  $5 \times 5$




Figure 5.21: mesh of support the function P1 number 6, splitted in  $5 \times 5$

## 5.7 Splitmesh

Another way to split mesh triangles is to use `splitmesh`, for example:

```

{
    // new stuff 2004 splitmesh (version 1.37)
    assert(version>=1.37);
    border a(t=0,2*pi){ x=cos(t); y=sin(t);label=1;}
    mesh Th=buildmesh(a(20));
    plot (Th,wait=1,ps="nosplitmesh.eps");
    Th=splitmesh(Th,1+5*(square(x-0.5)+y*y));
    plot (Th,wait=1,ps="splitmesh.eps");
}

```

*// see figure 5.22  
 // see figure 5.23*

## 5.8 Meshing Examples

**Example 5.7 (Two rectangles touching by a side)**

```

border a(t=0,1){x=t;y=0;};
border b(t=0,1){x=1;y=t;};
border c(t=1,0){x=t ;y=1;};
border d(t=1,0){x = 0; y=t;};
border c1(t=0,1){x=t ;y=1;};
border e(t=0,0.2){x=1;y=1+t;};
border f(t=1,0){x=t ;y=1.2;};

```





Figure 5.22: initial mesh

Figure 5.23: all left mesh triangle is split conformally in  $\text{int}(1+5*(\text{square}(x-0.5)+y*y)^2)$  triangles.

```

border g(t=0.2,0){x=0;y=1+t;};
int n=1;
mesh th = buildmesh(a(10*n)+b(10*n)+c(10*n)+d(10*n));
mesh TH = buildmesh ( c1(10*n) + e(5*n) + f(10*n) + g(5*n) );
plot(th,TH,ps="TouchSide.esp");

```

// Fig. 5.24

**Example 5.8 (NACA0012 Airfoil)**

```

border upper(t=0,1) { x = t;
  y = 0.17735*sqrt(t)-0.075597*t
  - 0.212836*(t^2)+0.17363*(t^3)-0.06254*(t^4); }
border lower(t=1,0) { x = t;
  y= -(0.17735*sqrt(t)-0.075597*t
  -0.212836*(t^2)+0.17363*(t^3)-0.06254*(t^4)); }
border c(t=0,2*pi) { x=0.8*cos(t)+0.5; y=0.8*sin(t); }
mesh Th = buildmesh(c(30)+upper(35)+lower(35));
plot(Th,ps="NACA0012.eps",bw=1);

```

// Fig. 5.25

**Example 5.9 (Cardioid)**

```

real b = 1, a = b;
border C(t=0,2*pi) { x=(a+b)*cos(t)-b*cos((a+b)*t/b);
  y=(a+b)*sin(t)-b*sin((a+b)*t/b); }
mesh Th = buildmesh(C(50));
plot(Th,ps="Cardioid.eps",bw=1);

```

// Fig. 5.26




Figure 5.24: Two rectangles touching by a side




Figure 5.25: NACA0012 Airfoil

**Example 5.10 (Cassini Egg)**

```

border C(t=0,2*pi) { x=(2*cos(2*t)+3)*cos(t);
                    y=(2*cos(2*t)+3)*sin(t); }
mesh Th = buildmesh(C(50));
plot(Th,ps="Cassini.eps",bw=1);

```

// Fig. 5.27




Figure 5.26: Domain with Cardioid curve boundary




Figure 5.27: Domain with Cassini Egg curve boundary

**Example 5.11 (By cubic Bezier curve)**

```

// A cubic Bezier curve connecting two points with two control points
func real bzi(real p0,real p1,real q1,real q2,real t)
{
    return p0*(1-t)^3+q1*3*(1-t)^2*t+q2*3*(1-t)*t^2+p1*t^3;
}

```

```

real[int] p00=[0,1], p01=[0,-1], q00=[-2,0.1], q01=[-2,-0.5];
real[int] p11=[1,-0.9], q10=[0.1,-0.95], q11=[0.5,-1];

```

```

real[int] p21=[2,0.7], q20=[3,-0.4], q21=[4,0.5];
real[int] q30=[0.5,1.1], q31=[1.5,1.2];
border G1(t=0,1) { x=bzi(p00[0],p01[0],q00[0],q01[0],t);
                  y=bzi(p00[1],p01[1],q00[1],q01[1],t); }
border G2(t=0,1) { x=bzi(p01[0],p11[0],q10[0],q11[0],t);
                  y=bzi(p01[1],p11[1],q10[1],q11[1],t); }
border G3(t=0,1) { x=bzi(p11[0],p21[0],q20[0],q21[0],t);
                  y=bzi(p11[1],p21[1],q20[1],q21[1],t); }
border G4(t=0,1) { x=bzi(p21[0],p00[0],q30[0],q31[0],t);
                  y=bzi(p21[1],p00[1],q30[1],q31[1],t); }

int m=5;
mesh Th = buildmesh(G1(2*m)+G2(m)+G3(3*m)+G4(m));
plot(Th,ps="Bezier.eps",bw=1);

```

// Fig 5.28

**Example 5.12 (Section of Engine)**

```

real a= 6., b= 1., c=0.5;
border L1(t=0,1) { x= -a; y= 1+b - 2*(1+b)*t; }
border L2(t=0,1) { x= -a+2*a*t; y= -1-b*(x/a)*(x/a)*(3-2*abs(x)/a );}
border L3(t=0,1) { x= a; y=-1-b + (1+ b )*t; }
border L4(t=0,1) { x= a - a*t; y=0; }
border L5(t=0,pi) { x= -c*sin(t)/2; y=c/2-c*cos(t)/2; }
border L6(t=0,1) { x= a*t; y=c; }
border L7(t=0,1) { x= a; y=c + (1+ b-c )*t; }
border L8(t=0,1) { x= a-2*a*t; y= 1+b*(x/a)*(x/a)*(3-2*abs(x)/a );}
mesh Th = buildmesh(L1(8)+L2(26)+L3(8)+L4(20)+L5(8)+L6(30)+L7(8)+L8(30));
plot(Th,ps="Engine.eps",bw=1);

```

// Fig. 5.29




Figure 5.29: Section of Engine

Figure 5.28: Boundary drawn by Bezier curves

**Example 5.13 (Domain with U-shape channel)**

```

real d = 0.1;
border L1(t=0,1-d) { x=-1; y=-d-t; }
border L2(t=0,1-d) { x=-1; y=1-t; }
border B(t=0,2) { x=-1+t; y=-1; }

```

// width of U-shape

```

border C1(t=0,1) { x=t-1; y=d; }
border C2(t=0,2*d) { x=0; y=d-t; }
border C3(t=0,1) { x=-t; y=-d; }
border R(t=0,2) { x=1; y=-1+t; }
border T(t=0,2) { x=1-t; y=1; }
int n = 5;
mesh Th = buildmesh (L1(n/2)+L2(n/2)+B(n)+C1(n)+C2(3)+C3(n)+R(n)+T(n));
plot(Th,ps="U-shape.eps",bw=1);

```

// Fig 5.30

#### Example 5.14 (Domain with V-shape cut)

```

real dAg = 0.01;
border C(t=dAg,2*pi-dAg) { x=cos(t); y=sin(t); };
real[int] pa(2), pb(2), pc(2);
pa[0] = cos(dAg); pa[1] = sin(dAg);
pb[0] = cos(2*pi-dAg); pb[1] = sin(2*pi-dAg);
pc[0] = 0; pc[1] = 0;
border seg1(t=0,1) { x=(1-t)*pb[0]+t*pc[0]; y=(1-t)*pb[1]+t*pc[1]; };
border seg2(t=0,1) { x=(1-t)*pc[0]+t*pa[0]; y=(1-t)*pc[1]+t*pa[1]; };
mesh Th = buildmesh(seg1(20)+C(40)+seg2(20));
plot(Th,ps="V-shape.eps",bw=1);

```

// angle of V-shape  
Fig. 5.31





Figure 5.30: Domain with U-shape channel changed by d

Figure 5.31: Domain with V-shape cut changed by dAg

#### Example 5.15 (Smiling face)

```

real d=0.1;
int m=5;
real a=1.5, b=2, c=0.7, e=0.01;
border F(t=0,2*pi) { x=a*cos(t); y=b*sin(t); }
border E1(t=0,2*pi) { x=0.2*cos(t)-0.5; y=0.2*sin(t)+0.5; }
border E2(t=0,2*pi) { x=0.2*cos(t)+0.5; y=0.2*sin(t)+0.5; }
func real st(real t) {
    return sin(pi*t)-pi/2;
}
border C1(t=-0.5,0.5) { x=(1-d)*c*cos(st(t)); y=(1-d)*c*sin(st(t)); }

```



```

border C2(t=0,1){x=((1-d)+d*t)*c*cos(st(0.5));y=((1-d)+d*t)*c*sin(st(0.5));}
border C3(t=0.5,-0.5) { x=c*cos(st(t)); y=c*sin(st(t)); }
border C4(t=0,1) { x=(1-d*t)*c*cos(st(-0.5)); y=(1-d*t)*c*sin(st(-0.5));}

border C0(t=0,2*pi) { x=0.1*cos(t); y=0.1*sin(t); }
mesh Th=buildmesh(F(10*m)+C1(2*m)+C2(3)+C3(2*m)+C4(3)
                  +C0(m)+E1(-2*m)+E2(-2*m));
plot(Th,ps="SmileFace.eps",bw=1); // see Fig. 5.32
}

```

### Example 5.16 (3point bending)

```

// Square for Three-Point Bend Specimens fixed on Fix1, Fix2
// It will be loaded on Load.

real a=1, b=5, c=0.1;
int n=5, m=b*n;
border Left(t=0,2*a) { x=-b; y=a-t; }
border Bot1(t=0,b/2-c) { x=-b+t; y=-a; }
border Fix1(t=0,2*c) { x=-b/2-c+t; y=-a; }
border Bot2(t=0,b-2*c) { x=-b/2+c+t; y=-a; }
border Fix2(t=0,2*c) { x=b/2-c+t; y=-a; }
border Bot3(t=0,b/2-c) { x=b/2+c+t; y=-a; }
border Right(t=0,2*a) { x=b; y=-a+t; }
border Top1(t=0,b-c) { x=b-t; y=a; }
border Load(t=0,2*c) { x=c-t; y=a; }
border Top2(t=0,b-c) { x=-c-t; y=a; }
mesh Th = buildmesh(Left(n)+Bot1(m/4)+Fix1(5)+Bot2(m/2)+Fix2(5)+Bot3(m/4)
                    +Right(n)+Top1(m/2)+Load(10)+Top2(m/2));
plot(Th,ps="ThreePoint.eps",bw=1); // Fig. 5.33

```




Figure 5.32: Smiling face (Mouth is changeable)




Figure 5.33: Domain for three-point bending test

## 5.9 How to change the label of elements and border elements of a mesh in FreeFem++ ?

Changing the label of elements and border elements will be done using the keyword **change**. The parameters for this command line are for a two dimensional and dimensional case:

**label** = is a vector of integer that contains successive pair of the old label number to the new label number .

**region** = is a vector of integer that contains successive pair of the old region number to new region number.

These vectors are composed of  $n_l$  successive pair of number  $O, N$  where  $n_l$  is the number (label or region) that we want to change. For example, we have

$$\text{label} = [O_1, N_1, \dots, O_{n_l}, N_{n_l}] \quad (5.3)$$

$$\text{region} = [O_1, N_1, \dots, O_{n_l}, N_{n_l}] \quad (5.4)$$

where  $O_i$  is the  $i^{\text{nd}}$  old number (label or region) to change in new number  $N_i$ .

An example of using this function is given in "glumesh2D.edp":

### Example 5.17 (glumesh2D.edp)

```

1:
2: mesh Th1=square(10,10);
3: mesh Th2=square(20,10,[x+1,y]);
4: verbosity=3;
5: int[int] r1=[2,0], r2=[4,0];
6: plot(Th1,wait=1);
7: Th1=change(Th1,label=r1); // Change the label of Edges of Th1 with label 2 in 0.
8: plot(Th1,wait=1);
9: Th2=change(Th2,label=r2); // Change the label of Edges of Th2 with label 4 in 0.
10: mesh Th=Th1+Th2; // "gluing together" of meshes Th1 and Th2
11: cout << " nb lab = " << int1d(Th1,1,3,4)(1./lenEdge)+int1d(Th2,1,2,3)(1./lenEdge)
12:      << " == " << int1d(Th,1,2,3,4)(1./lenEdge) <<" == " << ((10+20)+10)*2 << endl;
13: plot(Th,wait=1);
14: fespace Vh(Th,P1);
15: macro Grad(u) [dx(u),dy(u)]; // definition of a macro
16: Vh u,v;
17: solve P(u,v)=int2d(Th)(Grad(u)'*Grad(v))-int2d(Th)(v)+on(1,3,u=0);
18: plot(u,wait=1);

```

**“gluing” different mesh** In line 10 of previous file, the method to “gluing” different mesh of the same dimension in FreeFem++ is using. This function is just called using the symbol addition “+” between meshes. The method implemented need that the point in adjacent mesh are the same.

## 5.10 Mesh in three dimensions

### 5.10.1 Read/Write Statements for a Mesh in 3D

In three dimensions, the file mesh format supported for input and output files by FreeFem++ are the extension .msh and .mesh. These formats are described in the chapter on Mesh Files in two dimensions.

**extension file .msh** The structure of the files with extension .msh in 3D is given in Table 5.2. In this structure,  $n_v$  denotes the number of vertices,  $n_{tet}$  the number of tetrahedra and  $n_{tri}$  the number of triangles. For each vertex  $q^i$ ,  $i = 1, \dots, n_v$ , we denote by  $(q_x^i, q_y^i, q_z^i)$  the  $x$ -coordinate, the  $y$ -coordinate and the  $z$ -coordinate. Each tetrahedra  $T_k$ ,  $k = 1, \dots, n_{tet}$  has four vertices  $q^{k_1}, q^{k_2}, q^{k_3}, q^{k_4}$ . The boundary consists of an union of triangles. Each triangle  $be_j$ ,  $j = 1, \dots, n_{tri}$  has three vertices  $q^{j_1}, q^{j_2}, q^{j_3}$ .

$n_v$	$n_{tet}$	$n_{tri}$		
$q_x^1$	$q_y^1$	$q_z^1$	Vertex label	
$q_x^2$	$q_y^2$	$q_z^2$	Vertex label	
$\vdots$	$\vdots$	$\vdots$	$\vdots$	
$q_x^{n_v}$	$q_y^{n_v}$	$q_z^{n_v}$	Vertex label	
$1_1$	$1_2$	$1_3$	$1_4$	region label
$2_1$	$2_2$	$2_3$	$2_4$	region label
$\vdots$	$\vdots$	$\vdots$	$\vdots$	$\vdots$
$(n_{tet})_1$	$(n_{tet})_2$	$(n_{tet})_3$	$(n_{tet})_4$	region label
$1_1$	$1_2$	$1_3$	boundary label	
$2_1$	$2_2$	$2_3$	boundary label	
$\vdots$	$\vdots$	$\vdots$	$\vdots$	
$(n_{tri})_1$	$(n_{tri})_2$	$(n_{tri})_3$	boundary label	

Table 5.2: The structure of mesh file format “.msh” in three dimensions.

**extension file .mesh** The data structure for a three dimensional mesh is composed of the data structure presented in Section 12.1 and a data structure for tetrahedra. The tetrahedra of a three dimensional mesh are refereed using the following field:

- Tetrahedra  

$$\left( (I) \text{NbOfTetrahedrons} \right. \\
\left. \left( (@\text{Vertex}_i^j, j=1,4) \right), (I) \text{Ref}\phi_i^{tet}, i=1, \text{NbOfTetrahedrons} \right)$$

This field is express with the notation of Section 12.1.

### 5.10.2 TeGen: A tetrahedral mesh generator

**TetGen** TetGen is a software developed by Dr. Hang Si of Weierstrass Institute for Applied Analysis and Stochastics of Berlin in Germany [36]. TetGen is a free for research and non-commercial uses. For any commercial licence utilization, a commercial licence is available upon request to Hang Si.

This software is a tetrahedral mesh generator of a three dimensional domain defined by its boundary. The input domain take into account a polyhedral or a piecewise linear complex. This tetrahelization is a constrained Delaunay tetrahelization.

The method used in TetGen to control the quality of the mesh is a Delaunay refinement due to Shewchuk [37]. The quality measure of this algorithm is the Radius-Edge Ratio (see Section 1.3.1 [36] for more details). A theoretical bounds of this ratio of the algorithm of Shewchuk is obtained for a given complex of vertices, constrained segments and facets of surface mesh, with no input angle less than 90 degree. This theoretical bounds is 2.0.

The launch of Tetgen is done with the keyword `tetg`. The parameters of this command line is:

**label** = is a vector of integer that contains the old labels number at index  $2i$  and the new labels number at index  $2i + 1$  of Triangles. This parameters is initialized as label for the keyword change (5.3).

**switch** = A string expression. This string corresponds to the command line switch of Tetgen see Section 3.2 of [36].

**nbofholes**= Number of holes (default value size of holelist/3 (version 3.11)).

**holelist** = This array correspond to **holelist** of tetgenio data structure [36]. A real vector of size  $3 \times \text{nbofholes}$ . In TetGen, each hole is associated with a point inside this domain. This vector is  $x_1^h, y_1^h, z_1^h, x_2^h, y_2^h, z_2^h, \dots$ , where  $x_i^h, y_i^h, z_i^h$  is the associated point with the  $i^{\text{th}}$  hole.

**nbofregions** = Number of regions (size of regionlist/5 (version 3.11)).

**regionlist** = This array corresponds to **regionlist** of tetgenio data structure [36]. The attribute and the volume constraint of region are given in this real vector of size  $5 \times \text{nbofregions}$ . The  $i^{\text{th}}$  region is described by five elements:  $x$ -coordinate,  $y$ -coordinate and  $z$ -coordinate of a point inside this domain ( $x_i, y_i, z_i$ ); the attribute ( $at_i$ ) and the maximum volume for tetrahedra ( $mvol_i$ ) for this region. The **regionlist** vector is:  $x_1, y_1, z_1, at_1, mvol_1, x_2, y_2, z_2, at_2, mvol_2, \dots$ .

**nboffacetcl**= Number of facets constraints size of facetcl/2 (version 3.11)).

**facetcl**= This array corresponds to **facetconstraintlist** of tetgenio data structure [36]. The  $i^{\text{th}}$  facet constraint is defined by the facet marker  $Ref_i^{fc}$  and the maximum area for faces  $marea_i^{fc}$ . The **facetcl** array is:  $Ref_1^{fc}, marea_1^{fc}, Ref_2^{fc}, marea_2^{fc}, \dots$ . This parameters has no effect if switch q is not selected.

Principal switch parameters in TetGen:

- p Tetrahedralization of boundary.
- q Quality mesh generation. The bound of Radius-Edge Ratio will be given after the option q. By default, this value is 2.0.
- a Construct with the volumes constraints on tetrahedra. These volumes constraints are defined with the bound of the previous switch q or in the parameter **regionlist**.
- A Attributes reference to region given in the **regionlist**. The other regions have label 0. The option AA gives a different label at each region. This switch work with the option 'p'. If option 'r' is used, this switch has no effect.
- r Reconstructs and Refines a previously generated mesh. This character is only used with the command line **tetgreconstruction**.

- Y This switch allow to preserve the mesh on the exterior boundary. This switch must be used to ensure conformal mesh between two adjacents mesh.
- YY This switch allow to preserve the mesh on the exterior and interior boundary.
- C The consistency of the result's mesh is testing by TetGen.
- CC The consistency of the result's mesh is testing by TetGen and also checks constrained delaunay mesh (if 'p' switch is selected) or the consistency of Conformal Delaunay (if 'q' switch is selected).
- V Give information of the work of TetGen. More information can be obtained in specified 'VV' or 'VVV'.
- Q Quiet: No terminal output except errors
- M The coplanar facets are not merging.
- T Set a tolerance for coplanar test. The default value is  $1e - 8$ .
- d Itersections of facets are detected.

To obtain a tetrahedral mesh generator with tetgen, we need the surface mesh of three dimensional domain. We give now the command line in FreeFem++ to construct these meshes.

**keyword: “movemesh23”** A simple method to construct a surface is to place a two dimensional domain in a three dimensional space. This corresponding to move the domain by a displacement vector of this form  $\Phi(x, y) = (\Phi1(x, y), \Phi2(x, y), \Phi3(x, y))$ . The result of moving a two dimensional mesh Th2 by this three dimensional displacement is obtained using:

```
mesh3 Th3 = movemesh23(Th2, transfo=[Φ1, Φ2, Φ3]);
```

The parameters of this command line are:

**transfo** = [Φ1, Φ2, Φ3] set the displacement vector of transformation  $\Phi(x, y) = [\Phi1(x, y), \Phi2(x, y), \Phi3(x, y)]$ .

**label** = set integer label of triangles

**orientation=** set integer orientation of mesh.

**ptmerge** = A real expression. When you transform a mesh, some points can be merged. This parameters is the criteria to define two merging points. By default, we use

$$ptmerge = 1e - 7 \text{ Vol}(B),$$

where  $B$  is the smallest axis parallel boxes containing the discretized domain of  $\Omega$  and  $\text{Vol}(B)$  is the volume of this box.

We can ‘do a ‘gluing’’ of surface meshes using the process given in Section 5.9. An example to obtain a three dimensional mesh using the command line `tetg` and `movemesh23` is given in the file `tetgencube.edp`.

#### Example 5.18 (tetgencube.edp)

```
load "msh3" // file tetgencube.edp
load "tetgen"
```

```

real x0,x1,y0,y1;
x0=1.; x1=2.; y0=0.; y1=2*pi;
mesh Thsq1 = square(5,35,[x0+(x1-x0)*x,y0+(y1-y0)*y]);

func ZZ1min = 0;
func ZZ1max = 1.5;
func XX1 = x;
func YY1 = y;

mesh3 Th31h = movemesh23(Thsq1,transfo=[XX1,YY1,ZZ1max]);
mesh3 Th31b = movemesh23(Thsq1,transfo=[XX1,YY1,ZZ1min]);

// //////////////////////////////////////

x0=1.; x1=2.; y0=0.; y1=1.5;
mesh Thsq2 = square(5,8,[x0+(x1-x0)*x,y0+(y1-y0)*y]);

func ZZ2 = y;
func XX2 = x;
func YY2min = 0.;
func YY2max = 2*pi;

mesh3 Th32h = movemesh23(Thsq2,transfo=[XX2,YY2max,ZZ2]);
mesh3 Th32b = movemesh23(Thsq2,transfo=[XX2,YY2min,ZZ2]);

// //////////////////////////////////////

x0=0.; x1=2*pi; y0=0.; y1=1.5;
mesh Thsq3 = square(35,8,[x0+(x1-x0)*x,y0+(y1-y0)*y]);
func XX3min = 1.;
func XX3max = 2.;
func YY3 = x;
func ZZ3 = y;

mesh3 Th33h = movemesh23(Thsq3,transfo=[XX3max,YY3,ZZ3]);
mesh3 Th33b = movemesh23(Thsq3,transfo=[XX3min,YY3,ZZ3]);

// //////////////////////////////////////
mesh3 Th33 = Th31h+Th31b+Th32h+Th32b+Th33h+Th33b; // "gluing" surface meshes to obtain
the surface of cube
savemesh(Th33,"Th33.mesh");

// build a mesh of a axis parallel box with TetGen
real[int] domain =[1.5,pi,0.75,145,0.0025];
mesh3 Thfinal = tetg(Th33,switch="paAAQY",regionlist=domain); // Tetrahelize the
interior of the cube with tetgen
savemesh(Thfinal,"Thfinal.mesh");

// build a mesh of a half cylindrical shell of interior radius 1. and exterior radius
2 and heigh 1.5
func mv2x = x*cos(y);
func mv2y = x*sin(y);
func mv2z = z;
mesh3 Thmv2 = movemesh3(Thfinal, transfo=[mv2x,mv2y,mv2z]);
savemesh(Thmv2,"halfcylindricalshell.mesh")

```

The command `movemesh` is describe in the following section.

**The keyword “tetgtransfo”** This keyword correspond to a composition of command line `tetg` and `movemesh23`:

`tetgtransfo( Th2, transfo= [Φ1, Φ2, Φ3] ), ... ) = tetg( Th3surf, ... ),`

where `Th3surf = movemesh23( Th2,transfo=[Φ1, Φ2, Φ3] )` and `Th2` is the input two dimensional mesh of `tetgtransfo`.

The parameters of this command line are on the one hand the parameters:

`label, switch, regionlist nboffacetcl facetcl`

of keyword `tetg` and on the other hand the parameter `ptmerge` of keyword `movemesh23`.

**Remark:** To use `tetgtransfo`, the result’s mesh of `movemesh23` must be an closed surface and define one region only. Therefore, the parameter `regionlist` is defined for one region.

An example of this keyword can be found in line of file “buildlayers.edp”

**The keyword ”tetgconvexhull”** FreeFem++ , using `tetgen`, is able to build a tetrahelization from a set of points. This tetrahelization is a Delaunay mesh of the convex hull of the set of points.

The coordinates of the points can be initialized in two ways. The first is a file that contains the coordinate of points  $X_i = (x_i, y_i, z_i)$ . This files is organized as follows:

$$\begin{array}{ccc} n_v & & \\ x_1 & y_1 & z_1 \\ x_2 & y_2 & z_2 \\ \vdots & \vdots & \vdots \\ x_{n_v} & y_{n_v} & z_{n_v} \end{array}$$

The second way is to give three arrays that correspond respectively to the  $x$ –coordinates,  $y$ –coordinates and  $z$ –coordinates.

The parameters of this command line are

**switch** = A string expression. This string corresponds to the command line *switch* of TetGen see Section 3.2 of [36].

**reftet** = An integer expression. set the label of tetrahedra.

**label** = An integer expression. set the label of triangles.

In the string switch, we can’t used the option ‘p’ and ‘q’ of tetgen.

### 5.10.3 Reconstruct/Refine a three dimensional mesh with TetGen

Meshes in three dimension can be refined using TetGen with the command line `tetgreconstruction`.

The parameter of this keyword are

**region=** an integer array that allow to change the region number of tetrahedra. This array is defined as the parameter `reftet` in the keyword `change`.

**label=** an integer array that allow to change the label of boundary triangles. This array is defined as the parameter `label` in the keyword `change`.

**sizevolume=** a reel function. This function allows to constraint volume size of tetrahedra in the domain. (see example 5.31 to build 3d adapt mesh )

The parameter switch `nbofregions`, `regionlist`, `nboffacetcl` and `facetcl` of the command line which call TetGen (`tetg`) is used for `tetgrefine`.

In the parameter switch=, the character 'r' should be used without the character 'p'. For instance, see the manual of TetGen [36] for effect of 'r' to other character.

The parameter `regionlist` allows to define a new volume constraint in the region. The label in the `regionlist` will be the previous label of region. This parameter and `nbofregions` can't be used with parameter `sizevolume`.

Example:

#### Example 5.19 (refinesphere.edp)

*// file refinesphere.edp*

```
load "msh3"
load "tetgen"
load "medit"

mesh Th=square(10,20,[x*pi-pi/2,2*y*pi]);
// ]-pi/2,frac-pi2[×]0,2π[
// a parametrization of a sphere

func f1 =cos(x)*cos(y);
func f2 =cos(x)*sin(y);
func f3 = sin(x);
// partiel derivative of the parametrization DF

func f1x=sin(x)*cos(y);
func f1y=-cos(x)*sin(y);
func f2x=-sin(x)*sin(y);
func f2y=cos(x)*cos(y);
func f3x=cos(x);
func f3y=0;
// M = DF'DF

func m11=f1x^2+f2x^2+f3x^2;
func m21=f1x*f1y+f2x*f2y+f3x*f3y;
func m22=f1y^2+f2y^2+f3y^2;

func perio=[[4,y],[2,y],[1,x],[3,x]];
real hh=0.1;
real vv= 1/square(hh);
verbosity=2;
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
plot(Th,wait=1);

verbosity=2;

// construction of the surface of spheres

real Rmin = 1.;
func f1min = Rmin*f1;
func f2min = Rmin*f2;
func f3min = Rmin*f3;

mesh3 Th3=movemesh23(Th,transfo=[f1min,f2min,f3min]);

real[int] domain = [0.,0.,0.,145,0.01];
mesh3 Th3sph=tetg(Th3,switch="paAAQYY",nbofregions=1,regionlist=domain);

int[int] newlabel = [145,18];
```



```

real[int] domainrefine = [0.,0.,0.,145,0.0001];
mesh3 Th3sphrefine=tetgreconstruction(Th3sph,switch="raAQ",reftet=newlabel,
nbofregions=1,regionlist=domain,refinesizeofvolume=0.0001);

int[int] newlabel2 = [145,53];
func fsize = 0.01/(( 1 + 5*sqrt( (x-0.5)^2+(y-0.5)^2+(z-0.5)^2 ) ^3);
mesh3 Th3sphrefine2=tetgreconstruction(Th3sph,switch="raAQ",reftet=newlabel2,
sizeofvolume=fsize);

medit('sphere',Th3sph);
medit('isotroperefine',Th3sphrefine);
medit('anisotroperefine',Th3sphrefine2);

```

### 5.10.4 Moving mesh in three dimensions

Meshes in three dimensions can be translated rotated and deformed using the command line `movemesh` as in the 2D case (see section `movemesh` in chapter 5). If  $\Omega$  is tetrahedrized as  $T_h(\Omega)$ , and  $\Phi(x, y, z) = (\Phi_1(x, y, z), \Phi_2(x, y, z), \Phi_3(x, y, z))$  is a displacement vector then  $\Phi(T_h)$  is obtained by

```
mesh3 Th = movemesh( Th, transfo=[ $\Phi_1$ ,  $\Phi_2$ ,  $\Phi_3$ ], ... );
```

The parameters of `movemesh` in three dimensions are

**transfo** = [ $\Phi_1, \Phi_2, \Phi_3$ ] set the displacement vector of 3D transformation [ $\Phi_1(x, y, z), \Phi_2(x, y, z), \Phi_3(x, y, z)$ ].

**region** = set integer label of tetrahedra. 0 by default.

**label** = set the label of faces of border. This parameters is initialized as label for the keyword change (5.3).

**facemerge** = An integer expression. When you transform a mesh, some faces can be merged. This parameters equals to one if merge's faces is considered. Otherwise equals to zero. By default, this parameter is equals to 1.

**ptmerge** = A real expression. When you transform a mesh, some points can be merged. This parameters is the criteria to define two merging points. By default, we use

$$ptmerge = 1e - 7 \text{ Vol}(B),$$

where  $B$  is the smallest axis parallel boxes containing the discretion domain of  $\Omega$  and  $\text{Vol}(B)$  is the volume of this box.

An example of this command can be found in the file "Poisson3d.edp" located in the directory `examples++-3d`.

### 5.10.5 Layer mesh

In this section, we present the command line to obtain a Layer mesh: `buildlayermesh`. This mesh is obtained by extending a two dimensional mesh in the  $z$ -axis.

The domain  $\Omega_{3d}$  defined by the layer mesh is equal to  $\Omega_{3d} = \Omega_{2d} \times [zmin, zmax]$  where  $\Omega_{2d}$  is the domain define by the two dimensional mesh,  $zmin$  and  $zmax$  are function of  $\Omega_{2d}$  in  $R$  that defines respectively the lower surface and upper surface of  $\Omega_{3d}$ .




Figure 5.34: Example of Layer mesh in three dimension.

For a vertex of a two dimensional mesh  $V_i^{2d} = (x_i, y_i)$ , we introduce the number of associated vertices in the  $z$ -axis  $M_i + 1$ . We denote by  $M$  the maximum of  $M_i$  over the vertices of the two dimensional mesh. This value are called the number of layers (if  $\forall i, M_i = M$  then there are  $M$  layers in the mesh of  $\Omega_{3d}$ ).  $V_i^{2d}$  generated  $M + 1$  vertices which are defined by

$$\forall j = 0, \dots, M, \quad V_{i,j}^{3d} = (x_i, y_i, \theta_i(z_{i,j})),$$

where  $(z_{i,j})_{j=0,\dots,M}$  are the  $M + 1$  equidistant points on the interval  $[zmin(V_i^{2d}), zmax(V_i^{2d})]$ :

$$z_{i,j} = j \delta\alpha + zmin(V_i^{2d}), \quad \delta\alpha = \frac{zmax(V_i^{2d}) - zmin(V_i^{2d})}{M}.$$

The function  $\theta_i$ , defined on  $[zmin(V_i^{2d}), zmax(V_i^{2d})]$ , is given by

$$\theta_i(z) = \begin{cases} \theta_{i,0} & \text{if } z = zmin(V_i^{2d}), \\ \theta_{i,j} & \text{if } z \in ]\theta_{i,j-1}, \theta_{i,j}], \end{cases}$$

with  $(\theta_{i,j})_{j=0,\dots,M_i}$  are the  $M_i + 1$  equidistant points on the interval  $[zmin(V_i^{2d}), zmax(V_i^{2d})]$ .

Set a triangle  $K = (V_{i1}^{2d}, V_{i2}^{2d}, V_{i3}^{2d})$  of the two dimensional mesh.  $K$  is associated with a triangle on the upper surface (resp. on the lower surface) of layer mesh:  $(V_{i1,M}^{3d}, V_{i2,M}^{3d}, V_{i3,M}^{3d})$  (resp.  $(V_{i1,0}^{3d}, V_{i2,0}^{3d}, V_{i3,0}^{3d})$ ). Also  $K$  is associated with  $M$  volume prismatic elements which are defined by

$$\forall j = 0, \dots, M, \quad H_j = (V_{i1,j}^{3d}, V_{i2,j}^{3d}, V_{i3,j}^{3d}, V_{i1,j+1}^{3d}, V_{i2,j+1}^{3d}, V_{i3,j+1}^{3d}).$$

Theses volume elements can have some merged point:

- 0 merged point : prism
- 1 merged points : pyramid
- 2 merged points : tetrahedra
- 3 merged points : no elements

The elements with merged points are called degenerate elements. To obtain a mesh with tetrahedra, we decompose the pyramid into two tetrahedra and the prism into three tetrahedra. These tetrahedra are obtained by cutting the quadrilateral face of pyramid and prism with the diagonal which have the vertex with the maximum index (see [8] for the reason of this choice).

The arguments of `buildlayermesh` is a two dimensional mesh and the number of layers  $M$ . The parameters of this command are:

**labeldown** = Same as the previous case but for the lower/down face label.

An example of this command line is given in `buildlayermesh.edp`.

```

load "medit"
load "msh3"
func mesh3 Cube(int[int] & NN,real[int,int] &BB ,int[int,int] & L)
{
                                                    //    first build the 6 faces of the hex.

    real x0=BB(0,0),x1=BB(0,1);
    real y0=BB(1,0),y1=BB(1,1);
    real z0=BB(2,0),z1=BB(2,1);

    int nx=NN[0],ny=NN[1],nz=NN[2];
    mesh Thx = square(nx,ny,[x0+(x1-x0)*x,y0+(y1-y0)*y]);

    int[int] rup=[0,L(2,1)], rdown=[0,L(2,0)],
        rmid=[1,L(1,0), 2,L(0,1), 3, L(1,1), 4, L(0,0) ];
    mesh3 Th=buildlayers(Thx,nz, zbound=[z0,z1],
                        labelmid=rmid, labelup = rup,
                        labeldown = rdown);

    return Th;
}

```

The unit cube example:

```
include "Cube.idp"
int [int] NN=[10,10,10];           // the number of step in each direction
real [int,int] BB=[[0,1],[0,1],[0,1]]; // bounding box
int [int,int] L=[[1,2],[3,4],[5,6]]; // the label of the 6 face left,right,
                                     // front, back, down, right

mesh3 Th=Cube(NN,BB,L);
medit("Th",Th);                     // see figure 5.35
```

The cone example (an axisymtric mesh on a triangle with degenerateness).

### Example 5.21 (cone.edp)

```
load "msh3"
load "medit"

// cone using buildlayers with a triangle

real RR=1,HH=1;
border Taxe(t=0,HH){x=t;y=0;label=0;};
border Hypo(t=1,0){x=HH*t;y=RR*t;label=1;};
border Vert(t=0,RR){x=HH;y=t;label=2;};
int nn=10; real h= 1./nn;
mesh Th2=buildmesh( Taxe(HH*nn)+ Hypo(sqrt(HH*HH+RR*RR)*nn) + Vert(RR*nn) );
plot(Th2,wait=1); // the 2d mesh

int MaxLayersT=(int(2*pi*RR/h)/4)*4; // number of layers
real zminT = 0, zmaxT = 2*pi; // height 2*pi
func fx= y*cos(z); func fy= y*sin(z); func fz= x;
int [int] r1T=[0,0], r2T=[0,0,2,2], r4T=[0,2];

// trick function:
func deg= max(.01,y/max(x/HH,0.4) /RR); // the function defined the proportion
// of number layer close to axis with reference MaxLayersT

mesh3 Th3T=buildlayers(Th2,coef= deg, MaxLayersT,
                      zbound=[zminT,zmaxT],transfo=[fx,fy,fz],
                      facemerge=0, region=r1T, labelmid=r2T);
medit("cone",Th3T); // see figure 5.36
```

### Example 5.22 (buildlayermesh.edp)

```
// file buildlayermesh.edp

load "msh3"
load "tetgen"

// Test 1

int C1=99, C2=98; // could be anything
border C01(t=0,pi){ x=t; y=0; label=1;};
border C02(t=0,2*pi){ x=pi; y=t; label=1;};
border C03(t=0,pi){ x=pi-t; y=2*pi; label=1;};
border C04(t=0,2*pi){ x=0; y=2*pi-t; label=1;};
```




Figure 5.35: the mesh of a cube made with cube.edp




Figure 5.36: the mesh of a cone made with cone.edp

```

border C11(t=0,0.7){ x=0.5+t; y=2.5; label=C1;}
border C12(t=0,2){ x=1.2; y=2.5+t; label=C1;}
border C13(t=0,0.7){ x=1.2-t; y=4.5; label=C1;}
border C14(t=0,2){ x=0.5; y=4.5-t; label=C1;}

border C21(t=0,0.7){ x= 2.3+t; y=2.5; label=C2;}
border C22(t=0,2){ x=3; y=2.5+t; label=C2;}
border C23(t=0,0.7){ x=3-t; y=4.5; label=C2;}
border C24(t=0,2){ x=2.3; y=4.5-t; label=C2;}

mesh Th=buildmesh( C01(10)+C02(10)+ C03(10)+C04(10)
                  + C11(5)+C12(5)+C13(5)+C14(5)
                  + C21(-5)+C22(-5)+C23(-5)+C24(-5));

mesh Ths=buildmesh( C01(10)+C02(10)+ C03(10)+C04(10)
                   + C11(5)+C12(5)+C13(5)+C14(5) );

// construction of a box with one hole and two regions

func zmin=0.;
func zmax=1.;
int MaxLayer=10;

func XX = x*cos(y);
func YY = x*sin(y);
func ZZ = z;

int[int] r1=[0,41], r2=[98,98, 99,99, 1,56];
int[int] r3=[4,12];
// The triangles of uppper surface mesh
// generated by the triangle in the 2D region of mesh Th of label 4 as label 12.

```

```

int [int] r4=[4,45]; // The triangles of lower surface mesh
// generated by the triangle in the 2D region of mesh Th of label 4 as label 45.

mesh3 Th3=buildlayers( Th, MaxLayer, zbound=[zmin,zmax], region=r1,
                        labelmid=r2, labelup = r3, labeldown = r4 );
savemesh(Th3,"box2region1hole.mesh");

// construction of a sphere with TetGen

func XX1 = cos(y)*sin(x);
func YY1 = sin(y)*sin(x);
func ZZ1 = cos(x);
string test="paACQ";
cout << "test=" << test << endl;
mesh3 Th3sph=tetgtransfo(Ths,transfo=[XX1,YY1,ZZ1],switch=test,nbofregions=1,
                        regionlist=domain);
savemesh(Th3sph,"sphere2region.mesh");

```

## 5.11 Meshing examples

**Example 5.23 (lac.edp)** //file "lac.edp"

```

load 'msh3'
int nn=5;
border cc(t=0,2*pi){x=cos(t);y=sin(t);label=1;}
mesh Th2 = buildmesh(cc(100));
fespace Vh2(Th2,P2);
Vh2 ux,uy,p2;
int [int] rup=[0,2], rdlow=[0,1], rmid=[1,1,2,1,3,1,4,1];
func zmin = 2-sqrt(4-(x*x+y*y));
func zmax = 2-sqrt(3.);

mesh3 Th = buildlayers(Th2,nn,
                        coeff = max((zmax-zmin)/zmax, 1./nn),
                        zbound=[zmin,zmax],
                        labelmid=rmid;
                        labelup=rup;
                        labeldown=rldow);
savemesh(Th, 'Th.meshb');
exec('medit Th; Th.meshb');

```

**Example 5.24 (tetgenholeregion.edp)**

// file "tetgenholeregion.edp"

```

load "msh3"
load "tetgen"

mesh Th=square(10,20,[x*pi-pi/2,2*y*pi]); // [-pi/2, pi/2] x [0, 2pi]
// a parametrization of a sphere

func f1 =cos(x)*cos(y);
func f2 =cos(x)*sin(y);
func f3 = sin(x);

// partial derivative of the parametrization DF

func flx=sin(x)*cos(y);

```

```

func f1y=-cos(x)*sin(y);
func f2x=-sin(x)*sin(y);
func f2y=cos(x)*cos(y);
func f3x=cos(x);
func f3y=0;

//       $M = DF'DF$ 

func m11=f1x^2+f2x^2+f3x^2;
func m21=f1x*f1y+f2x*f2y+f3x*f3y;
func m22=f1y^2+f2y^2+f3y^2;

func perio=[[4,y],[2,y],[1,x],[3,x]];
real hh=0.1;
real vv= 1/square(hh);
verbosity=2;
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
plot(Th,wait=1);

verbosity=2;

//      construction of the surface of spheres

real Rmin  = 1.;
func f1min = Rmin*f1;
func f2min = Rmin*f2;
func f3min = Rmin*f3;

mesh3 Th3sph = movemesh23(Th,transfo=[f1min,f2min,f3min]);

real Rmax  = 2.;
func f1max = Rmax*f1;
func f2max = Rmax*f2;
func f3max = Rmax*f3;

mesh3 Th3sph2 = movemesh23(Th,transfo=[f1max,f2max,f3max]);

cout << "addition" << endl;
mesh3 Th3 = Th3sph+Th3sph2;

real[int] domain2 = [1.5,0.,0.,145,0.001,0.5,0.,0.,18,0.001];
cout << "=====" << endl;
cout << " tetgen call without hole " << endl;
cout << "=====" << endl;
mesh3 Th3fin = tetg(Th3,switch="paAAQYY",nbofregions=2,regionlist=domain2);
cout << "=====" << endl;
cout << "finish tetgen call without hole" << endl;
cout << "=====" << endl;
savemesh(Th3fin,"spherewithtworegion.mesh");

real[int] hole = [0.,0.,0.];
real[int] domain = [1.5,0.,0.,53,0.001];
cout << "=====" << endl;
cout << " tetgen call with hole " << endl;
cout << "=====" << endl;
mesh3 Th3finhole=tetg(Th3,switch="paAAQYY",nbofholes=1,holelist=hole,
nbofregions=1,regionlist=domain);
cout << "=====" << endl;

```

```
cout << "finish tetgen call with hole    " << endl;
cout << "===== " << endl;
savemesh(Th3finhole,"spherewithahole.mesh");
```

### 5.11.1 Build a 3d mesh of a cube with a balloon

First the MeshSurface.idp file to build boundary mesh of a Hexaedra and of a Sphere.

```
func mesh3 SurfaceHex(int[int] & N,real[int,int] &B ,int[int,int] & L,int orientation)
{
    real x0=B(0,0),x1=B(0,1);
    real y0=B(1,0),y1=B(1,1);
    real z0=B(2,0),z1=B(2,1);

    int nx=N[0],ny=N[1],nz=N[2];

    mesh Thx = square(ny,nz,[y0+(y1-y0)*x,z0+(z1-z0)*y]);
    mesh Thy = square(nx,nz,[x0+(x1-x0)*x,z0+(z1-z0)*y]);
    mesh Thz = square(nx,ny,[x0+(x1-x0)*x,y0+(y1-y0)*y]);

    int[int] refx=[0,L(0,0)],refX=[0,L(0,1)]; // Xmin, Ymax faces labels renumbering
    int[int] refy=[0,L(1,0)],refY=[0,L(1,1)]; // Ymin, Ymax faces labels renumbering
    int[int] refz=[0,L(2,0)],refZ=[0,L(2,1)]; // Zmin, Zmax faces labels renumbering

    mesh3 Thx0 = movemesh23(Thx,transfo=[x0,x,y],orientation=-orientation,label=refx);
    mesh3 Thx1 = movemesh23(Thx,transfo=[x1,x,y],orientation=+orientation,label=refX);
    mesh3 Thy0 = movemesh23(Thy,transfo=[x,y0,y],orientation=+orientation,label=refy);
    mesh3 Thy1 = movemesh23(Thy,transfo=[x,y1,y],orientation=-orientation,label=refY);
    mesh3 Thz0 = movemesh23(Thz,transfo=[x,y,z0],orientation=-orientation,label=refz);
    mesh3 Thz1 = movemesh23(Thz,transfo=[x,y,z1],orientation=+orientation,label=refZ);
    mesh3 Th= Thx0+Thx1+Thy0+Thy1+Thz0+Thz1;
    return Th;
}

func mesh3 Sphere(real R,real h,int L,int orientation)
{
    mesh Th=square(10,20,[x*pi-pi/2,2*y*pi]); // ] $\frac{-\pi}{2}$ ,frac{-pi2[x]0,2\pi[
// a parametrization of a sphere

    func f1 =cos(x)*cos(y);
    func f2 =cos(x)*sin(y);
    func f3 = sin(x);

// partiel derivative

    func f1x=sin(x)*cos(y);
    func f1y=-cos(x)*sin(y);
    func f2x=-sin(x)*sin(y);
    func f2y=cos(x)*cos(y);
    func f3x=cos(x);
    func f3y=0;

// the metric on the sphere M = DF'DF

    func m11=f1x^2+f2x^2+f3x^2;
    func m21=f1x*f1y+f2x*f2y+f3x*f3y;
    func m22=f1y^2+f2y^2+f3y^2;
```



```

func perio=[[4,y],[2,y],[1,x],[3,x]];           //   to store the periodic condition

real hh=h/R;                                   //   hh mesh size on unite sphere
real vv= 1/square(hh);
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
Th=adaptmesh(Th,m11*vv,m21*vv,m22*vv,IsMetric=1,periodic=perio);
int[int] ref=[0,L];

mesh3 ThS= movemesh23(Th,transfo=[f1*R,f2*R,f3*R],orientation=orientation,refface=ref);
return ThS;
}

```

The test of the two functions and the call to tetgen mesh generator

```

load "tetgen"
include "MeshSurface.idp"
  real hs = 0.1;                               //   mesh size on sphere
  int[int] N=[20,20,20];
  real [int,int] B=[[-1,1],[-1,1],[-1,1]];
  int [int,int] L=[[1,2],[3,4],[5,6]];
  mesh3 ThH = SurfaceHex(N,B,L,1);
  mesh3 ThS =Sphere(0.5,hs,7,1); //   "gluing" surface meshes to tolat boundary meshes

  mesh3 ThHS=ThH+ThS;
  savemesh(ThHS,"Hex-Sphere.mesh");
  exec("ffmedit Hex-Sphere.mesh;rm Hex-Sphere.mesh"); //   see 5.37

  real voltet=(hs^3)/6.;
  cout << " voltet = " << voltet << endl;
  real[int] domaine = [0,0,0,1,voltet,0,0,0.7,2,voltet];

  mesh3 Th = tetg(ThHS,switch="pqAAYYQ",nbofregions=2,regionlist=domaine);
  medit("Cube-With-Ball",Th); //   see 5.38

```

## 5.12 The output solution formats .sol and .solb

With the keyword savesol, we can store a scalar functions, a scalar FE functions, a vector fields, a vector FE fields, a symmetric tensor and a symmetric FE tensor.. Such format is used in medit.

**extension file .sol** The first two lines of the file are

- MeshVersionFormatted 0
- Dimension (I) dim




Figure 5.37: The surface mesh of the Hex with internal Sphere




Figure 5.38: The tet mesh of the cube with internal ball

The following fields begin with one of the following keyword: SolAtVertices, SolAtEdges, SolAtTriangles, SolAtQuadrilaterals, SolAtTetrahedra, SolAtPentahedra, SolAtHexahedra.

In each field, we give then in the next line the number of elements in the solutions (SolAtVertices: number of vertices, SolAtTriangles: number of triangles, ...). In other lines, we give the number of solutions, the type of solution (1: scalar, 2: vector, 3: symmetric tensor). And finally, we give the values of the solutions on the elements.

The file must be ended with the keyword End.

The real element of symmetric tensor

$$ST^{3d} = \begin{pmatrix} ST_{xx}^{3d} & ST_{xy}^{3d} & ST_{xz}^{3d} \\ ST_{yx}^{3d} & ST_{yy}^{3d} & ST_{yz}^{3d} \\ ST_{zx}^{3d} & ST_{zy}^{3d} & ST_{zz}^{3d} \end{pmatrix} \quad ST^{2d} = \begin{pmatrix} ST_{xx}^{2d} & ST_{xy}^{2d} \\ ST_{yx}^{2d} & ST_{yy}^{2d} \end{pmatrix} \quad (5.5)$$

stored in the extension .sol are respectively  $ST_{xx}^{3d}, ST_{yx}^{3d}, ST_{yy}^{3d}, ST_{zx}^{3d}, ST_{zy}^{3d}, ST_{zz}^{3d}$  and  $ST_{xx}^{2d}, ST_{yx}^{2d}, ST_{yy}^{2d}$ . An example of field with the keyword SolAtTetrahedra:

- SolAtTetrahedra
  - (I) NbOfTetrahedrons
  - nbsol typesol<sup>1</sup> ... typesol<sup>n</sup>
  - (( $(U_{ij}^k, \forall i \in \{1, \dots, \text{nbreaksol}^k\})$ ),  $\forall k \in \{1, \dots, \text{nbsol}\}$ )  $\forall j \in \{1, \dots, \text{NbOfTetrahedrons}\}$ )

where

- nbsol is an integer equal to the number of solutions
- typesol<sup>k</sup>, type of the solution number k, is
  - typesol<sup>k</sup> = 1 the solution k is scalar.

- $\text{typesol}^k = 2$  the solution  $k$  is vectorial.
- $\text{typesol}^k = 3$  the solution  $k$  is a symmetric tensor or symmetric matrix.
- $\text{nbrealsol}^k$  number of real to describe solution number  $k$  is
  - $\text{nbrealsol}^k = 1$  the solution  $k$  is scalar.
  - $\text{nbrealsol}^k = \text{dim}$  the solution  $k$  is vectorial ( $\text{dim}$  is the dimension of the solution).
  - $\text{nbrealsol}^k = \text{dim} * (\text{dim} + 1)/2$  the solution  $k$  is a symmetric tensor or symmetric matrix.
- $U_{ij}^k$  is a real equal to the value of the component  $i$  of the solution  $k$  at tetrahedra  $j$  on the associated mesh.

This field is written with the notation of Section 12.1. The format `.solb` is the same as format `.sol` but in binary (read/write is faster, storage is less).

A real scalar functions  $f1$ , a vector fields  $\Phi = [\Phi1, \Phi2, \Phi3]$  and a symmetric tensor  $ST^{3d}$  (5.5) at the vertices of the three dimensional mesh  $\text{Th3}$  is stored in the file "f1PhiTh3.sol" using

```
savesol("f1PhiST3dTh3.sol",Th3, f1, [\Phi1, \Phi2, \Phi3], VV3, order=1);
```

where  $VV3 = [ST_{xx}^{3d}, ST_{yx}^{3d}, ST_{yy}^{3d}, ST_{zx}^{3d}, ST_{zy}^{3d}, ST_{zz}^{3d}]$ . For a two dimensional mesh  $\text{Th}$ , A real scalar functions  $f2$ , a vector fields  $\Psi = [\Psi1, \Psi2]$  and a symmetric tensor  $ST^{2d}$  (5.5) at triangles is stored in the file "f2PsiST2dTh3.solb" using

```
savesol("f2PsiST2dTh3.solb",Th, f2, [\Psi1, \Psi2], VV2, order=0);
```

where  $VV2 = [ST_{xx}^{2d}, ST_{yx}^{2d}, ST_{yy}^{2d}]$  The arguments of `savesol` functions are the name of a file, a mesh and solutions. These arguments must be given in this order.

The parameters of this keyword are

**order** = 0 is the solution is given at the center of gravity of elements. 1 is the solution is given at the vertices of elements.

In the file, solutions are stored in this order : scalar solutions, vector solutions and finally symmetric tensor solutions.

## 5.13 medit

The keyword `medit` allows to display a mesh alone or a mesh and one or several functions defined on the mesh using the Pascal Frey's freeware `medit`. `Medit` opens its own window and uses OpenGL extensively. Naturally to use this command `medit` must be installed.

A visualization with `medit` of scalar solutions  $f1$  and  $f2$  continuous, piecewise linear and known at the vertices of the mesh  $\text{Th}$  is obtained using

```
medit("sol1 sol2",Th, f1, f2, order=1);
```

The first plot named "sol1" display  $f1$ . The second plot names "sol2" display  $f2$ .

The arguments of function `medit` are the name of the different scenes (separated by a space) of `medit`, a mesh and solutions. Each solution is associated with one scene. The scalar, vector and symmetric tensor solutions are specified in the format described in the section dealing with the keyword `savesol`.

The parameters of this command line are

**order** = 0 is the solution is given at the center of gravity of elements. 1 is the solution is given at the vertices of elements.

**meditff** = set the name of execute command of medit. By default, this string is medit.

**save** = set the name of a file .sol or .solb to save solutions.

This command line allows also to represent two different meshes and solutions on them in the same windows. The nature of solutions must be the same. Hence, we can visualize in the same window the different domains in a domain decomposition method for instance. A visualization with medit of scalar solutions  $h1$  and  $h2$  at vertices of the mesh Th1 and Th2 respectively are obtained using

```
medit("sol2domain",Th1, h1, Th2, h2, order=1);
```

#### Example 5.25 (meditddm.edp)

// meditddm.edp

```
load "medit"
```

// Initial Problem:

// Resolution of the following EDP:

```
//  $-\Delta u_s = f$  on  $\Omega = \{(x,y)|1 \leq \sqrt{x^2 + y^2} \leq 2\}$ 
```

```
//  $-\Delta u_1 = f_1$  on  $\Omega_1 = \{(x,y)|0.5 \leq \sqrt{x^2 + y^2} \leq 1\}$ 
```

```
//  $u = 1$  on  $\Gamma$  + Null Neumann condition on  $\Gamma_1$  and on  $\Gamma_2$ 
```

```
// We find the solution  $u$  in solving two EDP defined on domain  $\Omega$  and  $\Omega_1$ 
```

// This solution is visualize with medit

```
verbosity=3;
```

```
border Gamma(t=0,2*pi){x=cos(t); y=sin(t); label=1;;}
```

```
border Gamma1(t=0,2*pi){x=2*cos(t); y=2*sin(t); label=2;;}
```

```
border Gamma2(t=0,2*pi){x=0.5*cos(t); y=0.5*sin(t); label=3;;}
```

// construction of mesh of domain  $\Omega$

```
mesh Th=buildmesh(Gamma1(40)+Gamma(-40));
```

```
fespace Vh(Th,P2);
```

```
func f=sqrt(x*x+y*y);
```

```
Vh us,v;
```

```
macro Grad2(us) [dx(us),dy(us)]
```

// EOM

```
problem Lap2dOmega(us,v,init=false)=int2d(Th)(Grad2(v)' *Grad2(us))
```

```
- int2d(Th)(f*v)+on(1,us=1) ;
```

// Definition of EDP defined on the domain  $\Omega$

//  $-\Delta u_s = f_1$  on  $\Omega_1$ ,  $u_s = 1$  on  $\Gamma_1$ ,  $\frac{\partial u_s}{\partial n} = 0$  on  $\Gamma_2$

```
Lap2dOmega;
```

// construction of mesh of domain  $\Omega_1$

```
mesh Th1=buildmesh(Gamma(40)+Gamma2(-40));
```

```
fespace Vh1(Th1,P2);
```

```
func f1=10*sqrt(x*x+y*y);
```

```
Vh1 u1,v1;
```

```
macro Grad21(u1) [dx(u1),dy(u1)]
```

// EOM

```
problem Lap2dOmega1(u1,v1,init=false)=int2d(Th1)(Grad21(v1)' *Grad21(u1))
```

```
- int2d(Th1)(f1*v1)+on(1,u1=1) ;
```

```

// Resolution of EDP defined on the domain  $\Omega_1$ 
//  $-\Delta u_1 = f_1$  on  $\Omega_1$ ,  $u - 1 = 1$  on  $\Gamma_1$ ,  $\frac{\partial u_1}{\partial n} = 0$  on  $\Gamma_2$ 
Lap2dOmega1;

// vizualisation of solution of the initial problem
medit("solution",Th,us,Th1,u1,order=1,save="testsavemedit.solb");

```

**Example 5.26 (StockesUzawa.edp)**

// signe of pressure is correct

```

assert(version>1.18);
real s0=clock();
mesh Th=square(10,10);
fespace Xh(Th,P2),Mh(Th,P1);
Xh u1,u2,v1,v2;
Mh p,q,ppp;

varf bx(u1,q) = int2d(Th)( dx(u1)*q );
varf by(u1,q) = int2d(Th)( dy(u1)*q );
varf a(u1,u2)= int2d(Th)( dx(u1)*dx(u2) + dy(u1)*dy(u2) )
               + on(1,2,4,u1=0) + on(3,u1=1) ;

Xh bc1; bc1[] = a(0,Xh);
Xh b;

matrix A= a(Xh,Xh,solver=CG);
matrix Bx= bx(Xh,Mh);
matrix By= by(Xh,Mh);
Xh bcx=1,bcy=0;

func real[int] divup(real[int] & pp)
{
  int verb=verbosity;
  verbosity=0;
  b[] = Bx'*pp; b[] += bc1[] .*bcx[];
  u1[] = A^-1*b[];
  b[] = By'*pp; b[] += bc1[] .*bcy[];
  u2[] = A^-1*b[];
  ppp[] = Bx*u1[];
  ppp[] += By*u2[];
  verbosity=verb;
  return ppp[] ;
};
p=0;q=0;u1=0;v1=0;

LinearCG(divup,p[],q[],eps=1.e-6,nbiter=50);

divup(p[]);

plot([u1,u2],p,wait=1,value=true,coef=0.1);
medit("velocity pressure",Th,[u1,u2],p,order=1);

```

## 5.14 Mshmet

Mshmet is a software developed by P. Frey that allows to compute an anisotropic metric based on solutions (i.e. Hessian-based). This software can return also an isotropic metric. Moreover, mshmet can construct also a metric suitable for level sets interface capturing. The solution can be defined on 2D or 3D structured/unstructured meshes. For example, the solution can be an error estimate of a FE solutions.

Solutions for mshmet are given as an argument. The solution can be a func, a vector func, a symmetric tensor, a FE func, a FE vector func and a FE symmetric tensor. The symmetric tensor argument is defined as this type of data for datasol argument. This software accepts more than one solution.

For example, the metric  $M$  computed with mshmet for the solution  $u$  defined on the mesh  $Th$  is obtained by writing.

```
fespace Vh(Th,P1);
Vh u;                                     // a scalar FE func
real[int] M = mshmet(Th,u);
```

The parameters of the keyword mshmet are :

- **normalization** = <b> do a normalisation of all solution in [0, 1].
- **aniso** = <b> build aniso metric if 1 ( default 0: iso)
- **levelset** = <b> build metric for level set method (default: false)
- **verbosity** = <l>
- **nbregul** = <l> number of regularization's iteration of solutions given (default 0).
- **hmin** = <d>
- **hmax** = <d>
- **err** = <d> level of error.
- **width** = <d> the width
- **metric**= a vector of double. This vector contains an initial metric given to mshmet. The structure of the metric vector is described in the next paragraph.
- **loptions**=a vector of integer of size 7. This vector contains the integer parameters of mshmet(for expert only).
  - loptions(0): normalization (default 1).
  - loptions(1): isotropic parameters (default 0). 1 for isotropic metric results otherwise 0.
  - loptions(2): level set parameters (default 0). 1 for building level set metric otherwise 0.
  - loptions(3): debug parameters (default 0). 1 for turning on debug mode otherwise 0.
  - loptions(4): level of verbosity (default 10).
  - loptions(5): number of regularization's iteration of solutions given (default 0).
  - loptions(6): previously metric parameter (default 0). 1 for using previous metric otherwise 0.
- **doptions**= a vector of double of size 4. This vector contains the real parameters of mshmet (for expert only).
  - doptions(0): hmin : min size parameters (default 0.01).
  - doptions(1): hmax : max size parameters (default 1.0).
  - doptions(2): eps : tolerance parameters ( default 0.01).

– options(2): width : relative width for Level Set ( $0 < w < 1$ ) ( default 0.05).

The result of the keyword `mshmet` is a `real[int]` which contains the metric computed by `mshmet` at the different vertices  $V_i$  of the mesh.

With  $nv$  is the number of vertices, the structure of this vector is

$$M_{iso} = (m(V_0), m(V_1), \dots, m(V_{nv}))^t$$

for a isotropic metric  $m$ . For a symmetric tensor metric  $h = \begin{pmatrix} m_{11} & m_{12} & m_{13} \\ m_{21} & m_{22} & m_{23} \\ m_{31} & m_{32} & m_{33} \end{pmatrix}$ , the parameters metric is

$$M_{aniso} = (H(V_0), \dots, H(V_{nv}))^t$$

where  $H(V_i)$  is the vector of size 6 defined by [m11,m21,m22,m31,m32,m33]

#### Example 5.27 (mshmet.edp)

```
load "mshmet"
load "medit"
load "msh3"

border a(t=0,1.0){x=t; y=0; label=1;};
border b(t=0,0.5){x=1; y=t; label=2;};
border c(t=0,0.5){x=1-t; y=0.5;label=3;};
border d(t=0.5,1){x=0.5; y=t; label=4;};
border e(t=0.5,1){x=1-t; y=1; label=5;};
border f(t=0.0,1){x=0; y=1-t;label=6;};
mesh Th = buildmesh (a(6) + b(4) + c(4) +d(4) + e(4) + f(6));
savemesh(Th,"th.msh");
fespace Vh(Th,P1);
Vh u,v;
real error=0.01;
problem Problem1(u,v,solver=CG,eps=1.0e-6) =
  int2d(Th,qforder=2)( u*v*1.0e-10+ dx(u)*dx(v) + dy(u)*dy(v))
+int2d(Th,qforder=2)( (x-y)*v);

func zmin=0;
func zmax=1;
int MaxLayer=10;
mesh3 Th3 = buildlayers(Th,MaxLayer,zbound=[zmin,zmax]);
fespace Vh3(Th3,P2);
fespace Vh3P1(Th3,P1);
Vh3 u3,v3;
Vh3P1 usol;
problem Problem2(u3,v3,solver=sparsecv) =
  int3d(Th3)( u3*v3*1.0e-10+ dx(u3)*dx(v3) + dy(u3)*dy(v3) + dz(u3)*dz(v3))
- int3d(Th3)( v3) +on(0,1,2,3,4,5,6,u3=0);
Problem2;
cout << u3[].min << " " << u3[].max << endl;
savemesh(Th3,"metrictest.bis.mesh");
savesol("metrictest.sol",Th3,u3);

real[int] bb=mshmet(Th3,u3);
cout << bb << endl;
for(int ii=0; ii<Th3.nv; ii++)
  usol[][ii]=bb[ii];
savesol("metrictest.bis.sol",Th3,usol);
```

## 5.15 FreeYams

FreeYams is a surface mesh adaptation software which is developed by P. Frey. This software is a new version of yams. The adapted surface mesh is constructed with a geometric metric tensor field. This field is based on the intrinsic properties of the discrete surface. Also this software allows to construct a simplification of a mesh. This decimation is based on the Hausdorff distance between the initial and the current triangulation. Compared to the software yams, FreeYams can be used also to produce anisotropic triangulations adapted to level set simulations. A technical report on FreeYams is not available yet but a documentation on yams exists at <http://www.ann.jussieu.fr/~frey/software.html> [40].

To call FreeYams in Freefem++, we used the keyword `freeyams`. The arguments of this function are the initial mesh and/or metric. The metric with `freeyams` are a function, a FE function, a symmetric tensor function, a symmetric tensor FE function or a vector of double. If the metric is vector of double, this data must be given in `metric` parameter. Otherwise, the metric is given in the argument.

For example, the adapted mesh of *Thinit* defined by the metric *u* defined as FE function is obtained in writing.

```
fespace Vh(Thinit,P1);
Vh u;
mesh3 Th=freeyams(Thinit,u);
```

The symmetric tensor argument for `freeyams` keyword is defined as this type of data for `datasol` argument.

- `aniso` = <b> aniso or iso metric (default 0, iso)
- `mem` = <l> memory of for `freeyams` in Mb (default -1, `freeyams` choose)
- `hmin` = <d>
- `hmax` = <d>
- `gradation` = <d>
- `option` = <l>
  - 0 : mesh optimization (smoothing+swapping)
  - 1 : decimation+enrichment adapted to a metric map. (default)
  - 1 : decimation adapted to a metric map.
  - 2 : decimation+enrichment with a Hausdorff-like method
  - 2 : decimation with a Hausdorff-like method
  - 4 : split triangles recursively.
  - 9 : No-Shrinkage Vertex Smoothing
- `ridgeangle` = <d>
- `absolute` = <b>
- `verbosity` = <i>
- `metric`= vector expression. This parameters contains the metric at the different vertices on the initial mesh. With *nv* is the number of vertices, this vector is

$$M_{iso} = (m(V_0), m(V_1), \dots, m(V_{nv}))^t$$

for a scalar metric *m*. For a symmetric tensor metric  $h = \begin{pmatrix} m_{11} & m_{12} & m_{13} \\ m_{21} & m_{22} & m_{23} \\ m_{31} & m_{32} & m_{33} \end{pmatrix}$ , the parameters `metric` is

$$M_{aniso} = (H(V_0), \dots, H(V_{nv}))^t$$



where  $H(V_i)$  is the vector of size 6 defined by [m11,m21,m22,m31,m32,m33]

- **loptions**= a vector of integer of size 13. This vectors contains the integer options of FreeYams. (just for the expert )
  - **loptions(0)**: anisotropic parameter (default 0). If you give an anisotropic metric 1 otherwise 0.
  - **loptions(1)**: Finite Element correction parameter (default 0). 1 for *no* Finite Element correction otherwise 0.
  - **loptions(2)**: Split multiple connected points parameter (default 1). 1 for splitting multiple connected points otherwise 0.
  - **loptions(3)**: maximum value of memory size in Mbytes (default -1: the size is given by freeyams).
  - **loptions(4)**: set the value of the connected component which we want to obtain. (Remark: freeyams give an automatic value at each connected component).
  - **loptions(5)**: level of verbosity
  - **loptions(6)**: Create point on straight edge (no mapping) parameter (default 0). 1 for creating point on straight edge otherwise 0.
  - **loptions(7)**: validity check during smoothing parameter. This parameter is only used with No-Shrinkage Vertex Smoothing optimization (optimization option parameter 9). 1 for No validity checking during smoothing otherwise 0.
  - **loptions(8)**: number of desired's vertices (default -1).
  - **loptions(9)**: number of iteration of optimizations (default 30).
  - **loptions(10)**: ridge detection parameter (default 0) . 1 for detecting the ridge on the mesh otherwise 0. The ridge definition is given in the parameter doptions(12).
  - **loptions(11)**: vertex smoothing parameter (default 0). 1 for smoothing the vertices otherwise 0.
  - **loptions(12)**: Optimization level parameter (default 0).
    - \* 0 : mesh optimization (smoothing+swapping)
    - \* 1 : decimation+enrichment adaptated to a metric map.
    - \* -1: decimation adaptated to a metric map.
    - \* 2 : decimation+enrichment with a Hausdorff-like method
    - \* -2: decimation with a Hausdorff-like method
    - \* 4 : split triangles recursively.
    - \* 9 : No-Shrinkage Vertex Smoothing

**doptions**= a vector of double of size 11. This vectors contains the real options of freeyams.

- **doptions(0)**: Set the geometric approximation (Tangent plane deviation) (default 0.01).
- **doptions(1)**: Set the lamda parameter (default -1. ).
- **doptions(2)**: Set the mu parmeter (default -1. ).
- **doptions(3)**: Set the gradation value (Mesh density control) (default 1.3).
- **doptions(4)**: Set the minimal size(hmin) (default -2.0: the size is automatically computed).
- **doptions(5)**: Set the maximal size(hmax) (default -2.0: the size is automatically computed).
- **doptions(6)**: Set the tolerance of the control of Chordal deviation (default -2.0).
- **doptions(7)**: Set the quality of degradation (default 0.599).

- options(8): Set the declic parameter (default 2.0).
- options(9): Set the angular walton limitation parameter (default 45 degree).
- options(10): Set the angular ridge detection (default 45 degree).

### Example 5.28 (freeyams.edp)

```
load "msh3"
load "medit"
load "freeyams"
int nn=20;
mesh Th2=square(nn,nn);
fespace Vh2(Th2,P2);
Vh2 ux,uz,p2;
int[int] rup=[0,2], rdown=[0,1], rmid=[1,1,2,1,3,1,4,1];
real zmin=0,zmax=1;
mesh3 Th=buildlayers(Th2,nn, zbound=[zmin,zmax],
                    reffacemid=rmid, reffaceup = rup, reffacelow = rdown);

mesh3 Th3 = freeyams(Th);
medit("maillagesurfacique",Th3,wait=1);
```

## 5.16 mmg3d

Mmg3d is a 3D remeshing software developed by C. Dobrzynski and P. Frey (<http://www.math.u-bordeaux1.fr/~dobj/logiciels/mmg3d.php>). To obtain a version of this library send an e-mail at :

cecile.dobrzynski@math.ubordeaux1.fr or pascal.frey@upmc.fr.

This software allows to remesh an initial mesh made of tetrahedra. This initial mesh is adapted to a geometric metric tensor field or to a displacement vector (moving rigid body). The metric can be obtained with mshmet (see section 5.14).

### Remark 5 :

- (a) *If no metric is given, an isotropic metric is computed by analyzing the size of the edges in the initial mesh.*
- (b) *if a displacement is given, the vertices of the surface triangles are moved without verifying the geometrical structure of the new surface mesh.*

The parameters of mmg3d are :

- options= vector expression. This vector contains the option parameters of mmg3d. It is a vector of 6 values, with the following meaning:

**(0)** optimization parameters : (default 1)

- 0 : mesh optimization.
- 1 : adaptation with metric (deletion and insertion vertices) and optimization.
- 1: adaptation with metric (deletion and insertion vertices) without optimization.
- 4 : split tetrahedra (be careful modify the surface).
- 9 : moving mesh with optimization.
- 9: moving mesh without optimization.

**(1)** debug mode : (default 0)

- 1 : turn on debug mode.
- 0 : otherwise.

**(2)** Specify the size of bucket per dimension ( default 64)**(3)** swapping mode : (default 0)

- 1 : no edge or face flipping.
- 0 : otherwise.

**(4)** insert points mode : (default 0)

- 1 : no edge splitting or collapsing and no insert points.
- 0 : otherwise.

**(5)** verbosity level (default 3)

- **memory**= integer expression. Set the maximum memory size of new mesh in Mbytes. By default the number of maximum vertices, tetrahedra and triangles are respectively 500 000, 3000 000, 100000 which represent approximately a memory of 100 Mo.
- **metric**= vector expression. This vector contains the metric given at mmg3d. It is a vector of size  $nv$  or  $6\ nv$  respectively for an isotropic and anisotropic metric where  $nv$  is the number of vertices in the initial mesh. The structure of **metric** vector is described in the mshmet's section(section 5.14).
- **displacement**=  $[\Phi_1, \Phi_2, \Phi_3]$  set the displacement vector of the initial mesh  
 $\Phi(x, y) = [\Phi_1(x, y), \Phi_2(x, y), \Phi_3(x, y)]$ .
- **displVect**= sets the vector displacement in a vector expression. This vector contains the displacement at each point of the initial mesh. It is a vector of size  $3\ nv$ .

An example using this function is given in "mmg3d.edp":

**Example 5.29 (mmg3d.edp)**

```

//      test mmg3d

load "msh3"
load "medit"
load "mmg3d"
include "../examples++-3d/cube.idp"

int n=6;
int[int] Nxyz=[12,12,12];
real [int,int] Bxyz=[[0.,1.],[0.,1.],[0.,1.]];
int [int,int] Lxyz=[[1,1],[2,2],[2,2]];
mesh3 Th=Cube(Nxyz,Bxyz,Lxyz);

real[int] isometric(Th.nv);{
  for( int ii=0; ii<Th.nv; ii++)
    isometric[ii]=0.17;
}
```

```

mesh3 Th3=mmg3d( Th, memory=100, metric=isometric);

medit("init",Th);
medit("isometric",Th3);

```

An example of a moving mesh is given in `fallingspheres.edp`:

```

Example 5.30 (fallingspheres.edp) load "msh3" load "tetgen" load "medit" load "mmg3d"
include "MeshSurface.idp"

                                     //    build mesh of a box (311) wit 2 holes (300,310)

real hs = 0.8;
int[int] N=[4/hs,8/hs,11.5/hs];
real [int,int] B=[[-2,2],[-2,6],[-10,1.5]];
int [int,int] L=[[311,311],[311,311],[311,311]];
mesh3 ThH = SurfaceHex(N,B,L,1);
mesh3 ThSg =Sphere(1,hs,300,-1);
mesh3 ThSd =Sphere(1,hs,310,-1);  ThSd=movemesh3(ThSd,transfo=[x,4+y,z]);
mesh3 ThHS=ThH+ThSg+ThSd;           //    gluing surface meshes
medit("ThHS", ThHS);                //    see surface mesh

real voltet=(hs^3)/6.;
real[int] domaine = [0,0,-4,1,voltet];
real [int] holes=[0,0,0,0,4,0];
mesh3 Th = tetg(ThHS,switch="pqaAAYYQ",nbofregions=1,regionlist=domaine, nbofholes=2,holelist=holes);
medit("Box-With-two-Ball",Th);

                                     //    End build mesh

int[int] opt=[9,0,64,0,0,3];           //    options of mmg3d see freeem++ doc
real[int] vit=[0,0,-0.3];
func zero = 0.;
func dep  = vit[2];

fespace Vh(Th,P1);
macro Grad(u) [dx(u),dy(u),dz(u)]           //

Vh uh,vh;                                //    to compute the displacemnt field
problem Lap(uh,vh,solver=CG) = int3d(Th)(Grad(uh)')*Grad(vh)           //    ') for emacs
    + on(310,300,uh=dep) +on(311,uh=0.);

for(int it=0; it<29; it++){
    cout<<"  ITERATION          "<<it<<endl;
    Lap;
    plot(Th,uh);
    Th=mmg3d(Th,options=opt,displacement=[zero,zero,uh],memory=1000);
}

```

## 5.17 A first 3d isotope mesh adaptation process

### Example 5.31 (Laplace-Adapt-3d.edp)

```

load "msh3" load "tetgen" load "mshmet" load "medit"                                     // build initial mesh

int nn = 6;
int[int] l1111=[1,1,1,1],l01=[0,1],l11=[1,1]; // label numbering to have all label to 1
mesh3 Th3=buildlayers(square(nn,nn,region=0,label=l1111),
    nn, zbound=[0,1], labelmid=l11, labelup = l01, labeldown = l01);
Th3 = trunc(Th3,(x<0.5) | (y < 0.5) | (z < 0.5),label=1); // remove the ]0.5,1[3cube
// end of build initial mesh

fespace Vh(Th3,P1);
Vh u,v,usol,h;

macro Grad(u) [dx(u),dy(u),dz(u)] // EOM

problem Poisson(u,v,solver=CG) = int3d(Th3)( Grad(u)'*Grad(v) )
    -int3d(Th3)( 1*v ) + on(1,u=0);

real errm=1e-2; // level of error
for(int ii=0; ii<5; ii++)
{
    Poisson; // solve Poisson equation.
    cout <<" u min, max = " << u[].min << " "<< u[].max << endl;
    h=0. ; // for resizing h[] because the mesh change
    h[]=mshmet(Th3,u,normalization=1,aniso=0,nbregul=1,hmin=1e-3,hmax=0.3,err=errm);
    cout <<" h min, max = " << h[].min << " "<< h[].max
        << " " << h[].n << " " << Th3.nv << endl;
    plot(u,wait=1);
    errm*= 0.8; // change the level of error
    cout << " Th3" << Th3.nv < " " << Th3.nt << endl;
    Th3=tetgreconstruction(Th3,switch="raAQ",sizeofvolume=h*h*h/6.); // rebuild mesh
    medit("U-adap-iso-"+ii,Th3,u,wait=1);}

```



# Chapter 6

## Finite Elements

As stated in Section 2. FEM approximates all functions  $w$  as

$$w(x, y) \simeq w_0\phi_0(x, y) + w_1\phi_1(x, y) + \cdots + w_{M-1}\phi_{M-1}(x, y)$$

with finite element basis functions  $\phi_k(x, y)$  and numbers  $w_k$  ( $k = 0, \dots, M - 1$ ). The functions  $\phi_k(x, y)$  are constructed from the triangle  $T_{i_k}$ , and called *shape functions*. In FreeFem++ the finite element space

$$V_h = \{w \mid w_0\phi_0 + w_1\phi_1 + \cdots + w_{M-1}\phi_{M-1}, w_i \in \mathbb{R}\}$$

is easily created by

```
fespace IDspace(IDmesh,<IDFE>) ;
```

or with  $\ell$  pairs of periodic boundary condition in 2d

```
fespace IDspace(IDmesh,<IDFE>,  
                periodic=[[la_1,sa_1],[lb_1,sb_1],  
                        ...  
                        [la_k,sa_k],[lb_k,sb_k]]);
```

and in 3d

```
fespace IDspace(IDmesh,<IDFE>,  
                periodic=[[la_1,sa_1,ta_1],[lb_1,sb_1,tb_1],  
                        ...  
                        [la_k,sa_k,ta_k],[lb_k,sb_k,tb_k]]);
```

where

IDspace is the name of the space (e.g.  $V_h$ ),

IDmesh is the name of the associated mesh and <IDFE> is a identifier of finite element type.

In 2D we have a pair of periodic boundary condition, if  $[la_i, sa_i], [lb_i, sb_i]$  is a pair of `int`, and the 2 labels  $la_i$  and  $lb_i$  refer to 2 pieces of boundary to be in equivalence.

If  $[la_i, sa_i], [lb_i, sb_i]$  is a pair of `real`, then  $sa_i$  and  $sb_i$  give two common abscissa on the two boundary curve, and two points are identified as one if the two abscissa are equal.

In 2D, we have a pair of periodic boundary condition, if  $[la_i, sa_i, ta_i], [lb_i, sb_i, tb_i]$  is a pair of `int`, the 2 labels  $la_i$  and  $lb_i$  define the 2 piece of boundary to be in equivalence.

If  $[la_i, sa_i, ta_i], [lb_i, sb_i, tb_i]$  is a pair of `real`, then  $sa_i, ta_i$  and  $sb_i, tb_i$  give two common parameters on the two boundary surface, and two points are identified as one if the two parameters are equal.

**Remark 6** The 2D mesh of the two identified borders must be the same, so to be sure, use the parameter `fixeborder=true` in `buildmesh` command (see 5.1.2) like in example `periodic2bis.edp` (see 9.7).

As of today, the known types of finite element are:

**P0,P03d** piecewise constant discontinuous finite element (2d, 3d), the degrees of freedom are the barycenter element value.

$$P0_h = \left\{ v \in L^2(\Omega) \mid \text{for all } K \in \mathcal{T}_h \text{ there is } \alpha_K \in \mathbb{R} : v|_K = \alpha_K \right\} \quad (6.1)$$

**P1,P13d** piecewise linear continuous finite element (2d, 3d), the degrees of freedom are the vertices values.

$$P1_h = \left\{ v \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_1 \right\} \quad (6.2)$$

**P1dc** piecewise linear discontinuous finite element

$$P1dc_h = \left\{ v \in L^2(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_1 \right\} \quad (6.3)$$

Warning, due to interpolation problem, the degree of freedom is not the vertices but three vertices move inside with  $T(X) = G + .99(X - G)$  where  $G$  is the barycenter, (version 2.24-4).

**P1b,P1b3d** piecewise linear continuous finite element plus bubble (2d, 3d)

**The 2d case:**

$$P1b_h = \left\{ v \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_1 \oplus \text{Span}\{\lambda_0^K \lambda_1^K \lambda_2^K\} \right\} \quad (6.4)$$

**The 3d case:**

$$P1b_h = \left\{ v \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_1 \oplus \text{Span}\{\lambda_0^K \lambda_1^K \lambda_2^K \lambda_3^K\} \right\} \quad (6.5)$$

where  $\lambda_i^K, i = 0, \dots, d$  are the  $d + 1$  barycentric coordinate functions of the element  $K$  (triangle or tetrahedron).

**P2,P23d** piecewise  $P_2$  continuous finite element (2d, 3d),

$$P2_h = \left\{ v \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_2 \right\} \quad (6.6)$$

where  $P_2$  is the set of polynomials of  $\mathbb{R}^2$  of degrees  $\leq 2$ .

**P2b** piecewise  $P_2$  continuous finite element plus bubble,

$$P2_h = \left\{ v \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_2 \oplus \text{Span}\{\lambda_0^K \lambda_1^K \lambda_2^K\} \right\} \quad (6.7)$$

**P2dc** piecewise  $P_2$  discontinuous finite element,

$$P2dc_h = \left\{ v \in L^2(\Omega) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_2 \right\} \quad (6.8)$$

Warning, due to interpolation problem, the degree of freedom is not the six  $P_2$  nodes but six nodes move inside with  $T(X) = G + .99(X - G)$  where  $G$  is the barycenter, (version 2.24-4).



**RT0,RT03d** Raviart-Thomas finite element of degree 0.

The 2d case:

$$RT0_h = \left\{ \mathbf{v} \in H(\text{div}) \mid \forall K \in \mathcal{T}_h \quad \mathbf{v}|_K(x, y) = \begin{bmatrix} \alpha_K^1 \\ \alpha_K^2 \end{bmatrix} + \beta_K \begin{bmatrix} x \\ y \end{bmatrix} \right\} \quad (6.9)$$

The 3d case:

$$RT0_h = \left\{ \mathbf{v} \in H(\text{div}) \mid \forall K \in \mathcal{T}_h \quad \mathbf{v}|_K(x, y, z) = \begin{bmatrix} \alpha_K^1 \\ \alpha_K^2 \\ \alpha_K^3 \end{bmatrix} + \beta_K \begin{bmatrix} x \\ y \\ z \end{bmatrix} \right\} \quad (6.10)$$

where by writing  $\text{div } \mathbf{w} = \sum_{i=1}^d \partial w_i / \partial x_i$  with  $\mathbf{w} = (w_i)_{i=1}^d$ ,

$$H(\text{div}) = \left\{ \mathbf{w} \in L^2(\Omega)^d \mid \text{div } \mathbf{w} \in L^2(\Omega) \right\}$$

and where  $\alpha_K^1, \alpha_K^2, \alpha_K^3, \beta_K$  are real numbers.

**Edge03d** Nedelec finite element or Edge Element of degree 0.

The 3d case:

$$RT0_h = \left\{ \mathbf{v} \in H(\text{Curl}) \mid \forall K \in \mathcal{T}_h \quad \mathbf{v}|_K(x, y, z) = \begin{bmatrix} \alpha_K^1 \\ \alpha_K^2 \\ \alpha_K^3 \end{bmatrix} + \begin{bmatrix} \beta_K^1 \\ \beta_K^2 \\ \beta_K^3 \end{bmatrix} \times \begin{bmatrix} x \\ y \\ z \end{bmatrix} \right\} \quad (6.11)$$

where by writing  $\text{curl } \mathbf{w} = \begin{bmatrix} \partial w_2 / \partial x_3 - \partial w_3 / \partial x_2 \\ \partial w_3 / \partial x_1 - \partial w_1 / \partial x_3 \\ \partial w_1 / \partial x_2 - \partial w_2 / \partial x_1 \end{bmatrix}$  with  $\mathbf{w} = (w_i)_{i=1}^d$ ,

$$H(\text{curl}) = \left\{ \mathbf{w} \in L^2(\Omega)^d \mid \text{curl } \mathbf{w} \in L^2(\Omega)^d \right\}$$

and  $\alpha_K^1, \alpha_K^2, \alpha_K^3, \beta_K^1, \beta_K^2, \beta_K^3$  are real numbers.

**P1nc** piecewise linear element continuous at the middle of edge only.

## 6.1 Use of “fespace” in 2d

With the 2d finite element spaces

$$X_h = \{v \in H^1([0, 1]^2) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_1\}$$

$$X_{ph} = \{v \in X_h \mid v(\begin{bmatrix} 0 \\ 1 \end{bmatrix}) = v(\begin{bmatrix} 1 \\ 1 \end{bmatrix}), v(\begin{bmatrix} 0 \\ 0 \end{bmatrix}) = v(\begin{bmatrix} 1 \\ 0 \end{bmatrix})\}$$

$$M_h = \{v \in H^1([0, 1]^2) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_2\}$$

$$R_h = \{\mathbf{v} \in H^1([0, 1]^2)^2 \mid \forall K \in \mathcal{T}_h \quad \mathbf{v}|_K(x, y) = \begin{bmatrix} \alpha_K^1 \\ \alpha_K^2 \end{bmatrix} + \gamma_K \begin{bmatrix} x \\ y \end{bmatrix}\}$$

when  $\mathcal{T}_h$  is a mesh  $10 \times 10$  of the unit square  $]0, 1[^2$ , we only write in **FreeFem++** :

```
mesh Th=square(10,10);
fespace Xh(Th,P1); // scalar FE
fespace Xph(Th,P1,
    periodic=[[2,y],[4,y],[1,x],[3,x]]); // bi-periodic FE
fespace Mh(Th,P2); // scalar FE
fespace Rh(Th,RT0); // vectorial FE
```

where  $X_h, M_h, R_h$  expresses finite element spaces (called FE spaces)  $X_h, M_h, R_h$ , respectively.

To use FE-functions  $u_h, v_h \in X_h, p_h, q_h \in M_h$  and  $U_h, V_h \in R_h$ , we write :

```

Xh uh,vh;
Xph uph,vph;
Mh ph,qh;
Rh [Uxh,Uyh],[Vxh,Vyh];
Xh[int] Uh(10); // array of 10 function in Xh
Rh[int] [Wxh,Wyh](10); // array of 10 functions in Rh.
Wxh[5](0.5,0.5) // the 6th function at point (0.5,0.5)
Wxh[5][] // the array of the degree of freedom of the 6 function.

```

The functions  $U_h, V_h$  have two components so we have

$$U_h = \begin{pmatrix} U_{xh} \\ U_{yh} \end{pmatrix} \quad \text{and} \quad V_h = \begin{pmatrix} V_{xh} \\ V_{yh} \end{pmatrix}$$

## 6.2 Use of fespace in 3d

With the 3d finite element spaces

$$X_h = \{v \in H^1([0, 1]^3) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_1\}$$

$$X_{ph} = \{v \in X_h \mid v(\begin{smallmatrix} 0 \\ 0 \end{smallmatrix}) = v(\begin{smallmatrix} 1 \\ 1 \end{smallmatrix}), v(\begin{smallmatrix} 0 \\ 1 \end{smallmatrix}) = v(\begin{smallmatrix} 1 \\ 0 \end{smallmatrix})\}$$

$$M_h = \{v \in H^1([0, 1]^2) \mid \forall K \in \mathcal{T}_h \quad v|_K \in P_2\}$$

$$R_h = \{v \in H^1([0, 1]^2) \mid \forall K \in \mathcal{T}_h \quad v|_K(x, y) = \begin{pmatrix} \alpha_K \\ \beta_K \end{pmatrix} + \gamma_K \begin{pmatrix} x \\ y \end{pmatrix}\}$$

when  $\mathcal{T}_h$  is a mesh  $10 \times 10 \times 10$  of the unit cubic  $[0, 1]^3$ , we write in FreeFem++ :

```

mesh3 Th=buildlayers(square(10,10),10, zbound=[0,1]);
// label: 0 up, 1 down; 2 front, 3 left, 4 back, 5: right
fespace Xh(Th,P1); // scalar FE
fespace Xph(Th,P1,
    periodic=[[0,x,y],[1,x,y],
              [2,x,z],[4,x,z],
              [3,y,z],[5,y,z]]); // three-periodic FE (see Note 6.1)
fespace Mh(Th,P2); // scalar FE
fespace Rh(Th,RT03d); // vectorial FE

```

where Xh,Mh,Rh expresses finite element spaces (called FE spaces)  $X_h, M_h, R_h$ , respectively.

To define and use FE-functions  $u_h, v_h \in X_h$  and  $p_h, q_h \in M_h$  and  $U_h, V_h \in R_h$ , we write:

```

Xh uh,vh;
Xph uph,vph;
Mh ph,qh;
Rh [Uxh,Uyh,Uyzh],[Vxh,Vyh,Vyzh];
Xh[int] Uh(10); // array of 10 function in Xh
Rh[int] [Wxh,Wyh,Wzh](10); // array of 10 functions in Rh.
Wxh[5](0.5,0.5,0.5) // the 6th function at point (0.5,0.5,0.5)
Wxh[5][] // the array of the degree of freedom of
the 6 function.

```

The functions  $U_h, V_h$  have three components so we have

$$U_h = \begin{pmatrix} U_{xh} \\ U_{yh} \\ U_{zh} \end{pmatrix} \quad \text{and} \quad V_h = \begin{pmatrix} V_{xh} \\ V_{yh} \\ V_{zh} \end{pmatrix}$$

**Note 6.1** *One problem of the periodic boundary condition is the mesh must be the same on equivalence face, the BuildLayer mesh generation split quadrilateral faces with the diagonal passing through vertex with maximal number, so to be sure to have the same mesh on both face periodic the 2d numbering in corresponding edges must be compatible (for example the same variation). By Default, the numbering of square vertex are correct.*

*To change the mesh numbering you can use the `change` function like:*

```
{
int[int] old2new(0:Th.nv-1);           // for cleaning memory..
fespace Vh2(Th,P1);                     // array set on 0, 1, ..., nv-1
Vh2 sorder=x+y;                          // choose ordering increasing on 4 square borders with x or y
sort(sorder[],old2new);                  // build the inverse permutation
int[int] new2old=old2new^-1;             // inverse the permutation
Th= change(Th,renumv=new2old); change}
}
```

*the full example is in `examples++-3d/periodic-3d.edp`*

## 6.3 Lagrangian Finite Elements

### 6.3.1 P0-element

For each triangle ( $d=2$ ) or tetrahedron ( $d=3$ )  $T_k$ , the basis function  $\phi_k$  in  $Vh(Th, P0)$  is given by

$$\phi_k(\mathbf{x}) = 1 \text{ if } (\mathbf{x}) \in T_k, \quad \phi_k(\mathbf{x}) = 0 \text{ if } (\mathbf{x}) \notin T_k$$

If we write

$Vh(Th, P0); \quad Vh \quad fh=f(x,y);$

then for vertices  $q^{k_i}$ ,  $i = 1, 2, \dots, d+1$  in Fig. 6.1(a),  $f_h$  is built as

$$fh = f_h(x, y) = \sum_k f\left(\frac{\sum_i q^{k_i}}{d+1}\right) \phi_k$$

See Fig. 6.3 for the projection of  $f(x, y) = \sin(\pi x) \cos(\pi y)$  on  $Vh(Th, P0)$  when the mesh  $Th$  is a  $4 \times 4$ -grid of  $[-1, 1]^2$  as in Fig. 6.2.

### 6.3.2 P1-element


For each vertex  $q^i$ , the basis function  $\phi_i$  in  $Vh(Th, P1)$  is given by

$$\begin{aligned} \phi_i(x, y) &= a_i^k + b_i^k x + c_i^k y \text{ for } (x, y) \in T_k, \\ \phi_i(q^i) &= 1, \quad \phi_i(q^j) = 0 \text{ if } i \neq j \end{aligned}$$

The basis function  $\phi_{k_1}(x, y)$  with the vertex  $q^{k_1}$  in Fig. 6.1(a) at point  $p = (x, y)$  in triangle  $T_k$  simply coincide with the *barycentric coordinates*  $\lambda_1^k$  (*area coordinates*):

$$\phi_{k_1}(x, y) = \lambda_1^k(x, y) = \frac{\text{area of triangle}(p, q^{k_2}, q^{k_3})}{\text{area of triangle}(q^{k_1}, q^{k_2}, q^{k_3})}$$

If we write



Figure 6.1:  $P_1$  and  $P_2$  degrees of freedom on triangle  $T_k$ 

$\text{Vh}(\text{Th}, \mathbf{P1}); \text{Vh fh} = g(x, y);$

then

$$\text{fh} = f_h(x, y) = \sum_{i=1}^{n_v} f(q^i) \phi_i(x, y)$$

See Fig. 6.4 for the projection of  $f(x, y) = \sin(\pi x) \cos(\pi y)$  into  $\text{Vh}(\text{Th}, \mathbf{P1})$ .

Figure 6.2: Test mesh  $\text{Th}$  for projectionFigure 6.3: projection to  $\text{Vh}(\text{Th}, \mathbf{P0})$ 

### 6.3.3 P2-element

For each vertex or midpoint  $q^i$ , the basis function  $\phi_i$  in  $\text{Vh}(\text{Th}, \mathbf{P2})$  is given by

$$\begin{aligned} \phi_i(x, y) &= a_i^k + b_i^k x + c_i^k y + d_i^k x^2 + e_i^k xy + f_i^k y^2 \text{ for } (x, y) \in T_k, \\ \phi_i(q^i) &= 1, \quad \phi_i(q^j) = 0 \text{ if } i \neq j \end{aligned}$$

The basis function  $\phi_{k_1}(x, y)$  with the vertex  $q^{k_1}$  in Fig. 6.1(b) is defined by the *barycentric coordinates*:

$$\phi_{k_1}(x, y) = \lambda_1^k(x, y)(2\lambda_1^k(x, y) - 1)$$

and for the midpoint  $q^{k_2}$

$$\phi_{k_2}(x, y) = 4\lambda_1^k(x, y)\lambda_4^k(x, y)$$

If we write

$V_h(\text{Th}, \mathbf{P2}); V_h \text{ fh} = f(x, y);$

then

$$\text{fh} = f_h(x, y) = \sum_{i=1}^M f(q^i) \phi_i(x, y) \quad (\text{summation over all vertex or midpoint})$$

See Fig. 6.5 for the projection of  $f(x, y) = \sin(\pi x) \cos(\pi y)$  into  $V_h(\text{Th}, \mathbf{P2})$ .




Figure 6.4: projection to  $V_h(\text{Th}, \mathbf{P1})$




Figure 6.5: projection to  $V_h(\text{Th}, \mathbf{P2})$

## 6.4 P1 Nonconforming Element

Refer to [23] for details; briefly, we now consider non-continuous approximations so we shall lose the property

$$w_h \in V_h \subset H^1(\Omega)$$

If we write

$V_h(\text{Th}, \mathbf{P1nc}); V_h \text{ fh} = f(x, y);$

then

$$\text{fh} = f_h(x, y) = \sum_{i=1}^{n_v} f(m^i) \phi_i(x, y) \quad (\text{summation over all midpoint})$$

Here the basis function  $\phi_i$  associated with the midpoint  $m^i = (q^{k_i} + q^{k_{i+1}})/2$  where  $q^{k_i}$  is the  $i$ -th point in  $T_k$ , and we assume that  $j + 1 = 0$  if  $j = 3$ :

$$\begin{aligned} \phi_i(x, y) &= a_i^k + b_i^k x + c_i^k y \text{ for } (x, y) \in T_k, \\ \phi_i(m^i) &= 1, \quad \phi_i(m^j) = 0 \text{ if } i \neq j \end{aligned}$$

Strictly speaking  $\partial \phi_i / \partial x$ ,  $\partial \phi_i / \partial y$  contain Dirac distribution  $\rho \delta_{\partial T_k}$ . The numerical calculations will automatically *ignore* them. In [23], there is a proof of the estimation

$$\left( \sum_{k=1}^{n_v} \int_{T_k} |\nabla w - \nabla w_h|^2 dx dy \right)^{1/2} = O(h)$$

The basis functions  $\phi_k$  have the following properties.

1. For the bilinear form  $a$  defined in (2.6) satisfy

$$a(\phi_i, \phi_i) > 0, \quad a(\phi_i, \phi_j) \leq 0 \quad \text{if } i \neq j$$

$$\sum_{k=1}^{n_y} a(\phi_i, \phi_k) \geq 0$$

2.  $f \geq 0 \Rightarrow u_h \geq 0$

3. If  $i \neq j$ , the basis function  $\phi_i$  and  $\phi_j$  are  $L^2$ -orthogonal:

$$\int_{\Omega} \phi_i \phi_j \, dx dy = 0 \quad \text{if } i \neq j$$

which is false for  $P_1$ -element.

See Fig. 6.6 for the projection of  $f(x, y) = \sin(\pi x) \cos(\pi y)$  into  $\text{Vh}(\text{Th}, \mathbf{P1nc})$ . See Fig. 6.6 for the projection of  $f(x, y) = \sin(\pi x) \cos(\pi y)$  into  $\text{Vh}(\text{Th}, \mathbf{P1nc})$ .




Figure 6.6: projection to  $\text{Vh}(\text{Th}, \mathbf{P1nc})$




Figure 6.7: projection to  $\text{Vh}(\text{Th}, \mathbf{P1b})$

## 6.5 Other FE-space

For each triangle  $T_k \in \mathcal{T}_h$ , let  $\lambda_{k_1}(x, y)$ ,  $\lambda_{k_2}(x, y)$ ,  $\lambda_{k_3}(x, y)$  be the area coordinate of the triangle (see Fig. 6.1), and put

$$\beta_k(x, y) = 27\lambda_{k_1}(x, y)\lambda_{k_2}(x, y)\lambda_{k_3}(x, y) \quad (6.12)$$

called *bubble* function on  $T_k$ . The bubble function has the feature:

1.  $\beta_k(x, y) = 0$  if  $(x, y) \in \partial T_k$ .
2.  $\beta_k(q^{k_b}) = 1$  where  $q^{k_b}$  is the barycenter  $\frac{q^{k_1} + q^{k_2} + q^{k_3}}{3}$ .

If we write

$\text{Vh}(\text{Th}, \mathbf{P1b})$ ;  $\text{Vh fh} = f(x, y)$ ;

then

$$\text{fh} = f_h(x, y) = \sum_{i=1}^{n_y} f(q^i) \phi_i(x, y) + \sum_{k=1}^{n_t} f(q^{k_b}) \beta_k(x, y)$$

See Fig. 6.7 for the projection of  $f(x, y) = \sin(\pi x) \cos(\pi y)$  into  $\text{Vh}(\text{Th}, \mathbf{P1b})$ .

## 6.6 Vector valued FE-function

Functions from  $\mathbb{R}^2$  to  $\mathbb{R}^N$  with  $N = 1$  is called scalar function and called *vector valued* when  $N > 1$ . When  $N = 2$

**fespace** Vh(Th, [P0, P1]) ;

make the space

$$V_h = \{\mathbf{w} = (w_1, w_2) \mid w_1 \in V_h(\mathcal{T}_h, P_0), w_2 \in V_h(\mathcal{T}_h, P_1)\}$$

### 6.6.1 Raviart-Thomas element

In the Raviart-Thomas finite element  $RT0_h$ , the degree of freedom are the fluxes across edges  $e$  of the mesh, where the flux of the function  $\mathbf{f} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$  is  $\int_e \mathbf{f} \cdot \mathbf{n}_e$ ,  $\mathbf{n}_e$  is the unit normal of edge  $e$ .

This implies a orientation of all the edges of the mesh, for example we can use the global numbering of the edge vertices and we just go from small to large numbers.

To compute the flux, we use a quadrature with one Gauss point, the middle point of the edge. Consider a triangle  $T_k$  with three vertices  $(\mathbf{a}, \mathbf{b}, \mathbf{c})$ . Let denote the vertices numbers by  $i_a, i_b, i_c$ , and define the three edge vectors  $\mathbf{e}^1, \mathbf{e}^2, \mathbf{e}^3$  by  $\text{sgn}(i_b - i_c)(\mathbf{b} - \mathbf{c})$ ,  $\text{sgn}(i_c - i_a)(\mathbf{c} - \mathbf{a})$ ,  $\text{sgn}(i_a - i_b)(\mathbf{a} - \mathbf{b})$ ,

We get three basis functions,

$$\phi_1^k = \frac{\text{sgn}(i_b - i_c)}{2|T_k|}(\mathbf{x} - \mathbf{a}), \quad \phi_2^k = \frac{\text{sgn}(i_c - i_a)}{2|T_k|}(\mathbf{x} - \mathbf{b}), \quad \phi_3^k = \frac{\text{sgn}(i_a - i_b)}{2|T_k|}(\mathbf{x} - \mathbf{c}), \quad (6.13)$$

where  $|T_k|$  is the area of the triangle  $T_k$ . If we write

Vh(Th, **RT0**) ; Vh [f1h, f2h]=[f1(x,y), f2(x,y)] ;

then

$$\mathbf{f}_h = \mathbf{f}_h(x, y) = \sum_{k=1}^{n_t} \sum_{l=1}^6 n_{i_l j_l} \mathbf{e}^{i_l} |f_{j_l}(m^{i_l})| \phi_{i_l j_l}$$

where  $n_{i_l j_l}$  is the  $j_l$ -th component of the normal vector  $\mathbf{n}_{i_l}$ ,

$$\{m_1, m_2, m_3\} = \left\{ \frac{\mathbf{b} + \mathbf{c}}{2}, \frac{\mathbf{a} + \mathbf{c}}{2}, \frac{\mathbf{b} + \mathbf{a}}{2} \right\}$$

and  $i_l = \{1, 1, 2, 2, 3, 3\}$ ,  $j_l = \{1, 2, 1, 2, 1, 2\}$  with the order of  $l$ .




Figure 6.8: normal vectors of each edge

**Example 6.1** `mesh` `Th=square(2,2);`

`fespace` `Xh(Th,P1);`

`fespace` `Vh(Th,RT0);`

`Xh` `uh,vh;`

`Vh` `[Uxh,Uyh];`

`[Uxh,Uyh] = [sin(x),cos(y)];`

`vh= x^2+y^2;`

`Th = square(5,5);`

`uh = x^2+y^2;`

`Uxh = x;`

`vh = Uxh;`

`plot`(`uh,ps="onoldmesh.eps"`);

`uh = uh;`

`plot`(`uh,ps="onnewmesh.eps"`);

`vh([x-1/2,y])= x^2 + y^2;`

// ok vectorial FE function

// vh

// change the mesh

// Xh is unchange

// compute on the new Xh

// error: impossible to set only 1 component

// of a vector FE function.

// ok

// and now uh use the 5x5 mesh

// but the fespace of vh is always the 2x2 mesh

// figure 6.9

// do a interpolation of vh (old) of 5x5 mesh

// to get the new vh on 10x10 mesh.

// figure 6.10

// interpolate  $vh = ((x - 1/2)^2 + y^2)$




Figure 6.9:  $vh$  Iso on mesh  $2 \times 2$




Figure 6.10:  $vh$  Iso on mesh  $5 \times 5$

To get the value at a point  $x = 1, y = 2$  of the FE function `uh`, or `[Uxh,Uyh]`, one writes

`real` `value;`

`value = uh(2,4);`

`value = Uxh(2,4);`

// get value= uh(2,4)

// get value= Uxh(2,4)

// ----- or -----

`x=1;y=2;`

`value = uh;`

`value = Uxh;`

`value = Uyh;`

// get value= uh(1,2)

// get value= Uxh(1,2)

// get value= Uyh(1,2).

To get the value of the array associated to the FE function `uh`, one writes



```

real value = uh[][0] ;           // get the value of degree of freedom 0
real maxdf = uh[].max;           // maximum value of degree of freedom
int size = uh.n;                 // the number of degree of freedom
real[int] array(uh.n)= uh[];     // copy the array of the function uh

```

**Note 6.2** For a none scalar finite element function  $[U_{xh}, U_{yh}]$  the two array  $U_{xh}[]$  and  $U_{yh}[]$  are the same array, because the degree of freedom can touch more than one component.

## 6.7 A Fast Finite Element Interpolator

In practice one may discretize the variational equations by the Finite Element method. Then there will be one mesh for  $\Omega_1$  and another one for  $\Omega_2$ . The computation of integrals of products of functions defined on different meshes is difficult. Quadrature formulae and interpolations from one mesh to another at quadrature points are needed. We present below the interpolation operator which we have used and which is new, to the best of our knowledge. Let  $\mathcal{T}_h^0 = \cup_k T_k^0, \mathcal{T}_h^1 = \cup_k T_k^1$  be two triangulations of a domain  $\Omega$ . Let

$$V(\mathcal{T}_h^i) = \{C^0(\Omega_h^i) : f|_{T_k^i} \in P_0\}, \quad i = 0, 1$$

be the spaces of continuous piecewise affine functions on each triangulation.

Let  $f \in V(\mathcal{T}_h^0)$ . The problem is to find  $g \in V(\mathcal{T}_h^1)$  such that

$$g(q) = f(q) \quad \forall q \text{ vertex of } \mathcal{T}_h^1$$

Although this is a seemingly simple problem, it is difficult to find an efficient algorithm in practice. We propose an algorithm which is of complexity  $N^1 \log N^0$ , where  $N^i$  is the number of vertices of  $\mathcal{T}_h^i$ , and which is very fast for most practical 2D applications.

### Algorithm

The method has 5 steps. First a quadtree is built containing all the vertices of mesh  $\mathcal{T}_h^0$  such that in each terminal cell there are at least one, and at most 4, vertices of  $\mathcal{T}_h^0$ .

For each  $q^1$ , vertex of  $\mathcal{T}_h^1$  do:

**Step 1** Find the terminal cell of the quadtree containing  $q^1$ .

**Step 2** Find the nearest vertex  $q_j^0$  to  $q^1$  in that cell.

**Step 3** Choose one triangle  $T_k^0 \in \mathcal{T}_h^0$  which has  $q_j^0$  for vertex.

**Step 4** Compute the barycentric coordinates  $\{\lambda_j\}_{j=1,2,3}$  of  $q^1$  in  $T_k^0$ .

- – if all barycentric coordinates are positive, go to Step 5
- – else if one barycentric coordinate  $\lambda_i$  is negative replace  $T_k^0$  by the adjacent triangle opposite  $q_i^0$  and go to Step 4.
- – else two barycentric coordinates are negative so take one of the two randomly and replace  $T_k^0$  by the adjacent triangle as above.




Figure 6.11: To interpolate a function at  $q^0$  the knowledge of the triangle which contains  $q^0$  is needed. The algorithm may start at  $q^1 \in T_k^0$  and stall on the boundary (thick line) because the line  $q^0q^1$  is not inside  $\Omega$ . But if the holes are triangulated too (dotted line) then the problem does not arise.

**Step 5** Calculate  $g(q^1)$  on  $T_k^0$  by linear interpolation of  $f$ :

$$g(q^1) = \sum_{j=1,2,3} \lambda_j f(q_j^0)$$

**End**

Two problems need to be solved:

- What if  $q^1$  is not in  $\Omega_h^0$ ? Then Step 5 will stop with a boundary triangle. So we add a step which test the distance of  $q^1$  with the two adjacent boundary edges and select the nearest, and so on till the distance grows.
- What if  $\Omega_h^0$  is not convex and the marching process of Step 4 locks on a boundary? By construction Delaunay-Voronoi mesh generators always triangulate the convex hull of the vertices of the domain. So we make sure that this information is not lost when  $\mathcal{T}_h^0, \mathcal{T}_h^1$  are constructed and we keep the triangles which are outside the domain in a special list. Hence in step 5 we can use that list to step over holes if needed.

**Note 6.3** Step 3 requires an array of pointers such that each vertex points to one triangle of the triangulation.

**Note 6.4** The operator  $=$  is the interpolation operator of `FreeFem++`, The continuous finite functions are extended by continuity to the outside of the domain. Try the following example

```

mesh Ths= square(10,10);
mesh Thg= square(30,30,[x*3-1,y*3-1]);
plot(Ths,Thg,ps="overlapTh.eps",wait=1);
fespace Ch(Ths,P2); fespace Dh(Ths,P2dc);
fespace Fh(Thg,P2dc);
Ch us= (x-0.5)*(y-0.5);
Dh vs= (x-0.5)*(y-0.5);
Fh ug=us,vg=vs;
plot(us,ug,wait=1,ps="us-ug.eps"); // see figure 6.12
plot(vs,vg,wait=1,ps="vs-vg.eps"); // see figure 6.13

```




Figure 6.12: Extension of a continuous FE-function




Figure 6.13: Extension of discontinuous FE-function, see warning 6

## 6.8 Keywords: Problem and Solve

For FreeFem++ a problem must be given in variational form, so we need a bilinear form  $a(u, v)$ , a linear form  $\ell(f, v)$ , and possibly a boundary condition form must be added.

```
problem P(u,v) =
    a(u,v) - l(f,v)
    + (boundary condition);
```

**Note 6.5** When you want to formulate the problem and to solve it in the same time, you can use the keyword `solve`.

### 6.8.1 Weak form and Boundary Condition

To present the principles of Variational Formulations or also called weak forms for the PDEs, let us take a model problem : a Poisson equation with Dirichlet and Robin Boundary condition .

The problem is: Find  $u$  a real function defined on domain  $\Omega$  of  $\mathbb{R}^d$  ( $d = 2, 3$ ) such that

$$-\nabla \cdot (\kappa \nabla u) = f, \quad \text{in } \Omega, \quad au + \kappa \frac{\partial u}{\partial n} = b \quad \text{on } \Gamma_r, \quad u = g \quad \text{on } \Gamma_d \quad (6.14)$$

where

- if  $d = 2$  then  $\nabla \cdot (\kappa \nabla u) = \partial_x(\kappa \partial_x u) + \partial_y(\kappa \partial_y u)$  with  $\partial_x u = \frac{\partial u}{\partial x}$  and  $\partial_y u = \frac{\partial u}{\partial y}$
- if  $d = 3$  then  $\nabla \cdot (\kappa \nabla u) = \partial_x(\kappa \partial_x u) + \partial_y(\kappa \partial_y u) + \partial_z(\kappa \partial_z u)$  with  $\partial_x u = \frac{\partial u}{\partial x}$ ,  $\partial_y u = \frac{\partial u}{\partial y}$  and  $\partial_z u = \frac{\partial u}{\partial z}$
- the border  $\Gamma = \partial\Omega$  is split in  $\Gamma_d$  and  $\Gamma_n$  such that  $\Gamma_d \cup \Gamma_n = \emptyset$  and  $\Gamma_d \cap \Gamma_n = \partial\Omega$ ,
- $\kappa$  is a given positive function, such that  $\exists \kappa_0 \in \mathbb{R}, \quad 0 < \kappa_0 \leq \kappa$ .
- $a$  a given non negative function,

- $b$  a given function.

**Note 6.6** This is the well known Neumann boundary condition if  $a = 0$ , and if  $\Gamma_d$  is empty. In this case the function appears in the problem just by its derivatives, so it is defined only up to a constant (if  $u$  is a solution then  $u + c$  is also a solution).

Let  $v$  a regular test function null on  $\Gamma_d$ , by integration by parts we get

$$-\int_{\Omega} \nabla \cdot (\kappa \nabla u) v \, d\omega = \int_{\Omega} \kappa \nabla v \cdot \nabla u \, d\omega = \int_{\Omega} f v \, d\omega - \int_{\Gamma} v \kappa \frac{\partial u}{\partial \mathbf{n}} \, d\gamma, \quad (6.15)$$

where if  $d = 2$  the  $\nabla v \cdot \nabla u = (\frac{\partial u}{\partial x} \frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \frac{\partial v}{\partial y})$ , where if  $d = 3$  the  $\nabla v \cdot \nabla u = (\frac{\partial u}{\partial x} \frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \frac{\partial v}{\partial y} + \frac{\partial u}{\partial z} \frac{\partial v}{\partial z})$ , and where  $\mathbf{n}$  is the unitary outside normal of  $\partial\Omega$ .

Now we note that  $\kappa \frac{\partial u}{\partial \mathbf{n}} = -au + g$  on  $\Gamma_r$  and  $v = 0$  on  $\Gamma_d$  and  $\partial\Omega = \Gamma_d \cup \Gamma_n$  thus

$$-\int_{\partial\Omega} v \kappa \frac{\partial u}{\partial \mathbf{n}} = \int_{\Gamma_r} auv - \int_{\Gamma_r} bv$$

The problem becomes:

Find  $u \in V_g = \{v \in H^1(\Omega) / v = g \text{ on } \Gamma_d\}$  such that

$$\int_{\Omega} \kappa \nabla v \cdot \nabla u \, d\omega + \int_{\Gamma_r} auv \, d\gamma = \int_{\Omega} f v \, d\omega + \int_{\Gamma_r} bv \, d\gamma, \quad \forall v \in V_0 \quad (6.16)$$

where  $V_0 = \{v \in H^1(\Omega) / v = 0 \text{ on } \Gamma_d\}$

Except in the case of Neumann conditions everywhere, the problem (6.16) is well posed when  $\kappa \geq \kappa_0 > 0$ .

**Note 6.7** If we have only Neumann boundary condition, linear algebra tells us that the right hand side must be orthogonal to the kernel of the operator for the solution to exist. One way of writing the compatibility condition is:

$$\int_{\Omega} f \, d\omega + \int_{\Gamma} b \, d\gamma = 0$$

and a way to fix the constant is to solve for  $u \in H^1(\Omega)$  such that:

$$\int_{\Omega} \varepsilon uv \, d\omega + \int_{\Omega} \kappa \nabla v \cdot \nabla u \, d\omega = \int_{\Omega} f v \, d\omega + \int_{\Gamma_r} bv \, d\gamma, \quad \forall v \in H^1(\Omega) \quad (6.17)$$

where  $\varepsilon$  is a small parameter ( $\sim 10^{-10}$ ).

Remark that if the solution is of order  $\frac{1}{\varepsilon}$  then the compatibility condition is unsatisfied, otherwise we get the solution such that  $\int_{\Omega} u = 0$ , you can also add a Lagrange multiplier to solve the real mathematical problem like in the `examples++-tutorial/Laplace-lagrange-mult.edp` example.

In FreeFem++, the bidimensional problem (6.16) becomes

```

problem Pw(u,v) =
  int2d(Th)( kappa*( dx(u)*dx(u) + dy(u)*dy(u)) ) //   \int_{\Omega} \kappa \nabla v \cdot \nabla u \, d\omega
+ int1d(Th,gn)( a * u*v ) //   \int_{\Gamma_r} auv \, d\gamma
- int2d(Th)( f*v ) //   \int_{\Omega} f v \, d\omega
- int1d(Th,gn)( b * v ) //   \int_{\Gamma_r} bv \, d\gamma
+ on(gd)(u= g) ; //   u = g on \Gamma_d

```

where Th is a mesh of the the bidimensional domain  $\Omega$ , and gd and gn are respectively the boundary label of boundary  $\Gamma_d$  and  $\Gamma_n$ .

And the the three dimensional problem (6.16) becomes

```

macro Grad(u) [dx(u),dy(u),dz(u)] // EOM : definition of the 3d Grad macro
problem Pw(u,v) =
  int3d(Th)( kappa*( Grad(u)'*Grad(v) ) ) //  $\int_{\Omega} \kappa \nabla v \cdot \nabla u d\omega$ 
+ int2d(Th,gn)( a * u*v ) //  $\int_{\Gamma_f} a u v d\gamma$ 
- int3d(Th)( f*v ) //  $\int_{\Omega} f v d\omega$ 
- int2d(Th,gn)( b * v ) //  $\int_{\Gamma_f} b v d\gamma$ 
+ on(gd)(u= g) ; //  $u = g \text{ on } \Gamma_d$ 

```

where Th is a mesh of the three dimensional domain  $\Omega$ , and gd and gn are respectively the boundary label of boundary  $\Gamma_d$  and  $\Gamma_n$ .

## 6.9 Parameters affecting solve and problem

The parameters are FE functions real or complex, the number  $n$  of parameters is even ( $n = 2 * k$ ), the  $k$  first function parameters are unknown, and the  $k$  last are test functions.

**Note 6.8** *If the functions are a part of vectoriel FE then you must give all the functions of the vectorial FE in the same order (see laplaceMixte problem for example).*

**Note 6.9** *Don't mix complex and real parameters FE function.*

**Bug: 1** *The mixing of fespace with different periodic boundary condition is not implemented. So all the finite element spaces used for test or unknown functions in a problem, must have the same type of periodic boundary condition or no periodic boundary condition. No clean message is given and the result is unpredictable, Sorry.*

The parameters are:

**solver=** LU, CG, Crout,Cholesky,GMRES,sparsesolver, UMFPACK ...

The default solver is `sparsesolver` ( it is equal to UMFPACK if not other sparce solver is defined) or is set to LU if no direct sparse solver is available. The storage mode of the matrix of the underlying linear system depends on the type of solver chosen; for LU the matrix is sky-line non symmetric, for Crout the matrix is sky-line symmetric, for Cholesky the matrix is sky-line symmetric positive definite, for CG the matrix is sparse symmetric positive, and for GMRES, `sparsesolver` or UMFPACK the matrix is just sparse.

**eps=** a real expression.  $\varepsilon$  sets the stopping test for the iterative methods like CG. Note that if  $\varepsilon$  is negative then the stopping test is:

$$\|Ax - b\| < |\varepsilon|$$

if it is positive then the stopping test is

$$\|Ax - b\| < \frac{|\varepsilon|}{\|Ax_0 - b\|}$$

**init=** boolean expression, if it is false or 0 the matrix is reconstructed. Note that if the mesh changes the matrix is reconstructed too.

**precon=** name of a function (for example P) to set the preconditioner. The prototype for the function P must be

```
func real[int] P(real[int] & xx) ;
```

**tgval=** Huge value ( $10^{30}$ ) used to implement Dirichlet boundary conditions.

**tolpivot=** set the tolerance of the pivot in UMFPACK ( $10^{-1}$ ) and, LU, Crout, Cholesky factorisation ( $10^{-20}$ ).

**tolpivotsym=** set the tolerance of the pivot sym in UMFPACK

**strategy=** set the integer UMFPACK strategy (0 by default).

## 6.10 Problem definition

Below  $v$  is the unknown function and  $w$  is the test function.

After the "=" sign, one may find sums of:

- identifier(s); this is the name given earlier to the variational form(s) (type `varf`) for possible reuse.  
Remark, that the name in the "varf" of the unknown of test function is forgotten, we just used the order in argument list to recall name as in a C++ function, see note 6.14,
- the terms of the bilinear form itself: if  $K$  is a given function,

$$- \text{int3d}(\text{Th})(K*v*w) = \sum_{T \in \text{Th}} \int_T K v w$$

$$- \text{int3d}(\text{Th},1)(K*v*w) = \sum_{T \in \text{Th}, T \subset \Omega_1} \int_T K v w$$

$$- \text{int2d}(\text{Th})(K*v*w) = \sum_{T \in \text{Th}} \int_T K v w$$

$$- \text{int2d}(\text{Th},1)(K*v*w) = \sum_{T \in \text{Th}, T \subset \Omega_1} \int_T K v w$$

$$- \text{int1d}(\text{Th},2,5)(K*v*w) = \sum_{T \in \text{Th}} \int_{(\partial T \cup \Gamma) \cap (\Gamma_2 \cup \Gamma_5)} K v w$$

$$- \text{intalldges}(\text{Th})(K*v*w) = \sum_{T \in \text{Th}} \int_{\partial T} K v w$$

$$- \text{intalldges}(\text{Th},1)(K*v*w) = \sum_{T \in \text{Th}, T \subset \Omega_1} \int_{\partial T} K v w$$

- they contribute to the sparse matrix of type `matrix` which, whether declared explicitly or not is constructed by `FreeFem++`.

- the right handside of the PDE, volumic terms of the linear form: for given functions  $K, f$ :

$$- \text{int3d}(\text{Th})(K*w) = \sum_{T \in \text{Th}} \int_T K w$$

- $\text{int2d}(\text{Th})(K^*w) = \sum_{T \in \text{Th}} \int_T K w$
- $\text{int1d}(\text{Th}, 2, 5)(K^*w) = \sum_{T \in \text{Th}} \int_{(\partial T \cup \Gamma) \cap (\Gamma_2 \cup \Gamma_5)} K w$
- $\text{intalldges}(\text{Th})(f^*w) = \sum_{T \in \text{Th}} \int_{\partial T} f w$
- a vector of type `real[int]`

- The boundary condition terms :

- An "on" scalar form (for Dirichlet) : `on(1, u = g)`

The meaning is for all degree of freedom  $i$  of the boundary referred by "1", the diagonal term of the matrix  $a_{ii} = \text{tgv}$  with the *terrible geant value* `tgv` ( $=10^{30}$  by default) and the right hand side  $b[i] = "(\Pi_h g)[i]" \times \text{tgv}$ , where the  $"(\Pi_h g)[i]"$  is the boundary node value given by the interpolation of  $g$ .

- An "on" vectorial form (for Dirichlet) : `on(1, u1=g1, u2=g2)` If you have vectorial finite element like `RT0`, the 2 components are coupled, and so you have :  $b[i] = "(\Pi_h(g1, g2))[i]" \times \text{tgv}$ , where  $\Pi_h$  is the vectorial finite element interpolant.
- a linear form on  $\Gamma$  (for Neumann in 2d) `-int1d(Th))(f^*w)` or `-int1d(Th, 3))(f^*w)`
- a bilinear form on  $\Gamma$  or  $\Gamma_2$  (for Robin in 2d) `int1d(Th))(K^*v^*w)` or `int1d(Th, 2))(K^*v^*w)`.
- a linear form on  $\Gamma$  (for Neumann in 3d) `-int2d(Th))(f^*w)` or `-int2d(Th, 3))(f^*w)`
- a bilinear form on  $\Gamma$  or  $\Gamma_2$  (for Robin in 3d) `int2d(Th))(K^*v^*w)` or `int2d(Th, 2))(K^*v^*w)`.

#### Note 6.10

- If needed, the different kind of terms in the sum can appear more than once.
- the integral mesh and the mesh associated to test function or unknown function can be different in the case of linear form.
- $N.x$ ,  $N.y$  and  $N.z$  are the normal's components.

**Important:** it is not possible to write in the same integral the linear part and the bilinear part such as in `int1d(Th)(K^*v^*w - f^*w)`.

## 6.11 Numerical Integration

Let  $D$  be a  $N$ -dimensional bounded domain. For an arbitrary polynomial  $f$  of degree  $r$ , if we can find particular (quadrature) points  $\xi_j$ ,  $j = 1, \dots, J$  in  $D$  and (quadrature) constants  $\omega_j$  such that

$$\int_D f(x) = \sum_{\ell=1}^L c_\ell f(\xi_\ell) \quad (6.18)$$

then we have an error estimate (see Crouzeix-Mignot (1984)), and then there exists a constant  $C > 0$  such that,

$$\left| \int_D f(\mathbf{x}) - \sum_{\ell=1}^L \omega_\ell f(\xi_\ell) \right| \leq C|D|h^{r+1} \quad (6.19)$$

for any function  $r + 1$  times continuously differentiable  $f$  in  $D$ , where  $h$  is the diameter of  $D$  and  $|D|$  its measure (a point in the segment  $[q^i q^j]$  is given as

$$\{(x, y) | x = (1-t)q_x^i + tq_x^j, y = (1-t)q_y^i + tq_y^j, 0 \leq t \leq 1\}.$$

For a domain  $\Omega_h = \sum_{k=1}^{n_t} T_k$ ,  $\mathcal{T}_h = \{T_k\}$ , we can calculate the integral over  $\Gamma_h = \partial\Omega_h$  by

$$\begin{aligned} \int_{\Gamma_h} f(\mathbf{x}) ds &= \text{int1d}(\text{Th})(f) \\ &= \text{int1d}(\text{Th}, \text{qfe}=\text{*})(f) \\ &= \text{int1d}(\text{Th}, \text{qforder}=\text{*})(f) \end{aligned}$$

where \* stands for the name of the quadrature formula or the precision (order) of the Gauss formula.

Quadrature formula on an edge					
$L$	(qfe=)	qforder=	point in $[q^i q^j](=t)$	$\omega_\ell$	exact on $P_k, k =$
1	qf1pE	2	1/2	$ q^i q^j $	1
2	qf2pE	3	$(1 \pm \sqrt{1/3})/2$	$ q^i q^j /2$	3
3	<b>qf3pE</b>	6	$(1 \pm \sqrt{3/5})/2$ 1/2	$(5/18) q^i q^j $ $(8/18) q^i q^j $	5
4	qf4pE	8	$(1 \pm \frac{\sqrt{525+70\sqrt{30}}}{35})/2$ . $(1 \pm \frac{\sqrt{525-70\sqrt{30}}}{35})/2$ .	$\frac{18-\sqrt{30}}{72} q^i q^j $ $\frac{18+\sqrt{30}}{72} q^i q^j $	7
5	qf5pE	10	$(1 \pm \frac{\sqrt{245+14\sqrt{70}}}{21})/2$ 1/2 $(1 \pm \frac{\sqrt{245-14\sqrt{70}}}{21})/2$	$\frac{322-13\sqrt{70}}{1800} q^i q^j $ $\frac{64}{225} q^i q^j $ $\frac{322+13\sqrt{70}}{1800} q^i q^j $	9
2	qf1pElump	2	0 +1	$ q^i q^j /2$ $ q^i q^j /2$	1

where  $|q^i q^j|$  is the length of segment  $\overline{q^i q^j}$ . For a part  $\Gamma_1$  of  $\Gamma_h$  with the label “1”, we can calculate the integral over  $\Gamma_1$  by

$$\begin{aligned} \int_{\Gamma_1} f(x, y) ds &= \text{int1d}(\text{Th}, 1)(f) \\ &= \text{int1d}(\text{Th}, 1, \text{qfe}=\text{qf2pE})(f) \end{aligned}$$

The integrals over  $\Gamma_1, \Gamma_3$  are given by

$$\int_{\Gamma_1 \cup \Gamma_3} f(x, y) ds = \text{int1d}(\text{Th}, 1, 3)(f)$$

For each triangle  $T_k = [q^{k_1} q^{k_2} q^{k_3}]$ , the point  $P(x, y)$  in  $T_k$  is expressed by the *area coordinate* as  $P(\xi, \eta)$ :

$$\begin{aligned} |T_k| &= \frac{1}{2} \begin{vmatrix} 1 & q_x^{k_1} & q_y^{k_1} \\ 1 & q_x^{k_2} & q_y^{k_2} \\ 1 & q_x^{k_3} & q_y^{k_3} \end{vmatrix} & D_1 &= \begin{vmatrix} 1 & x & y \\ 1 & q_x^{k_2} & q_y^{k_2} \\ 1 & q_x^{k_3} & q_y^{k_3} \end{vmatrix} & D_2 &= \begin{vmatrix} 1 & q_x^{k_1} & q_y^{k_1} \\ 1 & x & y \\ 1 & q_x^{k_3} & q_y^{k_3} \end{vmatrix} & D_3 &= \begin{vmatrix} 1 & q_x^{k_1} & q_y^{k_1} \\ 1 & q_x^{k_2} & q_y^{k_2} \\ 1 & x & y \end{vmatrix} \\ \xi &= \frac{1}{2} D_1 / |T_k| & \eta &= \frac{1}{2} D_2 / |T_k| & \text{then } 1 - \xi - \eta &= \frac{1}{2} D_3 / |T_k| \end{aligned}$$



For a two dimensional domain or a border of three dimensional domain  $\Omega_h = \sum_{k=1}^{n_t} T_k$ ,  $\mathcal{T}_h = \{T_k\}$ , we can calculate the integral over  $\Omega_h$  by

$$\begin{aligned} \int_{\Omega_h} f(x, y) &= \text{int2d}(\text{Th})(f) \\ &= \text{int2d}(\text{Th}, \text{qft}=\text{*})(f) \\ &= \text{int2d}(\text{Th}, \text{qforder}=\text{*})(f) \end{aligned}$$

where \* stands for the name of quadrature formula or the order of the Gauss formula.

Quadrature formula on a triangle					
$L$	qft=	qforder=	point in $T_k$	$\omega_\ell$	exact on $P_k, k =$
1	qf1pT	2	$\left(\frac{1}{3}, \frac{1}{3}\right)$	$ T_k $	1
3	qf2pT	3	$\left(\frac{1}{2}, \frac{1}{2}\right)$ $\left(\frac{1}{2}, 0\right)$ $\left(0, \frac{1}{2}\right)$	$ T_k /3$ $ T_k /3$ $ T_k /3$	2
7	<b>qf5pT</b>	6	$\left(\frac{1}{3}, \frac{1}{3}\right)$ $\left(\frac{6-\sqrt{15}}{21}, \frac{6-\sqrt{15}}{21}\right)$ $\left(\frac{6-\sqrt{15}}{21}, \frac{9+2\sqrt{15}}{21}\right)$ $\left(\frac{9+2\sqrt{15}}{21}, \frac{6-\sqrt{15}}{21}\right)$ $\left(\frac{6+\sqrt{15}}{21}, \frac{6+\sqrt{15}}{21}\right)$ $\left(\frac{6+\sqrt{15}}{21}, \frac{9-2\sqrt{15}}{21}\right)$ $\left(\frac{9-2\sqrt{15}}{21}, \frac{6+\sqrt{15}}{21}\right)$	$0.225 T_k $ $\frac{(155-\sqrt{15}) T_k }{1200}$ $\frac{(155-\sqrt{15}) T_k }{1200}$ $\frac{(155-\sqrt{15}) T_k }{1200}$ $\frac{(155+\sqrt{15}) T_k }{1200}$ $\frac{(155+\sqrt{15}) T_k }{1200}$ $\frac{(155+\sqrt{15}) T_k }{1200}$	5
3	qf1pTlump		$(0, 0)$ $(1, 0)$ $(0, 1)$	$ T_k /3$ $ T_k /3$ $ T_k /3$	1
9	qf2pT4P1		$\left(\frac{1}{4}, \frac{3}{4}\right)$ $\left(\frac{3}{4}, \frac{1}{4}\right)$ $\left(0, \frac{1}{4}\right)$ $\left(0, \frac{3}{4}\right)$ $\left(\frac{1}{4}, 0\right)$ $\left(\frac{3}{4}, 0\right)$ $\left(\frac{1}{4}, \frac{1}{4}\right)$ $\left(\frac{1}{4}, \frac{1}{2}\right)$ $\left(\frac{1}{2}, \frac{1}{4}\right)$	$ T_k /12$ $ T_k /12$ $ T_k /12$ $ T_k /12$ $ T_k /12$ $ T_k /12$ $ T_k /6$ $ T_k /6$ $ T_k /6$	1
15	qf7pT	8	see [38] for detail		7
21	qf9pT	10	see [38] for detail		9

For a three dimensional domain  $\Omega_h = \sum_{k=1}^{n_t} T_k$ ,  $\mathcal{T}_h = \{T_k\}$ , we can calculate the integral over  $\Omega_h$  by

$$\begin{aligned} \int_{\Omega_h} f(x, y) &= \text{int3d}(\text{Th})(f) \\ &= \text{int3d}(\text{Th}, \text{qfV}=\text{*})(f) \\ &= \text{int3d}(\text{Th}, \text{qforder}=\text{*})(f) \end{aligned}$$

where \* stands for the name of quadrature formula or the order of the Gauss formula.

Quadrature formula on a tetraedron					
$L$	qfV=	qforder=	point in $T_k \in \mathbb{R}^3$	$\omega_\ell$	exact on $P_k, k =$
1	qfV1	2	$\left(\frac{1}{4}, \frac{1}{4}, \frac{1}{4}\right)$	$ T_k $	1
4	qfV2	3	$G4(0.58\dots, 0.13\dots, 0.13\dots)$	$ T_k /4$	2
14	<b>qfV5</b>	6	$G4(0.72\dots, 0.092\dots, 0.092\dots)$ $G4(0.067\dots, 0.31\dots, 0.31\dots)$ $G6(0.45\dots, 0.045\dots, 0.45\dots)$	$0.073\dots T_k $ $0.11\dots T_k $ $0.042\dots T_k $	5
4	qfV1lump		$G4(1, 0, 0)$	$ T_k /4$	1

Where  $G4(a, b, b)$  such that  $a + 3b = 1$  is the set of the four point in barycentric coordinate

$$\{(a, b, b, b), (b, a, b, b), (b, b, a, b), (b, b, b, a)\}$$

and where  $G6(a, b, b)$  such that  $2a + 2b = 1$  is the set of the six points in barycentric coordinate

$$\{(a, a, b, b), (a, b, a, b), (a, b, b, a), (b, b, a, a), (b, a, b, a), (b, a, a, b)\}.$$

**Note 6.11** These tetraedral quadrature formulae come from <http://www.cs.kuleuven.be/~nines/research/ecf/mtables.html>

**Note 6.12** By default, we use the formula which is exact for polynomials of degree 5 on triangles or edges (in bold in three tables).

## 6.12 Variational Form, Sparse Matrix, PDE Data Vector

In FreeFem++ it is possible to define variational forms, and use them to build matrices and vectors and store them to speed-up the script (4 times faster here).

For example let us solve the Thermal Conduction problem of section 3.4.

The variational formulation is in  $L^2(0, T; H^1(\Omega))$ ; we shall seek  $u^n$  satisfying

$$\forall w \in V_0; \quad \int_{\Omega} \frac{u^n - u^{n-1}}{\delta t} w + \kappa \nabla u^n \nabla w + \int_{\Gamma} \alpha (u^n - u_{ue}) w = 0$$

where  $V_0 = \{w \in H^1(\Omega) / w|_{\Gamma_{24}} = 0\}$ .

So the to code the method with the matrices  $A = (A_{ij})$ ,  $M = (M_{ij})$ , and the vectors  $u^n, b^n, b', b'', b_{cl}$  ( notation if  $w$  is a vector then  $w_i$  is a component of the vector).

$$u^n = A^{-1} b^n, \quad b' = b_0 + M u^{n-1}, \quad b'' = \frac{1}{\varepsilon} b_{cl}, \quad b_i^n = \begin{cases} b''_i & \text{if } i \in \Gamma_{24} \\ b'_i & \text{else if } i \notin \Gamma_{24} \end{cases} \quad (6.20)$$

Where with  $\frac{1}{\varepsilon} = \text{tgv} = 10^{30}$  :

$$A_{ij} = \begin{cases} \frac{1}{\varepsilon} & \text{if } i \in \Gamma_{24}, \text{ and } j = i \\ \int_{\Omega} w_j w_i / dt + k(\nabla w_j \cdot \nabla w_i) + \int_{\Gamma_{13}} \alpha w_j w_i & \text{else if } i \notin \Gamma_{24}, \text{ or } j \neq i \end{cases} \quad (6.21)$$

$$M_{ij} = \begin{cases} \frac{1}{\varepsilon} & \text{if } i \in \Gamma_{24}, \text{ and } j = i \\ \int_{\Omega} w_j w_i / dt & \text{else if } i \notin \Gamma_{24}, \text{ or } j \neq i \end{cases} \quad (6.22)$$

$$b_{0,i} = \int_{\Gamma_{13}} \alpha u_{ue} w_i \quad (6.23)$$

$$b_{cl} = u^0 \quad \text{the initial data} \quad (6.24)$$

```

// file thermal-fast.edp in examples++-tutorial

func fu0 = 10+90*x/6;
func k = 1.8*(y<0.5)+0.2;
real ue = 25. , alpha=0.25, T=5, dt=0.1 ;

mesh Th=square(30,5,[6*x,y]);
fespace Vh(Th,P1);

Vh u0=fu0,u=u0;

Create three variational formulation, and build the matrices A,M.

varf vthermic (u,v)= int2d(Th)(u*v/dt + k*(dx(u) * dx(v) + dy(u) * dy(v)))
+ int1d(Th,1,3)(alpha*u*v) + on(2,4,u=1);

varf vthermic0(u,v) = int1d(Th,1,3)(alpha*ue*v);

varf vMass (u,v)= int2d(Th)( u*v/dt) + on(2,4,u=1);

real tgv = 1e30;
matrix A= vthermic(Vh,Vh,tgv=tgv,solver=CG);
matrix M= vMass(Vh,Vh);

```

Now, to build the right hand size we need 4 vectors.

```

real[int] b0 = vthermic0(0,Vh);
real[int] bcn = vthermic(0,Vh);
real[int] bcl=tgv*u0[];

// constant part of the RHS
// tgv on Dirichlet boundary node ( !=0 )
// we have for the node i :  $i \in \Gamma_{24} \Leftrightarrow bcn[i] \neq 0$ 
// the Dirichlet boundary condition part

```

**Note 6.13** The boundary condition is implemented by penalization and vector `bcn` contains the contribution of the boundary condition  $u=1$ , so to change the boundary condition, we have just to multiply the vector `bc[]` by the current value  $f$  of the new boundary condition term by term with the operator `.*`. Section 9.6.2 *Examples++-tutorial/StokesUzawa.edp* gives a real example of using all this features.

And the new version of the algorithm is now:

```

ofstream ff("thermic.dat");
for(real t=0;t<T;t+=dt){
  real[int] b = b0 ;
  b += M*u[];
  b = bcn ? bcl : b ;
  u[] = A^-1*b;
  ff << t << " "<<u(3,0.5)<<endl;
  plot(u);
}
for(int i=0;i<20;i++)
  cout<<dy(u)(6.0*i/20.0,0.9)<<endl;
plot(u,fill=true,wait=1,ps="thermic.eps");

```

**Note 6.14** The functions appearing in the variational form are formal and local to the `varf` definition, the only important thing is the order in the parameter list, like in

```
varf vb1([u1,u2],q) = int2d(Th)( (dy(u1)+dy(u2)) *q) + int2d(Th)(1*q);
varf vb2([v1,v2],p) = int2d(Th)( (dy(v1)+dy(v2)) *p) + int2d(Th)(1*p);
```

To build matrix  $A$  from the bilinear part the variational form  $a$  of type `varf` simply write:

```
A = a(Vh,Wh [, ...] );
// where
// Vh is "fespace" for the unknow fields with a correct number of component
// Wh is "fespace" for the test fields with a correct number of component
```

Possible named parameters in " `[, ... ]`" are

**solver=** LU, CG, Crout, Cholesky, GMRES, sparsesolver, UMFPACK ...

The default solver is GMRES. The storage mode of the matrix of the underlying linear system depends on the type of solver chosen; for LU the matrix is sky-line non symmetric, for Crout the matrix is sky-line symmetric, for Cholesky the matrix is sky-line symmetric positive definite, for CG the matrix is sparse symmetric positive, and for GMRES, sparsesolver or UMFPACK the matrix is just sparse.

**factorize =** if true then do the matrix factorization for LU, Cholesky or Crout, the default value is *false*.

**eps=** a real expression.  $\varepsilon$  sets the stopping test for the iterative methods like CG. Note that if  $\varepsilon$  is negative then the stopping test is:

$$\|Ax - b\| < |\varepsilon|$$

if it is positive then the stopping test is

$$\|Ax - b\| < \frac{|\varepsilon|}{\|Ax_0 - b\|}$$

**precon=** name of a function (for example P) to set the preconditioner. The prototype for the function P must be

```
func real[int] P(real[int] & xx) ;
```

**tg=** Huge value ( $10^{30}$ ) used to implement Dirichlet boundary conditions.

**tolpivot=** set the tolerance of the pivot in UMFPACK ( $10^{-1}$ ) and, LU, Crout, Cholesky factorisation ( $10^{-20}$ ).

**tolpivotsym=** set the tolerance of the pivot sym in UMFPACK

**strategy=** set the integer UMFPACK strategy (0 by default).

**Note 6.15** The line of the matrix corresponding to the space `Wh` and the column of the matrix corresponding to the space `Vh`.

To build the dual vector  $b$  (of type `real[int]`) from the linear part of the variational form  $a$  do simply

```
real b(Vh.ndof);
b = a(0,Vh);
```

A first example to compute the area of each triangle  $K$  of mesh  $Th$ , just do:

```
fespace Nh(Th,P0); // the space function contant / triangle
Nh areaK;
varf varea(unused,chiK) = int2d(Th)(chiK);
etaK[] = varea(0,Ph);
```

Effectively, the basic functions of space  $Nh$ , are the characteristic function of the element of  $Th$ , and the numbering is the numeration of the element, so by construction:

$$\text{etaK}[i] = \int 1_{|K_i} = \int_{K_i} 1;$$

Now, we can use this to compute error indicators like in examples `AdaptResidualErrorIndicator.edp` in directory `examples++-tutorial`.

First to compute a continuous approximation to the function  $h$  "density mesh size" of the mesh  $Th$ .

```
fespace Vh(Th,P1);
Vh h ;
real[int] count(Th.nv);
varf vmeshsizen(u,v)=intalldges(Th,qfnpE=1)(v);
varf vedgecount(u,v)=intalldges(Th,qfnpE=1)(v/lenEdge);
// computation of the mesh size
// -----
count=vedgecount(0,Vh); // number of edge / vertex
h[] = vmeshsizen(0,Vh); // sum length edge / vertex
h[] = h[] ./ count; // mean lenght edge / vertex
```

To compute error indicator for Poisson equation :

$$\eta_K = \int_K h_K^2 |(f + \Delta u_h)|^2 + \int_{\partial K} h_e \left| \frac{\partial u_h}{\partial n} \right|^2$$

where  $h_K$  is size of the longest edge ( `hTriangle`),  $h_e$  is the size of the current edge ( `lenEdge`),  $n$  the normal.

```
fespace Nh(Th,P0); // the space function contant / triangle
Nh etak;
varf vetaK(unused,chiK) =
  intalldges(Th)(chiK*lenEdge*square(jump(N.x*dx(u)+N.y*dy(u))))
  +int2d(Th)(chiK*square(hTriangle*(f+dxx(u)+dyy(u))) );

etak[] = vetaK(0,Ph);
```

We add automatic expression optimization by default, if this optimization creates problems, it can be removed with the keyword `optimize` as in the following example :

```
varf a(u1,u2)= int2d(Th,optimize=false)( dx(u1)*dx(u2) + dy(u1)*dy(u2) )
+ on(1,2,4,u1=0) + on(3,u1=1) ;
```

Remark, it is all possible to build interpolation matrix, like in the following example:

```

mesh TH = square(3,4);
mesh th = square(2,3);
mesh Th = square(4,4);

fespace VH(TH,P1);
fespace Vh(th,P1);
fespace Wh(Th,P1);

matrix B= interpolate(VH,Vh);           //   build interpolation matrix Vh->VH
matrix BB= interpolate(Wh,Vh);         //   build interpolation matrix Vh->Wh

```

and after some operations on sparse matrices are available for example

```

int N=10;
real [int,int] A(N,N);                  //   a full matrix
real [int] a(N),b(N);
A =0;
for (int i=0;i<N;i++)
{
    A(i,i)=1+i;
    if(i+1 < N)    A(i,i+1)=-i;
    a[i]=i;
}
b=A*b;
cout << "xxxx\n";
matrix sparseA=A;
cout << sparseA << endl;
sparseA = 2*sparseA+sparseA';
sparseA = 4*sparseA+sparseA*5;
matrix sparseB=sparseA+sparseA+sparseA; ;
cout << "sparseB = " << sparseB(0,0) << endl;

```

## 6.13 Interpolation matrix

It is also possible to store the matrix of a linear interpolation operator from a finite element space  $V_h$  to another  $W_h$  to `interpolate( $W_h, V_h, \dots$ )` a function. Note that the continuous finite functions are extended by continuity outside of the domain.

The named parameters of function `interpolate` are:

**inside=** set true to create zero-extension.

**t=** set true to get the transposed matrix

**op=** set an integer written below

- 0** the default value and interpolate of the function
- 1** interpolate the  $\partial_x$
- 2** interpolate the  $\partial_y$
- 3** interpolate the  $\partial_z$

**U2Vc**= set the which is the component of  $W_h$  come in  $V_h$  in interpolate process in a int array so the size of the array is number of component of  $W_h$ , if the put  $-1$  then component is set to 0, like in the following example: (by default the component number is unchanged).

```
fespace V4h(Th4,[P1,P1,P1,P1]);
fespace V3h(Th,[P1,P1,P1]);
int[int] u2vc=[1,3,-1]; // -1 => put zero on the component
matrix IV34= interpolate(V3h,V4h,inside=0,U2Vc=u2vc); // V3h <- V4h
V4h [a1,a2,a3,a4]=[1,2,3,4];
V3h [b1,b2,b3]=[10,20,30];
b1[]=IV34*a1[];
```

So here we have:  $b1 == 2$ ,  $b2 == 4$ ,  $b3 == 0$  ..

### Example 6.2 (mat\_interpol.edp)

```
mesh Th=square(4,4);
mesh Th4=square(2,2,[x*0.5,y*0.5]);
plot(Th,Th4,ps="ThTh4.eps",wait=1);
fespace Vh(Th,P1);      fespace Vh4(Th4,P1);
fespace Wh(Th,P0);      fespace Wh4(Th4,P0);

matrix IV= interpolate(Vh,Vh4); // here the function is
// extended by continuity

cout << " IV Vh<-Vh4 " << IV << endl;
Vh v, vv;      Vh4 v4=x*y;
v=v4;          vv[]= IV*v4[]; // here v == vv =>
real[int] diff= vv[] - v[];
cout << " || v - vv || = " << diff.linfty << endl;
assert( diff.linfty<= 1e-6);
matrix IV0= interpolate(Vh,Vh4,inside=1); // here the function is
// extended by zero

cout << " IV Vh<-Vh4 (inside=1) " << IV0 << endl;
matrix IVt0= interpolate(Vh,Vh4,inside=1,t=1);
cout << " IV Vh<-Vh4^t (inside=1) " << IVt0 << endl;
matrix IV4t0= interpolate(Vh4,Vh);
cout << " IV Vh4<-Vh^t " << IV4t0 << endl;
matrix IW4= interpolate(Wh4,Wh);
cout << " IV Wh4<-Wh " << IW4 << endl;
matrix IW4V= interpolate(Wh4,Vh);
cout << " IV Wh4<-Vh " << IW4 << endl;
```

## 6.14 Finite elements connectivity

Here, we show how to get informations on a finite element space  $W_h(\mathcal{T}_n, *)$ , where “\*” may be P1, P2, P1nc, etc.

- $Wh.nt$  gives the number of element of  $W_h$
- $Wh.ndof$  gives the number of degrees of freedom or unknown
- $Wh.ndofK$  gives the number of degrees of freedom on one element

- $Wh(k,i)$  gives the number of  $i$ th degrees of freedom of element  $k$ .

See the following example:

**Example 6.3 (FE.edp)** `mesh Th=square(5,5);`  
`fespace Wh(Th,P2);`  
`cout << " nb of degree of freedom : " << Wh.ndof << endl;`  
`cout << " nb of degree of freedom / ELEMENT : " << Wh.ndofK << endl;`  
`int k= 2, kdf= Wh.ndofK ;;` // element 2  
`cout << " df of element " << k << ":" ;`  
`for (int i=0;i<kdf;i++) cout << Wh(k,i) << " ";`  
`cout << endl;`

The output is:

```
Nb Of Nodes = 121
Nb of DF = 121
FESpace:Gibbs: old skyline = 5841 new skyline = 1377
nb of degree of freedom : 121
nb of degree of freedom / ELEMENT : 6
df of element 2:78 95 83 87 79 92
```



# Chapter 7

## Visualization

Results created by the finite element method can be a huge set of data, so it is very important to render them easy to grasp. There are two ways of visualization in FreeFem++ : One, the default view, supports the drawing of meshes, isovalues of real FE-functions and of vector fields, all by the command `plot` (see Section 7.1 below). For publishing purpose, FreeFem++ can store these plots as postscript files.

Another method is to use external tools, for example, gnuplot (see Section 7.2), medit (see Section 7.3) using the command `system` to launch them and/or to save the data in text files.

### 7.1 Plot

With the command `plot`, meshes, isovalues of scalar functions and vector fields can be displayed.

The parameters of the `plot` command can be , meshes, real FE functions , arrays of 2 real FE functions, arrays of two arrays of double, to plot respectively a mesh, a function, a vector field, or a curve defined by the two arrays of double.

**Note 7.1** *The length of an arrow is always bound to be in [5%, 5%] of the screen size, to see something (else it will only look like porcupine).*

The parameters are

**wait=** boolean expression to wait or not (by default no wait). If true we wait for a keyboard event or mouse event, they respond to an event by the following characters

- +** to zoom in around the mouse cursor,
- to zoom out around the mouse cursor,
- =** to restore de initial graphics state,
- c** to decrease the vector arrows size,
- C** to increase the vector arrows size,
- r** to refresh the graphic window,
- f** to toggle between color fills and isovalues,
- b** to toggle into black and white,
- g** to toggle to grey or color ,
- v** to toggle the display of isovalue scale,
- ?** to show all active keyboard char,

**enter** go to the next plot,  
**ESC** close the graphics process.  
**otherwise** do nothing.

**ps=** string expression for the name of the file to save the plot in postscript

**coef=** the vector arrow size between arrow unit and domain unit.

**fill=** do a color fill between isovalues.

**cmm=** string expression to write the graphic window into

**value=** to plot the value of isolines and the value of vector arrows.

**aspectratio=** boolean to be sure that the aspect ratio of plot is preserved or not.

**bb=** array of 2 array ( like `[[0.1,0.2],[0.5,0.6]]`), to set the bounding box and specify a partial view where the box defined by the two corner points `[0.1,0.2]` and `[0.5,0.6]`.

**nbiso=** (int) sets the number of isovalues (20 by default)

**nbarrow=** (int) sets the number of colors of arrow values (20 by default)

**viso=** sets the array of isovalues (an array `real[int]` of increasing values)

**varrow=** sets the array of color arrows values (an array `real[int]`)

**bw=** (bool) sets or not the plot in black and white color.

**grey=** (bool) sets or not the plot in grey color.

**hsv=** (array of float) to defined color of  $3 \times n$  value in HSV color model declared for example by

```
real[int] colors = [h1,s1,v1,... , hn,vn,vn];
```

where  $h_i, s_i, v_i$  is the  $i$ th color to defined the color table.

**boundary=** (bool) to plot or not the boundary of the domain (true by default).

**dim=** (int) sets dim of the plot 2d or 3d (2 by default)

For example:

```
real[int] xx(10),yy(10);
mesh Th=square(5,5);
fespace Vh(Th,P1);
Vh uh=x*x+y*y,vh=-y^2+x^2;
int i;

// compute a cut
for (i=0;i<10;i++)
{
  x=i/10.; y=i/10.;
  xx[i]=i;
  yy[i]=uh; // value of uh at point (i/10. , i/10.)
}
plot(Th,uh,[uh,vh],value=true,ps="three.eps",wait=true); // figure 7.1
```

```

// zoom on box defined by the two corner points [0.1,0.2] and [0.5,0.6]
plot(uh,[uh,vh],bb=[[0.1,0.2],[0.5,0.6]],
     wait=true,greyscale=1,fill=1,value=1,ps="threeg.eps");
plot([xx,yy],ps="likegnu.eps",wait=true);

```

// figure 7.2  
// figure 7.3




Figure 7.1: mesh, isovalue, and vector




Figure 7.2: enlargement in grey of isovalue, and vector




Figure 7.3: Plots a cut of uh. Note that a refinement of the same can be obtained in combination with gnuplot

To change the color table and to choose the value of iso line you can do :

```

// from: http://en.wikipedia.org/wiki/HSV_color_space
// The HSV (Hue, Saturation, Value) model,
// defines a color space in terms of three constituent components:
//
// HSV color space as a color wheel 7.4
// Hue, the color type (such as red, blue, or yellow):
// Ranges from 0-360 (but normalized to 0-100% in some applications Here)

```

```

// Saturation, the "vibrancy" of the color: Ranges from 0-100%
// The lower the saturation of a color, the more "grayness" is present
// and the more faded the color will appear.
// Value, the brightness of the color:
// Ranges from 0-100%
//
real[int] colorhsv=[
    4./6., 1 , 0.5,
    4./6., 1 , 1,
    5./6., 1 , 1,
    1, 1. , 1,
    1, 0.5 , 1
];
real[int] viso(31);

for (int i=0;i<viso.n;i++)
    viso[i]=i*0.1;

plot(uh,viso=viso(0:viso.n-1),value=1,fill=1,wait=1,hsv=colorhsv);

```




Figure 7.4: hsv color cylinder




Figure 7.5: isovalue with an other color table

## 7.2 link with gnuplot

Example 3.2 shows how to generate a gnu-plot from a FreeFem++ file. Let us present here another technique which has the advantage of being online, i.e. one doesn't need to quit FreeFem++ to generate a gnu-plot. But this work only if gnuplot<sup>1</sup> is installed, and only on unix computer.

Add to the previous example:

```
{
    ofstream gnu("plot.gp");
    for (int i=0;i<=n;i++)
    {
        gnu << xx[i] << " " << yy[i] << endl;
    }
}

// the file plot.gp is close because the variable gnu is delete

// to call gnuplot command and wait 5 second (thanks to unix command)
// and make postscript plot

exec("echo 'plot \"plot.gp\" w l \
pause 5 \
set term postscript \
set output \"gnuplot.eps\" \
replot \
quit' | gnuplot");
```




Figure 7.6: Plots a cut of uh with gnuplot

## 7.3 link with medit

As said above, medit<sup>2</sup> is a freeware display package by Pascal Frey using OpenGL. Then you may run the following example.

Remark: Now medit software is include in FreeFem++ under `ffmedit` name.  
Now with version 3.2 or better

```
load "medit"
mesh Th=square(10,10,[2*x-1,2*y-1]);
fespace Vh(Th,P1);
Vh u=2-x*x-y*y;
medit("mm",u);
```

<sup>1</sup><http://www.gnuplot.info/>

<sup>2</sup><http://www-rocq.inria.fr/gamma/medit/medit.html>




Figure 7.7: medit plot

Before:

```

mesh Th=square(10,10,[2*x-1,2*y-1]);
fespace Vh(Th,P1);
Vh u=2-x*x-y*y;
savemesh(Th,"mm",[x,y,u*.5]);                                     // save mm.points and mm.faces file
                                                                    // for medit
                                                                    // build a mm.bb file

{
  ofstream file("mm.bb");
  file << "2 1 1 " << u[].n << " 2 \n";
  for (int j=0;j<u[].n ; j++)
    file << u[][j] << endl;
}

                                                                    // call medit command
exec("ffmedit mm");

                                                                    // clean files on unix OS
exec("rm mm.bb      mm.faces  mm.points");

```

# Chapter 8

## Algorithms

The complete example is in `algo.edp` file.

### 8.1 conjugate Gradient/GMRES

Suppose we want to solve the Euler problem (here  $x$  has nothing to do with the reserved variable for the first coordinate in FreeFem++) : find  $x \in \mathbb{R}^n$  such that

$$\nabla J(x) = \left( \frac{\partial J}{\partial x_i}(x) \right) = 0 \quad (8.1)$$

where  $J$  is a functional (to minimize for example) from  $\mathbb{R}^n$  to  $\mathbb{R}$ .

If the function is convex we can use the conjugate gradient to solve the problem, and we just need the function (named `dJ` for example) which compute  $\nabla J$ , so the parameters are the name of that function with prototype

```
func real[int] dJ(real[int] & xx);
```

which compute  $\nabla J$ , and a vector `x` of type ( of course the number 20 can be changed)

```
real[int] x(20);
```

to initialize the process and get the result.

Given an initial value  $x^{(0)}$ , a maximum number  $i_{\max}$  of iterations, and an error tolerance  $0 < \epsilon < 1$ : Put  $x = x^{(0)}$  and write

```
NLCG( $\nabla J$ , x, precon= M, nbiter=  $i_{\max}$ , eps=  $\epsilon$ );
```

will give the solution of  $x$  of  $\nabla J(x) = 0$ . We can omit parameters `precon`, `nbiter`, `eps`. Here  $M$  is the preconditioner whose default is the identity matrix. The stopping test is

$$\|\nabla J(x)\|_P \leq \epsilon \|\nabla J(x^{(0)})\|_P$$

Writing the minus value in `eps=`, i.e.,

```
NLCG( $\nabla J$ , x, precon= M, nbiter=  $i_{\max}$ , eps=  $-\epsilon$ );
```

we can use the stopping test

$$\|\nabla J(x)\|_P^2 \leq \epsilon$$

The parameters of these three functions are:

**nbiter=** set the number of iteration (by default 100)

**precon=** set the preconditioner function (P for example) by default it is the identity, remark the prototype is `func real[int] P(real[int] &x)`.

**eps=** set the value of the stop test  $\varepsilon$  ( $= 10^{-6}$  by default) if positive then relative test  $\|\nabla J(x)\|_P \leq \varepsilon \|\nabla J(x_0)\|_P$ , otherwise the absolute test is  $\|\nabla J(x)\|_P^2 \leq |\varepsilon|$ .

**veps=** set and return the value of the stop test, if positive then relative test  $\|\nabla J(x)\|_P \leq \varepsilon \|\nabla J(x_0)\|_P$ , otherwise the absolute test is  $\|\nabla J(x)\|_P^2 \leq |\varepsilon|$ . The return value is minus the real stop test (remark: it is useful in loop).

**Example 8.1 (algo.edp)** For a given function  $b$ , let us find the minimizer  $u$  of the functional

$$J(u) = \frac{1}{2} \int_{\Omega} f(|\nabla u|^2) - \int_{\Omega} ub$$

$$f(x) = ax + x - \ln(1+x), \quad f'(x) = a + \frac{x}{1+x}, \quad f''(x) = \frac{1}{(1+x)^2}$$

under the boundary condition  $u = 0$  on  $\partial\Omega$ .

```
func real J(real[int] & u)
{
  Vh w;w[]=u; // copy array u in the finite element function w
  real r=int2d(Th)(0.5*f( dx(w)*dx(w) + dy(w)*dy(w) ) - b*w) ;
  cout << "J(u) =" << r << " " << u.min << " " << u.max << endl;
  return r;
}

// -----

Vh u=0; // the current value of the solution
Ph alpha; // of store df(|\nabla u|^2)
int iter=0;
alpha=df( dx(u)*dx(u) + dy(u)*dy(u) ); // optimization

func real[int] dJ(real[int] & u)
{
  int verb=verbosity; verbosity=0;
  Vh w;w[]=u; // copy array u in the finite element function w
  alpha=df( dx(w)*dx(w) + dy(w)*dy(w) ); // optimization
  varf au(uh,vh) = int2d(Th)( alpha*( dx(w)*dx(vh) + dy(w)*dy(vh) ) - b*vh)
    + on(1,2,3,4,u=0);
  u= au(0,Vh);
  verbosity=verb;
  return u; // warning no return of local array
}
```

We want to construct also a preconditioner  $C$  with solving the problem: find  $u_h \in V_{0h}$  such that

$$\forall v_h \in V_{0h}, \quad \int_{\Omega} \alpha \nabla u_h \cdot \nabla v_h = \int_{\Omega} b v_h$$

where  $\alpha = f'(|\nabla u|^2)$ .

```
varf alap(uh,vh)= int2d(Th)( alpha *( dx(uh)*dx(vh) + dy(uh)*dy(vh) ))
+ on(1,2,3,4,u=0);
```



```

varf amass(uh)= int2d(Th)( uh*vh)  + on(1,2,3,4,uh=0);

matrix Amass = alap(Vh,Vh,solver=CG);                                     //
matrix Alap=  alap(Vh,Vh,solver=Cholesky,factorize=1);                 //

                                                                    //  the preconditionner function
func real[int] C(real[int] & u)
{
    real[int] w = Amass*u;
    u = Alap^-1*w;
    return u;                                                            //  no return of local array variable
}

/* To solve the problem, we make 10 iteration of the conjugate gradient, recompute the preconditioner and
restart the conjugate gradient: */

    verbosity=5;
    int conv=0;
    real eps=1e-6;
    for(int i=0;i<20;i++)
    {
        conv=NLCG(dJ,u[],nbiter=10,precon=C,veps=eps);                  //
        if (conv) break;                                                //  if converge break loop
        alpha=df( dx(u)*dx(u) + dy(u)*dy(u) );                          //  recompute alpha optimization
        Alap = alap(Vh,Vh,solver=Cholesky,factorize=1);
        cout << " restart with new preconditionner " << conv
            << " eps =" << eps << endl;
    }

    plot (u,wait=1,cmm="solution with NLCG");

```

For a given symmetric positive matrix  $A$ , consider the quadratic form

$$J(\mathbf{x}) = \frac{1}{2} \mathbf{x}^T A \mathbf{x} - \mathbf{b}^T \mathbf{x}$$

then  $J(\mathbf{x})$  is minimized by the solution  $\mathbf{x}$  of  $A\mathbf{x} = \mathbf{b}$ . In this case, we can use the function `LinearCG`

```
LinearCG(A, x, precon= M, nbiter= imax, eps= ±ε);
```

If  $A$  is not symmetric, we can use GMRES(Generalized Minimum Residual) algorithm by

```
LinearGMRES(A, x, precon= M, nbiter= imax, eps= ±ε);
```

Also, we can use the non-linear version of GMRES algorithm (the functional  $J$  is just convex)

```
LinearGMRES(∇J, x, precon= M, nbiter= imax, eps= ±ε);
```

For detail of these algorithms, refer to [14][Chapter IV, 1.3].

## 8.2 Optimization

Two algorithms of COOOL a package [27] are interfaced with the Newton Raphson method (call `Newton`) and the BFGS method. Be careful of these algorithms, because their implementation use full matrices.

Example of utilization

```

real[int] b(10),u(10);
func real J(real[int] & u)
{
    real s=0;
    for (int i=0;i<u.n;i++)
        s +=(i+1)*u[i]*u[i]*0.5 - b[i]*u[i];
    cout << "J ="<< s << " u =" << u[0] << " " << u[1] << "...\\n" ;
    return s;
}

// the grad of J (this is a affine version (the RHS is in )
func real[int] DJ(real[int] &u)
{
    for (int i=0;i<u.n;i++)
        u[i]=(i+1)*u[i]-b[i];
    return u;
}; // return of global variable ok

b=1; u=2; // set right hand side and initial gest
BFGS(J,dJ,u,eps=1.e-6,nbiter=20,nbiterline=20);
cout << "BFGS: J(u) = " << J(u) << endl;

```

# Chapter 9

## Mathematical Models

**Summary** This chapter goes deeper into a number of problems that **FreeFem++** can solve. It is a complement to chapter 3 which was only an introduction. Users are invited to contribute to make this data base of problems grow.

### 9.1 Static Problems

#### 9.1.1 Soap Film

Our starting point here will be the mathematical model to find the shape of **soap film** which is glued to the ring on the  $xy$ -plane


$$C = \{(x, y); x = \cos t, y = \sin t, 0 \leq t \leq 2\pi\}.$$

We assume the shape of the film is described by the graph  $(x, y, u(x, y))$  of the vertical displacement  $u(x, y)$  ( $x^2 + y^2 < 1$ ) under a vertical pressure  $p$  in terms of force per unit area and an initial tension  $\mu$  in terms of force per unit length.

Consider the “small plane” ABCD, A:  $(x, y, u(x, y))$ , B:  $(x, y, u(x + \delta x, y))$ , C:  $(x, y, u(x + \delta x, y + \delta y))$  and D:  $(x, y, u(x, y + \delta y))$ . Denote by  $\mathbf{n}(x, y) = (n_x(x, y), n_y(x, y), n_z(x, y))$  the normal vector of the surface  $z = u(x, y)$ . We see that the vertical force due to the tension  $\mu$  acting along the edge AD is  $-\mu n_x(x, y)\delta y$  and the the vertical force acting along the edge AD is

$$\mu n_x(x + \delta x, y)\delta y \simeq \mu \left( n_x(x, y) + \frac{\partial n_x}{\partial x} \delta x \right) (x, y) \delta y.$$

Similarly, for the edges AB and DC we have



$$-\mu n_y(x, y)\delta x, \quad \mu \left( n_y(x, y) + \frac{\partial n_y}{\partial y} \delta y \right) (x, y) \delta x.$$

The force in the vertical direction on the surface ABCD due to the tension  $\mu$  is given by

$$\mu (\partial n_x / \partial x) \delta x \delta y + T (\partial n_y / \partial y) \delta y \delta x.$$

Assuming small displacements, we have

$$\begin{aligned} v_x &= (\partial u / \partial x) / \sqrt{1 + (\partial u / \partial x)^2 + (\partial u / \partial y)^2} \simeq \partial u / \partial x, \\ v_y &= (\partial u / \partial y) / \sqrt{1 + (\partial u / \partial x)^2 + (\partial u / \partial y)^2} \simeq \partial u / \partial y. \end{aligned}$$

Letting  $\delta x \rightarrow dx$ ,  $\delta y \rightarrow dy$ , we have the equilibrium of the vertical displacement of soap film on ABCD by  $p$

$$\mu dx dy \partial^2 u / \partial x^2 + \mu dx dy \partial^2 u / \partial y^2 + p dx dy = 0.$$

Using the Laplace operator  $\Delta = \partial^2 / \partial x^2 + \partial^2 / \partial y^2$ , we can find the virtual displacement write the following

$$-\Delta u = f \quad \text{in } \Omega \quad (9.1)$$

where  $f = p/\mu$ ,  $\Omega = \{(x, y); x^2 + y^2 < 1\}$ . Poisson's equation (2.1) appears also in **electrostatics** taking the form of  $f = \rho/\epsilon$  where  $\rho$  is the charge density,  $\epsilon$  the dielectric constant and  $u$  is named as electrostatic potential. The soap film is glued to the ring  $\partial\Omega = C$ , then we have the boundary condition

$$u = 0 \quad \text{on } \partial\Omega \quad (9.2)$$

If the force is gravity, for simplify, we assume that  $f = -1$ .

### Example 9.1 (a\_tutorial.edp)

```



1 : border a(t=0,2*pi){ x = cos(t); y = sin(t);label=1;};
2 :
3 : mesh disk = buildmesh(a(50));
4 : plot(disk);
5 : fespace femp1(disk,P1);
6 : femp1 u,v;
7 : func f = -1;
8 : problem laplace(u,v) =
9 :   int2d(disk)( dx(u)*dx(v) + dy(u)*dy(v) )           // bilinear form
10 : - int2d(disk)( f*v )                                   // linear form
11 : + on(1,u=0) ;                                           // boundary condition
12 : func ue = (x^2+y^2-1)/4;                                // ue: exact solution
13 : laplace;
14 : femp1 err = u - ue;
15 :
16 : plot (u,ps="aTutorial.eps",value=true,wait=true);
17 : plot(err,value=true,wait=true);
18 :
19 : cout << "error L2=" << sqrt(int2d(disk)( err^2 ))<< endl;
20 : cout << "error H1=" << sqrt( int2d(disk)((dx(u)-x/2)^2)
21 :   + int2d(disk)((dy(u)-y/2)^2))<< endl;
22 :
23 : disk = adaptmesh(disk,u,err=0.01);
24 : plot(disk,wait=1);
25 :
26 : laplace;
27 :
28 : plot (u,value=true,wait=true);

```

```

29 : err = u - ue;                                     // become FE-function on adapted mesh
30 : plot(err,value=true,wait=true);
31 : cout << "error L2=" << sqrt(int2d(disk)( err^2 ) )<< endl;
32 : cout << "error H10=" << sqrt(int2d(disk)((dx(u)-x/2)^2)
33 :                               + int2d(disk)((dy(u)-y/2)^2))<< endl;

```

Figure 9.1: isovalue of  $u$ Figure 9.2: a side view of  $u$ 

In 19th line, the  $L^2$ -error estimation between the exact solution  $u_e$ ,

$$\|u_h - u_e\|_{0,\Omega} = \left( \int_{\Omega} |u_h - u_e|^2 \, dx dy \right)^{1/2}$$

and from 20th line to 21th line, the  $H^1$ -error seminorm estimation

$$|u_h - u_e|_{1,\Omega} = \left( \int_{\Omega} |\nabla u_h - \nabla u_e|^2 \, dx dy \right)^{1/2}$$

are done on the initial mesh. The results are  $\|u_h - u_e\|_{0,\Omega} = 0.000384045$ ,  $|u_h - u_e|_{1,\Omega} = 0.0375506$ .

After the adaptation, we have  $\|u_h - u_e\|_{0,\Omega} = 0.000109043$ ,  $|u_h - u_e|_{1,\Omega} = 0.0188411$ . So the numerical solution is improved by adaptation of mesh.

## 9.1.2 Electrostatics

We assume that there is no current and a time independent charge distribution. Then the electric field  $\mathbf{E}$  satisfies

$$\operatorname{div} \mathbf{E} = \rho / \epsilon, \quad \operatorname{curl} \mathbf{E} = 0 \quad (9.3)$$

where  $\rho$  is the charge density and  $\epsilon$  is called the permittivity of free space. From the second equation in (9.3), we can introduce the electrostatic potential such that  $\mathbf{E} = -\nabla \phi$ . Then we have Poisson's equation  $-\Delta \phi = f$ ,  $f = -\rho / \epsilon$ . We now obtain the equipotential line which is the level curve of  $\phi$ , when there are no charges except conductors  $\{C_i\}_{1,\dots,K}$ . Let us assume  $K$  conductors  $C_1, \dots, C_K$  within an enclosure  $C_0$ . Each one is held at an electrostatic potential  $\varphi_i$ . We assume that the enclosure  $C_0$  is held at potential 0. In order to know  $\varphi(x)$  at any point  $x$  of the domain  $\Omega$ , we must solve

$$-\Delta \varphi = 0 \quad \text{in } \Omega, \quad (9.4)$$

where  $\Omega$  is the interior of  $C_0$  minus the conductors  $C_i$ , and  $\Gamma$  is the boundary of  $\Omega$ , that is  $\sum_{i=0}^N C_i$ . Here  $g$  is any function of  $x$  equal to  $\varphi_i$  on  $C_i$  and to 0 on  $C_0$ . The boundary equation is a reduced form for:

$$\varphi = \varphi_i \text{ on } C_i, \quad i = 1 \dots N, \quad \varphi = 0 \text{ on } C_0. \quad (9.5)$$

**Example 9.2** First we give the geometrical informations;  $C_0 = \{(x,y); x^2 + y^2 = 5^2\}$ ,  $C_1 = \{(x,y) : \frac{1}{0.3^2}(x-2)^2 + \frac{1}{3^2}y^2 = 1\}$ ,  $C_2 = \{(x,y) : \frac{1}{0.3^2}(x+2)^2 + \frac{1}{3^2}y^2 = 1\}$ . Let  $\Omega$  be the disk enclosed by  $C_0$  with the elliptical holes enclosed by  $C_1$  and  $C_2$ . Note that  $C_0$  is described counterclockwise, whereas the elliptical holes are described clockwise, because the boundary must be oriented so that the computational domain is to its left.

```

// a circle with center at (0,0) and radius 5
border C0(t=0,2*pi) { x = 5 * cos(t); y = 5 * sin(t); }
border C1(t=0,2*pi) { x = 2+0.3 * cos(t); y = 3*sin(t); }
border C2(t=0,2*pi) { x = -2+0.3 * cos(t); y = 3*sin(t); }

mesh Th = buildmesh(C0(60)+C1(-50)+C2(-50));
plot(Th,ps="electroMesh"); // figure 9.3
fespace Vh(Th,P1); // P1 FE-space
Vh uh,vh; // unknown and test function.
problem Electro(uh,vh) = // definition of the problem
    int2d(Th)( dx(uh)*dx(vh) + dy(uh)*dy(vh) ) // bilinear
    + on(C0,uh=0) // boundary condition on C0
    + on(C1,uh=1) // +1 volt on C1
    + on(C2,uh=-1) ; // -1 volt on C2

Electro; // solve the problem, see figure 9.4 for the solution
plot(uh,ps="electro.eps",wait=true); // figure 9.4

```




Figure 9.3: Disk with two elliptical holes




Figure 9.4: Equipotential lines, where  $C_1$  is located in right hand side

### 9.1.3 Aerodynamics

Let us consider a wing profile  $S$  in a uniform flow. Infinity will be represented by a large circle  $\Gamma_\infty$ . As previously, we must solve

$$\Delta\varphi = 0 \quad \text{in } \Omega, \quad \varphi|_S = c, \quad \varphi|_{\Gamma_\infty} = u_{\infty 1x} - u_{\infty 2x} \quad (9.6)$$

where  $\Omega$  is the area occupied by the fluid,  $u_\infty$  is the air speed at infinity,  $c$  is a constant to be determined so that  $\partial_n\varphi$  is continuous at the trailing edge  $P$  of  $S$  (so-called Kutta-Joukowski condition). Lift is proportional to  $c$ . To find  $c$  we use a superposition method. As all equations in (9.6) are linear, the solution  $\varphi_c$  is a linear function of  $c$

$$\varphi_c = \varphi_0 + c\varphi_1, \quad (9.7)$$

where  $\varphi_0$  is a solution of (9.6) with  $c = 0$  and  $\varphi_1$  is a solution with  $c = 1$  and zero speed at infinity. With these two fields computed, we shall determine  $c$  by requiring the continuity of  $\partial\varphi/\partial n$  at the trailing edge. An equation for the upper surface of a NACA0012 (this is a classical wing profile in aerodynamics; the rear of the wing is called the trailing edge) is:

$$y = 0.17735\sqrt{x} - 0.075597x - 0.212836x^2 + 0.17363x^3 - 0.06254x^4. \quad (9.8)$$

Taking an incidence angle  $\alpha$  such that  $\tan \alpha = 0.1$ , we must solve

$$-\Delta\varphi = 0 \quad \text{in } \Omega, \quad \varphi|_{\Gamma_1} = y - 0.1x, \quad \varphi|_{\Gamma_2} = c, \quad (9.9)$$

where  $\Gamma_2$  is the wing profile and  $\Gamma_1$  is an approximation of infinity. One finds  $c$  by solving:

$$-\Delta\varphi_0 = 0 \quad \text{in } \Omega, \quad \varphi_0|_{\Gamma_1} = y - 0.1x, \quad \varphi_0|_{\Gamma_2} = 0, \quad (9.10)$$

$$-\Delta\varphi_1 = 0 \quad \text{in } \Omega, \quad \varphi_1|_{\Gamma_1} = 0, \quad \varphi_1|_{\Gamma_2} = 1. \quad (9.11)$$

The solution  $\varphi = \varphi_0 + c\varphi_1$  allows us to find  $c$  by writing that  $\partial_n\varphi$  has no jump at the trailing edge  $P = (1, 0)$ . We have  $\partial_n\varphi - (\varphi(P^+) - \varphi(P))/\delta$  where  $P^+$  is the point just above  $P$  in the direction normal to the profile at a distance  $\delta$ . Thus the jump of  $\partial_n\varphi$  is  $(\varphi_0|_{P^+} + c(\varphi_1|_{P^+} - 1)) + (\varphi_0|_{P^-} + c(\varphi_1|_{P^-} - 1))$  divided by  $\delta$  because the normal changes sign between the lower and upper surfaces. Thus

$$c = -\frac{\varphi_0|_{P^+} + \varphi_0|_{P^-}}{(\varphi_1|_{P^+} + \varphi_1|_{P^-} - 2)}, \quad (9.12)$$

which can be programmed as:

$$c = -\frac{\varphi_0(0.99, 0.01) + \varphi_0(0.99, -0.01)}{(\varphi_1(0.99, 0.01) + \varphi_1(0.99, -0.01) - 2)}. \quad (9.13)$$

#### Example 9.3

```

//      Computation of the potential flow around a NACA0012 airfoil.
//      The method of decomposition is used to apply the Joukowski condition
//      The solution is seeked in the form psi0 + beta psi1 and beta is
//      adjusted so that the pressure is continuous at the trailing edge

border a(t=0,2*pi) { x=5*cos(t); y=5*sin(t); }; //      approximates infinity

border upper(t=0,1) { x = t;
  y = 0.17735*sqrt(t)-0.075597*t
  - 0.212836*(t^2)+0.17363*(t^3)-0.06254*(t^4); }
border lower(t=1,0) { x = t;
  y= -(0.17735*sqrt(t)-0.075597*t
```

```

-0.212836*(t^2)+0.17363*(t^3)-0.06254*(t^4)); }
border c(t=0,2*pi) { x=0.8*cos(t)+0.5; y=0.8*sin(t); }

wait = true;
mesh Zoom = buildmesh(c(30)+upper(35)+lower(35));
mesh Th = buildmesh(a(30)+upper(35)+lower(35));
fespace Vh(Th,P2);
Vh psi0,psi1,vh; // P1 FE space
// unknown and test function.
fespace ZVh(Zoom,P2);

solve Joukowski0(psi0,vh) = // definition of the problem
    int2d(Th)( dx(psi0)*dx(vh) + dy(psi0)*dy(vh) ) // bilinear form
+ on(a,psi0=y-0.1*x) // boundary condition form
+ on(upper,lower,psi0=0);
plot(psi0);



solve Joukowski1(psi1,vh) = // definition of the problem
    int2d(Th)( dx(psi1)*dx(vh) + dy(psi1)*dy(vh) ) // bilinear form
+ on(a,psi1=0) // boundary condition form
+ on(upper,lower,psi1=1);

plot(psi1);

// continuity of pressure at trailing edge
real beta = psi0(0.99,0.01)+psi0(0.99,-0.01);
beta = -beta / (psi1(0.99,0.01)+ psi1(0.99,-0.01)-2);

Vh psi = beta*psi1+psi0;
plot(psi);
ZVh Zpsi=psi;
plot(Zpsi,bw=true);
ZVh cp = -dx(psi)^2 - dy(psi)^2;
plot(cp);
ZVh Zcp=cp;
plot(Zcp,nbiso=40);

```

Figure 9.5: isovalue of  $cp = -(\partial_x \psi)^2 - (\partial_y \psi)^2$ Figure 9.6: Zooming of  $cp$



### 9.1.4 Error estimation

There are famous estimation between the numerical result  $u_h$  and the exact solution  $u$  of the problem 2.1 and 2.2: If triangulations  $\{\mathcal{T}_h\}_{h \downarrow 0}$  is regular (see Section 5.4), then we have the estimates

$$|\nabla u - \nabla u_h|_{0,\Omega} \leq C_1 h \quad (9.14)$$

$$\|u - u_h\|_{0,\Omega} \leq C_2 h^2 \quad (9.15)$$

with constants  $C_1, C_2$  independent of  $h$ , if  $u$  is in  $H^2(\Omega)$ . It is known that  $u \in H^2(\Omega)$  if  $\Omega$  is convex.

In this section we check (9.14) and (9.15). We will pick up numerical error if we use the numerical derivative, so we will use the following for (9.14).

$$\begin{aligned} \int_{\Omega} |\nabla u - \nabla u_h|^2 dx dy &= \int_{\Omega} \nabla u \cdot \nabla (u - 2u_h) dx dy + \int_{\Omega} \nabla u_h \cdot \nabla u_h dx dy \\ &= \int_{\Omega} f(u - 2u_h) dx dy + \int_{\Omega} f u_h dx dy \end{aligned}$$

The constants  $C_1, C_2$  are depend on  $\mathcal{T}_h$  and  $f$ , so we will find them by FreeFem++. In general, we cannot get the solution  $u$  as a elementary functions (see Section 4.7) even if spetical functions are added. Instead of the exact solution, here we use the approximate solution  $u_0$  in  $V_h(\mathcal{T}_h, P_2)$ ,  $h \sim 0$ .

#### Example 9.4

```

1 : mesh Th0 = square(100,100);
2 : fespace V0h(Th0,P2);
3 : V0h u0,v0;
4 : func f = x*y; // sin(pi*x)*cos(pi*y);
5 :
6 : solve Poisson0(u0,v0) =
7 :   int2d(Th0)( dx(u0)*dx(v0) + dy(u0)*dy(v0) ) // bilinear form
8 :   - int2d(Th0)( f*v0 ) // linear form
9 :   + on(1,2,3,4,u0=0) ; // boundary condition
10 :
11 : plot(u0);
12 :
13 : real[int] errL2(10), errH1(10);
14 :
15 : for (int i=1; i<=10; i++) {
16 :   mesh Th = square(5+i*3,5+i*3);
17 :   fespace Vh(Th,P1);
18 :   fespace Ph(Th,P0);
19 :   Ph h = hTriangle; // get the size of all triangles
20 :   Vh u,v;
21 :   solve Poisson(u,v) =
22 :     int2d(Th)( dx(u)*dx(v) + dy(u)*dy(v) ) // bilinear form
23 :     - int2d(Th)( f*v ) // linear form
24 :     + on(1,2,3,4,u=0) ; // boundary condition
25 :   V0h uu = u;
26 :   errL2[i-1] = sqrt( int2d(Th0)((uu - u0)^2) /h[] .max^2;
27 :   errH1[i-1] = sqrt( int2d(Th0)( f*(u0-2*uu+uu) ) /h[] .max;
28 : }
29 : cout << "C1 = " << errL2.max << "("<<errL2.min<<")"<< endl;
30 : cout << "C2 = " << errH1.max << "("<<errH1.min<<")"<< endl;

```

We can guess that  $C_1 = 0.0179253(0.0173266)$  and  $C_2 = 0.0729566(0.0707543)$ , where the numbers inside the parentheses are minimum in calculation.

### 9.1.5 Periodic Boundary Conditions

We now solve the Poisson equation

$$-\Delta u = \sin(x + \pi/4) * \cos(y + \pi/4.)$$

on the square  $]0, 2\pi[^2$  under bi-periodic boundary condition  $u(0, y) = u(2\pi, y)$  for all  $y$  and  $u(x, 0) = u(x, 2\pi)$  for all  $x$ . These boundary conditions are achieved from the definition of the periodic finite element space.

#### Example 9.5 (periodic.edp)

```

mesh Th=square(10,10,[2*x*pi,2*y*pi]);
                                // defined the fespacewith periodic condition
                                // label : 2 and 4 are left and right side with y the curve abscissa
                                // 1 and 2 are bottom and upper side with x the curve abscissa
fespace Vh(Th,P2,periodic=[[2,y],[4,y],[1,x],[3,x]]);
Vh uh,vh;                                // unknown and test function.
func f=sin(x+pi/4.)*cos(y+pi/4.);        // right hand side function

problem laplace(uh,vh) =                // definition of the problem
    int2d(Th)( dx(uh)*dx(vh) + dy(uh)*dy(vh) )    // bilinear form
    + int2d(Th)( -f*vh )                    // linear form
;

laplace;                                // solve the problem
plot(uh,ps="period.eps",value=true);    // to see the result

```




Figure 9.7: The isovalue of solution  $u$  with periodic boundary condition

The periodic condition does not necessarily require parallel boundaries. Example 9.6 give such example.

#### Example 9.6 (periodic4.edp)

```

real r=0.25;
                                // a diamond with a hole
border a(t=0,1){x=-t+1; y=t;label=1;};
border b(t=0,1){ x=-t; y=1-t;label=2;};

```

```

border c(t=0,1){ x=t-1; y=-t;label=3;};
border d(t=0,1){ x=t; y=-1+t;label=4;};
border e(t=0,2*pi){ x=r*cos(t); y=-r*sin(t);label=0;};
int n = 10;
mesh Th= buildmesh(a(n)+b(n)+c(n)+d(n)+e(n));
plot(Th,wait=1);
real r2=1.732;
func abs=sqrt(x^2+y^2);
//    warning for periodic condition:
//    side a and c
//    on side a (label 1)  $x \in [0,1]$  or  $x-y \in [-1,1]$ 
//    on side c (label 3)  $x \in [-1,0]$  or  $x-y \in [-1,1]$ 
//                //    so the common abscissa can be respectively  $x$  and  $x+1$ 
//                //    or you can try curviline abscissa  $x-y$  and  $x-y$ 

//    1 first way
//    fespace Vh(Th,P2,periodic=[[2,1+x],[4,x],[1,x],[3,1+x]]);
//    2 second way
fespace Vh(Th,P2,periodic=[[2,x+y],[4,x+y],[1,x-y],[3,x-y]]);

Vh uh,vh;

func f=(y+x+1)*(y+x-1)*(y-x+1)*(y-x-1);
real intf = int2d(Th)(f);
real mTh = int2d(Th)(1);
real k = intf/mTh;
problem laplace(uh,vh) =
    int2d(Th)( dx(uh)*dx(vh) + dy(uh)*dy(vh) ) + int2d(Th)( (k-f)*vh ) ;
laplace;
plot(uh,wait=1,ps="perio4.eps");

```




Figure 9.8: The isovalue of solution  $u$  for  $\Delta u = ((y+x)^2 + 1)((y-x)^2 + 1) - k$ , in  $\Omega$  and  $\partial_n u = 0$  on hole, and with two periodic boundary condition on external border

An other example with no equal border, just to see if the code works.

**Example 9.7 (periodic4bis.edp)**

```

//      irregular boundary condition.
//      to build border AB

macro LINEBORDER(A,B,lab) border A#B(t=0,1){real t1=1.-t;
  x=A#x*t1+B#x*t;y=A#y*t1+B#y*t;label=lab;} //      EOM
//      compute ||AB|| a=(ax,ay) et B =(bx,by)
macro dist(ax,ay,bx,by) sqrt(square((ax)-(bx))+ square((ay)-(by))) //      EOM
macro Grad(u) [dx(u),dy(u)] //      EOM

real Ax=0.9,Ay=1;          real Bx=2,By=1;
real Cx=2.5,Cy=2.5;        real Dx=1,Dy=2;
real gx = (Ax+Bx+Cx+Dx)/4.; real gy = (Ay+By+Cy+Dy)/4.;

LINEBORDER(A,B,1)
LINEBORDER(B,C,2)
LINEBORDER(C,D,3)
LINEBORDER(D,A,4)

int n=10;

real l1=dist(Ax,Ay,Bx,By);
real l2=dist(Bx,By,Cx,Cy);
real l3=dist(Cx,Cy,Dx,Dy);
real l4=dist(Dx,Dy,Ax,Ay);
func s1=dist(Ax,Ay,x,y)/l1; //      abscisse on AB = ||AX||/||AB||
func s2=dist(Bx,By,x,y)/l2; //      abscisse on BC = ||BX||/||BC||
func s3=dist(Cx,Cy,x,y)/l3; //      abscisse on CD = ||CX||/||CD||
func s4=dist(Dx,Dy,x,y)/l4; //      abscisse on DA = ||DX||/||DA||

mesh Th=buildmesh(AB(n)+BC(n)+CD(n)+DA(n),fixeborder=1); //

verbosity=6; //      to see the abscisse value pour the periodic condition.
fespace Vh(Th,P1,periodic=[[1,s1],[3,s3],[2,s2],[4,s4]]);
verbosity=1;
Vh u,v;
real cc=0;
cc= int2d(Th)((x-gx)*(y-gy)-cc)/Th.area;
cout << " compatibility =" << int2d(Th)((x-gx)*(y-gy)-cc) << endl;

solve Poission(u,v)=int2d(Th)(Grad(u)'*Grad(v)+ 1e-10*u*v)
-int2d(Th)(10*v*((x-gx)*(y-gy)-cc));
plot(u,wait=1,value=1);

```

**Example 9.8 (Period-Poisson-cube-ballon.edp)**

```

verbosity=1;
load "msh3"
load "tetgen"
load "medit"

bool buildTh=0;

```

```

mesh3 Th;
try { // a way to build one time the mesh and read if the file exist.
    Th=readmesh3("Th-hex-sph.mesh");
}
catch(...) { buildTh=1;}
if( buildTh ){
    ...
    put the code example page // 5.11.1124
    without the first line
}

fespace Ph(Th,P0);
verbosity=50;
fespace Vh(Th,P1,periodic=[[3,x,z],[4,x,z],[1,y,z],[2,y,z],[5,x,y],[6,x,y]]); // back
and front
verbosity=1;
Ph reg=region;

cout << " centre = " << reg(0,0,0) << endl;
cout << " exterieur = " << reg(0,0,0.7) << endl;

macro Grad(u) [dx(u),dy(u),dz(u)] // EOM

Vh uh,vh;
real x0=0.3,y0=0.4,z0=0.6;
func f= sin(x*2*pi+x0)*sin(y*2*pi+y0)*sin(z*2*pi+z0);
real gn = 1.;
real cf= 1;
problem P(uh,vh)=
    int3d(Th,1)( Grad(uh)'*Grad(vh)*100)
    + int3d(Th,2)( Grad(uh)'*Grad(vh)*2)
    + int3d(Th) (vh*f)
    ;
    P;
plot(uh,wait=1, nbiso=6);
medit(" uh ",Th, uh);

```

### 9.1.6 Poisson Problems with mixed boundary condition

Here we consider the Poisson equation with mixed boundary conditions: For given functions  $f$  and  $g$ , find  $u$  such that

$$\begin{aligned}
 -\Delta u &= f & \text{in } \Omega \\
 u &= g & \text{on } \Gamma_D, \quad \partial u / \partial n = 0 & \text{on } \Gamma_N
 \end{aligned} \tag{9.16}$$

where  $\Gamma_D$  is a part of the boundary  $\Gamma$  and  $\Gamma_N = \Gamma \setminus \overline{\Gamma_D}$ . The solution  $u$  has the singularity at the points  $\{\gamma_1, \gamma_2\} = \overline{\Gamma_D} \cap \overline{\Gamma_N}$ . When  $\Omega = \{(x, y); -1 < x < 1, 0 < y < 1\}$ ,  $\Gamma_N = \{(x, y); -1 \leq x < 0, y = 0\}$ ,  $\Gamma_D = \partial\Omega \setminus \Gamma_N$ , the singularity will appear at  $\gamma_1 = (0, 0)$ ,  $\gamma_2 = (-1, 0)$ , and  $u$  has the expression

$$u = K_i u_S + u_R, \quad u_R \in H^2(\text{near } \gamma_i), \quad i = 1, 2$$

with a constants  $K_i$ . Here  $u_S = r_j^{1/2} \sin(\theta_j/2)$  by the local polar coordinate  $(r_j, \theta_j)$  at  $\gamma_j$  such that  $(r_1, \theta_1) = (r, \theta)$ . Instead of polar coordinate system  $(r, \theta)$ , we use that  $r = \sqrt{x^2 + y^2}$  and  $\theta = \text{atan2}(y, x)$  in FreeFem++ .





Figure 9.10:

Figure 9.9: view of the surface isovalue of periodic solution  $u_h$       view a the cut of the solution  $u_h$  with `ffmedit`

**Example 9.9** Assume that  $f = -2 \times 30(x^2 + y^2)$  and  $g = u_e = 10(x^2 + y^2)^{1/4} \sin([\tan^{-1}(y/x)]/2) + 30(x^2 y^2)$ , where  $u_e$  is the exact solution.

```

1 : border N(t=0,1) { x=-1+t; y=0; label=1; };
2 : border D1(t=0,1){ x=t; y=0; label=2;};
3 : border D2(t=0,1){ x=1; y=t; label=2; };
4 : border D3(t=0,2){ x=1-t; y=1; label=2;};
5 : border D4(t=0,1) { x=-1; y=1-t; label=2; };
6 :
7 : mesh T0h = buildmesh(N(10)+D1(10)+D2(10)+D3(20)+D4(10));
8 : plot(T0h,wait=true);
9 : fespace V0h(T0h,P1);
10 : V0h u0, v0;
11 :
12 : func f=-2*30*(x^2+y^2); // given function
13 : // the singular term of the solution is K*us (K: constant)
14 : func us = sin(atan2(y,x)/2)*sqrt( sqrt(x^2+y^2) );
15 : real K=10.;
16 : func ue = K*us + 30*(x^2*y^2);
17 :
18 : solve Poisson0(u0,v0) =
19 :   int2d(T0h)( dx(u0)*dx(v0) + dy(u0)*dy(v0) ) // bilinear form
20 :   - int2d(T0h)( f*v0 ) // linear form
21 :   + on(2,u0=ue) ; // boundary condition
22 :
23 : // adaptation by the singular term
24 : mesh Th = adaptmesh(T0h,us);
25 : for (int i=0;i< 5;i++)
26 : {
27 :   mesh Th=adaptmesh(Th,us);
28 : } ;

```

```

29 :
30 : fespace Vh(Th, P1);
31 : Vh u, v;
32 : solve Poisson(u,v) =
33 :   int2d(Th)( dx(u)*dx(v) + dy(u)*dy(v) )           // bilinear form
34 : - int2d(Th)( f*v )                                   // linear form
35 : + on(2,u=ue) ;                                       // boundary condition
36 :
37 : /* plot the solution */
38 : plot(Th,ps="adaptDNmix.ps");
39 : plot(u,wait=true);
40 :
41 : Vh uue = ue;
42 : real H1e = sqrt( int2d(Th)( dx(uue)^2 + dy(uue)^2 + uue^2 ) );
43 :
44 : /* calculate the H1 Sobolev norm */
45 : Vh err0 = u0 - ue;
46 : Vh err = u - ue;
47 : Vh H1err0 = int2d(Th)( dx(err0)^2+dy(err0)^2+err0^2 );
48 : Vh H1err = int2d(Th)( dx(err)^2+dy(err)^2+err^2 );
49 : cout <<"Relative error in first mesh "<< int2d(Th)(H1err0)/H1e<<endl;
50 : cout <<"Relative error in adaptive mesh "<< int2d(Th)(H1err)/H1e<<endl;

```

From 24th line to 28th, adaptation of meshes are done using the base of singular term. In 42th line,  $H1e=\|u_e\|_{1,\Omega}$  is calculated. In last 2 lines, the relative errors are calculated, that is,

$$\begin{aligned} \|u_h^0 - u_e\|_{1,\Omega}/H1e &= 0.120421 \\ \|u_h^a - u_e\|_{1,\Omega}/H1e &= 0.0150581 \end{aligned}$$

where  $u_h^0$  is the numerical solution in  $T0h$  and  $u_h^a$  is  $u$  in this program.

### 9.1.7 Poisson with mixte finite element

Here we consider the Poisson equation with mixed boundary value problems: For given functions  $f$ ,  $g_d$ ,  $g_n$ , find  $p$  such that

$$\begin{aligned} -\Delta p &= 1 & \text{in } \Omega \\ p &= g_d & \text{on } \Gamma_D, \quad \partial p / \partial n = g_n & \text{on } \Gamma_N \end{aligned} \quad (9.17)$$

where  $\Gamma_D$  is a part of the boundary  $\Gamma$  and  $\Gamma_N = \Gamma \setminus \overline{\Gamma_D}$ .

The mixte formulation is: find  $p$  and  $\mathbf{u}$  such that

$$\begin{aligned} \nabla p + \mathbf{u} &= \mathbf{0} & \text{in } \Omega \\ \nabla \cdot \mathbf{u} &= f & \text{in } \Omega \\ p &= g_d & \text{on } \Gamma_D, \quad \partial u \cdot \mathbf{n} = \mathbf{g}_n \cdot \mathbf{n} & \text{on } \Gamma_N \end{aligned} \quad (9.18)$$

where  $\mathbf{g}_n$  is a vector such that  $\mathbf{g}_n \cdot \mathbf{n} = g_n$ .

The variationnal formulation is,

$$\begin{aligned} \forall \mathbf{v} \in \mathbb{V}_0, \quad \int_{\Omega} p \nabla \cdot \mathbf{v} + \mathbf{v} \mathbf{v} &= \int_{\Gamma_d} g_d \mathbf{v} \cdot \mathbf{n} \\ \forall q \in \mathbb{P} \quad \int_{\Omega} q \nabla \cdot \mathbf{u} &= \int_{\Omega} q f \\ \partial u \cdot \mathbf{n} &= \mathbf{g}_n \cdot \mathbf{n} & \text{on } \Gamma_N \end{aligned} \quad (9.19)$$

where the functionnal space are:

$$\mathbb{P} = L^2(\Omega), \quad \mathbb{V} = H(\text{div}) = \{\mathbf{v} \in L^2(\Omega)^2, \nabla \cdot \mathbf{v} \in L^2(\Omega)\}$$

and

$$\mathbb{V}_0 = \{\mathbf{v} \in \mathbb{V}; \quad \mathbf{v} \cdot \mathbf{n} = 0 \quad \text{on } \Gamma_N\}.$$

To write, the FreeFem++ example, we have just to choose the finites elements spaces. here  $\mathbb{V}$  space is discretize with Raviart-Thomas finite element  $\text{RT0}$  and  $\mathbb{P}$  is discretize by constant finite element  $\text{P0}$ .

### Example 9.10 (LaplaceRT.edp)

```

mesh Th=square(10,10);
fespace Vh(Th,RT0);
fespace Ph(Th,P0);
func gd = 1.;
func g1n = 1.;
func g2n = 1.;

Vh [u1,u2],[v1,v2];
Ph p,q;

problem laplaceMixte([u1,u2,p],[v1,v2,q],
                      solver=GMRES,eps=1.0e-10,
                      tgv=1e30,dimKrylov=150)
=
  int2d(Th)( p*q*1e-15 // this term is here to be sur
               // that all sub matrix are inversible (LU requirement)
            + u1*v1 + u2*v2 + p*(dx(v1)+dy(v2)) + (dx(u1)+dy(u2))*q )
+ int2d(Th) ( q)
- int1d(Th,1,2,3)( gd*(v1*N.x +v2*N.y)) // on  $\Gamma_D$ 
+ on(4,u1=g1n,u2=g2n); // on  $\Gamma_N$ 

laplaceMixte;

plot([u1,u2],coef=0.1,wait=1,ps="lapRTuv.eps",value=true);
plot(p,fill=1,wait=1,ps="laRTp.eps",value=true);

```

## 9.1.8 Metric Adaptation and residual error indicator

We do metric mesh adaption and compute the classical residual error indicator  $\eta_T$  on the element  $T$  for the Poisson problem.

**Example 9.11 (adaptindicatorP2.edp)** *First, we solve the same problem as in a previous example.*

```

1 : border ba(t=0,1.0){x=t; y=0; label=1;}; // see Fig,5.15
2 : border bb(t=0,0.5){x=1; y=t; label=2;};
3 : border bc(t=0,0.5){x=1-t; y=0.5;label=3;};
4 : border bd(t=0.5,1){x=0.5; y=t; label=4;};
5 : border be(t=0.5,1){x=1-t; y=1; label=5;};
6 : border bf(t=0.0,1){x=0; y=1-t;label=6;};
7 : mesh Th = buildmesh (ba(6) + bb(4) + bc(4) +bd(4) + be(4) + bf(6));
8 : savemesh(Th,"th.msh");
9 : fespace Vh(Th,P2);

```



```

10 : fespace Nh(Th,P0);
11 : Vh u,v;
12 : Nh rho;
13 : real[int] viso(21);
14 : for (int i=0;i<viso.n;i++)
15 :   viso[i]=10.^(+(i-16.)/2.);
16 : real error=0.01;
17 : func f=(x-y);
18 : problem Problem1(u,v,solver=CG,eps=1.0e-6) =
19 :   int2d(Th,qforder=5)( u*v*1.0e-10+ dx(u)*dx(v) + dy(u)*dy(v))
20 :   + int2d(Th,qforder=5)( -f*v);
21 : /*****

```

Now, the local error indicator  $\eta_T$  is:

$$\eta_T = \left( h_T^2 \|f + \Delta u_h\|_{L^2(T)}^2 + \sum_{e \in \mathcal{E}_K} h_e \left\| \left[ \frac{\partial u_h}{\partial n_k} \right] \right\|_{L^2(e)}^2 \right)^{\frac{1}{2}}$$

where  $h_T$  is the longest's edge of  $T$ ,  $\mathcal{E}_T$  is the set of  $T$  edge not on  $\Gamma = \partial\Omega$ ,  $n_T$  is the outside unit normal to  $K$ ,  $h_e$  is the length of edge  $e$ ,  $[g]$  is the jump of the function  $g$  across edge (left value minus right value). Of course, we can use a variational form to compute  $\eta_T^2$ , with test function constant function in each triangle.

```

29 : *****/
30 :
31 : varf indicator2(uu,chiK) =
32 :   intalldges(Th)(chiK*lenEdge*square(jump(N.x*dx(u)+N.y*dy(u))))
33 :   +int2d(Th)(chiK*square(hTriangle*(f+dxx(u)+dyy(u))) );
34 : for (int i=0;i< 4;i++)
35 : {
36 :   Problem1;
37 :   cout << u[].min << " " << u[].max << endl;
38 :   plot(u,wait=1);
39 :   cout << " indicator2 " << endl;
40 :
41 :   rho[] = indicator2(0,Nh);
42 :   rho=sqrt(rho);
43 :   cout << "rho =   min " << rho[].min << " max=" << rho[].max << endl;
44 :   plot(rho,fill=1,wait=1,cmm="indicator density ",ps="rhoP2.eps",
         value=1,viso=viso,nbiso=viso.n);
45 :   plot(Th,wait=1,cmm="Mesh ",ps="ThrhoP2.eps");
46 :   Th=adaptmesh(Th,[dx(u),dy(u)],err=error,anisomax=1);
47 :   plot(Th,wait=1);
48 :   u=u;
49 :   rho=rho;
50 :   error = error/2;
51 : } ;

```

If the method is correct, we expect to look the graphics by an almost constant function  $\eta$  on your computer as in Fig. 9.11.




Figure 9.11: Density of the error indicator with isotropic  $P_2$  metric

### 9.1.9 Adaptation using residual error indicator

In the previous example we compute the error indicator, now we use it, to adapt the mesh. The new mesh size is given by the following formulae:

$$h_{n+1}(x) = \frac{h_n(x)}{f_n(\eta_K(x))}$$

where  $\eta_n(x)$  is the level of error at point  $x$  given by the local error indicator,  $h_n$  is the previous “mesh size” field, and  $f_n$  is a user function define by  $f_n = \min(3, \max(1/3, \eta_n/\eta_n^*))$  where  $\eta_n^* = \text{mean}(\eta_n)c$ , and  $c$  is an user coefficient generally close to one.

#### Example 9.12 (AdaptResidualErrorIndicator.edp)

First a macro MeshSizecomputation to get a  $P_1$  mesh size as the average of edge length.

```
// macro the get the current mesh size
// parameter
// in: Th the mesh
// Vh P1 fespace on Th
// out :
// h: the Vh finite element finite set to the current mesh size
macro MeshSizecomputation(Th,Vh,h)
{ /* Th mesh   Vh P1 finite element space
  h the P1 mesh size value */
  real[int] count(Th.nv);
  /* mesh size (lenEdge = integral(e) 1 ds) */
  varf vmeshsize(u,v)=intalldges(Th,qfnpE=1)(v);
  /* number of edge / par vertex */
  varf vedgecount(u,v)=intalldges(Th,qfnpE=1)(v/lenEdge);
  /*
  computation of the mesh size
  ----- */
```

```

count=vedgecount(0,Vh);
h[]=0.;
h[]=vmeshsizen(0,Vh);
cout << " count min = "<< count.min << " " << count.max << endl;
h[]=h[]./count;
    cout << " -- bound meshsize = " <<h[].min << " " << h[].max << endl;
} //    end of macro MeshSizecomputation

```

*A second macro to remesh according to the new mesh size.*

```

//    macro to remesh according the de residual indicator
//    in:
//    Th the mesh
//    Ph P0 fespace on Th
//    Vh P1 fespace on Th
//    vindicator the varf of to evaluate the indicator to 2
//    coef on etameam ..
//    -----

macro ReMeshIndicator(Th,Ph,Vh,vindicator,coef)
{
Vh h=0;
/*evalutate the mesh size */
MeshSizecomputation(Th,Vh,h);
Ph etak;
etak[]=vindicator(0,Ph);
etak[]=sqrt(etak[]);
real etastar= coef*(etak[].sum/etak[].n);
cout << " etastar = " << etastar << " sum=" << etak[].sum << " " << endl;

/* here etaK is discontinous
   we use the P1 L2 projection with mass lumping . */

Vh fn,sigma;
varf veta(unused,v)=int2d(Th)(etak*v);
varf vun(unused,v)=int2d(Th)(1*v);
fn[] = veta(0,Vh);
sigma[]= vun(0,Vh);
fn[]= fn[]./ sigma[];
fn = max(min(fn/etastar,3.),0.3333) ;

/* new mesh size */
h = h / fn ;
/* plot(h,wait=1); */
/* build the new mesh */
Th=adaptmesh(Th,IsMetric=1,h,splitpbedge=1,nbvx=10000);
}

```

*We skip the mesh construction, see the previous example,*

```

fespace Vh(Th,P1);
fespace Ph(Th,P0);

real hinit=0.2;
Vh h=hinit;

//    FE space definition ---
//    for the mesh size and solution
//    for the error indicator

//    initial mesh size
//    the FE function for the mesh size
//    to build a mesh with a given mesh size : meshsize

```

```

Th=adaptmesh(Th,h,IsMetric=1,splitpbedge=1,nbvx=10000);
plot(Th,wait=1,ps="RRI-Th-init.eps");
Vh u,v;

func f=(x-y);

problem Poisson(u,v) =
    int2d(Th,qforder=5)( u*v*1.0e-10+ dx(u)*dx(v) + dy(u)*dy(v))
    - int2d(Th,qforder=5)( f*v);

varf indicator2(unused,chiK) =
    intalledges(Th)(chiK*lenEdge*square(jump(N.x*dx(u)+N.y*dy(u))))
    +int2d(Th)(chiK*square(hTriangle*(f+dxx(u)+dyy(u))) );

for (int i=0;i< 10;i++)
{
u=u;
Poisson;
plot(Th,u,wait=1);
real cc=0.8;
if(i>5) cc=1;
ReMeshIndicator(Th,Ph,Vh,indicator2,cc);
plot(Th,wait=1);
}

```




Figure 9.12: the error indicator with isotropic  $P_1$ , the mesh and isovalue of the solution

## 9.2 Elasticity

Consider an elastic plate with undeformed shape  $\Omega \times ]-h, h[$  in  $\mathbb{R}^3$ ,  $\Omega \subset \mathbb{R}^2$ . By the deformation of the plate, we assume that a point  $P(x_1, x_2, x_3)$  moves to  $\mathcal{P}(\xi_1, \xi_2, \xi_3)$ . The vector  $\mathbf{u} = (u_1, u_2, u_3) = (\xi_1 -$

$x_1, \xi_2 - x_2, \xi_3 - x_3$ ) is called the *displacement vector*. By the deformation, the line segment  $\overline{\mathbf{x}, \mathbf{x} + \tau \Delta \mathbf{x}}$  moves approximately to  $\overline{\mathbf{x} + u(\mathbf{x}), \mathbf{x} + \tau \Delta \mathbf{x} + u(\mathbf{x} + \tau \Delta \mathbf{x})}$  for small  $\tau$ , where  $\mathbf{x} = (x_1, x_2, x_3)$ ,  $\Delta \mathbf{x} = (\Delta x_1, \Delta x_2, \Delta x_3)$ . We now calculate the ratio between two segments

$$\eta(\tau) = \tau^{-1} |\Delta \mathbf{x}|^{-1} (|u(\mathbf{x} + \tau \Delta \mathbf{x}) - u(\mathbf{x}) + \tau \Delta \mathbf{x}| - \tau |\Delta \mathbf{x}|)$$

then we have (see e.g. [16, p.32])

$$\lim_{\tau \rightarrow 0} \eta(\tau) = (1 + 2e_{ij} \nu_i \nu_j)^{1/2} - 1, \quad 2e_{ij} = \frac{\partial u_k}{\partial x_i} \frac{\partial u_k}{\partial x_j} + \left( \frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right)$$

where  $\nu_i = \Delta x_i |\Delta \mathbf{x}|^{-1}$ . If the deformation is *small*, then we may consider that

$$(\partial u_k / \partial x_i)(\partial u_k / \partial x_i) \approx 0$$

and the following is called *small strain tensor*

$$\varepsilon_{ij}(u) = \frac{1}{2} \left( \frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right)$$

The tensor  $e_{ij}$  is called *finite strain tensor*.

Consider the small plane  $\Delta \Pi(\mathbf{x})$  centered at  $\mathbf{x}$  with the unit normal direction  $\mathbf{n} = (n_1, n_2, n_3)$ , then the surface on  $\Delta \Pi(\mathbf{x})$  at  $\mathbf{x}$  is

$$(\sigma_{1j}(\mathbf{x})n_j, \sigma_{2j}(\mathbf{x})n_j, \sigma_{3j}(\mathbf{x})n_j)$$

where  $\sigma_{ij}(\mathbf{x})$  is called *stress tensor* at  $\mathbf{x}$ . Hooke's law is the assumption of a linear relation between  $\sigma_{ij}$  and  $\varepsilon_{ij}$  such as

$$\sigma_{ij}(\mathbf{x}) = c_{ijkl}(\mathbf{x}) \varepsilon_{ij}(\mathbf{x})$$

with the symmetry  $c_{ijkl} = c_{jikl}, c_{ijkl} = c_{ijlk}, c_{ijkl} = c_{klij}$ .

If Hooke's tensor  $c_{ijkl}(\mathbf{x})$  do not depend on the choice of coordinate system, the material is called *isotropic* at  $\mathbf{x}$ . If  $c_{ijkl}$  is constant, the material is called *homogeneous*. In homogeneous isotropic case, there is *Lamé constants*  $\lambda, \mu$  (see e.g. [16, p.43]) satisfying

$$\sigma_{ij} = \lambda \delta_{ij} \text{div} u + 2\mu \varepsilon_{ij} \quad (9.20)$$

where  $\delta_{ij}$  is Kronecker's delta. We assume that the elastic plate is fixed on  $\Gamma_D \times ]-h, h[$ ,  $\Gamma_D \subset \partial \Omega$ . If the body force  $f = (f_1, f_2, f_3)$  is given in  $\Omega \times ]-h, h[$  and surface force  $g$  is given in  $\Gamma_N \times ]-h, h[$ ,  $\Gamma_N = \partial \Omega \setminus \overline{\Gamma_D}$ , then the equation of equilibrium is given as follows:

$$-\partial_j \sigma_{ij} = f_i \text{ in } \Omega \times ]-h, h[, \quad i = 1, 2, 3 \quad (9.21)$$

$$\sigma_{ij} n_j = g_i \text{ on } \Gamma_N \times ]-h, h[, \quad u_i = 0 \text{ on } \Gamma_D \times ]-h, h[, \quad i = 1, 2, 3 \quad (9.22)$$

We now explain the plain elasticity.

**Plain strain:** On the end of plate, the contact condition  $u_3 = 0$ ,  $g_3 =$  is satisfied. In this case, we can suppose that  $f_3 = g_3 = u_3 = 0$  and  $\mathbf{u}(x_1, x_2, x_3) = \bar{\mathbf{u}}(x_1, x_2)$  for all  $-h < x_3 < h$ .

**Plain stress:** The cylinder is assumed to be very thin and subjected to no load on the ends  $x_3 = \pm h$ , that is,

$$\sigma_{3i} = 0, \quad x_3 = \pm h, \quad i = 1, 2, 3$$

The assumption leads that  $\sigma_{3i} = 0$  in  $\Omega \times ]-h, h[$  and  $\mathbf{u}(x_1, x_2, x_3) = \bar{\mathbf{u}}(x_1, x_2)$  for all  $-h < x_3 < h$ .

**Generalized plain stress:** The cylinder is subjected to no load at  $x_3 = \pm h$ . Introducing the mean values with respect to thickness,

$$\bar{u}_i(x_1, x_2) = \frac{1}{2h} \int_{-h}^h u(x_1, x_2, x_3) dx_3$$

and we derive  $\bar{u}_3 \equiv 0$ . Similarly we define the mean values  $\bar{f}, \bar{g}$  of the body force and surface force as well as the mean values  $\bar{\varepsilon}_{ij}$  and  $\bar{\sigma}_{ij}$  of the components of stress and strain, respectively.

In what follows we omit the overlines of  $\bar{u}, \bar{f}, \bar{g}, \bar{\varepsilon}_{ij}$  and  $\bar{\sigma}_{ij}$ . Then we obtain similar equation of equilibrium given in (9.21) replacing  $\Omega \times ]-h, h[$  with  $\Omega$  and changing  $i = 1, 2$ . In the case of plane stress,  $\sigma_{ij} = \lambda^* \delta_{ij} \operatorname{div} u + 2\mu \varepsilon_{ij}$ ,  $\lambda^* = (2\lambda\mu)/(\lambda + \mu)$ .

The equations of elasticity are naturally written in variational form for the displacement vector  $u(x) \in V$  as

$$\int_{\Omega} [2\mu \varepsilon_{ij}(u) \varepsilon_{ij}(v) + \lambda \varepsilon_{ii}(u) \varepsilon_{jj}(v)] = \int_{\Omega} f \cdot v + \int_{\Gamma} g \cdot v, \forall v \in V$$

where  $V$  is the linear closed subspace of  $H^1(\Omega)^2$ .

**Example 9.13 (Beam.edp)** Consider elastic plate with the undeformed rectangle shape  $]0, 10[ \times ]0, 2[$ . The body force is the gravity force  $f$  and the boundary force  $g$  is zero on lower and upper side. On the two vertical sides of the beam are fixed.

```

//      a weighting beam sitting on a

int bottombeam = 2;
border a(t=2,0) { x=0; y=t ;label=1;};
border b(t=0,10) { x=t; y=0 ;label=bottombeam;};
border c(t=0,2) { x=10; y=t ;label=1;};
border d(t=0,10) { x=10-t; y=2; label=3;};
real E = 21.5;
real sigma = 0.29;
real mu = E/(2*(1+sigma));
real lambda = E*sigma/((1+sigma)*(1-2*sigma));
real gravity = -0.05;
mesh th = buildmesh( b(20)+c(5)+d(20)+a(5));
fespace Vh(th,[P1,P1]);
Vh [uu,vv], [w,s];
cout << "lambda,mu,gravity =" << lambda << " " << mu << " " << gravity << endl;
//      deformation of a beam under its own weight
//      see lame.edp example 3.9
real sqrt2=sqrt(2.);
macro epsilon(u1,u2) [dx(u1),dy(u2),(dy(u1)+dx(u2))/sqrt2] //      EOM
macro div(u,v) ( dx(u)+dy(v) ) //      EOM

solve bb([uu,vv],[w,s])=
    int2d(th)(
        lambda*div(w,s)*div(uu,vv)
        +2.*mu*( epsilon(w,s)'*epsilon(uu,vv) )
    )
    + int2d(th) (-gravity*s)
    + on(1,uu=0,vv=0)
;

plot([uu,vv],wait=1);
plot([uu,vv],wait=1,bb=[[-0.5,2.5],[2.5,-0.5]]);
mesh th1 = movemesh(th, [x+uu, y+vv]);
plot(th1,wait=1);

```

**Example 9.14 (beam-3d.edp)** Consider elastic box with the undeformed parallelepiped shape  $]0, 5[ \times ]0, 1[ \times ]0, 1[$ . The body force is the gravity force  $\mathbf{f}$  and the boundary force  $\mathbf{g}$  is zero on all face except one the one vertical left face where the beam is fixed.

```
include "cube.idp"
int[int] Nxyz=[20,5,5];
real [int,int] Bxyz=[[0.,5.],[0.,1.],[0.,1.]];
int [int,int] Lxyz=[[1,2],[2,2],[2,2]];
mesh3 Th=Cube(Nxyz,Bxyz,Lxyz);

real E = 21.5e4, sigma = 0.29;
real mu = E/(2*(1+sigma));
real lambda = E*sigma/((1+sigma)*(1-2*sigma));
real gravity = -0.05;

fespace Vh(Th, [P1,P1,P1]);
Vh [u1,u2,u3], [v1,v2,v3];
cout << "lambda,mu,gravity ="<<lambda<< " " << mu << " " << gravity << endl;

real sqrt2=sqrt(2.);
macro epsilon(u1,u2,u3) [dx(u1),dy(u2),dz(u3), (dz(u2)+dy(u3))/sqrt2,
                        (dz(u1)+dx(u3))/sqrt2, (dy(u1)+dx(u2))/sqrt2] // EOM
macro div(u1,u2,u3) ( dx(u1)+dy(u2)+dz(u3) ) // EOM

solve Lamé([u1,u2,u3], [v1,v2,v3])=
  int3d(Th)(
    lambda*div(u1,u2,u3)*div(v1,v2,v3)
    +2.*mu*( epsilon(u1,u2,u3)'*epsilon(v1,v2,v3) ) // ')
  )
  - int3d(Th) (gravity*v3)
  + on(1,u1=0,u2=0,u3=0)
  ;
real dmax= u1[].max;
cout << " max displacement = " << dmax << endl;
real coef= 0.1/dmax;
int[int] ref2=[1,0,2,0];
mesh3 Thm=movemesh3(Th,transfo=[x+u1*coef,y+u2*coef,z+u3*coef],label=ref2);
Thm=change(Thm,label=ref2);
plot(Th,Thm, wait=1,cmm="coef amplification = "+coef ); // see fig 9.13
```

### 9.2.1 Fracture Mechanics

Consider the plate with the crack whose undeformed shape is a curve  $\Sigma$  with the two edges  $\gamma_1, \gamma_2$ . We assume the stress tensor  $\sigma_{ij}$  is the state of plate stress regarding  $(x, y) \in \Omega_\Sigma = \Omega \setminus \Sigma$ . Here  $\Omega$  stands for the undeformed shape of elastic plate without crack. If the part  $\Gamma_N$  of the boundary  $\partial\Omega$  is fixed and a load  $\mathcal{L} = (\mathbf{f}, \mathbf{g}) \in L^2(\Omega)^2 \times L^2(\Gamma_N)^2$  is given, then the displacement  $\mathbf{u}$  is the minimizer of the potential energy functional

$$\mathcal{E}(\mathbf{v}; \mathcal{L}, \Omega_\Sigma) = \int_{\Omega_\Sigma} \{w(x, \mathbf{v}) - \mathbf{f} \cdot \mathbf{v}\} - \int_{\Gamma_N} \mathbf{g} \cdot \mathbf{v}$$

over the functional space  $V(\Omega_\Sigma)$ ,

$$V(\Omega_\Sigma) = \left\{ \mathbf{v} \in H^1(\Omega_\Sigma)^2; \mathbf{v} = 0 \quad \text{on } \Gamma_D = \partial\Omega \setminus \overline{\Gamma_N} \right\},$$



coef amplification = 3997.95




Figure 9.13: 3d Beam deformed and undeformed box

where  $w(x, \mathbf{v}) = \sigma_{ij}(\mathbf{v})\varepsilon_{ij}(\mathbf{v})/2$ ,

$$\sigma_{ij}(\mathbf{v}) = C_{ijkl}(x)\varepsilon_{kl}(\mathbf{v}), \quad \varepsilon_{ij}(\mathbf{v}) = (\partial v_i / \partial x_j + \partial v_j / \partial x_i) / 2, \quad (C_{ijkl} : \text{Hooke's tensor}).$$

If the elasticity is homogeneous isotropic, then the displacement  $\mathbf{u}(x)$  is decomposed in an open neighborhood  $U_k$  of  $\gamma_k$  as in (see e.g. [17])

$$\mathbf{u}(x) = \sum_{l=1}^2 K_l(\gamma_k) r_k^{1/2} S_{kl}^C(\theta_k) + \mathbf{u}_{k,R}(x) \quad \text{for } x \in \Omega_\Sigma \cap U_k, \quad k = 1, 2 \quad (9.23)$$

with  $\mathbf{u}_{k,R} \in H^2(\Omega_\Sigma \cap U_k)^2$ , where  $U_k$ ,  $k = 1, 2$  are open neighborhoods of  $\gamma_k$  such that  $\partial L_1 \cap U_1 = \gamma_1$ ,  $\partial L_m \cap U_2 = \gamma_2$ , and

$$\begin{aligned} S_{k1}^C(\theta_k) &= \frac{1}{4\mu} \frac{1}{(2\pi)^{1/2}} \begin{bmatrix} [2\kappa - 1] \cos(\theta_k/2) - \cos(3\theta_k/2) \\ -[2\kappa + 1] \sin(\theta_k/2) + \sin(3\theta_k/2) \end{bmatrix}, \\ S_{k2}^C(\theta_k) &= \frac{1}{4\mu} \frac{1}{(2\pi)^{1/2}} \begin{bmatrix} -[2\kappa - 1] \sin(\theta_k/2) + 3 \sin(3\theta_k/2) \\ -[2\kappa + 1] \cos(\theta_k/2) + \cos(3\theta_k/2) \end{bmatrix}. \end{aligned} \quad (9.24)$$

where  $\mu$  is the shear modulus of elasticity,  $\kappa = 3 - 4\nu$  ( $\nu$  is the Poisson's ratio) for plane strain and  $\kappa = \frac{3-\nu}{1+\nu}$  for plane stress.

The coefficients  $K_1(\gamma_i)$  and  $K_2(\gamma_i)$ , which are important parameters in fracture mechanics, are called stress intensity factors of the opening mode (mode I) and the sliding mode (mode II), respectively.

For simplicity, we consider the following simple crack

$$\Omega = \{(x, y) : -1 < x < 1, -1 < y < 1\}, \quad \Sigma = \{(x, y) : -1 \leq x \leq 0, y = 0\}$$

with only one crack tip  $\gamma = (0, 0)$ . Unfortunately, **FreeFem++** cannot treat crack, so we use the modification of the domain with U-shape channel (see Fig. 5.30) with  $d = 0.0001$ . The undeformed crack  $\Sigma$  is approximated by

$$\begin{aligned} \Sigma_d &= \{(x, y) : -1 \leq x \leq -10 * d, -d \leq y \leq d\} \\ &\cup \{(x, y) : -10 * d \leq x \leq 0, -d + 0.1 * x \leq y \leq d - 0.1 * x\} \end{aligned}$$



and  $\Gamma_D = R$  in Fig. 5.30. In this example, we use three technique:

- Fast Finite Element Interpolator from the mesh  $\text{Th}$  to  $\text{Zoom}$  for the scale-up of near  $\gamma$ .
- After obtaining the displacement vector  $\mathbf{u} = (u, v)$ , we shall watch the deformation of the crack near  $\gamma$  as follows,

```
mesh Plate = movemesh(Zoom, [x+u, y+v]);
plot(Plate);
```

- Adaptivity is an important technique here, because a large singularity occurs at  $\gamma$  as shown in (9.23).

The first example creates mode I deformation by the opposed surface force on  $B$  and  $T$  in the vertical direction of  $\Sigma$ , and the displacement is fixed on  $R$ .

In a laboratory, fracture engineers use photoelasticity to make stress field visible, which shows the principal stress difference

$$\sigma_1 - \sigma_2 = \sqrt{(\sigma_{11} - \sigma_{22})^2 + 4\sigma_{12}^2} \quad (9.25)$$

where  $\sigma_1$  and  $\sigma_2$  are the principal stresses. In opening mode, the photoelasticity make symmetric pattern concentrated at  $\gamma$ .

**Example 9.15 (Crack Opening,  $K_2(\gamma) = 0$ )** {CrackOpen.edp}

```
real d = 0.0001;
int n = 5;
real cb=1, ca=1, tip=0.0;
border L1(t=0, ca-d) { x=-cb; y=-d-t; }
border L2(t=0, ca-d) { x=-cb; y=ca-t; }
border B(t=0, 2) { x=cb*(t-1); y=-ca; }
border C1(t=0, 1) { x=-ca*(1-t)+(tip-10*d)*t; y=d; }
border C21(t=0, 1) { x=(tip-10*d)*(1-t)+tip*t; y=d*(1-t); }
border C22(t=0, 1) { x=(tip-10*d)*t+tip*(1-t); y=-d*t; }
border C3(t=0, 1) { x=(tip-10*d)*(1-t)-ca*t; y=-d; }
border C4(t=0, 2*d) { x=-ca; y=-d+t; }
border R(t=0, 2) { x=cb; y=cb*(t-1); }
border T(t=0, 2) { x=cb*(1-t); y=ca; }
mesh Th = buildmesh (L1(n/2)+L2(n/2)+B(n)
                    +C1(n)+C21(3)+C22(3)+C3(n)+R(n)+T(n));

cb=0.1; ca=0.1;
plot(Th, wait=1);
mesh Zoom = buildmesh (L1(n/2)+L2(n/2)+B(n)+C1(n)
                    +C21(3)+C22(3)+C3(n)+R(n)+T(n));

plot(Zoom, wait=1);
real E = 21.5;
real sigma = 0.29;
real mu = E/(2*(1+sigma));
real lambda = E*sigma/((1+sigma)*(1-2*sigma));
fespace Vh(Th, [P2, P2]);
fespace zVh(Zoom, P2);
Vh [u, v], [w, s];
solve Problem([u, v], [w, s]) =
  int2d(Th)(
    2*mu*(dx(u)*dx(w) + ((dx(v)+dy(u))*(dx(s)+dy(w)))/4 )
    + lambda*(dx(u)+dy(v))*(dx(w)+dy(s))/2
  )
```

```

-int1d(Th,T)(0.1*(4-x)*s)+int1d(Th,B)(0.1*(4-x)*s)
+on(R,u=0)+on(R,v=0); // fixed
;

zVh Sx, Sy, Sxy, N;
for (int i=1; i<=5; i++)
{
  mesh Plate = movemesh(Zoom,[x+u,y+v]); // deformation near  $\gamma$ 
  Sx = lambda*(dx(u)+dy(v)) + 2*mu*dx(u);
  Sy = lambda*(dx(u)+dy(v)) + 2*mu*dy(v);
  Sxy = mu*(dy(u) + dx(v));
  N = 0.1*1*sqrt((Sx-Sy)^2+4*Sxy^2); // principal stress difference
  if (i==1) {
    plot(Plate,ps="1stCOD.eps",bw=1); // Fig. 9.14
    plot(N,ps="1stPhoto.eps",bw=1); // Fig. 9.14
  } else if (i==5) {
    plot(Plate,ps="LastCOD.eps",bw=1); // Fig. 9.15
    plot(N,ps="LastPhoto.eps",bw=1); // Fig. 9.15
    break;
  }
  Th=adaptmesh(Th,[u,v]);
  Problem;
}

```







Figure 9.14: Crack open displacement (COD) and Principal stress difference in the first mesh      Figure 9.15: COD and Principal stress difference in the last adaptive mesh

It is difficult to create mode II deformation by the opposed shear force on  $B$  and  $T$  that is observed in a laboratory. So we use the body shear force along  $\Sigma$ , that is, the  $x$ -component  $f_1$  of the body force  $f$  is given by

$$f_1(x, y) = H(y - 0.001) * H(0.1 - y) - H(-y - 0.001) * H(y + 0.1)$$

where  $H(t) = 1$  if  $t > 0$ ;  $= 0$  if  $t < 0$ .

**Example 9.16 (Crack Sliding,  $K_2(\gamma) = 0$ )** (use the same mesh  $Th$ )

```

cb=0.01; ca=0.01;
mesh Zoom = buildmesh (L1(n/2)+L2(n/2)+B(n)+C1(n)
                        +C21(3)+C22(3)+C3(n)+R(n)+T(n));
(use same FE-space Vh and elastic modulus)
fespace Vh1(Th,P1);
Vh1 fx = ((y>0.001)*(y<0.1))-((y<-0.001)*(y>-0.1)) ;

```

```

solve Problem([u,v],[w,s]) =
    int2d(Th)(
        2*mu*(dx(u)*dx(w) + ((dx(v)+dy(u))*(dx(s)+dy(w)))/4 )
        + lambda*(dx(u)+dy(v))*(dx(w)+dy(s))/2
    )
    -int2d(Th)(fx*w)
    +on(R,u=0)+on(R,v=0); // fixed
;

for (int i=1; i<=3; i++)
{
    mesh Plate = movemesh(Zoom,[x+u,y+v]); // deformation near γ
    Sx = lambda*(dx(u)+dy(v)) + 2*mu*dx(u);
    Sy = lambda*(dx(u)+dy(v)) + 2*mu*dy(v);
    Sxy = mu*(dy(u) + dx(v));
    N = 0.1*1*sqrt((Sx-Sy)^2+4*Sxy^2); // principal stress difference
    if (i==1) {
        plot(Plate,ps="1stCOD2.eps",bw=1); // Fig. 9.17
        plot(N,ps="1stPhoto2.eps",bw=1); // Fig. 9.16
    } else if (i==3) {
        plot(Plate,ps="LastCOD2.eps",bw=1); // Fig. 9.17
        plot(N,ps="LastPhoto2.eps",bw=1); // Fig. 9.17
        break;
    }
    Th=adaptmesh(Th,[u,v]);
    Problem;
}

```





Figure 9.16: (COD) and Principal stress difference in the first mesh





Figure 9.17: COD and Principal stress difference in the last adaptive mesh

## 9.3 Nonlinear Static Problems

Here we propose to solve the following non-linear academic problem of minimization of a functional

$$J(u) = \int_{\Omega} \frac{1}{2} f(|\nabla u|^2) - u * b$$

where  $u$  is function of  $H_0^1(\Omega)$  and  $f$  defined by

$$f(x) = a * x + x - \ln(1 + x), \quad f'(x) = a + \frac{x}{1 + x}, \quad f''(x) = \frac{1}{(1 + x)^2}$$

### 9.3.1 Newton-Raphson algorithm

Now, we solve the Euler problem  $\nabla J(u) = 0$  with Newton-Raphson algorithm, that is,

$$u^{n+1} = u^n - (\nabla^2 J(u^n))^{-1} * \nabla J(u^n)$$

First we introduce the two variational form  $\text{vdJ}$  and  $\text{vhJ}$  to compute respectively  $\nabla J$  and  $\nabla^2 J$

```
//      method of Newton-Raphson to solve dJ(u)=0;
//
//      u^{n+1} = u^n - (\frac{\partial dJ}{\partial u_i})^{-1} * dJ(u^n)
//
//      -----
//      Ph dalpha ; //      to store 2f''(|\nabla u|^2) optimisation
//
//      the variational form of evaluate dJ = \nabla J
//      -----
//      dJ = f'()*( dx(u)*dx(vh) + dy(u)*dy(vh)
//      varf vdJ(uh,vh) = int2d(Th)( alpha*( dx(u)*dx(vh) + dy(u)*dy(vh) ) - b*vh)
//      + on(1,2,3,4, uh=0);
//
//      the variational form of evaluate ddJ = \nabla^2 J
//      hJ(uh,vh) = f'()*( dx(uh)*dx(vh) + dy(uh)*dy(vh)
//      + 2*f''()*( dx(u)*dx(uh) + dy(u)*dy(uh) ) * (dx(u)*dx(vh) + dy(u)*dy(vh))
//      varf vhJ(uh,vh) = int2d(Th)( alpha*( dx(uh)*dx(vh) + dy(uh)*dy(vh) )
//      + dalpha*( dx(u)*dx(vh) + dy(u)*dy(vh) )*( dx(u)*dx(uh) + dy(u)*dy(uh) ) )
//      + on(1,2,3,4, uh=0);
//
//      the Newton algorithm
//      Vh v,w;
//      u=0;
//      for (int i=0;i<100;i++)
//      {
//          alpha = df( dx(u)*dx(u) + dy(u)*dy(u) ) ; //      optimization
//          dalpha = 2*ddf( dx(u)*dx(u) + dy(u)*dy(u) ) ; //      optimization
//          v[] = vdJ(0,Vh); //      v = \nabla J(u)
//          real res = v[]'*v[]; //      the dot product
//          cout << i << " residu^2 = " << res << endl;
//          if( res< 1e-12) break;
//          matrix H= vhJ(Vh,Vh,factorize=1,solver=LU); //
//          w[] = H^-1*v[];
//          u[] -= w[];
//      }
//      plot (u,wait=1,cmm="solution with Newton-Raphson");
```

Remark: This example is in `Newton.edp` file of `examples++-tutorial` directory.

## 9.4 Eigenvalue Problems

This section depends on your installation of FreeFem++; you need to have compiled (see README\_arpack), ARPACK. This tools is available in FreeFem++ if the word “eigenvalue” appear in line “Load:”, like:

```
-- FreeFem++ v1.28 (date Thu Dec 26 10:56:34 CET 2002)
file : LapEigenValue.edp
Load: lg_fem lg_mesh eigenvalue
```

This tools is based on the `arpack++`<sup>1</sup> the object-oriented version of ARPACK eigenvalue package [1]. The function `EigenValue` computes the generalized eigenvalue of  $Au = \lambda Bu$  where  $\sigma = \sigma$  is the shift of the method. The matrix  $OP$  is defined with  $A - \sigma B$ . The return value is the number of converged eigenvalue (can be greater than the number of eigen value `nev`=)

```
int k=EigenValue(OP,B,nev= , sigma= );
```

where the matrix  $OP = A - \sigma B$  with a solver and boundary condition, and the matrix  $B$ .

### Note 9.1 Boundary condition and Eigenvalue Problems

*The locking (Dirichlet ) boundary condition is make with exact penalization so we put  $1e30=10^{30}$  on the diagonal term of the locked degree of freedom (see equation (6.20)). So take Dirichlet boundary condition just on  $A$  and not on  $B$ . because we solve  $w = OP^{-1} * B * v$ .*

*If you put locking (Dirichlet ) boundary condition on  $B$  matrix (with key work **on**) you get small spurious modes ( $10^{-30}$ ), due to boundary condition, but if you forget the locking boundary condition on  $B$  matrix (no key work "on") you get huge spurious ( $10^{30}$ ) modes associated to these boundary conditons. We compute only small mode, so we get the good one in this case.*

**sym**= the problem is symmetric (all the eigen value are real)

**nev**= the number desired eigenvalues (nev) close to the shift.

**value**= the array to store the real part of the eigenvalues

**ivalue**= the array to store the imag. part of the eigenvalues

**vector**= the FE function array to store the eigenvectors

**rawvector**= an array of type `real[int,int]` to store eigenvectors by column. (up to version 2-17).

For real non symmetric problems, complex eigenvectors are given as two consecutive vectors, so if eigenvalue  $k$  and  $k + 1$  are complex conjugate eigenvalues, the  $k$ th vector will contain the real part and the  $k + 1$ th vector the imaginary part of the corresponding complex conjugate eigenvectors.

**tol**= the relative accuracy to which eigenvalues are to be determined;

**sigma**= the shift value;

**maxit**= the maximum number of iterations allowed;

**ncv**= the number of Arnoldi vectors generated at each iteration of ARPACK.

---

<sup>1</sup><http://www.caam.rice.edu/software/ARPACK/>

**Example 9.17 (lapEigenValue.edp)** In the first example, we compute the eigenvalues and the eigenvectors of the Dirichlet problem on square  $\Omega = ]0, \pi[^2$ .

The problem is to find:  $\lambda$ , and  $\nabla u_\lambda$  in  $\mathbb{R} \times H_0^1(\Omega)$

$$\int_{\Omega} \nabla u_\lambda \nabla v = \lambda \int_{\Omega} uv \quad \forall v \in H_0^1(\Omega)$$

The exact eigenvalues are  $\lambda_{n,m} = (n^2 + m^2), (n, m) \in \mathbb{N}_*^2$  with the associated eigenvectors are  $u_{m,n} = \sin(nx) * \sin(my)$ .

We use the generalized inverse shift mode of the `arpack++` library, to find 20 eigenvalues and eigenvectors close to the shift value  $\sigma = 20$ .

```
//      Computation of the eigen value and eigen vector of the
//      Dirichlet problem on square ]0,π[²
//      -----
//      we use the inverse shift mode
//      the shift is given with the real sigma
//      -----
//      find λ and u_λ ∈ H_0¹(Ω) such that:
//      ∫_Ω ∇u_λ ∇v = λ ∫_Ω u_λ v, ∀ v ∈ H_0¹(Ω)
verbosity=10;
mesh Th=square(20,20,[pi*x,pi*y]);
fespace Vh(Th,P2);
Vh u1,u2;

real sigma = 20;                                     //      value of the shift

//      OP = A - sigma B ; // the shifted matrix
varf op(u1,u2)= int2d(Th)( dx(u1)*dx(u2) + dy(u1)*dy(u2) - sigma* u1*u2 )
                    + on(1,2,3,4,u1=0) ;              //      Boundary condition

varf b([u1],[u2]) = int2d(Th)( u1*u2 );              //      no Boundary condition see note 9.1
matrix OP= op(Vh,Vh,solver=Crout,factorize=1);        //      crout solver because the matrix in
not positive
matrix B= b(Vh,Vh,solver=CG,eps=1e-20);

//      important remark:
//      the boundary condition is make with exact penalization:
//      we put 1e30=lgv on the diagonal term of the lock degree of freedom.
//      So take Dirichlet boundary condition just on a variational form
//      and not on b variational form.
//      because we solve w = OP⁻¹ * B * v

int nev=20;                                           //      number of computed eigen value close to sigma

real[int] ev(nev);                                   //      to store the nev eigenvalue
Vh[int] eV(nev);                                     //      to store the nev eigenvector

int k=EigenValue(OP,B,sym=true,sigma=sigma,value=ev,vector=eV,
tol=1e-10,maxit=0,ncv=0);

//      tol= the tolerance
//      maxit= the maximum iteration see arpack doc.
//      ncv see arpack doc. http://www.caam.rice.edu/software/ARPACK/
```

```

//    the return value is number of converged eigen value.

for (int i=0;i<k;i++)
{
    u1=eV[i];
    real gg = int2d(Th)(dx(u1)*dx(u1) + dy(u1)*dy(u1));
    real mm= int2d(Th)(u1*u1) ;
    cout << " ---- " << i<< " " << ev[i]<< " err= "
        <<int2d(Th)(dx(u1)*dx(u1) + dy(u1)*dy(u1) - (ev[i])*u1*u1) << " --- "<<endl;
    plot(eV[i],cmm="Eigen Vector "+i+" valeur =" + ev[i] ,wait=1,value=1);
}

```

*The output of this example is:*

```

Nb of edges on Mortars = 0
Nb of edges on Boundary = 80, neb = 80
Nb Of Nodes = 1681
Nb of DF = 1681
Real symmetric eigenvalue problem: A*x - B*x*lambda

```

```

Thanks to ARPACK++ class ARrcSymGenEig
Real symmetric eigenvalue problem: A*x - B*x*lambda
Shift and invert mode sigma=20

```

```

Dimension of the system          : 1681
Number of 'requested' eigenvalues : 20
Number of 'converged' eigenvalues : 20
Number of Arnoldi vectors generated: 41
Number of iterations taken       : 2

```

Eigenvalues:

```

lambda[1]: 5.0002
lambda[2]: 8.00074
lambda[3]: 10.0011
lambda[4]: 10.0011
lambda[5]: 13.002
lambda[6]: 13.0039
lambda[7]: 17.0046
lambda[8]: 17.0048
lambda[9]: 18.0083
lambda[10]: 20.0096
lambda[11]: 20.0096
lambda[12]: 25.014
lambda[13]: 25.0283
lambda[14]: 26.0159
lambda[15]: 26.0159
lambda[16]: 29.0258
lambda[17]: 29.0273
lambda[18]: 32.0449
lambda[19]: 34.049
lambda[20]: 34.0492

```

```

---- 0 5.0002 err= -0.000225891 ---

```

```

---- 1 8.00074 err= -0.000787446 ---
---- 2 10.0011 err= -0.00134596 ---
---- 3 10.0011 err= -0.00134619 ---
---- 4 13.002 err= -0.00227747 ---
---- 5 13.0039 err= -0.004179 ---
---- 6 17.0046 err= -0.00623649 ---
---- 7 17.0048 err= -0.00639952 ---
---- 8 18.0083 err= -0.00862954 ---
---- 9 20.0096 err= -0.0110483 ---
---- 10 20.0096 err= -0.0110696 ---
---- 11 25.014 err= -0.0154412 ---
---- 12 25.0283 err= -0.0291014 ---
---- 13 26.0159 err= -0.0218532 ---
---- 14 26.0159 err= -0.0218544 ---
---- 15 29.0258 err= -0.0311961 ---
---- 16 29.0273 err= -0.0326472 ---
---- 17 32.0449 err= -0.0457328 ---
---- 18 34.049 err= -0.0530978 ---
---- 19 34.0492 err= -0.0536275 ---

```





Figure 9.18: Isovalue of 11th eigenvector  $u_{4,3} - u_{3,4}$

Figure 9.19: Isovalue of 12th eigenvector  $u_{4,3} + u_{3,4}$

## 9.5 Evolution Problems

FreeFem++ also solves evolution problems such as the heat equation:

$$\begin{aligned}
 \frac{\partial u}{\partial t} - \mu \Delta u &= f \quad \text{in } \Omega \times ]0, T[, \\
 u(x, 0) &= u_0(x) \quad \text{in } \Omega; \quad (\partial u / \partial n)(x, t) = 0 \quad \text{on } \partial\Omega \times ]0, T[.
 \end{aligned} \tag{9.26}$$



with a positive viscosity coefficient  $\mu$  and homogeneous Neumann boundary conditions. We solve (9.26) by FEM in space and finite differences in time. We use the definition of the partial derivative of the solution in the time derivative,

$$\frac{\partial u}{\partial t}(x, y, t) = \lim_{\tau \rightarrow 0} \frac{u(x, y, t) - u(x, y, t - \tau)}{\tau}$$

which indicates that  $u^m(x, y) = u(x, y, m\tau)$  will satisfy approximatively

$$\frac{\partial u}{\partial t}(x, y, m\tau) \simeq \frac{u^m(x, y) - u^{m-1}(x, y)}{\tau}$$

The time discretization of heat equation (9.27) is as follows:

$$\begin{aligned} \frac{u^{m+1} - u^m}{\tau} - \mu \Delta u^{m+1} &= f^{m+1} \quad \text{in } \Omega \\ u^0(x) &= u_0(x) \quad \text{in } \Omega; \quad \partial u^{m+1} / \partial n(x) = 0 \quad \text{on } \partial\Omega, \quad \text{for all } m = 0, \dots, [T/\tau], \end{aligned} \quad (9.27)$$

which is so-called *backward Euler method* for (9.27). To obtain the variational formulation, multiply with the test function  $v$  both sides of the equation:

$$\int_{\Omega} \{u^{m+1}v - \tau \Delta u^{m+1}v\} = \int_{\Omega} \{u^m + \tau f^{m+1}\}v.$$

By the divergence theorem, we have

$$\int_{\Omega} \{u^{m+1}v + \tau \nabla u^{m+1} \cdot \nabla v\} - \int_{\partial\Omega} \tau (\partial u^{m+1} / \partial n) v = \int_{\Omega} \{u^m v + \tau f^{m+1}v\}.$$

By the boundary condition  $\partial u^{m+1} / \partial n = 0$ , it follows that

$$\int_{\Omega} \{u^{m+1}v + \tau \nabla u^{m+1} \cdot \nabla v\} - \int_{\Omega} \{u^m v + \tau f^{m+1}v\} = 0. \quad (9.28)$$

Using the identity just above, we can calculate the finite element approximation  $u_h^m$  of  $u^m$  in a step-by-step manner with respect to  $t$ .

**Example 9.18** We now solve the following example with the exact solution  $u(x, y, t) = tx^4$ .

$$\begin{aligned} \frac{\partial u}{\partial t} - \mu \Delta u &= x^4 - \mu 12tx^2 \quad \text{in } \Omega \times ]0, 3[, \quad \Omega = ]0, 1[^2 \\ u(x, y, 0) &= 0 \quad \text{on } \Omega, \quad u|_{\partial\Omega} = t * x^4 \end{aligned}$$

```

//      heat equation  $\partial_t u = -\mu \Delta u = x^4 - \mu 12tx^2$ 

mesh Th=square(16,16);
fespace Vh(Th,P1);

Vh u,v,uu,f,g;
real dt = 0.1, mu = 0.01;
problem dHeat(u,v) =
  int2d(Th) ( u*v + dt*mu*(dx(u)*dx(v) + dy(u)*dy(v)))
  + int2d(Th) (- uu*v - dt*f*v )
  + on(1,2,3,4,u=g);

real t = 0;
uu = 0;
//      start from t=0
//      u(x,y,0)=0

```

```

for (int m=0;m<=3/dt;m++)
{
    t=t+dt;
    f = x^4-mu*t*12*x^2;
    g = t*x^4;
    dHeat;
    plot(u,wait=true);
    uu = u;
    cout <<"t="<<t<<"L^2-Error="<<sqrt( int2d(Th)((u-t*x^4)^2) ) << endl;
}

```

In the last statement, the  $L^2$ -error  $\left(\int_{\Omega} |u - tx^4|^2\right)^{1/2}$  is calculated at  $t = m\tau$ ,  $\tau = 0.1$ . At  $t = 0.1$ , the error is 0.000213269. The errors increase with  $m$  and 0.00628589 at  $t = 3$ .

The iteration of the backward Euler (9.28) is made by **for loop** (see Section 4.9).

**Note 9.2** The stiffness matrix in the loop is used over and over again. **FreeFem++** support reuses of stiffness matrix.

### 9.5.1 Mathematical Theory on Time Difference Approximations.

In this section, we show the advantage of implicit schemes. Let  $V, H$  be separable Hilbert space and  $V$  is dense in  $H$ . Let  $a$  be a continuous bilinear form over  $V \times V$  with coercivity and symmetry. Then  $\sqrt{a(v, v)}$  become equivalent to the norm  $\|v\|$  of  $V$ .

**Problem Ev**( $f, \Omega$ ): For a given  $f \in L^2(0, T; V')$ ,  $u^0 \in H$

$$\begin{aligned} \frac{d}{dt}(u(t), v) + a(u(t), v) &= (f(t), v) \quad \forall v \in V, \quad a.e. t \in [0, T] \\ u(0) &= u^0 \end{aligned} \quad (9.29)$$

where  $V'$  is the dual space of  $V$ . Then, there is an unique solution  $u \in L^\infty(0, T; H) \cap L^2(0, T; V)$ .

Let us denote the time step by  $\tau > 0$ ,  $N_T = [T/\tau]$ . For the discretization, we put  $u^n = u(n\tau)$  and consider the time difference for each  $\theta \in [0, 1]$

$$\begin{aligned} \frac{1}{\tau} (u_h^{n+1} - u_h^n, \phi_i) + a(u_h^{n+\theta}, \phi_i) &= \langle f^{n+\theta}, \phi_i \rangle \\ i &= 1, \dots, m, \quad n = 0, \dots, N_T \\ u_h^{n+\theta} &= \theta u_h^{n+1} + (1 - \theta) u_h^n, \quad f^{n+\theta} = \theta f^{n+1} + (1 - \theta) f^n \end{aligned} \quad (9.30)$$

Formula (9.30) is the *forward Euler scheme* if  $\theta = 0$ , *Crank-Nicolson scheme* if  $\theta = 1/2$ , the *backward Euler scheme* if  $\theta = 1$ .

Unknown vectors  $u^n = (u_h^1, \dots, u_h^M)^T$  in

$$u_h^n(x) = u_1^n \phi_1(x) + \dots + u_m^n \phi_m(x), \quad u_1^n, \dots, u_m^n \in \mathbb{R}$$

are obtained from solving the matrix

$$\begin{aligned} (M + \theta \tau A) u^{n+1} &= \{M - (1 - \theta) \tau A\} u^n + \tau \{\theta f^{n+1} + (1 - \theta) f^n\} \\ M &= (m_{ij}), \quad m_{ij} = (\phi_j, \phi_i), \quad A = (a_{ij}), \quad a_{ij} = a(\phi_j, \phi_i) \end{aligned} \quad (9.31)$$

Refer [22, pp.70–75] for solvability of (9.31). The stability of (9.31) is in [22, Theorem 2.13]:

Let  $\{\mathcal{T}_h\}_{h>0}$  be regular triangulations (see Section 5.4). Then there is a number  $c_0 > 0$  independent of  $h$  such that,

$$|u_h^n|^2 \leq \begin{cases} \frac{1}{\delta} \left\{ |u_h^0|^2 + \tau \sum_{k=0}^{n-1} \|f^{k+\theta}\|_{V_h'}^2 \right\} & \theta \in [0, 1/2) \\ |u_h^0|^2 + \tau \sum_{k=0}^{n-1} \|f^{k+\theta}\|_{V_h'}^2 & \theta \in [1/2, 1] \end{cases} \quad (9.32)$$

if the following are satisfied:

1. When  $\theta \in [0, 1/2)$ , then we can take a time step  $\tau$  in such a way that

$$\tau < \frac{2(1-\delta)}{(1-2\theta)c_0^2} h^2 \quad (9.33)$$

for arbitrary  $\delta \in (0, 1)$ .

2. When  $1/2 \leq \theta \leq 1$ , we can take  $\tau$  arbitrary.

### Example 9.19

```

mesh Th=square(12,12);
fespace Vh(Th,P1);
fespace Ph(Th,P0);

Ph h = hTriangle; // mesh sizes for each triangle
real tau = 0.1, theta=0.;
func real f(real t) {
    return x^2*(x-1)^2 + t*(-2 + 12*x - 11*x^2 - 2*x^3 + x^4);
}
ofstream out("err02.csv"); // file to store calculations
out << "mesh size = "<<h[.max]<<", time step = "<<tau<<endl;
for (int n=0;n<5/tau;n++) \
    out<<n*tau<<",";
out << endl;
Vh u,v,oldU;
Vh f1, f0;
problem aTau(u,v) =
    int2d(Th) ( u*v + theta*tau*(dx(u)*dx(v) + dy(u)*dy(v) + u*v))
    - int2d(Th) (oldU*v - (1-theta)*tau*(dx(oldU)*dx(v)+dy(oldU)*dy(v)+oldU*v))
    - int2d(Th) (tau*( theta*f1+(1-theta)*f0 )*v );

while (theta <= 1.0) {
    real t = 0, T=3; // from t=0 to T
    oldU = 0; // u(x,y,0)=0
    out <<theta<<",";
    for (int n=0;n<T/tau;n++) {
        t = t+tau;
        f0 = f(n*tau); f1 = f((n+1)*tau);
        aTau;
        oldU = u;
        plot(u);
        Vh uex = t*x^2*(1-x)^2; // exact sol.= tx^2(1-x)^2
        Vh err = u - uex; // err = FE-sol - exact
        out<< abs(err[.max])/abs(uex[.max]) <<","; // ||err||_{L^\infty(\Omega)}/||u_{ex}||_{L^\infty(\Omega)}
    }
    out << endl;

```




Figure 9.20:  $\max_{x \in \Omega} |u_h^n(\theta) - u_{ex}(n\tau)| / \max_{x \in \Omega} |u_{ex}(n\tau)|$  at  $n = 0, 1, \dots, 29$

```

    theta = theta + 0.1;
}

```

We can see in Fig. 9.20 that  $u_h^n(\theta)$  become unstable at  $\theta = 0.4$ , and figures are omitted in the case  $\theta < 0.4$ .

## 9.5.2 Convection

The hyperbolic equation

$$\partial_t u + \alpha \cdot \nabla u = f; \text{ for a vector-valued function } \alpha, \quad (9.34)$$

appears frequently in scientific problems, for example in the Navier-Stokes equations, in the Convection-Diffusion equation, etc.

In the case of 1-dimensional space, we can easily find the general solution  $(x, t) \mapsto u(x, t) = u^0(x - \alpha t)$  of the following equation, if  $\alpha$  is constant,

$$\partial_t u + \alpha \partial_x u = 0, \quad u(x, 0) = u^0(x), \quad (9.35)$$

because  $\partial_t u + \alpha \partial_x u = -\alpha \dot{u}^0 + \alpha \dot{u}^0 = 0$ , where  $\dot{u}^0 = du^0(x)/dx$ . Even if  $\alpha$  is not constant, the construction works on similar principles. One begins with the ordinary differential equation (with the convention that  $\alpha$  is prolonged by zero apart from  $(0, L) \times (0, T)$ ):

$$\dot{X}(\tau) = +\alpha(X(\tau), \tau), \quad \tau \in (0, t) \quad X(t) = x$$

In this equation  $\tau$  is the variable and  $x, t$  are parameters, and we denote the solution by  $X_{x,t}(\tau)$ . Then it is noticed that  $(x, t) \rightarrow v(X(\tau), \tau)$  in  $\tau = t$  satisfies the equation

$$\partial_t v + \alpha \partial_x v = \partial_t X \dot{v} + \alpha \partial_x X \dot{v} = 0$$

and by the definition  $\partial_t X = \dot{X} = +\alpha$  and  $\partial_x X = \partial_x x$  in  $\tau = t$ , because if  $\tau = t$  we have  $X(\tau) = x$ . The general solution of (9.35) is thus the value of the boundary condition in  $X_{x,t}(0)$ , that is to say  $u(x, t) = u^0(X_{x,t}(0))$  where  $X_{x,t}(0)$  is on the  $x$  axis,  $u(x, t) = u^0(X_{x,t}(0))$  if  $X_{x,t}(0)$  is on the axis of  $t$ .

In higher dimension  $\Omega \subset \mathbb{R}^d$ ,  $d = 2, 3$ , the equation for the convection is written

$$\partial_t u + \alpha \cdot \nabla u = 0 \text{ in } \Omega \times (0, T)$$

where  $\mathbf{a}(x, t) \in \mathbb{R}^d$ . FreeFem++ implements the Characteristic-Galerkin method for convection operators. Recall that the equation (9.34) can be discretized as

$$\frac{Du}{Dt} = f \quad \text{i.e.} \quad \frac{du}{dt}(X(t), t) = f(X(t), t) \quad \text{where} \quad \frac{dX}{dt}(t) = \alpha(X(t), t)$$

where  $D$  is the total derivative operator. So a good scheme is one step of backward convection by the method of Characteristics-Galerkin

$$\frac{1}{\tau} (u^{m+1}(x) - u^m(X^m(x))) = f^m(x) \quad (9.36)$$

where  $X^m(x)$  is an approximation of the solution at  $t = m\tau$  of the ordinary differential equation

$$\frac{dX}{dt}(t) = \alpha^m(X(t)), \quad X((m+1)\tau) = x.$$

where  $\alpha^m(x) = (\alpha_1(x, m\tau), \alpha_2(x, m\tau))$ . Because, by Taylor's expansion, we have

$$\begin{aligned} u^m(X(m\tau)) &= u^m(X((m+1)\tau)) - \tau \sum_{i=1}^d \frac{\partial u^m}{\partial x_i}(X((m+1)\tau)) \frac{\partial X_i}{\partial t}((m+1)\tau) + o(\tau) \\ &= u^m(x) - \tau \alpha^m(x) \cdot \nabla u^m(x) + o(\tau) \end{aligned} \quad (9.37)$$

where  $X_i(t)$  are the  $i$ -th component of  $X(t)$ ,  $u^m(x) = u(x, m\tau)$  and we used the chain rule and  $x = X((m+1)\tau)$ . From (9.37), it follows that

$$u^m(X^m(x)) = u^m(x) - \tau \alpha^m(x) \cdot \nabla u^m(x) + o(\tau). \quad (9.38)$$

Also we apply Taylor's expansion for  $t \mapsto u^m(x - \alpha^m(x)t)$ ,  $0 \leq t \leq \tau$ , then

$$u^m(x - \alpha\tau) = u^m(x) - \tau \alpha^m(x) \cdot \nabla u^m(x) + o(\tau).$$

Putting

$$\text{convect}(\alpha, -\tau, u^m) \approx u^m(x - \alpha^m\tau),$$

we can get the approximation

$$u^m(X^m(x)) \approx \text{convect}([a_1^m, a_2^m], -\tau, u^m) \quad \text{by } X^m \approx x \mapsto x - \tau[a_1^m(x), a_2^m(x)].$$

A classical convection problem is that of the “rotating bell” (quoted from [14][p.16]). Let  $\Omega$  be the unit disk centered at 0, with its center rotating with speed  $\alpha_1 = y$ ,  $\alpha_2 = -x$ . We consider the problem (9.34) with  $f = 0$  and the initial condition  $u(x, 0) = u^0(x)$ , that is, from (9.36)

$$u^{m+1}(x) = u^m(X^m(x)) \approx \text{convect}(\alpha, -\tau, u^m).$$

The exact solution is  $u(x, t) = u(X(t))$  where  $X$  equals  $x$  rotated around the origin by an angle  $\theta = -t$  (rotate in clockwise). So, if  $u^0$  in a 3D perspective looks like a bell, then  $u$  will have exactly the same shape, but rotated by the same amount. The program consists in solving the equation until  $T = 2\pi$ , that is for a full revolution and to compare the final solution with the initial one; they should be equal.

**Example 9.20 (convect.edp)** `border C(t=0, 2*pi) { x=cos(t); y=sin(t); }; // the unit circle`  
`mesh Th = buildmesh(C(70)); // triangulates the disk`  
`fespace Vh(Th, P1);`  
`Vh u0 = exp(-10*((x-0.3)^2 + (y-0.3)^2)); // give u^0`

```

real dt = 0.17, t=0;
Vh a1 = -y, a2 = x;
Vh u;
for (int m=0; m<2*pi/dt ; m++) {
    t += dt;
    u=convect([a1,a2],-dt,u0);
    u0=u;
    plot(u,cmm=" t="+t + ", min=" + u[].min + ", max=" + u[].max,wait=0);
};

```

// time step  
 // rotation velocity  
 //  $u^{m+1}$   
  
 //  $u^{m+1} = u^m(X^m(x))$   
 //  $m++$

**Note 9.3** The scheme *convect* is unconditionally stable, then the bell become lower and lower (the maximum of  $u^{37}$  is 0.406 as shown in Fig. 9.22).

convection: t=0, min=1.55289e-09, max=0.983612




Figure 9.21:  $u^0 = e^{-10((x-0.3)^2 + (y-0.3)^2)}$

convection: t=6.29, min=1.55289e-09, max=0.40659m=37




Figure 9.22: The bell at  $t = 6.29$

### 9.5.3 2D Black-Scholes equation for an European Put option

In mathematical finance, an option on two assets is modeled by a Black-Scholes equations in two space variables, (see for example Wilmott et al[39] or Achdou et al [3]).

$$\begin{aligned}
 \partial_t u + \frac{(\sigma_1 x)^2}{2} \frac{\partial^2 u}{\partial x^2} + \frac{(\sigma_2 y)^2}{2} \frac{\partial^2 u}{\partial y^2} \\
 + \rho xy \frac{\partial^2 u}{\partial x \partial y} + rS_1 \frac{\partial u}{\partial x} + rS_2 \frac{\partial u}{\partial y} - rP = 0
 \end{aligned} \tag{9.39}$$

which is to be integrated in  $(0, T) \times \mathbb{R}^+ \times \mathbb{R}^+$  subject to, in the case of a put

$$u(x, y, T) = (K - \max(x, y))^+. \tag{9.40}$$

Boundary conditions for this problem may not be so easy to devise. As in the one dimensional case the PDE contains boundary conditions on the axis  $x_1 = 0$  and on the axis  $x_2 = 0$ , namely two one dimensional Black-Scholes equations driven respectively by the data  $u(0, +\infty, T)$  and  $u(+\infty, 0, T)$ . These will be automatically accounted for because they are embedded in the PDE. So if we do nothing in the variational form (i.e. if we take a Neumann boundary condition at these two axis in the strong form) there will be no disturbance to these. At infinity in one of the variable, as in 1D, it makes sense to impose  $u = 0$ . We take

$$\sigma_1 = 0.3, \quad \sigma_2 = 0.3, \quad \rho = 0.3, \quad r = 0.05, \quad K = 40, \quad T = 0.5 \tag{9.41}$$

An implicit Euler scheme is used and a mesh adaptation is done every 10 time steps. To have an unconditionally stable scheme, the first order terms are treated by the Characteristic Galerkin method, which, roughly, approximates

$$\frac{\partial u}{\partial t} + a_1 \frac{\partial u}{\partial x} + a_2 \frac{\partial u}{\partial y} \approx \frac{1}{\tau} (u^{n+1}(x) - u^n(x - \alpha\tau)) \quad (9.42)$$

**Example 9.21** [BlackSchol.edp]

```

// file BlackScholes2D.edp

int m=30,L=80,LL=80, j=100;
real sigx=0.3, sigy=0.3, rho=0.3, r=0.05, K=40, dt=0.01;
mesh th=square(m,m,[L*x,LL*y]);
fespace Vh(th,P1);

Vh u=max(K-max(x,y),0.);
Vh xveloc, yveloc, v,uold;

for (int n=0; n*dt <= 1.0; n++)
{
  if(j>20) { th = adaptmesh(th,u,verbosity=1,abserror=1,nbjacoby=2,
    err=0.001, nbvx=5000, omega=1.8, ratio=1.8, nbsmooth=3,
    splitpbedge=1, maxsubdiv=5,rescaling=1) ;
    j=0;
    xveloc = -x*r+x*sigx^2+x*rho*sigx*sigy/2;
    yveloc = -y*r+y*sigy^2+y*rho*sigx*sigy/2;
    u=u;
  };
  uold=u;
  solve eq1(u,v,init=j,solver=LU) = int2d(th)( u*v*(r+1/dt)
    + dx(u)*dx(v)*(x*sigx)^2/2 + dy(u)*dy(v)*(y*sigy)^2/2
    + (dy(u)*dx(v) + dx(u)*dy(v))*rho*sigx*sigy*x*y/2)
    - int2d(th)( v*convect([xveloc,yveloc],dt,w)/dt) + on(2,3,u=0);

  j=j+1;
};
plot(u,wait=1,value=1);

```

Results are shown on Fig. 9.21).

## 9.6 Navier-Stokes Equation

### 9.6.1 Stokes and Navier-Stokes

The Stokes equations are: for a given  $f \in L^2(\Omega)^2$ ,

$$\left. \begin{aligned} -\Delta \mathbf{u} + \nabla p &= \mathbf{f} \\ \nabla \cdot \mathbf{u} &= 0 \end{aligned} \right\} \quad \text{in } \Omega \quad (9.43)$$

where  $\mathbf{u} = (u_1, u_2)$  is the velocity vector and  $p$  the pressure. For simplicity, let us choose Dirichlet boundary conditions on the velocity,  $\mathbf{u} = \mathbf{u}_\Gamma$  on  $\Gamma$ .




Figure 9.23: The adapted triangulation




Figure 9.24: The level line of the European basquet put option

In Temam [Theorem 2.2], there is a weak form of (9.43): Find  $\mathbf{v} = (v_1, v_2) \in \mathbf{V}(\Omega)$

$$\mathbf{V}(\Omega) = \{\mathbf{w} \in H_0^1(\Omega)^2 \mid \operatorname{div} \mathbf{w} = 0\}$$

which satisfy

$$\sum_{i=1}^2 \int_{\Omega} \nabla u_i \cdot \nabla v_i = \int_{\Omega} \mathbf{f} \cdot \mathbf{w} \quad \text{for all } \mathbf{v} \in \mathbf{V}$$

Here it is used the existence  $p \in H^1(\Omega)$  such that  $\mathbf{u} = \nabla p$ , if

$$\int_{\Omega} \mathbf{u} \cdot \mathbf{v} = 0 \quad \text{for all } \mathbf{v} \in \mathbf{V}$$

Another weak form is derived as follows: We put

$$\mathbf{V} = H_0^1(\Omega)^2; \quad \mathbf{W} = \left\{ q \in L^2(\Omega) \mid \int_{\Omega} q = 0 \right\}$$

By multiplying the first equation in (9.43) with  $\mathbf{v} \in \mathbf{V}$  and the second with  $q \in \mathbf{W}$ , subsequent integration over  $\Omega$ , and an application of Green's formula, we have

$$\begin{aligned} \int_{\Omega} \nabla \mathbf{u} \cdot \nabla \mathbf{v} - \int_{\Omega} \operatorname{div} \mathbf{v} p &= \int_{\Omega} \mathbf{f} \cdot \mathbf{v} \\ \int_{\Omega} \operatorname{div} \mathbf{u} q &= 0 \end{aligned}$$

This yields the weak form of (9.43): Find  $(\mathbf{u}, p) \in \mathbf{V} \times \mathbf{W}$  such that

$$a(\mathbf{u}, \mathbf{v}) + b(\mathbf{v}, p) = (\mathbf{f}, \mathbf{v}) \tag{9.44}$$

$$b(\mathbf{u}, q) = 0 \tag{9.45}$$



for all  $(\mathbf{v}, q) \in V \times W$ , where

$$a(\mathbf{u}, \mathbf{v}) = \int_{\Omega} \nabla \mathbf{u} \cdot \nabla \mathbf{v} = \sum_{i=1}^2 \int_{\Omega} \nabla u_i \cdot \nabla v_i \quad (9.46)$$

$$b(\mathbf{u}, q) = - \int_{\Omega} \operatorname{div} \mathbf{u} q \quad (9.47)$$

Now, we consider finite element spaces  $V_h \subset V$  and  $W_h \subset W$ , and we assume the following basis functions

$$\begin{aligned} V_h &= V_h \times V_h, \quad V_h = \{v_h \mid v_h = v_1 \phi_1 + \cdots + v_{M_V} \phi_{M_V}\}, \\ W_h &= \{q_h \mid q_h = q_1 \varphi_1 + \cdots + q_{M_W} \varphi_{M_W}\} \end{aligned}$$

The discrete weak form is: Find  $(\mathbf{u}_h, p_h) \in V_h \times W_h$  such that

$$\begin{aligned} a(\mathbf{u}_h, \mathbf{v}_h) + b(\mathbf{v}_h, p_h) &= (f, \mathbf{v}_h), \quad \forall \mathbf{v}_h \in V_h \\ b(\mathbf{u}_h, q_h) &= 0, \quad \forall q_h \in W_h \end{aligned} \quad (9.48)$$

**Note 9.4** Assume that:

1. There is a constant  $\alpha_h > 0$  such that

$$a(\mathbf{v}_h, \mathbf{v}_h) \geq \alpha \|\mathbf{v}_h\|_{1,\Omega}^2 \quad \text{for all } \mathbf{v}_h \in Z_h$$

where

$$Z_h = \{\mathbf{v}_h \in V_h \mid b(\mathbf{v}_h, q_h) = 0 \quad \text{for all } q_h \in W_h\}$$

2. There is a constant  $\beta_h > 0$  such that

$$\sup_{\mathbf{v}_h \in V_h} \frac{b(\mathbf{v}_h, q_h)}{\|\mathbf{v}_h\|_{1,\Omega}} \geq \beta_h \|q_h\|_{0,\Omega} \quad \text{for all } q_h \in W_h$$

Then we have an unique solution  $(\mathbf{u}_h, p_h)$  of (9.48) satisfying

$$\|\mathbf{u} - \mathbf{u}_h\|_{1,\Omega} + \|p - p_h\|_{0,\Omega} \leq C \left( \inf_{\mathbf{v}_h \in V_h} \|\mathbf{u} - \mathbf{v}_h\|_{1,\Omega} + \inf_{q_h \in W_h} \|p - q_h\|_{0,\Omega} \right)$$

with a constant  $C > 0$  (see e.g. [20, Theorem 10.4]).

Let us denote that

$$\begin{aligned} \mathbf{A} &= (A_{ij}), \quad A_{ij} = \int_{\Omega} \nabla \phi_j \cdot \nabla \phi_i \quad i, j = 1, \dots, M_V \\ \mathbf{B} &= (Bx_{ij}, By_{ij}), \quad Bx_{ij} = - \int_{\Omega} \partial \phi_j / \partial x \varphi_i \quad By_{ij} = - \int_{\Omega} \partial \phi_j / \partial y \varphi_i \\ &\quad i = 1, \dots, M_W; j = 1, \dots, M_V \end{aligned} \quad (9.49)$$

then (9.48) is written by

$$\begin{pmatrix} \mathbf{A} & \mathbf{B}^* \\ \mathbf{B} & \mathbf{0} \end{pmatrix} \begin{pmatrix} \mathbf{U}_h \\ \{p_h\} \end{pmatrix} = \begin{pmatrix} \mathbf{F}_h \\ \mathbf{0} \end{pmatrix} \quad (9.50)$$

where

$$\mathbf{A} = \begin{pmatrix} \mathbf{A} & \mathbf{0} \\ \mathbf{0} & \mathbf{A} \end{pmatrix} \quad \mathbf{B}^* = \begin{pmatrix} \mathbf{B}x^T \\ \mathbf{B}y^T \end{pmatrix} \quad \mathbf{U}_h = \begin{pmatrix} \{u_{1,h}\} \\ \{u_{2,h}\} \end{pmatrix} \quad \mathbf{F}_h = \begin{pmatrix} \{\int_{\Omega} f_1 \phi_i\} \\ \{\int_{\Omega} f_2 \phi_i\} \end{pmatrix}$$

**Penalty method:** This method consists of replacing (9.48) by a more regular problem: Find  $(\mathbf{v}_h^\epsilon, p_h^\epsilon) \in \mathbf{V}_h \times \tilde{W}_h$  satisfying

$$\begin{aligned} a(\mathbf{u}_h^\epsilon, \mathbf{v}_h) + b(\mathbf{v}_h, p_h^\epsilon) &= (\mathbf{f}, \mathbf{v}_h), \quad \forall \mathbf{v}_h \in \mathbf{V}_h \\ b(\mathbf{u}_h^\epsilon, q_h) - \epsilon(p_h^\epsilon, q_h) &= 0, \quad \forall q_h \in \tilde{W}_h \end{aligned} \quad (9.51)$$

where  $\tilde{W}_h \subset L^2(\Omega)$ . Formally, we have

$$\operatorname{div} \mathbf{u}_h^\epsilon = \epsilon p_h^\epsilon$$

and the corresponding algebraic problem

$$\begin{pmatrix} \mathbf{A} & \mathbf{B}^* \\ \mathbf{B} & -\epsilon \mathbf{I} \end{pmatrix} \begin{pmatrix} \mathbf{U}_h^\epsilon \\ \{p_h^\epsilon\} \end{pmatrix} = \begin{pmatrix} \mathbf{F}_h \\ \mathbf{0} \end{pmatrix}$$

**Note 9.5** We can eliminate  $p_h^\epsilon = (1/\epsilon) \mathbf{B} \mathbf{U}_h^\epsilon$  to obtain

$$(\mathbf{A} + (1/\epsilon) \mathbf{B}^* \mathbf{B}) \mathbf{U}_h^\epsilon = \mathbf{F}_h^\epsilon \quad (9.52)$$

Since the matrix  $\mathbf{A} + (1/\epsilon) \mathbf{B}^* \mathbf{B}$  is symmetric, positive-definite, and sparse, (9.52) can be solved by known technique. There is a constant  $C > 0$  independent of  $\epsilon$  such that

$$\|\mathbf{u}_h - \mathbf{u}_h^\epsilon\|_{1,\Omega} + \|p_h - p_h^\epsilon\|_{0,\Omega} \leq C\epsilon$$

(see e.g. [20, 17.2])

**Example 9.22 (Cavity.edp)** The driven cavity flow problem is solved first at zero Reynolds number (Stokes flow) and then at Reynolds 100. The velocity pressure formulation is used first and then the calculation is repeated with the stream function vorticity formulation.

We solve the driven cavity problem by the penalty method (9.51) where  $\mathbf{u}_\Gamma \cdot \mathbf{n} = 0$  and  $\mathbf{u}_\Gamma \cdot \mathbf{s} = 1$  on the top boundary and zero elsewhere (  $\mathbf{n}$  is the unit normal to  $\Gamma$ , and  $\mathbf{s}$  the unit tangent to  $\Gamma$ ).

The mesh is constructed by

```
mesh Th=square(8,8);
```

We use a classical Taylor-Hood element technic to solve the problem:

The velocity is approximated with the  $P_2$  FE (  $X_h$  space), and the the pressure is approximated with the  $P_1$  FE (  $M_h$  space),

where

$$X_h = \{ \mathbf{v} \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad \mathbf{v}|_K \in P_2 \}$$

and

$$M_h = \{ p \in H^1(\Omega) \mid \forall K \in \mathcal{T}_h \quad p|_K \in P_1 \}$$

The FE spaces and functions are constructed by

```
fespace Xh(Th,P2); // definition of the velocity component space
```

```
fespace Mh(Th,P1); // definition of the pressure space
Xh u2,v2;
Xh u1,v1;
Mh p,q;
```

The Stokes operator is implemented as a system-solve for the velocity  $(u1,u2)$  and the pressure  $p$ . The test function for the velocity is  $(v1,v2)$  and  $q$  for the pressure, so the variational form (9.48) in freefem language is:

```
solve Stokes (u1,u2,p,v1,v2,q,solver=Croux) =
  int2d(Th)( ( dx(u1)*dx(v1) + dy(u1)*dy(v1)
    + dx(u2)*dx(v2) + dy(u2)*dy(v2) )
    - p*q*(0.000001)
    - p*dx(v1) - p*dy(v2)
    - dx(u1)*q - dy(u2)*q
  )
+ on(3,u1=1,u2=0)
+ on(1,2,4,u1=0,u2=0); // see Section 5.1.1 for labels 1,2,3,4
```

Each unknown has its own boundary conditions.

If the streamlines are required, they can be computed by finding  $\psi$  such that  $\text{rot}\psi = u$  or better,

$$-\Delta\psi = \nabla \times u$$

```
Xh psi,phi;
```

```
solve streamlines(psi,phi) =
  int2d(Th)( dx(psi)*dx(phi) + dy(psi)*dy(phi))
+ int2d(Th)( -phi*(dy(u1)-dx(u2)))
+ on(1,2,3,4,psi=0);
```

Now the Navier-Stokes equations are solved

$$\frac{\partial u}{\partial t} + u \cdot \nabla u - \nu \Delta u + \nabla p = 0, \quad \nabla \cdot u = 0$$

with the same boundary conditions and with initial conditions  $u = 0$ .

This is implemented by using the convection operator `convect` for the term  $\frac{\partial u}{\partial t} + u \cdot \nabla u$ , giving a discretization in time

$$\begin{aligned} \frac{1}{\tau}(u^{n+1} - u^n \circ X^n) - \nu \Delta u^{n+1} + \nabla p^{n+1} &= 0, \\ \nabla \cdot u^{n+1} &= 0 \end{aligned} \quad (9.53)$$

The term  $u^n \circ X^n(x) \approx u^n(x - u^n(x)\tau)$  will be computed by the operator “`convect`”, so we obtain

```
int i=0;
real nu=1./100.;
real dt=0.1;
real alpha=1/dt;
```

```
Xh up1,up2;
```

```
problem NS (u1,u2,p,v1,v2,q,solver=Croux,init=i) =
```

```

    int2d(Th)(
        alpha*( u1*v1 + u2*v2)
        + nu * ( dx(u1)*dx(v1) + dy(u1)*dy(v1)
        + dx(u2)*dx(v2) + dy(u2)*dy(v2) )
        - p*q*(0.000001)
        - p*dx(v1) - p*dy(v2)
        - dx(u1)*q - dy(u2)*q
    )
+ int2d(Th) ( -alpha*
    convect([up1,up2],-dt,up1)*v1 -alpha*convect([up1,up2],-dt,up2)*v2 )
+ on(3,u1=1,u2=0)
+ on(1,2,4,u1=0,u2=0)
;

for (i=0;i<=10;i++)
{
    up1=u1;
    up2=u2;
    NS;
    if ( !(i % 10)) // plot every 10 iteration
        plot(coef=0.2,cmm=" [u1,u2] and p ",p,[u1,u2]);
} ;

```

Notice that the stiffness matrices are reused (keyword `init=i`)

## 9.6.2 Uzawa Algorithm and Conjugate Gradients

We solve Stokes problem without penalty. The classical iterative method of Uzawa is described by the algorithm (see e.g. [20, 17.3], [29, 13] or [30, 13]):

**Initialize:** Let  $p_h^0$  be an arbitrary chosen element of  $L^2(\Omega)$ .

**Calculate  $u_h^n$ :** Once  $p_h^n$  is known,  $v_h^n$  is the solution of

$$u_h^n = A^{-1}(f_h - B^* p_h^n)$$

**Advance  $p_h$ :** Let  $p_h^{n+1}$  be defined by

$$p_h^{n+1} = p_h^n + \rho_n B u_h^n$$

There is a constant  $\alpha > 0$  such that  $\alpha \leq \rho_n \leq 2$  for each  $n$ , then  $u_h^n$  converges to the solution  $u_h$ , and then  $Bv_h^n \rightarrow 0$  as  $n \rightarrow \infty$  from the *Advance*  $p_h$ . This method in general converges quite slowly.

First we define mesh, and the Taylor-Hood approximation. So  $X_h$  is the velocity space, and  $M_h$  is the pressure space.

### Example 9.23 (StokesUzawa.edp)

```

mesh Th=square(10,10);
fespace Xh(Th,P2),Mh(Th,P1);
Xh u1,u2,v1,v2;
Mh p,q,ppp; // ppp is a working pressure

varf bx(u1,q) = int2d(Th)( -(dx(u1)*q));
varf by(u1,q) = int2d(Th)( -(dy(u1)*q));

```

```

varf a(u1,u2)= int2d(Th)( dx(u1)*dx(u2) + dy(u1)*dy(u2) )
                + on(3,u1=1) + on(1,2,4,u1=0) ;
                                //    remark: put the on(3,u1=1) before on(1,2,4,u1=0)
                                //    because we want zero on intersection %

matrix A= a(Xh,Xh,solver=CG);
matrix Bx= bx(Xh,Mh);
matrix By= by(Xh,Mh);
                                //    B = (Bx By)

Xh bc1; bc1[] = a(0,Xh);
Xh bc2; bc2[] = 0 ;
Xh b;
                                //    boundary condition contribution on u1
                                //    no boundary condition contribution on u2

 $p_h^n \rightarrow \mathbf{BA}^{-1}(-\mathbf{B}^* p_h^n) = -\text{div} \mathbf{u}_h$  is realized as the function divup.

```

```

func real[int] divup(real[int] & pp)
{
    b[] = Bx'*pp; b[] *=-1; b[] += bc1[] ;    u1[] = A^-1*b[];
    b[] = By'*pp; b[] *=-1; b[] += bc2[] ;    u2[] = A^-1*b[];
    //     $\mathbf{u}^n = \mathbf{A}^{-1}(\mathbf{Bx}^T p_h^n \quad \mathbf{By}^T p_h^n)^T$ 
    ppp[] = Bx*u1[];
    ppp[] += By*u2[];
    return ppp[] ;
};
                                //    compute u1(pp)
                                //    compute u2(pp)
                                //    ppp = Bxu1
                                //    +Byu2

```

Call now the conjugate gradient algorithm:

```

p=0;q=0;
LinearCG(divup,p[],eps=1.e-6,nbiter=50);
//    if n > 50 or  $|p_h^{n+1} - p_h^n| \leq 10^{-6}$ , then the loop end.
divup(p[]);
                                //    compute the final solution

plot([u1,u2],p,wait=1,value=true,coef=0.1);

```

### 9.6.3 NSUzawaCahouetChabart.edp

In this example we solve the Navier-Stokes equation, in the driven-cavity, with the Uzawa algorithm preconditioned by the Cahouet-Chabart method (see [31] for all the details).

The idea of the preconditioner is that in a periodic domain, all differential operators commute and the Uzawa algorithm comes to solving the linear operator  $\nabla \cdot ((\alpha Id + \nu \Delta)^{-1} \nabla)$ , where  $Id$  is the identity operator. So the preconditioner suggested is  $\alpha \Delta^{-1} + \nu Id$ .

To implement this, we reuse the previous example, by including a file. Then we define the time step  $\Delta t$ , viscosity, and new variational form and matrix.

#### Example 9.24 (NSUzawaCahouetChabart.edp)

```

include "StokesUzawa.edp"
real dt=0.05, alpha=1/dt;
                                //    include the Stokes part
                                //    Δt

cout << " alpha = " << alpha;

```

```

real xnu=1./400;                                     // viscosity  $\nu = \text{Reynolds number}^{-1}$ 

// the new variational form with mass term
varf at(u1,u2)= int2d(Th)( xnu*dx(u1)*dx(u2)
+ xnu*dy(u1)*dy(u2) + u1*u2*alpha )
+ on(1,2,4,u1=0) + on(3,u1=1) ;

A = at(Xh,Xh,solver=CG);                             // change the matrix

// set the 2 convect variational form
varf vfconv1(uu,vv) = int2d(Th,qforder=5) (convect([u1,u2],-dt,u1)*vv*alpha);
varf vfconv2(v2,v1) = int2d(Th,qforder=5) (convect([u1,u2],-dt,u2)*v1*alpha);

int idt;                                              // index of time set
real temps=0;                                       // current time

Mh pprec,prhs;
varf vfMass(p,q) = int2d(Th)(p*q);
matrix MassMh=vfMass(Mh,Mh,solver=CG);

varf vFLap(p,q) = int2d(Th)(dx(pprec)*dx(q)+dy(pprec)*dy(q) + pprec*q*1e-10);
matrix LapMh= vFLap(Mh,Mh,solver=Cholesky);

```

*The function to define the preconditioner*

```

func real[int] CahouetChabart(real[int] & xx)
{
//  $\mathbf{xx} = \int (\text{div} \mathbf{u}) w_i$ 
//  $\alpha \text{LapMh}^{-1} + \nu \text{MassMh}^{-1}$ 

    pprec[] = LapMh-1* xx;
    prhs[] = MassMh-1*xx;
    pprec[] = alpha*pprec[]+xnu* prhs[];
    return pprec[];
};

```

*The loop in time. Warning with the stop test of the conjugate gradient, because we start from the previous solution and the end the previous solution is close to the final solution, don't take a relative stop test to the first residual, take an absolute stop test ( negative here)*

```

for (idt = 1; idt < 50; idt++)
{
    temps += dt;
    cout << " ----- temps " << temps << " \n ";
    b1[] = vfconv1(0,Xh);
    b2[] = vfconv2(0,Xh);
    cout << " min b1 b2 " << b1[].min << " " << b2[].min << endl;
    cout << " max b1 b2 " << b1[].max << " " << b2[].max << endl;
// call Conjugate Gradient with preconditioner '
// warning eps < 0 => absolute stop test
    LinearCG(divup,p[],eps=-1.e-6,nbiter=50,precon=CahouetChabart);
    divup(p[]);                                     // computed the velocity

    plot([u1,u2],p,wait=!(idt%10),value= 1,coef=0.1);
}

```




Figure 9.25: Solution of the cavity driven problem at Reynolds number 400 with the Cahouet-Chabart algorithm.

## 9.7 Variational inequality

We present, a classical example of variational inequality.

Let us denote  $C = \{u \in H_0^1(\Omega), u \leq g\}$

The problem is :

$$u = \arg \min_{u \in C} J(u) = \frac{1}{2} \int_{\Omega} \nabla u \cdot \nabla u - \int_{\Omega} f u$$

where  $f$  and  $g$  are given function.

The solution is a projection on the convex  $C$  of  $f^*$  for the scalar product  $((v, w)) = \int_{\Omega} \nabla v \cdot \nabla w$  of  $H_0^1(\Omega)$  where  $f^*$  is solution of  $((f^*, v)) = \int_{\Omega} f v, \forall v \in H_0^1(\Omega)$ . The projection on a convex satisfy clearly  $\forall v \in C, ((u - v, u - \tilde{f})) \leq 0$ , and after expanding, we get the classical inequality

$$\forall v \in C, \int_{\Omega} \nabla(u - v) \nabla u \leq \int_{\Omega} (u - v) f.$$

We can also rewrite the problem as a saddle point problem

Find  $\lambda, u$  such that:

$$\max_{\lambda \in L^2(\Omega), \lambda \geq 0} \min_{u \in H_0^1(\Omega)} \mathcal{L}(u, \lambda) = \frac{1}{2} \int_{\Omega} \nabla u \cdot \nabla u - \int_{\Omega} f u + \int_{\Omega} \lambda (u - g)^+$$

where  $((u - g)^+ = \max(0, u - g))$

This saddle point problem is equivalent to find  $u, \lambda$  such that:

$$\begin{cases} \int_{\Omega} \nabla u \cdot \nabla v + \lambda v^+ d\omega = \int_{\Omega} f u, & \forall v \in H_0^1(\Omega) \\ \int_{\Omega} \mu (u - g)^+ = 0, & \forall \mu \in L^2(\Omega), \mu \geq 0, \lambda \geq 0, \end{cases} \quad (9.54)$$

A algorithm to solve the previous problem is:

1.  $k=0$ , and choose,  $\lambda_0$  belong  $H^{-1}(\Omega)$
2. loop on  $k = 0, \dots$ 
  - (a) set  $I_k = \{x \in \Omega / \lambda_k + c * (u_{k+1} - g) \leq 0\}$
  - (b)  $V_{g,k+1} = \{v \in H_0^1(\Omega) / v = g \text{ on } I_k\}$ ,
  - (c)  $V_{0,k+1} = \{v \in H_0^1(\Omega) / v = 0 \text{ on } I_k\}$ ,
  - (d) Find  $u_{k+1} \in V_{g,k+1}$  and  $\lambda_{k+1} \in H^{-1}(\Omega)$  such that

$$\begin{cases} \int_{\Omega} \nabla u_{k+1} \cdot \nabla v_{k+1} d\omega = \int_{\Omega} f v_{k+1}, & \forall v_{k+1} \in V_{0,k+1} \\ \langle \lambda_{k+1}, v \rangle = \int_{\Omega} \nabla u_{k+1} \cdot \nabla v - f v d\omega \end{cases}$$

where  $\langle, \rangle$  is the duality bracket between  $H_0^1(\Omega)$  and  $H^{-1}(\Omega)$ , and  $c$  is a penalty constant (large enough).

You can find all the mathematic about this algorithm in [33].

Now how to do that in FreeFem++

The full example is:

#### Example 9.25 (VI.edp)

```

mesh Th=square(20,20);
real eps=1e-5;
fespace Vh(Th,P1);
int n = Vh.ndof;
Vh uh,uhp;
Vh Ik;
real[int] rhs(n);
real c=1000;
func f=1;
func fd=0;
Vh g=0.05;

real[int] Aii(n),Aiin(n);

real tgv = 1e30;

// the variational form of the problem:
varf a(uh,vh) =
    int2d(Th)( dx(uh)*dx(vh) + dy(uh)*dy(vh) )
    - int2d(Th)( f*vh )
    + on(1,2,3,4,uh=fd) ;

// two version of the matrix of the problem
matrix A=a(Vh,Vh,tgv=tgv,solver=CG);
matrix AA=a(Vh,Vh,solver=GC);

// the mass Matrix construction:
varf vM(uh,vh) = int2d(Th)(uh*vh);
matrix M=vM(Vh,Vh);

```

*// P1 FE space*  
*// number of Degree of freedom*  
*// solution and previous one*  
*// to def the set where the containt is reached.*  
*// to store the right and side of the equation*  
*// the penalty parameter of the algorith*  
*// right hand side function*  
*// Dirichlet boundary condition function*  
*// the discret function g*  
*// to store the diagonal of the matrix 2 version*  
*// a huge value for exact penalization*  
*// of boundary condition*  
*// definition of the problem*  
*// bilinear form*  
*// linear form*  
*// boundary condition form*  
*// one changing*  
*// one for computing residual*  
*// to do a fast computing of L^2 norm : sqrt( u'\*(w=M\*u))*



```

Aii=A.diag;           // get the diagonal of the matrix (appear in version 1.46-1)

rhs = a(0,Vh,tgv=tgv);
Ik =0;
uhp=-tgv;              // previous value is
Vh lambda=0;
for(int iter=0;iter<100;++iter)
{
    real[int] b(n) ; b=rhs;           // get a copy of the Right hand side
    real[int] Ak(n);                  // the complementary of Ik ( !Ik = (Ik-1))
    // Today the operator Ik- 1. is not implement so we do:
    Ak= 1.; Ak -= Ik[];               // build Ak = ! Ik
    // adding new locking condition on b and on the diagonal if (Ik ==1 )
    b = Ik[] .* g[];      b *= tgv;    b -= Ak .* rhs;
    Aii = Ik[] * tgv;      Aii += Ak .* Aii;           // set Aii= tgv i ∈ Ik
    A.diag = Aii;         // set the matrix diagonal (appear in version 1.46-1)
    set(A,solver=CG);      // important to change preconditioning for solving
    uh[] = A^-1* b;        // solve the problem with more locking condition
    lambda[] = AA * uh[];   // compute the residual ( fast with matrix)
    lambda[] += rhs;        // remark rhs = - ∫ fv

    Ik = ( lambda + c*( g- uh)) < 0.;           // the new of locking value

    plot(Ik, wait=1,cmm=" lock set ",value=1,ps="VI-lock.eps",fill=1 );
    plot(uh,wait=1,cmm="uh",ps="VI-uh.eps");
    // trick to compute L^2 norm of the variation (fast method)
    real[int] diff(n),Mdiff(n);
    diff= uh[]-uhp[];
    Mdiff = M*diff;
    real err = sqrt(Mdiff'*diff);
    cout << " || u_{k=1} - u_{k} ||_2 " << err << endl;
    if(err< eps) break;               // stop test
    uhp[]=uh[] ;                     // set the previous solution
}
savemesh(Th, "mm", [x,y,uh*10]);    // for medit plotting

```

Remark, as you can see on this example, some vector , or matrix operator are not implemented so a way is to skip the expression and we use operator +=, -= to merge the result.

## 9.8 Domain decomposition

We present, three classic examples, of domain decomposition technique: first, Schwarz algorithm with overlapping, second Schwarz algorithm without overlapping (also call Shur complement), and last we show to use the conjugate gradient to solve the boundary problem of the Shur complement.

### 9.8.1 Schwarz Overlap Scheme

To solve

$$-\Delta u = f, \text{ in } \Omega = \Omega_1 \cup \Omega_2 \quad u|_{\Gamma} = 0$$

the Schwarz algorithm runs like this

$$\begin{aligned} -\Delta u_1^{n+1} &= f \text{ in } \Omega_1 & u_1^{n+1}|_{\Gamma_1} &= u_2^n \\ -\Delta u_2^{n+1} &= f \text{ in } \Omega_2 & u_2^{n+1}|_{\Gamma_2} &= u_1^n \end{aligned}$$

where  $\Gamma_i$  is the boundary of  $\Omega_i$  and on the condition that  $\Omega_1 \cap \Omega_2 \neq \emptyset$  and that  $u_i$  are zero at iteration 1.

Here we take  $\Omega_1$  to be a quadrangle,  $\Omega_2$  a disk and we apply the algorithm starting from zero.




Figure 9.26: The 2 overlapping mesh TH and th

#### Example 9.26 (Schwarz-overlap.edp)

```
int inside = 2; // inside boundary
int outside = 1; // outside boundary
border a(t=1,2){x=t;y=0;label=outside;};
border b(t=0,1){x=2;y=t;label=outside;};
border c(t=2,0){x=t ;y=1;label=outside;};
border d(t=1,0){x = 1-t; y = t;label=inside;};
border e(t=0, pi/2){ x= cos(t); y = sin(t);label=inside;};
border el(t=pi/2, 2*pi){ x= cos(t); y = sin(t);label=outside;};
int n=4;
mesh th = buildmesh( a(5*n) + b(5*n) + c(10*n) + d(5*n));
mesh TH = buildmesh( e(5*n) + el(25*n) );
plot(th,TH,wait=1); // to see the 2 meshes
```

The space and problem definition is :

```
fespace vh(th,P1);
fespace VH(TH,P1);
vh u=0,v; VH U,V;
int i=0;

problem PB(U,V,init=i,solver=Cholesky) =
  int2d(TH)( dx(U)*dx(V)+dy(U)*dy(V) )
+ int2d(TH)( -V) + on(inside,U = u) + on(outside,U= 0 ) ;
problem pb(u,v,init=i,solver=Cholesky) =
  int2d(th)( dx(u)*dx(v)+dy(u)*dy(v) )
+ int2d(th)( -v) + on(inside ,u = U) + on(outside,u = 0 ) ;
```

The calculation loop:

```
for ( i=0 ;i< 10; i++)
{
```

```

PB;
pb;
plot(U,u,wait=true);
};

```




Figure 9.27: Isovalues of the solution at iteration 0 and iteration 9

### 9.8.2 Schwarz non Overlap Scheme

To solve

$$-\Delta u = f \text{ in } \Omega = \Omega_1 \cup \Omega_2 \quad u|_{\Gamma} = 0,$$

the Schwarz algorithm for domain decomposition without overlapping runs like this




Figure 9.28: The two none overlapping mesh TH and th

Let introduce  $\Gamma_i$  is common the boundary of  $\Omega_1$  and  $\Omega_2$  and  $\Gamma_e^i = \partial\Omega_i \setminus \Gamma_i$ .

The problem find  $\lambda$  such that  $(u_1|_{\Gamma_i} = u_2|_{\Gamma_i})$  where  $u_i$  is solution of the following Laplace problem:

$$-\Delta u_i = f \text{ in } \Omega_i \quad u_i|_{\Gamma_i} = \lambda \quad u_i|_{\Gamma_e^i} = 0$$

To solve this problem we just make a loop with upgrading  $\lambda$  with

$$\lambda = \lambda \pm \frac{(u_1 - u_2)}{2}$$

where the sign + or - of  $\pm$  is choose to have convergence.

### Example 9.27 (Schwarz-no-overlap.edp)

```

//      schwarz1 without overlapping

int inside = 2;
int outside = 1;
border a(t=1,2){x=t;y=0;label=outside;};
border b(t=0,1){x=2;y=t;label=outside;};
border c(t=2,0){x=t ;y=1;label=outside;};
border d(t=1,0){x = 1-t; y = t;label=inside;};
border e(t=0, 1){ x= 1-t; y = t;label=inside;};
border e1(t=pi/2, 2*pi){ x= cos(t); y = sin(t);label=outside;};
int n=4;
mesh th = buildmesh( a(5*n) + b(5*n) + c(10*n) + d(5*n));
mesh TH = buildmesh ( e(5*n) + e1(25*n) );
plot(th,TH,wait=1,ps="schwarz-no-u.eps");
fespace vh(th,P1);
fespace VH(TH,P1);
vh u=0,v; VH U,V;
vh lambda=0;
int i=0;

problem PB(U,V,init=i,solver=Cholesky) =
  int2d(TH)( dx(U)*dx(V)+dy(U)*dy(V) )
+ int2d(TH)( -V)
+ int1d(TH,inside)(lambda*V) + on(outside,U= 0 ) ;
problem pb(u,v,init=i,solver=Cholesky) =
  int2d(th)( dx(u)*dx(v)+dy(u)*dy(v) )
+ int2d(th)( -v)
+ int1d(th,inside)(-lambda*v) + on(outside,u = 0 ) ;

for ( i=0 ;i< 10; i++)
{
  PB;
  pb;
  lambda = lambda - (u-U)/2;
  plot(U,u,wait=true);
};

plot(U,u,ps="schwarz-no-u.eps");

```




Figure 9.29: Isovalues of the solution at iteration 0 and iteration 9 without overlapping

### 9.8.3 Schwarz-gc.edp

To solve

$$-\Delta u = f \text{ in } \Omega = \Omega_1 \cup \Omega_2 \quad u|_{\Gamma} = 0,$$

the Schwarz algorithm for domain decomposition without overlapping runs like this

Let introduce  $\Gamma_i$  is common the boundary of  $\Omega_1$  and  $\Omega_2$  and  $\Gamma_e^i = \partial\Omega_i \setminus \Gamma_i$ .

The problem find  $\lambda$  such that  $(u_1|_{\Gamma_i} = u_2|_{\Gamma_i})$  where  $u_i$  is solution of the following Laplace problem:

$$-\Delta u_i = f \text{ in } \Omega_i \quad u_i|_{\Gamma_i} = \lambda \quad u_i|_{\Gamma_e^i} = 0$$

The version of this example for Shur component. The border problem is solve with conjugate gradient. First, we construct the two domain

#### Example 9.28 (Schwarz-gc.edp)

```

//      Schwarz without overlapping (Shur complement Neumann -> Dirichet)
real cpu=clock();
int inside = 2;
int outside = 1;

border Gamma1(t=1,2){x=t;y=0;label=outside;};
border Gamma2(t=0,1){x=2;y=t;label=outside;};
border Gamma3(t=2,0){x=t ;y=1;label=outside;};

border GammaInside(t=1,0){x = 1-t; y = t;label=inside;};

border GammaArc(t=pi/2, 2*pi){ x= cos(t); y = sin(t);label=outside;};
int n=4;

//      build the mesh of  $\Omega_1$  and  $\Omega_2$ 
mesh Th1 = buildmesh( Gamma1(5*n) + Gamma2(5*n) + GammaInside(5*n) + Gamma3(5*n));
mesh Th2 = buildmesh ( GammaInside(-5*n) + GammaArc(25*n) );
plot(Th1,Th2);

//      defined the 2 FE space
fespace Vh1(Th1,P1),          Vh2(Th2,P1);

```

**Note 9.6** It is impossible to define a function just on a part of boundary, so the  $\lambda$  function must be defined on the all domain  $\Omega_1$  such as

```
Vh1 lambda=0; // take  $\lambda \in V_{h1}$ 
```

The two Poisson problem:

```
Vh1 u1,v1;          Vh2 u2,v2;
int i=0; // for factorization optimization
problem Pb2(u2,v2,init=i,solver=Cholesky) =
    int2d(Th2)( dx(u2)*dx(v2)+dy(u2)*dy(v2) )
+ int2d(Th2)( -v2)
+ int1d(Th2,inside)(-lambda*v2) + on(outside,u2= 0 ) ;
problem Pb1(u1,v1,init=i,solver=Cholesky) =
    int2d(Th1)( dx(u1)*dx(v1)+dy(u1)*dy(v1) )
+ int2d(Th1)( -v1)
+ int1d(Th1,inside)(+lambda*v1) + on(outside,u1 = 0 ) ;
```

or, we define a border matrix, because the  $\lambda$  function is none zero inside the domain  $\Omega_1$ :

```
varf b(u2,v2,solver=CG) =int1d(Th1,inside)(u2*v2);
matrix B= b(Vh1,Vh1,solver=CG);
```

The boundary problem function,

$$\lambda \longrightarrow \int_{\Gamma_i} (u_1 - u_2)v_1$$

```
func real[int] BoundaryProblem(real[int] &l)
{
    lambda[]=1; // make FE function form 1
    Pb1; Pb2;
    i++; // no refactorization i !=0
    v1=-(u1-u2);
    lambda[]=B*v1[];
    return lambda[] ;
};
```

**Note 9.7** The difference between the two notations  $v1$  and  $v1[]$  is:  $v1$  is the finite element function and  $v1[]$  is the vector in the canonical basis of the finite element function  $v1$ .

```
Vh1 p=0,q=0; // solve the problem with Conjugate Gradient
LinearCG(BoundaryProblem,p[],eps=1.e-6,nbiter=100);
// compute the final solution, because CG works with increment
BoundaryProblem(p[]); // solve again to have right u1,u2

cout << " -- CPU time schwarz-gc:" << clock()-cpu << endl;
plot(u1,u2); // plot
```

## 9.9 Fluid/Structures Coupled Problem

This problem involves the Lamé system of elasticity and the Stokes system for viscous fluids with velocity  $\mathbf{u}$  and pressure  $p$ :

$$-\Delta \mathbf{u} + \nabla p = 0, \nabla \cdot \mathbf{u} = 0, \text{ in } \Omega, \mathbf{u} = \mathbf{u}_\Gamma \text{ on } \Gamma = \partial\Omega$$

where  $\mathbf{u}_\Gamma$  is the velocity of the boundaries. The force that the fluid applies to the boundaries is the normal stress

$$\mathbf{h} = (\nabla \mathbf{u} + \nabla \mathbf{u}^T) \mathbf{n} - p \mathbf{n}$$

Elastic solids subject to forces deform: a point in the solid, at  $(x, y)$  goes to  $(X, Y)$  after. When the displacement vector  $\mathbf{v} = (v_1, v_2) = (X - x, Y - y)$  is small, Hooke's law relates the stress tensor  $\sigma$  inside the solid to the deformation tensor  $\epsilon$ :

$$\sigma_{ij} = \lambda \delta_{ij} \nabla \cdot \mathbf{v} + 2\mu \epsilon_{ij}, \epsilon_{ij} = \frac{1}{2} \left( \frac{\partial v_i}{\partial x_j} + \frac{\partial v_j}{\partial x_i} \right)$$

where  $\delta$  is the Kronecker symbol and where  $\lambda, \mu$  are two constants describing the material mechanical properties in terms of the modulus of elasticity, and Young's modulus.

The equations of elasticity are naturally written in variational form for the displacement vector  $\mathbf{v}(x) \in V$  as

$$\int_{\Omega} [2\mu \epsilon_{ij}(\mathbf{v}) \epsilon_{ij}(\mathbf{w}) + \lambda \epsilon_{ii}(\mathbf{v}) \epsilon_{jj}(\mathbf{w})] = \int_{\Omega} \mathbf{g} \cdot \mathbf{w} + \int_{\Gamma} \mathbf{h} \cdot \mathbf{w}, \forall \mathbf{w} \in V$$

The data are the gravity force  $\mathbf{g}$  and the boundary stress  $\mathbf{h}$ .

**Example 9.29 (fluidStruct.edp)** *In our example the Lamé system and the Stokes system are coupled by a common boundary on which the fluid stress creates a displacement of the boundary and hence changes the shape of the domain where the Stokes problem is integrated. The geometry is that of a vertical driven cavity with an elastic lid. The lid is a beam with weight so it will be deformed by its own weight and by the normal stress due to the fluid reaction. The cavity is the  $10 \times 10$  square and the lid is a rectangle of height  $l = 2$ .*

*A beam sits on a box full of fluid rotating because the left vertical side has velocity one. The beam is bent by its own weight, but the pressure of the fluid modifies the bending.*

*The bending displacement of the beam is given by  $(uu, vv)$  whose solution is given as follows.*

```

//      Fluid-structure interaction for a weighting beam sitting on a
//      square cavity filled with a fluid.

int bottombeam = 2; //      label of bottombeam
border a(t=2,0) { x=0; y=t ;label=1;}; //      left beam
border b(t=0,10) { x=t; y=0 ;label=bottombeam;}; //      bottom of beam
border c(t=0,2) { x=10; y=t ;label=1;}; //      righth beam
border d(t=0,10) { x=10-t; y=2; label=3;}; //      top beam
real E = 21.5;
real sigma = 0.29;
real mu = E/(2*(1+sigma));
real lambda = E*sigma/((1+sigma)*(1-2*sigma));
real gravity = -0.05;
mesh th = buildmesh( b(20)+c(5)+d(20)+a(5));
fespace Vh(th,P1);
Vh uu,w,vv,s,fluidforce=0;
cout << "lambda,mu,gravity ="<<lambda<< " " << mu << " " << gravity << endl;
//      deformation of a beam under its own weight

```

```

solve bb([uu,vv],[w,s]) =
    int2d(th)(
        lambda*div(w,s)*div(uu,vv)
        +2.*mu*( epsilon(w,s)'*epsilon(uu,vv) )
    )
+ int2d(th) (-gravity*s)
+ on(1,uu=0,vv=0)
+ fluidforce[];
;

plot([uu,vv],wait=1);
mesh th1 = movemesh(th, [x+uu, y+vv]);
plot(th1,wait=1);

```

Then Stokes equation for fluids at low speed are solved in the box below the beam, but the beam has deformed the box (see border h):

```

// Stokes on square b,e,f,g driven cavity on left side g
border e(t=0,10) { x=t; y=-10; label= 1; }; // bottom
border f(t=0,10) { x=10; y=-10+t ; label= 1; }; // right
border g(t=0,10) { x=0; y=-t ;label= 2;}; // left
border h(t=0,10) { x=t; y=vv(t,0)*( t>=0.001 )*(t <= 9.999);
                    label=3;}; // top of cavity deformed

mesh sh = buildmesh(h(-20)+f(10)+e(10)+g(10));
plot(sh,wait=1);

```

We use the Uzawa conjugate gradient to solve the Stokes problem like in example Section 9.6.2

```

fespace Xh(sh,P2),Mh(sh,P1);
Xh u1,u2,v1,v2;
Mh p,q,ppp;

varf bx(u1,q) = int2d(sh)( -(dx(u1)*q));

varf by(u1,q) = int2d(sh)( -(dy(u1)*q));

varf Lap(u1,u2)= int2d(sh)( dx(u1)*dx(u2) + dy(u1)*dy(u2) )
                    + on(2,u1=1) + on(1,3,u1=0) ;

Xh bc1; bc1[] = Lap(0,Xh);
Xh brhs;

matrix A= Lap(Xh,Xh,solver=CG);
matrix Bx= bx(Xh,Mh);
matrix By= by(Xh,Mh);
Xh bcx=0,bcy=1;

func real[int] divup(real[int] & pp)
{
    int verb=verbosity;
    verbosity=0;
    brhs[] = Bx'*pp; brhs[] += bc1[] .*bcx[];
    u1[] = A^-1*brhs[];
    brhs[] = By'*pp; brhs[] += bc1[] .*bcy[];
}

```



```

    u2[] = A^-1*brhs[];
    ppp[] = Bx*u1[];
    ppp[] += By*u2[];
    verbosity=verb;
    return ppp[] ;
};

```

*do a loop on the two problem*

```

for(step=0;step<2;++step)
{
    p=0;q=0;u1=0;v1=0;

    LinearCG(divup,p[],eps=1.e-3,nbiter=50);
    divup(p[]);

```

*Now the beam will feel the stress constraint from the fluid:*

```

Vh sigma11,sigma22,sigma12;
Vh uu1=uu,vv1=vv;

sigma11([x+uu,y+vv]) = (2*dx(u1)-p);
sigma22([x+uu,y+vv]) = (2*dy(u2)-p);
sigma12([x+uu,y+vv]) = (dx(u1)+dy(u2));

```

*which comes as a boundary condition to the PDE of the beam:*

```

solve bbst([uu,vv],[w,s],init=i) =
    int2d(th)(
        lambda*div(w,s)*div(uu,vv)
        +2.*mu*( epsilon(w,s)'*epsilon(uu,vv) )
    )
+ int2d(th) (-gravity*s)
+ int1d(th,bottombeam)( -coef*( sigma11*N.x*w + sigma22*N.y*s
                                + sigma12*(N.y*w+N.x*s) ) )
+ on(1,uu=0,vv=0);
plot([uu,vv],wait=1);
real err = sqrt(int2d(th)( (uu-uu1)^2 + (vv-vv1)^2 ));
cout << " Erreur L2 = " << err << "-----\n";

```

*Notice that the matrix generated by bbst is reused (see init=i). Finally we deform the beam*

```

th1 = movemesh(th, [x+0.2*uu, y+0.2*vv]);
plot(th1,wait=1);
}

```

*// end of loop*

## 9.10 Transmission Problem

Consider an elastic plate whose displacement change vertically, which is made up of three plates of different materials, welded on each other. Let  $\Omega_i$ ,  $i = 1, 2, 3$  be the domain occupied by  $i$ -th material with tension  $\mu_i$




Figure 9.30: Fluid velocity and pressure (left) and displacement vector (center) of the structure and displaced geometry (right) in the fluid-structure interaction of a soft side and a driven cavity

(see Section 9.1.1). The computational domain  $\Omega$  is the interior of  $\overline{\Omega_1} \cup \overline{\Omega_2} \cup \overline{\Omega_3}$ . The vertical displacement  $u(x, y)$  is obtained from

$$-\mu_i \Delta u = f \text{ in } \Omega_i \quad (9.55)$$

$$\mu_i \partial_n u|_{\Gamma_i} = -\mu_j \partial_n u|_{\Gamma_j} \text{ on } \overline{\Omega_i} \cap \overline{\Omega_j} \quad \text{if } 1 \leq i < j \leq 3 \quad (9.56)$$

where  $\partial_n u|_{\Gamma_i}$  denotes the value of the normal derivative  $\partial_n u$  on the boundary  $\Gamma_i$  of the domain  $\Omega_i$ . By introducing the characteristic function  $\chi_i$  of  $\Omega_i$ , that is,

$$\chi_i(x) = 1 \quad \text{if } x \in \Omega_i; \quad \chi_i(x) = 0 \quad \text{if } x \notin \Omega_i \quad (9.57)$$

we can easily rewrite (9.55) and (9.56) to the weak form. Here we assume that  $u = 0$  on  $\Gamma = \partial\Omega$ .  
problem Transmission: For a given function  $f$ , find  $u$  such that

$$a(u, v) = \ell(f, v) \quad \text{for all } v \in H_0^1(\Omega) \quad (9.58)$$

$$a(u, v) = \int_{\Omega} \mu \nabla u \cdot \nabla v, \quad \ell(f, v) = \int_{\Omega} f v$$

where  $\mu = \mu_1 \chi_1 + \mu_2 \chi_2 + \mu_3 \chi_3$ . Here we notice that  $\mu$  become the discontinuous function.

With dissipation, and at the thermal equilibrium, the temperature equation is:

This example explains the definition and manipulation of *region*, i.e. subdomains of the whole domain.

Consider this L-shaped domain with 3 diagonals as internal boundaries, defining 4 subdomains:

```

//      example using region keyword
//      construct a mesh with 4 regions (sub-domains)

border a(t=0,1){x=t;y=0;};
border b(t=0,0.5){x=1;y=t;};
border c(t=0,0.5){x=1-t;y=0.5;};
border d(t=0.5,1){x=0.5;y=t;};
border e(t=0.5,1){x=1-t;y=1;};
border f(t=0,1){x=0;y=1-t;};

```

```

border i1(t=0,0.5){x=t;y=1-t;};
border i2(t=0,0.5){x=t;y=t;};
border i3(t=0,0.5){x=1-t;y=t;};

mesh th = buildmesh (a(6) + b(4) + c(4) +d(4) + e(4) +
    f(6)+i1(6)+i2(6)+i3(6));
fespace Ph(th,P0);
fespace Vh(th,P1);

Ph reg=region;
plot(reg,fill=1,wait=1,value=1);

```

*// internal boundary*

*// constant discontinuous functions / element*

*//  $P_1$  continuous functions / element*

*// defined the  $P_0$  function associated to region number*




Figure 9.31: the function reg




Figure 9.32: the function nu

region is a keyword of FreeFem++ which is in fact a variable depending of the current position (is not a function today, use `Ph reg=region;` to set a function). This variable value returned is the number of the subdomain of the current position. This number is defined by "buildmesh" which scans while building the mesh all its connected component. So to get the number of a region containing a particular point one does:

```

int nupper=reg(0.4,0.9);
int nlower=reg(0.9,0.1);
cout << " nlower " << nlower << ", nupper = " << nupper<< endl;
// defined the characteristics functions of upper and lower region
Ph nu=1+5*(region==nlower) + 10*(region==nupper);
plot(nu,fill=1,wait=1);

```

*// get the region number of point (0.4,0.9)*

*// get the region number of point (0.9,0.1)*

*// defined the characteristics functions of upper and lower region*

This is particularly useful to define discontinuous functions such as might occur when one part of the domain is copper and the other one is iron, for example.

We this in mind we proceed to solve a Laplace equation with discontinuous coefficients ( $\nu$  is 1, 6 and 11 below).

```

Ph nu=1+5*(region==nlower) + 10*(region==nupper);
plot(nu,fill=1,wait=1);
problem lap(u,v) = int2d(th)( nu*( dx(u)*dx(v)*dy(u)*dy(v) ))
+ int2d(-1*v) + on(a,b,c,d,e,f,u=0);
plot(u);

```




Figure 9.33: the isovalue of the solution  $u$

## 9.11 Free Boundary Problem

The domain  $\Omega$  is defined with:

```

real L=10; // longueur du domaine
real h=2.1; // hauteur du bord gauche
real h1=0.35; // hauteur du bord droite

// maillage d'un trapèze
border a(t=0,L){x=t;y=0;}; // bottom:  $\Gamma_a$ 
border b(t=0,h1){x=L;y=t;}; // right:  $\Gamma_b$ 
border f(t=L,0){x=t;y=t*(h1-h)/L+h;}; // free surface:  $\Gamma_f$ 
border d(t=h,0){x=0;y=t;}; // left:  $\Gamma_d$ 

int n=4;
mesh Th=buildmesh (a(10*n)+b(6*n)+f(8*n)+d(3*n));
plot(Th,ps="dTh.eps");

```




Figure 9.34: The mesh of the domain  $\Omega$

The free boundary problem is:

Find  $u$  and  $\Omega$  such that:

$$\left\{ \begin{array}{ll} -\Delta u = 0 & \text{in } \Omega \\ u = y & \text{on } \Gamma_b \\ \frac{\partial u}{\partial n} = 0 & \text{on } \Gamma_d \cup \Gamma_a \\ \frac{\partial u}{\partial n} = \frac{q}{K} n_x \text{ and } u = y & \text{on } \Gamma_f \end{array} \right.$$

We use a fixed point method;  $\Omega^0 = \Omega$

in two step, fist we solve the classical following problem:

$$\left\{ \begin{array}{ll} -\Delta u = 0 & \text{in } \Omega^n \\ u = y & \text{on } \Gamma_b^n \\ \frac{\partial u}{\partial n} = 0 & \text{on } \Gamma_d^n \cup \Gamma_a^n \\ u = y & \text{on } \Gamma_f^n \end{array} \right.$$

The variational formulation is:

find  $u$  on  $V = H^1(\Omega^n)$ , such than  $u = y$  on  $\Gamma_b^n$  and  $\Gamma_f^n$

$$\int_{\Omega^n} \nabla u \nabla u' = 0, \quad \forall u' \in V \text{ with } u' = 0 \text{ on } \Gamma_b^n \cup \Gamma_f^n$$

and secondly to construct a domain deformation  $\mathcal{F}(x, y) = [x, y - v(x, y)]$

where  $v$  is solution of the following problem:

$$\begin{cases} -\Delta v = 0 & \text{in } \Omega^n \\ v = 0 & \text{on } \Gamma_a^n \\ \frac{\partial v}{\partial n} = 0 & \text{on } \Gamma_b^n \cup \Gamma_d^n \\ \frac{\partial v}{\partial n} = \frac{\partial u}{\partial n} - \frac{q}{K} n_x & \text{on } \Gamma_f^n \end{cases}$$

The variational formulation is:

find  $v$  on  $V$ , such that  $v = 0$  on  $\Gamma_a^n$

$$\int_{\Omega^n} \nabla v \nabla v' = \int_{\Gamma_f^n} \left( \frac{\partial u}{\partial n} - \frac{q}{K} n_x \right) v', \quad \forall v' \in V \text{ with } v' = 0 \text{ on } \Gamma_a^n$$

Finally the new domain  $\Omega^{n+1} = \mathcal{F}(\Omega^n)$

**Example 9.30 (freeboundary.edp)** *The FreeFem++ implementation is:*

```

real q=0.02; // flux entrant
real K=0.5; // permeabilité

fespace Vh(Th,P1);
int j=0;

Vh u,v,uu,vv;

problem Pu(u,uu,solver=CG) = int2d(Th)( dx(u)*dx(uu)+dy(u)*dy(uu))
+ on(b,f,u=y) ;

problem Pv(v,vv,solver=CG) = int2d(Th)( dx(v)*dx(vv)+dy(v)*dy(vv))
+ on (a, v=0) + int1d(Th,f)(vv*((q/K)*N.y- (dx(u)*N.x+dy(u)*N.y)));

real errv=1;
real erradap=0.001;
verbosity=1;
while(errv>1e-6)
{
  j++;
  Pu;
  Pv;
  plot(Th,u,v ,wait=0);
  errv=int1d(Th,f)(v*v);
  real coef=1;

  real mintcc = checkmovemesh(Th,[x,y])/5.; //
  real mint = checkmovemesh(Th,[x,y-v*coef]);

  if (mint<mintcc || j%10==0) { // mesh to bad => remeshing
    Th=adaptmesh(Th,u,err=erradap) ;
    mintcc = checkmovemesh(Th,[x,y])/5.;
  }

  while (1)

```

```

{
  real mint = checkmovemesh(Th,[x,y-v*coef]);



  if (mint>mintcc) break;

  cout << " min |T|  " << mint << endl;
  coef /= 1.5;
}

Th=movemesh(Th,[x,y-coef*v]);
cout << "\n\n"<<j <<"----- errv = " << errv << "\n\n";

}
plot(Th,ps="d_Thf.eps");
plot(u,wait=1,ps="d_u.eps");

```

Figure 9.35: The final solution on the new domain  $\Omega^{72}$ Figure 9.36: The adapted mesh of the domain  $\Omega^{72}$ 

## 9.12 Non linear Elasticity (nolinear-elas.edp)

The nonlinear elasticity problem is: find the displacement  $(u_1, u_2)$  minimizing  $J$

$$\min J(u_1, u_2) = \int_{\Omega} f(F2) - \int_{\Gamma_p} P_a u_2$$

where  $F2(u_1, u_2) = A(E[u_1, u_2], E[u_1, u_2])$  and  $A(X, Y)$  is bilinear sym. positive form with respect two matrix  $X, Y$ . where  $f$  is a given  $C^2$  function, and  $E[u_1, u_2] = (E_{ij})_{i=1,2, j=1,2}$  is the Green-Saint Venant deformation tensor defined with:

$$E_{ij} = 0.5(\partial_i u_j + \partial_j u_i) + \sum_k \partial_i u_k \times \partial_j u_k$$

Denote  $\mathbf{u} = (u_1, u_2)$ ,  $\mathbf{v} = (v_1, v_2)$ ,  $\mathbf{w} = (w_1, w_2)$ .

So, the differential of  $J$  is

$$DJ(\mathbf{u})(\mathbf{v}) = \int DF2(\mathbf{u})(\mathbf{v}) f'(F2(\mathbf{u})) - \int_{\Gamma_p} P_a v_2$$

where  $DF2(\mathbf{u})(\mathbf{v}) = 2 A( DE[\mathbf{u}](\mathbf{v}), E[\mathbf{u}] )$  and  $DE$  is the first differential of  $E$ .

The second order differential is

$$\begin{aligned} D^2 J(\mathbf{u})((\mathbf{v}), (\mathbf{w})) &= \int DF2(\mathbf{u})(\mathbf{v}) DF2(\mathbf{u})(\mathbf{w}) f''(F2(\mathbf{u})) \\ &+ \int D^2 F2(\mathbf{u})(\mathbf{v}, \mathbf{w}) f'(F2(\mathbf{u})) \end{aligned}$$

where

$$D^2 F2(\mathbf{u})(\mathbf{v}, \mathbf{w}) = 2 A( D^2 E[\mathbf{u}](\mathbf{v}, \mathbf{w}), E[\mathbf{u}] ) + 2 A( DE[\mathbf{u}](\mathbf{v}), DE[\mathbf{u}](\mathbf{w}) ).$$

and  $D^2 E$  is the second differential of  $E$ .

So all notations can be define with macros:

```

macro EL(u, v) [dx(u), (dx(v)+dy(u)), dy(v)] // is [e11, 2e12, e22]

macro ENL(u, v) [
(dx(u)*dx(u)+dx(v)*dx(v))*0.5,
(dx(u)*dy(u)+dx(v)*dy(v)) ,
(dy(u)*dy(u)+dy(v)*dy(v))*0.5 ] // EOM ENL

macro dENL(u, v, uu, vv) [(dx(u)*dx(uu)+dx(v)*dx(vv)),
(dx(u)*dy(uu)+dx(v)*dy(vv)+dx(uu)*dy(u)+dx(vv)*dy(v)),
(dy(u)*dy(uu)+dy(v)*dy(vv)) ] //

macro E(u, v) (EL(u, v)+ENL(u, v)) // is [E11, 2E12, E22]
macro dE(u, v, uu, vv) (EL(uu, vv)+dENL(u, v, uu, vv)) //
macro ddE(u, v, uu, vv, uuu, vvv) dENL(uuu, vvv, uu, vv) //
macro F2(u, v) (E(u, v)'*A*E(u, v)) //
macro dF2(u, v, uu, vv) (E(u, v)'*A*dE(u, v, uu, vv)*2. ) //
macro ddF2(u, v, uu, vv, uuu, vvv) (
(dE(u, v, uu, vv)'*A*dE(u, v, uuu, vvv))*2.
+ (E(u, v)'*A*ddE(u, v, uu, vv, uuu, vvv))*2. ) // EOM

```

The Newton Method is

choose  $n = 0$ , and  $u_0, v_0$  the initial displacement

- loop:
- find  $(du, dv)$  : solution of

$$D^2 J(u_n, v_n)((w, s), (du, dv)) = DJ(u_n, v_n)(w, s), \quad \forall w, s$$

- $u_n = u_n - du, \quad v_n = v_n - dv$
- until  $(du, dv)$  small is enough






Figure 9.37: The deformed domain

The way to implement this algorithm in FreeFem++ is use a macro tool to implement  $A$  and  $F2, f, f', f''$ . A macro is like in ccp preprocessor of C++ , but this begin by `macro` and the end of the macro definition is before the comment `//`. In this case the macro is very useful because the type of parameter can be change. And it is easy to make automatic differentiation.

```

// non linear elasticity model
// for hyper elasticity problem
// -----
macro f(u) (u) // end of macro
macro df(u) (1) // end of macro
macro ddf(u) (0) // end of macro

// -- du caouchouc --- (see the notes of Herve Le Dret.)
// -----

real mu = 0.012e5; // kg/cm2
real lambda = 0.4e5; // kg/cm2
//
//  $\sigma = 2\mu E + \lambda \text{tr}(E)Id$ 
//  $A(u, v) = \sigma(u) : E(v)$ 
//
// ( a b )
// ( b c )
//
// tr*Id : (a,b,c) -> (a+c, 0, a+c)
// so the associated matrix is:
// ( 1 0 1 )
// ( 0 0 0 )
// ( 1 0 1 )

// -----v
real a11= 2*mu + lambda ;
real a22= mu ;
// because [0, 2 * t12, 0]'A[0, 2 * s12, 0] =
// = 2 * mu * (t12 * s12 + t21 * s21) = 4 * mu * t12 * s12

real a33= 2*mu + lambda ;
real a12= 0 ;
real a13= lambda ;
real a23= 0 ;

// symmetric part
real a21= a12 ;
real a31= a13 ;
real a32= a23 ;

```

```

// the matrix A.
func A = [ [ a11,a12,a13],[ a21,a22,a23],[ a31,a32,a33] ];

real Pa=1e2; // a pressure of 100 Pa
// -----

int n=30,m=10;
mesh Th= square(n,m,[x,.3*y]); // label: 1 bottom, 2 right, 3 up, 4 left;
int bottom=1, right=2,upper=3,left=4;

plot(Th);

fespace Wh(Th,P1dc);
fespace Vh(Th,[P1,P1]);
fespace Sh(Th,P1);

Wh e2,fe2,dfe2,ddfe2; // optimisation
Wh ett,ezz,err,erz; // optimisation

Vh [uu,vv], [w,s],[un,vn];
[un,vn]=[0,0]; // intialisation
[uu,vv]=[0,0];

varf vmass([uu,vv],[w,s],solver=CG) = int2d(Th)( uu*w + vv*s );
matrix M=vmass(Vh,Vh);
problem NonLin([uu,vv],[w,s],solver=LU)=
  int2d(Th,qforder=1)( // (D2J(un)) part
    dF2(un,vn,uu,vv)*dF2(un,vn,w,s)*ddfe2
    + ddF2(un,vn,w,s,uu,vv)*dfe2
  )
  - int1d(Th,3)(Pa*s)
  - int2d(Th,qforder=1)( // (DJ(un)) part
    dF2(un,vn,w,s)*dfe2 )
  + on(right,left,uu=0,vv=0);
;

// Newton's method
// -----

Sh u1,v1;
for (int i=0;i<10;i++)
{
  cout << "Loop " << i << endl;
  e2 = F2(un,vn);
  dfe2 = df(e2) ;
  ddfe2 = ddf(e2);
  cout << " e2 max " << e2[].max << " , min" << e2[].min << endl;
  cout << " de2 max " << dfe2[].max << " , min" << dfe2[].min << endl;
  cout << " dde2 max " << ddfe2[].max << " , min" << ddfe2[].min << endl;
  NonLin; // compute [uu,vv] = (D2J(un))-1(DJ(un))

  w[] = M*uu[];

```

```

real res = sqrt(w[]' * uu[]); // norme  $L^2$  of  $[uu, vv]$ 
u1 = uu;
v1 = vv;
cout << " L^2 residual = " << res << endl;
cout << " u1 min =" << u1[].min << ", u1 max= " << u1[].max << endl;
cout << " v1 min =" << v1[].min << ", v2 max= " << v1[].max << endl;
plot([uu,vv],wait=1,cmm=" uu, vv " );
un[] -= uu[];
plot([un,vn],wait=1,cmm=" displacement " );
if (res<1e-5) break;
}

plot([un,vn],wait=1);
mesh th1 = movemesh(Th, [x+un, y+vn]);
plot(th1,wait=1); // see figure 9.37

```

## 9.13 Compressible Neo-Hookean Materials: Computational Solutions

Author : Alex Sadovsky mailsashas@gmail.com

### 9.13.1 Notation

In what follows, the symbols  $\mathbf{u}, \mathbf{F}, \mathbf{B}, \mathbf{C}, \underline{\sigma}$  denote, respectively, the displacement field, the deformation gradient, the left Cauchy-Green strain tensor  $\mathbf{B} = \mathbf{F}\mathbf{F}^T$ , the right Cauchy-Green strain tensor  $\mathbf{C} = \mathbf{F}^T\mathbf{F}$ , and the Cauchy stress tensor. We also introduce the symbols  $I_1 := \text{tr } \mathbf{C}$  and  $J := \det \mathbf{F}$ . Use will be made of the identity

$$\frac{\partial J}{\partial \mathbf{C}} = J\mathbf{C}^{-1} \quad (9.59)$$

The symbol  $\mathbf{I}$  denotes the identity tensor. The symbol  $\Omega_0$  denotes the reference configuration of the body to be deformed. The unit volume in the reference (resp., deformed) configuration is denoted  $dV$  (resp.,  $dV_0$ ); these two are related by

$$dV = JdV_0,$$

which allows an integral over  $\Omega$  involving the Cauchy stress  $\mathbf{T}$  to be rewritten as an integral of the Kirchhoff stress  $\kappa = J\mathbf{T}$  over  $\Omega_0$ .

### Recommended References

For an exposition of nonlinear elasticity and of the underlying linear- and tensor algebra, see [34]. For an advanced mathematical analysis of the Finite Element Method, see [35]. An explanation of the Finite Element formulation of a nonlinear elastostatic boundary value problem, see <http://www.engin.brown.edu/courses/en222/Notes/FEMfinitetrain/FEMfinitetrain.htm>.

### 9.13.2 A Neo-Hookean Compressible Material

**Constitutive Theory and Tangent Stress Measures** The strain energy density function is given by

$$W = \frac{\mu}{2}(I_1 - \text{tr } \mathbf{I} - 2 \ln J) \quad (9.60)$$

(see [32], formula (12)).

The corresponding 2nd Piola-Kirchoff stress tensor is given by

$$\mathbf{S}_n := \frac{\partial W}{\partial \mathbf{E}}(\mathbf{F}_n) = \mu(\mathbf{I} - \mathbf{C}^{-1}) \quad (9.61)$$

The Kirchhoff stress, then, is

$$\kappa = \mathbf{F} \mathbf{S} \mathbf{F}^T = \mu(\mathbf{B} - \mathbf{I}) \quad (9.62)$$

The tangent Kirchhoff stress tensor at  $\mathbf{F}_n$  acting on  $\delta \mathbf{F}_{n+1}$  is, consequently,

$$\frac{\partial \kappa}{\partial \mathbf{F}}(\mathbf{F}_n) \delta \mathbf{F}_{n+1} = \mu \left[ \mathbf{F}_n (\delta \mathbf{F}_{n+1})^T + \delta \mathbf{F}_{n+1} (\mathbf{F}_n)^T \right] \quad (9.63)$$

**The Weak Form of the BVP in the Absence of Body (External) Forces** The  $\Omega_0$  we are considering is an elliptical annulus, whose boundary consists of two concentric ellipses (each allowed to be a circle as a special case), with the major axes parallel. Let  $P$  denote the dead stress load (traction) on a portion  $\partial \Omega_0^t$  (= the inner ellipse) of the boundary  $\partial \Omega_0$ . On the rest of the boundary, we prescribe zero displacement.

The weak formulation of the boundary value problem is

$$0 = \left. \begin{aligned} & \int_{\Omega_0} \kappa[\mathbf{F}] : \{(\nabla \otimes \mathbf{w})(\mathbf{F})^{-1}\} \\ & - \int_{\partial \Omega_0^t} P \cdot \hat{\mathbf{N}}_0 \end{aligned} \right\}$$

For brevity, in the rest of this section we assume  $P = 0$ . The provided FreeFem++ code, however, does not rely on this assumption and allows for a general value and direction of  $P$ .

Given a Newton approximation  $\mathbf{u}_n$  of the displacement field  $\mathbf{u}$  satisfying the BVP, we seek the correction  $\delta \mathbf{u}_{n+1}$  to obtain a better approximation

$$\mathbf{u}_{n+1} = \mathbf{u}_n + \delta \mathbf{u}_{n+1}$$

by solving the weak formulation

$$\left. \begin{aligned} 0 &= \int_{\Omega_0} \kappa[\mathbf{F}_n + \delta \mathbf{F}_{n+1}] : \{(\nabla \otimes \mathbf{w})(\mathbf{F}_n + \delta \mathbf{F}_{n+1})^{-1}\} - \int_{\partial \Omega_0^t} P \cdot \hat{\mathbf{N}}_0 \\ &= \int_{\Omega_0} \left\{ \kappa[\mathbf{F}_n] + \frac{\partial \kappa}{\partial \mathbf{F}}[\mathbf{F}_n] \delta \mathbf{F}_{n+1} \right\} : \{(\nabla \otimes \mathbf{w})(\mathbf{F}_n + \delta \mathbf{F}_{n+1})^{-1}\} \\ &= \int_{\Omega_0} \left\{ \kappa[\mathbf{F}_n] + \frac{\partial \kappa}{\partial \mathbf{F}}[\mathbf{F}_n] \delta \mathbf{F}_{n+1} \right\} : \{(\nabla \otimes \mathbf{w})(\mathbf{F}_n^{-1} + \mathbf{F}_n^{-2} \delta \mathbf{F}_{n+1})\} \\ &= \int_{\Omega_0} \kappa[\mathbf{F}_n] : \{(\nabla \otimes \mathbf{w}) \mathbf{F}_n^{-1}\} \\ &\quad - \int_{\Omega_0} \kappa[\mathbf{F}_n] : \{(\nabla \otimes \mathbf{w})(\mathbf{F}_n^{-2} \delta \mathbf{F}_{n+1})\} \\ &\quad + \int_{\Omega_0} \left\{ \frac{\partial \kappa}{\partial \mathbf{F}}[\mathbf{F}_n] \delta \mathbf{F}_{n+1} \right\} : \{(\nabla \otimes \mathbf{w}) \mathbf{F}_n^{-1}\} \end{aligned} \right\} \quad \text{for all test functions } \mathbf{w}, \quad (9.64)$$

where we have taken

$$\delta \mathbf{F}_{n+1} = \nabla \otimes \delta \mathbf{u}_{n+1}$$

**Note:** Contrary to standard notational use, the symbol  $\delta$  here bears no variational context. By  $\delta$  we mean simply an increment in the sense of Newton's Method. The role of a variational virtual displacement here is played by  $\mathbf{w}$ .

### 9.13.3 An Approach to Implementation in FreeFem++

The associated file is `examples++-tutorial/nl-elast-neo-Hookean.edp`.

Introducing the code-like notation, where a string in  $\langle \rangle$ 's is to be read as one symbol, the individual components of the tensor

$$\langle TanK \rangle := \frac{\partial \kappa}{\partial \mathbf{F}}[\mathbf{F}_n] \delta \mathbf{F}_{n+1} \quad (9.65)$$

will be implemented as the macros  $\langle TanK11 \rangle, \langle TanK12 \rangle, \dots$

The individual components of the tensor quantities

$$\mathbf{D}_1 := \mathbf{F}_n(\delta\mathbf{F}_{n+1})^T + \delta\mathbf{F}_{n+1}(\mathbf{F}_n)^T,$$

$$\mathbf{D}_2 := \mathbf{F}_n^{-T} \delta\mathbf{F}_{n+1},$$

$$\mathbf{D}_3 := (\nabla \otimes \mathbf{w}) \mathbf{F}_n^{-2} \delta\mathbf{F}_{n+1},$$

and

$$\mathbf{D}_4 := (\nabla \otimes \mathbf{w}) \mathbf{F}_n^{-1},$$

will be implemented as the macros

$$\left. \begin{aligned} &\langle d1Aux11 \rangle, \langle d1Aux12 \rangle, \quad \dots, \langle d1Aux22 \rangle, \\ &\langle d2Aux11 \rangle, \langle d2Aux12 \rangle, \quad \dots, \langle d2Aux22 \rangle \\ &\langle d3Aux11 \rangle, \langle d3Aux12 \rangle, \quad \dots, \langle d3Aux22 \rangle \\ &\langle d4Aux11 \rangle, \langle d4Aux12 \rangle, \quad \dots, \langle d4Aux22 \rangle \end{aligned} \right\}, \quad (9.66)$$

respectively.

In the above notation, the tangent Kirchhoff stress term becomes

$$\frac{\partial \kappa}{\partial \mathbf{F}}(\mathbf{F}_n) \delta\mathbf{F}_{n+1} = \mu \mathbf{D}_1 \quad (9.67)$$

while the weak BVP formulation acquires the form

$$\left. \begin{aligned} 0 &= \int_{\Omega_0} \kappa[\mathbf{F}_n] : \mathbf{D}_4 \\ &- \int_{\Omega_0} \kappa[\mathbf{F}_n] : \mathbf{D}_3 \\ &+ \int_{\Omega_0} \left\{ \frac{\partial \kappa}{\partial \mathbf{F}}[\mathbf{F}_n] \delta\mathbf{F}_{n+1} \right\} : \mathbf{D}_4 \end{aligned} \right\} \quad \text{for all test functions } \mathbf{w} \quad (9.68)$$



# Chapter 10

## MPI Parallel version

A first attempt of parallelization of FreeFem++ is made here with **mpi**. An extended interface with MPI has been added to FreeFem++ version 3.5, (see the MPI documentation for the functionality of the language at <http://www.mpi-forum.org/docs/mpi21-report.pdf>).

### 10.1 MPI keywords

The following keywords and concepts are used:

**mpiCom** to defined a *communication world*

**mpiGroup** to defined a group of *processors* in the communication world

**mpiRequest** to defined a equest to wait for the end of the communication

### 10.2 MPI constants

**mpisize** The total number of *processes*,

**mpirank** the id-number of my current process in  $\{0, \dots, mpisize - 1\}$ ,

**mpiUndefined** The MPI\_Undefined constant,

**mpiAnySource** The MPI\_ANY\_SOURCE constant,

**mpiCommWorld** The MPI\_COMM\_WORLD constant ,

... and all the keywords of MPI\_Op for the *reduce* operator:

mpiMAX, mpiMIN, mpiSUM, mpiPROD, mpiLAND, mpiLOR, mpiLXOR, mpiBAND, mpiBXOR.

### 10.3 MPI Constructor

```
int[int] proc1=[1,2,3],proc2=[0,4];
mpiGroup grp(procs);           // set MPI_Group to proc 1,2,3 in MPI_COMM_WORLD
mpiGroup grp1(comm,proc1);     // set MPI_Group to proc 1,2,3 in comm
```

```

mpiGroup grp2(grp,proc2); // set MPI.Group to grp union proc1

mpiComm comm=mpiCommWorld; // set a MPI.Comm to MPI.COMM_WORLD
mpiComm ncomm(mpiCommWorld,grp); // set the MPI.Comm form grp
// MPI.COMM_WORLD
mpiComm ncomm(comm,color,key); // MPI.Comm_split(MPI.Comm comm,
// int color, int key, MPI.Comm *ncomm)
mpiComm ncomm(processor(local_comm,local_leader),
processor(peer_comm,peer_leader),tag);
// build MPI_INTERCOMM_CREATE(local_comm, local_leader, peer_comm,
// remote_leader, tag, &ncomm)
mpiComm ncomm(intercomm,height) ; // build using
// MPI_Intercomm_merge( intercomm, high, &ncomm)
mpiRequest rq; // defined an MPI_Request
mpiRequest[int] arq(10); // defined an array of 10 MPI_Request

```

## 10.4 MPI functions

```

mpiSize(comm) ; // return the size of comm (int)
mpiRank(comm) ; // return the rank in comm (int)

processor(i) // return processor i with no Resquest in MPI_COMM_WORLD
processor(mpiAnySource) // return processor any source
// with no Resquest in MPI_COMM_WORLD
processor(i,comm) // return processor i with no Resquest in comm
processor(comm,i) // return processor i with no Resquest in comm
processor(i,rq,comm) // return processor i with Resquest rq in comm
processor(i,rq) // return processor i with Resquest rq in
// MPI_COMM_WORLD
processorblock(i) // return processor i in MPI_COMM_WORLD
// in block mode for synchronously communication
processorblock(mpiAnySource) // return processor any source
// in MPI_COMM_WORLD in block mode for synchronously communication
processorblock(i,comm) // return processor i in in comm in block mode

mpiBarrier(comm) ; // do a MPI.Barrier on communicator comm,
mpiWait(rq); // wait on of Request,
mpiWaitAll(arq); // wait add of Request array,
mpiWtime() ; // return MPIWtime in second (real),
mpiWtick() ; // return MPIWTick in second (real),

```

where a processor is just a integer rank, pointer to a MPI\_comm and pointer to a MPI\_Request, and processorblock with a special MPI\_Request.

## 10.5 MPI communicator operator

```

int status; // to get the MPI status of send / recv
processor(10) << a << b; // send a,b asynchronously to the process 1,
processor(10) >> a >> b; // receive a,b synchronously from the process 10,
broadcast(processor(10,comm),a); // broadcast from processor
// of com to other comm processor

```



```

status=Send( processor(10,comm) , a);           // send synchronously
// to the process 10 the data a
status=Recv( processor(10,comm) , a);           // receive synchronously
// from the process 10 the data a;
status=Isend( processor(10,comm) , a);          // send asynchronously to
// the process 10 , the data a without request
status=Isend( processor(10,rq,comm) , a) ;      // send asynchronously to
// the process 10, the data a with request
status=Irecv( processor(10,rq) , a) ;           // receive synchronously from
// the process 10, the data a;
status=Irecv( processor(10) , a) ;             // Error
// Error asynchronously without request .
broadcast(processor(comm,a));                  // Broadcast to all process of comm

```

where the data type of a can be of type of int,real, complex, int[int], double[int], complex[int], int[int,int], double[int,int], complex[int,int], mesh, mesh3, mesh[int], mesh3[int], matrix, matrix<complex>

```

processor(10,rq) << a ;                        // send asynchronously to the process 10
// the data a with request
processor(10,rq) >> a ;                        // receive asynchronously from the process 10
// the data a with request

```

If a,b are arrays or full matrices of int, real, or complex, we can use the following MPI functions:

```

mpiAlltoall(a,b[,comm]) ;
mpiAllgather(a,b[,comm]) ;
mpiGather(a,b,processor(..) ) ;
mpiScatter(a,b,processor(..)) ;
mpiReduce(a,b,processor(..),mpiMAX) ;
mpiAllReduce(a,b,comm, mpiMAX) ;
mpiReduceScatter(a,b,comm, mpiMAX) ;

```

See the examples++-mpi/essai.edp to test of all this functionality and Thank, to Guy-Antoine Atenekeg Kahou, for his help to code this interface.

## 10.6 Schwarz example in parallel

This example is a rewriting of example schwarz-overlap in section 9.8.1.

```

[examples++-mpi] Hecht%lamboot
LAM 6.5.9/MPI 2 C++/ROMIO - Indiana University
[examples++-mpi] hecht% mpirun -np 2 FreeFem++-mpi schwarz-c.edp

```

```

// a new coding version c, methode de schwarz in parallele
// with 2 proc.
// -----
// F.Hecht december 2003
// -----
// to test the broadcast instruction
// and array of mesh
// add add the stop test
// -----

```

```

if ( mpisize != 2 ) {
    cout << " sorry number of processeur !=2 " << endl;
    exit(1);}
verbosity=3;
real pi=4*atan(1);
int inside = 2;
int outside = 1;
border a(t=1,2){x=t;y=0;label=outside;};
border b(t=0,1){x=2;y=t;label=outside;};
border c(t=2,0){x=t ;y=1;label=outside;};
border d(t=1,0){x = 1-t; y = t;label=inside;};
border e(t=0, pi/2){ x= cos(t); y = sin(t);label=inside;};
border e1(t=pi/2, 2*pi){ x= cos(t); y = sin(t);label=outside;};
int n=4;
mesh[int] Th(mpisize);
if (mpirank == 0)
    Th[0] = buildmesh( a(5*n) + b(5*n) + c(10*n) + d(5*n));
else
    Th[1] = buildmesh ( e(5*n) + e1(25*n) );

broadcast(processor(0),Th[0]);
broadcast(processor(1),Th[1]);

fespace Vh(Th[mpirank],P1);
fespace Vhother(Th[1-mpirank],P1);

Vh u=0,v;
Vhother U=0;
int i=0;

problem pb(u,v,init=i,solver=Cholesky) =
    int2d(Th[mpirank])( dx(u)*dx(v)+dy(u)*dy(v) )
    - int2d(Th[mpirank])( v)
    + on(inside,u = U) + on(outside,u= U ) ;

for ( i=0 ;i< 20; i++)
{
    cout << mpirank << " loop " << i << endl;
    pb;
    // send u to the other proc, receive in U
    processor(1-mpirank) << u[]; processor(1-mpirank) >> U[];
    real err0,err1;
    err0 = int1d(Th[mpirank],inside)(square(U-u)) ;
    // send err0 to the other proc, receive in err1
    processor(1-mpirank)<<err0; processor(1-mpirank)>>err1;
    real err= sqrt(err0+err1);
    cout <<" err = " << err << " err0 = " << err0
        << " , err1 = " << err1 << endl;
    if(err<1e-3) break;
};
if (mpirank==0)
    plot(u,U,ps="uU.eps");

```

### 10.6.1 True parallel Schwarz example

This is a explanation of the two script `examples++-mpi/MPIGMRES[2]D.edp`, a Schwarz parallel with a complexity almost independent of the number of process (with a coarse grid preconditioner).

Thank to F. Nataf.

To solve the following Poisson problem on domain  $\Omega$  with boundary  $\Gamma$  in  $L^2(\Omega)$  :

$$-\Delta u = f, \text{ in } \Omega, \text{ and } u = g \text{ on } \Gamma,$$

where  $f$  and  $g$  are two given functions of  $L^2(\Omega)$  and of  $H^{\frac{1}{2}}(\Gamma)$ ,

Let introduce  $(\pi_i)_{i=1,\dots,N_p}$  a regular partition of the unity of  $\Omega$ , q-e-d:

$$\pi_i \in C^0(\Omega) : \quad \pi_i \geq 0 \text{ and } \sum_{i=1}^{N_p} \pi_i = 1.$$

Denote  $\Omega_i$  the sub domain which is the support of  $\pi_i$  function and also denote  $\Gamma_i$  the boundary of  $\Omega_i$ .

The parallel Schwarz method is Let  $\ell = 0$  the iterator and a initial guest  $u^0$  respecting the boundary condition (i.e.  $u^0|_{\Gamma} = g$ ).

$$\forall i = 1 \dots, N_p : \quad -\Delta u_i^\ell = f, \text{ in } \Omega_i, \quad \text{and } u_i^\ell = u^\ell \text{ on } \Gamma_i \setminus \Gamma, \quad u_i^\ell = g \text{ on } \Gamma_i \cap \Gamma \quad (10.1)$$

$$u^{\ell+1} = \sum_{i=1}^{N_p} \pi_i u_i^\ell \quad (10.2)$$

After discretization with the Lagrange finite element method, with a compatible mesh  $\mathcal{T}_{hi}$  of  $\Omega_i$ , i. e., the exist a global mesh  $\mathcal{T}_h$  such that  $\mathcal{T}_{hi}$  is include in  $\mathcal{T}_h$ . Let us denote:

- $V_{hi}$  the finite element space corresponding to domain  $\Omega_i$ ,
- $\mathcal{N}_{hi}$  is the set of the degree of freedom  $\sigma_i^k$ ,
- $\mathcal{N}_{hi}^{\Gamma_i}$  is the set of the degree of freedom of  $V_{hi}$  on the boundary  $\Gamma_i$  of  $\Omega_i$ ,
- $\sigma_i^k(v_h)$  is the value the degree of freedom  $k$ ,
- $V_{0hi} = \{v_h \in V_{hi} : \forall k \in \mathcal{N}_{hi}^{\Gamma_i}, \quad \sigma_i^k(v_h) = 0\}$ ,
- the conditional expression  $a ? b : c$  is defined like in C of C++ language by

$$a ? b : c \equiv \begin{cases} \text{if } a \text{ is true then return } b \\ \text{else return } c \end{cases}.$$

**Remark** we never use finite element space associated to the full domain  $\Omega$  because it to expensive.

We have to defined to operator to build the previous algorithm:

We denote  $u_{hi}^\ell$  the restriction of  $u_h^\ell$  on  $V_{hi}$ , so the discrete problem on  $\Omega_i$  of problem (10.1) is find  $u_{hi}^\ell \in V_{hi}$  such that:

$$\forall v_{hi} \in V_{0i} : \quad \int_{\Omega_i} \nabla v_{hi} \cdot \nabla u_{hi}^\ell = \int_{\Omega_i} f v_{hi}, \quad \forall k \in \mathcal{N}_{hi}^{\Gamma_i} : \quad \sigma_i^k(u_{hi}^\ell) = (k \in \Gamma) ? g_i^k : \sigma_i^k(u_{hi}^\ell) \quad (10.3)$$

where  $g_i^k$  is the value of  $g$  associated to the degree of freedom  $k \in \mathcal{N}_{hi}^{\Gamma_i}$ .

In FreeFem++, it can be written has with  $U$  is the vector corresponding to  $u_{hi}^\ell$  and the vector  $U1$  is the vector corresponding to  $u_{hi}^\ell$  is the solution of:

```

real[int] U1(Ui.n);
real[int] b= onG .* U;
b = onG ? b : Bi ;
U1 = Ai^-1*b;

```

where  $\text{onG}[i] = (i \in \Gamma_i \setminus \Gamma) ? 1 : 0$ , and  $\text{Bi}$  the right of side of the problem, are defined by

```

fespace Whi(Thi,P2); // def of the Finite element space.
varf vPb(U,V)= int3d(Thi)(grad(U)'*grad(V)) + int3d(Thi)(F*V) +on(1,U=g) + on(10,U=G);
varf vPbon(U,V)=on(10,U=1)+on(1,U=0);
matrix Ai = vPb(Whi,Whi,solver=sparsesolver);
real[int] onG = vPbon(0,Whi);
real[int] Bi=vPb(0,Whi);

```

where the freefem++ label of  $\Gamma$  is 1 and the label of  $\Gamma_i \setminus \Gamma$  is 10.

To build the transfer/update part corresponding to (10.2) equation on process  $i$ , let us call  $\text{njpart}$  the number the neighborhood of domain of  $\Omega_i$  (i.e:  $\pi_j$  is none 0 of  $\Omega_i$ ), we store in an array  $\text{jpart}$  of size  $\text{njpart}$  all this neighborhood. Let us introduce two array of matrix,  $\text{Smj}[j]$  to defined the vector to send from  $i$  to  $j$  a neighborhood process, and the matrix  $\text{rMj}[j]$  to after to reduce owith neighborhood  $j$  domain.

So the tranfert and update part compute  $v_i = \pi_i u_i + \sum_{j \in J_i} \pi_j u_j$  and can be write the freefem++ function Update:

```

func bool Update(real[int] &ui, real[int] &vi)
{ int n= jpart.n;
  for(int j=0;j<njpart;++j) Usend[j][]=sMj[j]*ui;
  mpiRequest[int] rq(n*2);
  for (int j=0;j<n;++j) Irecv(processor(jpart[j],comm,rq[j ]), Ri[j][]);
  for (int j=0;j<n;++j) Isend(processor(jpart[j],comm,rq[j+n]), Si[j][]);
  for (int j=0;j<n*2;++j) int k= mpiWaitAny(rq);
  // apply the unity local partition .
  vi = Pii*ui; // set to  $\pi_i u_i$ 
  for(int j=0;j<njpart;++j) vi += rMj[j]*Vrecv[j][]; // add  $\pi_j u_j$ 
  return true; }

```

where the buffer are defined by:

```

InitU(njpart,Whij,Thij,aThij,Usend) // defined the send buffer
InitU(njpart,Whij,Thij,aThij,Vrecv) // defined the revc buffer

```

with the following macro definition:

```

macro InitU(n,Vh,Th,aTh,U) Vh[int] U(n); for(int j=0;j<n;++j) {Th=aTh[j]; U[j]=0;} //

```

**First gmres algorithm:** you can easily accelerate the fixe point algorithm by using a parallel GMRES algorithm after the introduction the following affine  $\mathcal{A}_i$  operator sub domain  $\Omega_i$ .

```

func real[int] DJ0(real[int]& U) {
  real[int] V(U.n) , b= onG .* U;
  b = onG ? b : Bi ;
  V = Ai^-1*b;
}

```

```
Update(V,U);
V -= U; return V; }
```

Where the parallel MPIGMRES or MPICG algorithm is just a simple way to solve in parallel the following  $A_i x_i = b_i, i = 1, \dots, N_p$  by just changing the dot product by reduce the local dot product of all process with the following MPI code:

```
template<class R> R ReduceSum1(R s,MPI_Comm * comm)
{   R r=0;
    MPI_Allreduce( &s, &r, 1 ,MPI_TYPE<R>::TYPE(), MPI_SUM, *comm );
    return r; }
```

This is done in MPIGC dynamics library tool.

**Second gmres algorithm:** Use schwarz algorithm as a preconditioner of basic GMRES method to solving the parallel problem.

```
func real[int] DJ(real[int]& U)                                // the original problem
{
    ++kiter;
    real[int] V(U.n);
    V = Ai*U;
    V = onGi ? 0.: V;                                         // remove boundary term ...
    return V;
}

func real[int] PDJ(real[int]& U)                                // the preconditioner
{
    real[int] V(U.n);
    real[int] b= onG ? 0. : U;
    V = Ai^-1*b;
    Update(V,U);
    return U;
}
```

**Third gmres algorithm:** Add a coarse solver to the previous algorithm  
First build a coarse grid on processor 0, and the

```
matrix AC,Rci,Pci;                                           //
if(mpiRank(comm)==0)
    AC = vPbC(VhC,VhC,solver=sparsesolver);                 // the corase problem

Pci= interpolate(Whi,VhC);                                     // the projection on coarse grid.
Rci = Pci'*Pii;                                               // the Restriction on Process i grid with the partition  $\pi_i$ 

func bool CoarseSolve(real[int]& V,real[int]& U,mpiComm& comm)
{
    real[int] Uc(Rci.n),Bc(Uc.n);                             // solvibg the coarse probleme
    Uc= Rci*U;
    mpiReduce(Uc,Bc,processor(0,comm),mpiSUM);
    if(mpiRank(comm)==0)
        Uc = AC^-1*Bc;
    broadcast(processor(0,comm),Uc);
    V = Pci*Uc;
```

}

The New preconditionner

```

func real[int] PDJC(real[int]& U) //
{ //   Precon C1= Precon //, C2 precon Coarse
//   Idea : F. Nataf.
//    $0 \sim (I - C1A)(I - C2A) \Rightarrow I \sim -C1AC2A + C1A + C2A$ 
//   New Prec  $P = C1 + C2 - C1AC2 = C1(I - A C2) + C2$ 
//    $(C1(I - A C2) + C2) U_0$ 
//    $V = -C2*U_0$ 
//   ....
real[int] V(U.n);
CoarseSolve(V,U,comm);
V = -V;
U += Ai*V; //   //   -C2*Uo
//   U = (I-A C2) Uo
real[int] b= onG ? 0. : U;
U = Ai^-1*b; //   ( C1( I -A C2) Uo
V = U -V; //
Update(V,U);
return U;
}

```

The code to the 4 algorithms:

```

real epss=1e-6;
int rgmres=0;
if(gmres==1)
{
  rgmres=MPIAffineGMRES(DJ0,u[],veps=epss,nbiter=300,comm=comm,
                        dimKrylov=100,verbosity=ipart ? 0: 50);
  real[int] b= onG .* u[];
  b = onG ? b : Bi ;
  v[] = Ai^-1*b;
  Update(v[],u[]);
}
else if(gmres==2)
  rgmres= MPILinearGMRES(DJ,precon=PDJ,u[],Bi,veps=epss,nbiter=300,comm=comm,
                        ,dimKrylov=100,verbosity=ipart ? 0: 50);
else if(gmres==3)
  rgmres= MPILinearGMRES(DJ,precon=PDJC,u[],Bi,veps=epss,nbiter=300,comm=comm,
                        dimKrylov=100,verbosity=ipart ? 0: 50);
else //   algo Shwarz for demo ...
  for(int iter=0;iter <10; ++iter)
    ....

```

We have all ingredient to solve in parallel if we have et the partitions of the unity. To build this partition we do: the initial step on process 1 tp build a coarse mesh,  $\mathcal{T}_h^*$  of the full domain, and build the partition  $\pi$  function constant equal to  $i$  on each sub domain  $O_i, i = 1, \dots, N_p$ , of the grid with the Metis graph partitioner [?] and on each process  $i$  in  $1 \dots, N_p$  do

1. Broadcast from process 1, the mesh  $\mathcal{T}_h^*$  (call Thii in freefem++ script), and  $\pi$  function,
2. remark that the characteristic function  $\mathbf{1}_{O_i}$  of domain  $O_i$ , is defined by  $(\pi = i)?1 : 0$ ,

3. let us call  $\Pi_P^2$  (resp.  $\Pi_V^2$ ) the  $L^2$  on  $P_h^*$  the space of the constant finite element function per element on  $\mathcal{T}_h^*$  (resp.  $V_h^*$  the space of the affine continuous finite element per element on  $\mathcal{T}_h^*$ ). and build in parallel the  $\pi_i$  and  $\Omega_i$ , such that  $O_i \subset \Omega_i$  where  $O_i = \text{supp}((\Pi_V^2 \Pi_C^2)^m \mathbf{I}_{O_i})$ , and  $m$  is the overlaps size on the coarse mesh (generally one),

(this is done in function `AddLayers(Thii,suppii[],nlayer,phii[])`; We choose a function  $\pi_i^* = (\Pi_1^2 \Pi_0^2)^m \mathbf{I}_{O_i}$  so the partition of the unity is simply defined by

$$\pi_i = \frac{\pi_i^*}{\sum_{j=1}^{N_p} \pi_j^*} \quad (10.4)$$

The set  $J_i$  of neighborhood of the domain  $\Omega_i$ , and the local version on  $V_{hi}$  can be defined the array `jpart` and `njpart` with:

```
Vhi pii=pi_i^* ;  Vhi[int] pij(npij);          //    local partition of 1 = pii + \sum_j pij[j]

int[int] jpart(npart);  int njpart=0;
Vhi sumphi = pi_i^* ;
for (int i=0;i<npart;++i)
  if(i != ipart ) {
    if(int3d(Thi)( pi_j^*)>0) {
      pij[njpart]=pi_j^*;
      sumphi[] += pij[njpart][];
      jpart[njpart++]=i;}}}
  pii[]=pii[] ./ sumphi[];
  for (int j=0;j<njpart;++j) pij[j][] = pij[j][] ./ sumphi[];
  jpart.resize(njpart);
```

4. We call  $\mathcal{T}_{hij}^*$  the sub mesh part of  $\mathcal{T}_{hi}$  where  $\pi_j$  are none zero. and tank to the function `trunc` to build this array,

```
for(int jp=0;jp<njpart;++jp)
  aThij[jp] = trunc(Thi,pij[jp]>1e-10,label=10);
```

5. At this step we have all on the coarse mesh , so we can build the fine final mesh by splitting all meshes : `Thi` , `Thij[j]` , `Thij[j]` with `freefem++ trunc` mesh function which do restriction and slipping.

6. The construction of the send/rcv matrices `sMj` and `rMj` : can done with this code:

```
mesh3 Thij=Thi;                                     //    variable meshes
fespace Whij(Thij,Pk);                             //    variable fespace ..
matrix Pii; Whi wpii=pii; Pii = wpii[];             //    Diagonal matrix corresponding \times \pi_i
matrix[int] sMj(njpart), rMj(njpart);               //    M send/rcv case..
for(int jp=0;jp<njpart;++jp)
  { int j=jpart[jp];
    Thij = aThij[jp];                               //    change mesh to change Whij,Whij
    matrix I = interpolate(Whij,Whi);                //    Whij <- Whi
    sMj[jp] = I*Pii;                                 //    Whi -> s Whij
    rMj[jp] = interpolate(Whij,Whi,t=1); }}          //    Whij -> Whi
```

To build a not too bad application, I have added code to change variable from parameter value with the following code

```
include "getARGV.idp"
verbosity=getARGV("-vv",0);
int vdebug=getARGV("-d",1);
int ksplit=getARGV("-k",10);
int nloc = getARGV("-n",25);
string sff=getARGV("-p","", "");
int gmres=getARGV("-gmres",3);
bool dplot=getARGV("-dp",0);
int nC = getARGV("-N",max(nloc/10,4));
```

And small include to make graphic in parallel of distributed solution of vector  $u$  on mesh  $T_h$  with the following interface:

```
include "MPIplot.idp"
func bool plotMPIall(mesh &Th, real[int] &u, string cm)
{ PLOTMPIALL(mesh, Pk, Th, u, { cmm=cm, nbiso=20, fill=1, dim=3, value=1}); return 1; }
```

remark the {cmm=cm, ... =1} in the macro argument is a way to quote macro argument so the argument is cmm=cm, ... =1.



# Chapter 11

## Parallel sparse solvers

Parallel sparse solvers use several processors to solve linear systems of equation. Like sequential, parallel linear solvers can be direct or iterative. In `FreeFem++` both are available.

### 11.1 Using parallel sparse solvers in `FreeFem++`

We recall that the solver parameters are defined in the following commands: `solve`, `problem`, `set` (setting parameter of a matrix) and in the construction of the matrix corresponding to a bilinear form. In these commands, the parameter `solver` must be set to `sparsesolver` for parallel sparse solver. We have added specify parameters to these command lines for parallel sparse solvers. These are

- `lparams`: vector of integer parameters (l is for the c++ type long)
- `dparams`: vector of real parameters
- `sparams`: string parameters
- `datafilename`: name of the file which contains solver parameters

The following four parameters are only for direct solvers and are vectors. These parameters allow the user to preprocess the matrix (see the section on sparse direct solver above for more information).

- `permr`: row permutation (integer vector)
- `permc`: column permutation or inverse row permutation (integer vector)
- `scaler`: row scaling (real vector)
- `scalec`: column scaling (real vector)

There are two possibilities to control solver parameters. The first method defines parameters with `lparams`, `dparams` and `sparams` in `.edp` file. The second one reads the solver parameters from a data file. The name of this file is specified by `datafilename`. If `lparams`, `dparams`, `sparams` or `datafilename` is not provided by the user, the solver's default value is used.

To use parallel solver in `FreeFem++`, we need to load the dynamic library corresponding to this solver. For example to use MUMPS solver as parallel solver in `FreeFem`, write in the `.edp` file `load "MUMPS_FreeFem"`. If the libraries are not loaded, the default sparse solver will be loaded (default sparse solver is UMFPACK). The table 11.1 gives this new value for the different libraries.

We also add functions (see Table 11.2) with no parameter to change the default sparse solver in the `.edp` file. To use these functions, we need to load the library corresponding to the solver. An example of using different parallel sparse solvers for the same problem is given in `testdirectsolvers.edp` (directory `example+ + -mpi`).

Libraries	default sparse solver	
	real	complex
MUMPS_FreeFem	mumps	mumps
real_SuperLU_DIST_FreeFem	SuperLU_DIST	previous solver
complex_SuperLU_DIST_FreeFem	previous solver	SuperLU_DIST
real_pastix_FreeFem	pastix	previous solver
complex_pastix_FreeFem	previous solver	pastix
hips_FreeFem	hips	previous solver
hypre_FreeFem	hypre	previous solver
parms_FreeFem	parms	previous solver

Table 11.1: Default sparse solver for real and complex arithmetics when we load a parallel sparse solver library

function	default sparse solver	
	real	complex
defaulttoMUMPS()	mumps	mumps
realdefaulttoSuperLUdist()	SuperLU_DIST	previous solver
complexdefaulttoSuperLUdist()	previous solver	SuperLU_DIST
realdefaulttopastix()	pastix	previous solver
complexdefaulttopastix()	previous solver	pastix
defaulttohips()	hips	previous solver
defaulttohypre()	hypre	previous solver
defaulttoparms()	parms	previous solver

Table 11.2: Functions that allow to change the default sparse solver for real and complex arithmetics and the result of these functions

### Example 11.1 (testdirectsolvers.edp)

```

load "../src/solver/MUMPS_FreeFem"
                                // default solver : real-> MUMPS, complex -> MUMPS
load "../src/solver/real_SuperLU_DIST_FreeFem"
                                // default solver : real-> SuperLU_DIST, complex -> MUMPS
load "../src/solver/real_pastix_FreeFem"
                                // default solver : real-> pastix, complex -> MUMPS
                                // solving with pastix
{
  matrix A =
    [[ 1,  2,      2,  1, 1],
     [ 2,   12,    0, 10, 10],
     [ 2,    0,    1,  0, 2],
     [ 1,   10,    0, 22, 0.],
     [ 1,   10,    2,  0., 22]];

  real[int] xx = [ 1,32,45,7,2], x(5), b(5), di(5);
  b=A*xx;
  cout << "b=" << b << endl;
  cout << "xx=" << xx << endl;
}

```

```

    set(A,solver=sparsesolver,datafilename="ffpastix_iparm_dparm.txt");
    cout << "solving solution" << endl;
    x = A^-1*b;
    cout << "b=" << b << endl;
    cout << "x=" << endl; cout << x << endl;
    di = xx-x;
    if(mpirank==0){
    cout << "x-xx="<< endl; cout << "Linf "<< di.linf << " L2 " << di.l2 << endl;
    }
}

// solving with SuperLU_DIST
realdefaulttoSuperLUDist();
// default solver : real-> SuperLU_DIST, complex -> MUMPS
{
    matrix A =
        [[ 1, 2, 2, 1, 1],
         [ 2, 12, 0, 10, 10],
         [ 2, 0, 1, 0, 2],
         [ 1, 10, 0, 22, 0.],
         [ 1, 10, 2, 0., 22]];

    real[int] xx = [ 1,32,45,7,2], x(5), b(5), di(5);
    b=A*xx;
    cout << "b=" << b << endl;
    cout << "xx=" << xx << endl;

    set(A,solver=sparsesolver,datafilename="ffsuperlu_dist_fileparam.txt");
    cout << "solving solution" << endl;
    x = A^-1*b;
    cout << "b=" << b << endl;
    cout << "x=" << endl; cout << x << endl;
    di = xx-x;
    if(mpirank==0){
    cout << "x-xx="<< endl; cout << "Linf "<< di.linf << " L2 " << di.l2 << endl;
    }
}

// solving with MUMPS
defaulttoMUMPS();
// default solver : real-> MUMPS, complex -> MUMPS
{
    matrix A =
        [[ 1, 2, 2, 1, 1],
         [ 2, 12, 0, 10, 10],
         [ 2, 0, 1, 0, 2],
         [ 1, 10, 0, 22, 0.],
         [ 1, 10, 2, 0., 22]];

    real[int] xx = [ 1,32,45,7,2], x(5), b(5), di(5);
    b=A*xx;
    cout << "b=" << b << endl;
    cout << "xx=" << xx << endl;

    set(A,solver=sparsesolver,datafilename="ffmumps_fileparam.txt");
    cout << "solving solution" << endl;

```

```

x = A^-1*b;
cout << "b=" << b << endl;
cout << "x=" << endl; cout << x << endl;
di = xx-x;
if(mpirank==0){
cout << "x-xx=" << endl; cout << "Linf " << di.linf << " L2 " << di.l2 << endl;
}
}

```

## 11.2 Sparse direct solver

In this section, we present the sparse direct solvers interfaced with **FreeFem++** .

### 11.2.1 MUMPS solver

Multifrontal Massively Parallel Solver (MUMPS) is a free library [?, ?, ?]. This package solves linear system of the form  $A x = b$  where  $A$  is a square sparse matrix with a direct method. The square matrix considered in MUMPS can be either unsymmetric, symmetric positive definite or general symmetric. The method implemented in MUMPS is a direct method based on a multifrontal approach [?]. It constructs a direct factorization  $A = L U$ ,  $A = L^T D L$  depending of the symmetry of the matrix  $A$ . MUMPS uses the following libraries : BLAS[?, ?], BLACS and ScaLAPACK[?].

**Remark 7** *MUMPS does not solve linear system with a rectangular matrix.*

**Installation of MUMPS** To used MUMPS in **FreeFem++** , you have to install the MUMPS package into your computer. MUMPS is written in Fortran 90. The parallel version is constructed using MPI [?] for message passing and BLAS [?, ?], BLACS and ScaLAPACK[?]. Therefore, a fortran compiler is needed, and MPI, BLAS, BLACS and ScaLAPACK . An installation procedure to obtain this package is given in the file README.COMPILE in the directory src/solver of **FreeFem++** .

**Creating Library of MUMPS interface for FreeFem++ :** The MUMPS interface for **FreeFem++** is given in file MUMPS\_freemem.cpp (directory src/solver/ ). This interface works with the release 3.8.3 and 3.8.4 of MUMPS. To used MUMPS in **FreeFem++** , we need the library corresponding to this interface. A description to obtain this library is given in the file README.COMPILE in the directory src/solver of **FreeFem++** . We recall here the procedure. Go to the directory src/solver in **FreeFem++** package. Edit the file makefile-sparsesolver.inc to yours system: comment Section 1, comment line corresponding to libraries BLAS, BLACS, ScaLAPACK, Metis, scotch in Section 2 and comment in Section 3 the paragraph corresponding to MUMPS solver. And then type **make mumps** in a terminal window.

Now we give a short description of MUMPS parameters before describing the method to call MUMPS in **FreeFem++** .

**MUMPS parameters:** There are four input parameters in MUMPS (see [?]). Two integers SYM and PAR, a vector of integer of size 40 INCTL and a vector of real of size 15 CNTL. The first parameter gives the type of the matrix: 0 for unsymmetric matrix, 1 for symmetric positive matrix and 2 for general symmetric. The second parameter defined if the host processor work during the factorization and solves steps : PAR=1 host processor working and PAR=0 host processor not working. The parameter INCTL and CNTL is the control parameter of MUMPS. The vectors ICNTL and CNTL in MUMPS becomes with index 1 like vector in fortran. A short description of all parameters of ICNTL and CNTL is given in `ffmumps_fileparam.txt`. For more details see the users' guide [?].

We describe now some elements of the main parameters of ICNTL for MUMPS.

**Input matrix parameter** The input matrix is controlled by parameters ICNTL(5) and ICNTL(18). The matrix format (resp. matrix pattern and matrix entries) are controlled by INCTL(5) (resp. INCTL(18)). The different values of ICNTL(5) are 0 for assembled format and 1 for element format. In the current release of FreeFem++, we consider that FE matrix or matrix is storage in assembled format. Therefore, INCTL(5) is treated as 0 value. The main option for ICNTL(18): INCTL(18)=0 centrally on the host processor, ICNTL(18)=3 distributed the input matrix pattern and the entries (recommended option for distributed matrix by developer of MUMPS). For other values of ICNTL(18) see the user's guide of MUMPS. These values can be used also in FreeFem++.

The default option implemented in FreeFem++ are ICNTL(5)=0 and ICNTL(18)=0.

**Preprocessing parameter** The preprocessed matrix  $A_p$  that will be effectively factored is defined by

$$A_p = P D_r A Q_c D_c P^t$$

where  $P$  is the permutation matrix,  $Q_c$  is the column permutation,  $D_r$  and  $D_c$  are diagonal matrix for respectively row and column scaling. The ordering strategy to obtain  $P$  is controlled by parameter ICNTL(7). The permutation of zero free diagonal  $Q_c$  is controlled by parameter ICNTL(6). The row and column scaling is controlled by parameter ICNTL(18). These option are connected and also strongly related with ICNTL(12) (see documentation of mumps for more details [?]). The parameters `permr`, `scaler`, and `scalec` in FreeFem++ allow to give permutation matrix( $P$ ), row scaling ( $D_r$ ) and column scaling ( $D_c$ ) of the user respectively.

**Calling MUMPS in FreeFem++** To call MUMPS in FreeFem++ , we need to load the dynamic library `MUMPS_freefem.dylib` (MacOSX), `MUMPS_freefem.so` (Unix) or `MUMPS_freefem.dll` (Windows). This is done in typing load "MUMPS\_freefem" in the .edp file. We give now the two methods to give the option of MUMPS solver in FreeFem++ .

**Solver parameters is defined in .edp file:** In this method, we need to give the parameters `lparams` and `dparams`. These parameters are defined for MUMPS by

$$\begin{aligned} & \text{lparams}[0] = \text{SYM}, \\ & \text{lparams}[1] = \text{PAR}, \\ \forall i = 1, \dots, 40, & \quad \text{lparams}[i+1] = \text{ICNTL}(i). \\ \forall i = 1, \dots, 15, & \quad \text{dparams}[i-1] = \text{CNTL}(i). \end{aligned}$$

**Reading solver parameters on a file:** The structure of data file for MUMPS in FreeFem++ is : first line parameter SYM and second line parameter PAR and in the following line the different value of vectors ICNTL and CNTL. An example of this parameter file is given in `ffmumpsfileparam.txt`.

```

0          /* SYM :: 0 for non symmetric matrix, 1 for symmetric definite positive matrix and
2 general symmetric matrix*/
1          /* PAR :: 0 host not working during factorization and solves steps, 1 host working
during factorization and solves steps*/
-1         /* ICNTL(1) :: output stream for error message */
-1         /* ICNTL(2) :: output for diagnostic printing, statics and warning message */
-1         /* ICNTL(3) :: for global information */
0          /* ICNTL(4) :: Level of printing for error, warning and diagnostic message */
0          /* ICNTL(5) :: matrix format : 0 assembled format, 1 elemental format. */
7          /* ICNTL(6) :: control option for permuting and/or scaling the matrix in analysis
phase */
3          /* ICNTL(7) :: pivot order strategy : AMD, AMF, metis, pord scotch*/
77         /* ICNTL(8) :: Row and Column scaling strategy */
1          /* ICNTL(9) :: 0 solve  $Ax = b$ , 1 solve the transposed system  $A^t x = b$  : parameter
is not considered in the current release of freefem++*/
0          /* ICNTL(10) :: number of steps of iterative refinement */
0          /* ICNTL(11) :: statics related to linear system depending on ICNTL(9) */
1          /* ICNTL(12) :: constrained ordering strategy for general symmetric matrix */
0          /* ICNTL(13) :: method to control splitting of the root frontal matrix */
20         /* ICNTL(14) :: percentage increase in the estimated working space (default 20%)*
0          /* ICNTL(15) :: not used in this release of MUMPS */
0          /* ICNTL(16) :: not used in this release of MUMPS */
0          /* ICNTL(17) :: not used in this release of MUMPS */
3          /* ICNTL(18) :: method for given : matrix pattern and matrix entries : */
0          /* ICNTL(19) :: method to return the Schur complement matrix */
0          /* ICNTL(20) :: right hand side form ( 0 dense form, 1 sparse form) : parameter
will be set to 0 for freefem++ */
0          /* ICNTL(21) :: 0, 1 kept distributed solution : parameter is not considered in
the current release of freefem++ */
0          /* ICNTL(22) :: controls the in-core/out-of-core (OOC) facility */
0          /* ICNTL(23) :: maximum size of the working memory in Megabyte than MUMPS can allocate
per working processor */
0          /* ICNTL(24) :: control the detection of null pivot */
0          /* ICNTL(25) :: control the computation of a null space basis */
0          /* ICNTL(26) :: This parameter is only significant with Schur option (ICNTL(19)
not zero). : parameter is not considered in the current release of freefem++ */
-8         /* ICNTL(27) (Experimental parameter subject to change in next release of MUMPS)
:: control the blocking factor for multiple righthand side during the solution phase : parameter
is not considered in the current release of freefem++ */
0          /* ICNTL(28) :: not used in this release of MUMPS*/
0          /* ICNTL(29) :: not used in this release of MUMPS*/
0          /* ICNTL(30) :: not used in this release of MUMPS*/
0          /* ICNTL(31) :: not used in this release of MUMPS*/
0          /* ICNTL(32) :: not used in this release of MUMPS*/
0          /* ICNTL(33) :: not used in this release of MUMPS*/
0          /* ICNTL(34) :: not used in this release of MUMPS*/
0          /* ICNTL(35) :: not used in this release of MUMPS*/
0          /* ICNTL(36) :: not used in this release of MUMPS*/
0          /* ICNTL(37) :: not used in this release of MUMPS*/
0          /* ICNTL(38) :: not used in this release of MUMPS*/
1          /* ICNTL(39) :: not used in this release of MUMPS*/
0          /* ICNTL(40) :: not used in this release of MUMPS*/
0.01       /* CNTL(1) :: relative threshold for numerical pivoting */
1e-8       /* CNTL(2) :: stopping criteria for iterative refinement */
-1         /* CNTL(3) :: threshold for null pivot detection */

```

```

-1      /* CNTL(4) :: determine the threshold for partial pivoting */
0.0     /* CNTL(5) :: fixation for null pivots */
0       /* CNTL(6) :: not used in this release of MUMPS */
0       /* CNTL(7) :: not used in this release of MUMPS */
0       /* CNTL(8) :: not used in this release of MUMPS */
0       /* CNTL(9) :: not used in this release of MUMPS */
0       /* CNTL(10) :: not used in this release of MUMPS */
0       /* CNTL(11) :: not used in this release of MUMPS */
0       /* CNTL(12) :: not used in this release of MUMPS */
0       /* CNTL(13) :: not used in this release of MUMPS */
0       /* CNTL(14) :: not used in this release of MUMPS */
0       /* CNTL(15) :: not used in this release of MUMPS */

```

If no solver parameter is given, we used default option of MUMPS solver.

**example** A simple example of calling MUMPS in FreeFem++ with this two methods is given in the file `testsolver_MUMPS.edp` in the directory `examples++-mpi`.

### 11.2.2 SuperLU distributed solver

The package SuperLU\_DIST [?, ?] solves linear systems using LU factorization. It is a free scientific library under BSD license. The web site of this project is <http://crd.lbl.gov/~xiaoye/SuperLU>. This library provides functions to handle square or rectangular matrix in real and complex arithmetics. The method implemented in SuperLU\_DIST is a supernodal method [?]. New release of this package includes a parallel symbolic factorization [?]. This scientific library is written in C and MPI for communications.

**Installation of SuperLU\_DIST:** To use SuperLU\_DIST in FreeFem++ , you have to install SuperLU\_DIST package. We need MPI and ParMetis library to do this compilation. An installation procedure to obtain this package is given in the file `README_COMPILE` in the directory `src/solver/` of the `freefem++` package.

**Creating Library of SuperLU\_DIST interface for FreeFem++ :** The FreeFem++ interface to SuperLU\_DIST for real (resp. complex) arithmetics is given in file `real.SuperLU_DIST.FreeFem.cpp` (resp. `complex.SuperLU_DIST.FreeFem.cpp`). These files are in the directory `src/solver/`. These interfaces are compatible with the release 3.2.1 of SuperLU\_DIST. To use SuperLU\_DIST in FreeFem++ , we need libraries corresponding to these interfaces. A description to obtain these libraries is given in the file `README_COMPILE` in the directory `src/solver` of FreeFem++ . We recall here the procedure. Go to the directory `src/solver` in FreeFem++ package. Edit the file `makefile-sparsesolver.inc` in your system : comment Section 1, comment line corresponding to libraries BLAS, Metis, ParMetis in Section 2 and comment in Section 3 the paragraph corresponding to SuperLU\_DIST solver. And just type **make rsludist** (resp. **make csludist**) in the terminal to obtain the dynamic library of interface for real (resp. complex) arithmetics.

Now we give a short description of SuperLU\_DIST parameters before describing the method to call SuperLU\_DIST in FreeFem++ .

**SuperLU\_DIST parameters:** We describe now some parameters of SuperLU\_DIST. The SuperLU\_DIST library use a 2D-logical process group. This process grid is specifies by *nprow* (process row) and *npcol* (process column) such that  $N_p = nprow \cdot npcol$  where  $N_p$  is the number of all process allocated for SuperLU\_DIST.





```

NO                      /* ReplaceTinyPivot : NO, YES*/
NO                      /* SolveInitialized : NO, YES*/
NO                      /* RefineInitialized : NO, YES*/
NO                      /* PrintStat : NO, YES*/
NOEQUIL                 /* DiagScale : NOEQUIL, ROW, COL, BOTH*/

```

If no solver parameter is given, we used default option of SuperLU\_DIST solver.

**Example 11.2** A simple example of calling SuperLU\_DIST in FreeFem++ with this two methods is given in the file `testsolver_superLU_DIST.edp` in the directory `examples++-mpi`.

### 11.2.3 Pastix solver

Pastix (Parallel Sparse matrix package) is a free scientific library under CECILL-C license. This package solves sparse linear system with a direct and block ILU(k) iterative methods. This solver can be applied to a real or complex matrix with a symmetric pattern [?].

**Installation of Pastix:** To use Pastix in FreeFem++ , you have to install pastix package in first. To compile this package, we need a fortran 90 compiler, scotch [?] or Metis [?] ordering library and MPI. An installation procedure to obtain this package is given in the file `.src/solver/ README_COMPILE` in the section pastix of the FreeFem++ package.

**Creating Library of pastix interface for FreeFem++ :** The FreeFem++ interface to pastix is given in file `real_pastix_FreeFem.cpp` (resp. `complex_pastix_FreeFem.cpp`) for real (resp.complex) arithmetics. This interface is compatible with the release 2200 of pastix and is designed for a global matrix. We have also implemented interface for distributed matrices. To use pastix in FreeFem++ , we need the library corresponding to this interface. A description to obtain this library is given in the file `README_COMPILE` in the directory `src/solver` of FreeFem++ . We recall here the procedure. Go to the directory `src/solver` in FreeFem++ package. Edit the file `makefile-sparsesolver.inc` to yours system : comment Section 1, comment line corresponding to libraries BLAS, METIS and SCOTCH in Section 2 and comment in Section 3 the paragraph corresponding to pastix solver. And just type **make rpastix** (resp. **make cpastix**) in the terminal to obtain the dynamic library of interface for real (resp. complex) arithmetics.

Now we give a short description of pastix parameters before describing the method to call pastix in FreeFem++ .

**Pastix parameters:** The input `matrix` parameter of FreeFem++ depend on pastix interface. `matrix=assembled` for non distributed matrix. It is the same parameter for SuperLU\_DIST. There are four parameters in Pastix : `iparm`, `dparm`, `perm` and `invp`. These parameters are respectively the integer parameters (vector of size 64), real parameters (vector of size 64), permutation matrix and inverse permutation matrix respectively. `iparm` and `dparm` vectors are described in [?]. The parameters `permr` and `permc` in FreeFem++ are provided to give permutation matrix and inverse permutation matrix of the user respectively.

**Solver parameters defined in .edp file:** To call Pastix in FreeFem++ in this case, we need to specify the parameters **lparams** and **dparams**. These parameters are defined by

$$\forall i = 0, \dots, 63, \quad \text{lparams}[i] = \text{iparm}[i].$$

$$\forall i = 0, \dots, 63, \quad \text{dparams}[i] = \text{dparm}[i].$$

direct solver	square matrix			rectangular matrix		
	sym	sym pattern	unsym	sym	sym pattern	unsym
SuperLU_DIST	yes	yes	yes	yes	yes	yes
MUMPS	yes	yes	yes	no	no	no
pastix	yes	yes	no	no	no	no

Table 11.3: Type of matrix used by the different direct sparse solver

**Reading solver parameters on a file:** The structure of data file for pastix parameters in FreeFem++ is : first line structure parameters of the matrix and in the following line the value of vectors iparm and dparm in this order.

```

assembled /* matrix input :: assembled, distributed global and distributed */
iparm[0]
iparm[1]
...
...
iparm[63]
dparm[0]
dparm[1]
...
...
dparm[63]

```

An example of this file parameter is given in ffpastix\_iparm\_dparm.txt with a description of these parameters. This file is obtained with the example file iparm.txt and dparm.txt including in the pastix package.

If no solver parameter is given, we use the default option of pastix solver.

**Example:** A simple example of calling pastix in FreeFem++ with this two methods is given in the file testsolver\_pastix.edp in the directory examples++-mpi.

In Table 11.3, we recall the different matrix considering in the different direct solvers.

## 11.3 Parallel sparse iterative solver

Concerning **iterative solvers**, we have chosen *pARMS* [?], *HIPS* [?] and *Hypre* [?]. Each software implements a different type of parallel preconditioner. So, *pARMS* implements algebraic domain decomposition preconditioner type such as additive Schwarz [?] and interface method [?]; while *HIPS* implements hierarchical incomplete factorization [?] and finally *HYPRE* implements multilevel preconditioner are AMG (Algebraic MultiGrid) [?] and parallel approximated inverse [?].

To use one of these programs in FreeFem++, you have to install it independently of FreeFem++. It is also necessary to install the MPI communication library which is essential for communication between the processors and, in some cases, software partitioning graphs like METIS [?] or Scotch [?].

All this preconditioners are used with Krylov subspace methods accelerators. Krylov subspace methods are iterative methods which consist in finding a solution  $x$  of linear system  $Ax = b$  inside the affine space  $x_0 + K_m$  by imposing that  $b - Ax \perp \mathcal{L}_m$ , where  $K_m$  is Krylov subspace of dimension  $m$  defined by  $K_m = \{r_0, Ar_0, A^2r_0, \dots, A^{m-1}r_0\}$  and  $\mathcal{L}_m$  is another subspace of dimension  $m$  which depends on type of Krylov subspace. For example in GMRES,  $\mathcal{L}_m = AK_m$ .

We realized an interface which is easy to use, so that the call of these different softwares in FreeFem++ is done in the same way. You just have to load the solver and then specify the parameters to apply to the specific solvers. In the rest of this chapter, when we talk about Krylov subspace methods we mean one among GMRES, CG and BICGSTAB.

### 11.3.1 pARMS solver

**pARMS** (*parallel Algebraic Multilevel Solver*) is a software developed by Youssef Saad and al at University of Minnesota [?]. This software is specialized in the resolution of large sparse non symmetric linear systems of equation. Solvers developed in pARMS is the Krylov subspace type. It consists of variants of GMRES like FGMRES(Flexible GMRES) , DGMRES(Deflated GMRES) [?] and BICGSTAB. pARMS also implements parallel preconditioner like RAS (Restricted Additive Schwarz)[?] and Schur Complement type preconditioner [?].

All these parallel preconditioners are based on the principle of domain decomposition. Thus, the matrix  $A$  is partitioned into sub matrices  $A_i (i = 1, \dots, p)$  where  $p$  represents the number of partitions one needs. The union of  $A_i$  forms the original matrix. The solution of the overall system is obtained by solving the local systems on  $A_i$  (see [?]). Therefore, a distinction is made between iterations on  $A$  and the local iterations on  $A_i$ . To solve the local problem on  $A_i$  there are several preconditioners as **ilut** (Incomplete LU with threshold), **iluk**(Incomplete LU with level of fill in) and **ARMS**( Algebraic Recursive Multilevel Solver). But to use pAMRS in FreeFem++ you have first to install pAMRS.

**Installation of pARMS** To install pARMS, you must first download the pARMS package at [?]. Once the download is complete, you must unpack package pARMS and follow the installation procedure described in file README to create the library **libparms.a**.

**Using pARMS as interface to FreeFem++** Before calling pARMS solver inside FreeFem++, you must compile file *parms\_FreeFem.cpp* to create a dynamic library *parms\_FreeFem.so*. To do this, move to the directory *src/solver* of FreeFem++, edit the file *makefileparms.inc* to specify the following variables:

<b>PARMS_DIR :</b>	Directory of pARMS
<b>PARMS_INCLUDE :</b>	Directory for header of pARMS
<b>METIS :</b>	METIS directory
<b>METIS_LIB :</b>	METIS librairy
<b>MPI :</b>	MPI directory
<b>MPI_INCLUDE :</b>	MPI headers
<b>FREEFEM :</b>	FreeFem++ directory
<b>FREEFEM_INCLUDE :</b>	FreeFem++ header for sparse linear solver
<b>LIBBLAS :</b>	Blas library

After that, in the command line type **make parms** to create *parms\_FreeFem.so*.

As usual in FreeFem++, we will show by examples how to call pARMS in FreeFem++. There are three ways of doing this:

**Example 1: Default parameters** This example comes from user guide of FreeFem++ [?] at page 12.

#### Example 11.3

```
1: load parms_freefem // Tell FreeFem that you will use pARMS
2: border C(t=0,2*pi){x=cos(t); y=sin(t);label=1;}
3: mesh Th = buildmesh (C(50));
```

```

4: fespace Vh(Th,P2);
5: Vh u,v;
6: func f= x*y;
7: problem Poisson(u,v,solver=sparse solver) =           // bilinear part will use
8:   int2d(Th)(dx(u)*dx(v) + dy(u)*dy(v)) // a sparse solver, in this case pARMS
9:   - int2d(Th)( f*v) // right hand side
10:  + on(1,u=0) ; // Dirichlet boundary condition
11:
12: real cpu=clock();
13: Poisson; // SOLVE THE PDE
14: plot(u);
15: cout << " CPU time = " << clock()-cpu << endl;

```

In line 1 of example 11.3 we load in memory the pARMS dynamic library with interface FreeFem++. After this, in line 7 we specify that the bilinear form will be solved by the last sparse linear solver load in memory which, in this case, is pARMS.

The parameter used in pARMS in this case is the default one since the user does not have to provide any parameter.

Here are some default parameters:

**solver=FGMRES, Krylov dimension=30, Maximum of Krylov=1000, Tolerance for convergence= $1e-08$ .**(see book of Saad [?] to understand all this parameters.)

**preconditionner=Restricted Additif Schwarz [?], Inner Krylov dimension=5, Maximum of inner Krylov dimension=5, Inner preconditionner=ILUK.**

To specify the parameters to apply to the solver, the user can either give an integer vector for **integer parameters** and real vectors for **real parameters** or provide a **file** which contains those parameters.

**Example 2: User specifies parameters inside two vectors** Lets us consider Navier Stokes example 11.4 . In this example we solve linear systems coming from discretization of Navier Stokes equation with pARMS. Parameters of solver is specified by user.

**Example 11.4 (Stokes.edp)** include "manual.edp"

```

include "includes.edp";
include "mesh_with_cylinder.edp";
include "bc_poiseuille_in_square.edp";
include "fe_functions.edp";
0: load parms_FreeFem
1: int[int] iparm(16); real[int] dparam(6);
2: int ,ii;
3: for(ii=0;ii<16;ii++){iparm[ii]=-1;} for(ii=0;ii<6;ii++) dparam[ii]=-1.0;
4: fespace Vh(Th,[P2,P2,P1]);
5: iparm[0]=0;
6: varf Stokes ([u,v,p],[ush,vsh,psh},{solver=sparse solver}) =
  int2d(Th)( nu*( dx(u)*dx(ush) + dy(u)*dy(ush) + dx(v)*dx(vsh) + dy(v)*dy(vsh) )
    - p*psh*(1.e-6) // p epsilon
    - p*(dx(ush)+dy(vsh)) // + dx(p)*ush + dy(p)*vsh
    - (dx(u)+dy(v))*psh // psh div(u)
  )
  + on(cylinder,infwall,supwall,u=0.,v=0.)+on(inlet,u=uc,v=0); // Bdy conditions
7: matrix AA=Stokes(VVh,VVh);
8: set(AA,solver=sparse solver,lparams=iparm,dparams=dparam); // Set pARMS as linear
solver

```

```

9: real[int] bb= Stokes(0,VWh); real[int] sol(AA.n);
10: sol= AA^-1 * bb;

```

We need two vectors to specify the parameters of the linear solver. In line 1 of example 11.4 we have declared these vectors(**int**[**int**] **iparm**(16); **real**[**int**] **dparm**(6);) . In line 3 we have initialized these vectors by negative values. We do this because all parameters values in pARMS are positive and if you do not change the negative values of one entry of this vector, the default value will be set. In tables (table 11.4 and 11.5) , we have the meaning of different entries of these vectors.

Entries of <b>iparm</b>	Significations of each entries
<b>iparm</b> [0]	Krylov subspace methods. Different values for this parameters are specify on table 11.6
<b>iparm</b> [1]	Preconditionner. Different preconditionners for this parameters are specify on table 11.7
<b>iparm</b> [2]	Krylov subspace dimension in outer iteration: default value 30
<b>iparm</b> [3]	Maximum of iterations in outer iteration: default value 1000
<b>iparm</b> [4]	Number of level in arms when used.
<b>iparm</b> [5]	Krylov subspace dimension in inner iteration: default value 3
<b>iparm</b> [6]	Maximum of iterations in inner iteration: default value 3
<b>iparm</b> [7]	Symmetric(=1 for symmetric) or unsymmetric matrix: default value 0(unsymmetric matrix)
<b>iparm</b> [8]	Overlap size between different subdomain: default value 0(no overlap)
<b>iparm</b> [9]	Scale the input matrix or not: Default value 1 (Matrix should be scale)
<b>iparm</b> [10]	Block size in arms when used: default value 20
<b>iparm</b> [11]	lfl0 (ilut, iluk, and arms) : default value 20
<b>iparm</b> [12]	lfl for Schur complement const : default value 20
<b>iparm</b> [13]	lfl for Schur complement const : default value 20
<b>iparm</b> [14]	Multicoloring or not in ILU when used : default value 1
<b>iparm</b> [15]	Inner iteration : default value 0
<b>iparm</b> [16]	Print message when solving:default 0(no message print). 0: no message is print, 1: Convergence informations like number of iteration and residual , 2: Timing for a different step like preconditioner 3 : Print all informations.

Table 11.4: Meaning of **lparams** corresponding variables for example 11.4

We run example 11.4 on cluster pararent of Grid5000 and report results in table 11.8.

In this example, we fix the matrix size (in term of finite element, we fix the mesh) and increase the number of processors used to solve the linear system. We saw that, when the number of processors increases, the time for solving the linear equation decreases, even if the number of iteration increases. This proves that, using pARMS as solver of linear systems coming from discretization of partial differential equation in FreeFem++ can decrease drastically the total time of simulation.

### 11.3.2 Interfacing with HIPS

**HIPS** (*Hierarchical Iterative Parallel Solver*) is a scientific library that provides an efficient parallel iterative solver for very large sparse linear systems. HIPS is available as free software under the CeCILL-C licence.

Entries of dparam	Significations of each entries
dparm[0]	precision for outer iteration : default value 1e-08
dparm[1]	precision for inner iteration: default value 1e-2
dparm[2]	tolerance used for diagonal domain: : default value 0.1
dparm[3]	drop tolerance droptol0 (ilut, iluk, and arms) : default value 1e-2
dparm[4]	droptol for Schur complement const: default value 1e-2
dparm[5]	droptol for Schur complement const: default value 1e-2

Table 11.5: Significations of **dparams** corresponding variables for example 11.4

Values of iparm[0]	Krylov subspace methods
0	FGMRES (Flexible GMRES)
1	DGMRES (Deflated GMRES)
2	BICGSTAB

Table 11.6: Krylov Solvers in pARMS

The interface that we realized is compatible with release **1.2 beta.rc4** of HIPS.

HIPS implements two solver classes which are the iteratives class ( GMRES, PCG) and the Direct class. Concerning preconditionners, HIPS implements a type of multilevel ILU. For further informations on those preconditionners see [?, ?].

**Installation of HIPS** To install HIPS, first download the HIPS package at [?], unpack it and go to the HIPS source directory. The installation of HIPS is machine dependence. For example, to install HIPS on a linux cluster copy the file *Makefile\_Inc\_Examples/makefile.inc.gnu* on the root directory of HIPS with the name **makefile.inc**. After this, edit **makefile.inc** to set values of different variables and type **make all**.

**Using HIPS as the interface to FreeFem++** Before calling the HIPS solver inside FreeFem++, you must compile file *hips\_FreeFem.cpp* to create dynamic library *hips\_FreeFem.so*. To do this, move to the directory *src/solver* of FreeFem++ and edit the file *makefile.inc* to specify the following variables:

```

HIPS_DIR :           Directory of HIPS
HIPS_INCLUDE:        -I$(HIPS_DIR)/SRC/INCLUDE : Directory for HIPS headers
LIB_DIR :            -L$(HIPS_DIR)/LIB : Librairies directory
LIBHIPSSEQUENTIAL : $(HIPS_DIR)/LIB/libhipssequential.a: HIPS utilities library
LIBHIPS :            $(HIPS_DIR)/LIB/libhips.a: HIPS library
FREEFEM :            FreeFem++ directory
FREEFEM_INCLUDE :    FreeFem headers for sparse linear solver
METIS :              METIS directory
METIS_LIB :          METIS library
MPI :                MPI directory
MPI_INCLUDE :        MPI headers

```

After specifies all the variables, in the command line in the directory *src/solver* type **make hips** to create *hips\_FreeFem.so*.

Like with pARMS, the calling of HIPS in FreeFem++ can be done in three different manners. We will present only one example where the user specifies the parameters through keywords lparams and dparams.

Values of iparm[1]	Preconditionners
0	Preconditioners type is <i>additive Schwartz preconditioner with ilu0 as local preconditioner,</i>
1	preconditioner type is <i>additive Schwartz preconditioner with iluk as local preconditioner,</i>
2	preconditioner type is <i>additive Schwartz preconditioner with ilut as local preconditioner,</i>
3	preconditioner type is <i>additive Schwartz preconditioner with arms as local preconditioner,</i>
4	preconditioner type is <i>Left Schur complement preconditioner with ilu0 as local preconditioner,</i>
5	preconditioner type is <i>Left Schur complement preconditioner with ilut as local preconditioner,</i>
6	preconditioner type is <i>Left Schur complement preconditioner with iluk as local preconditioner,</i>
7	preconditioner type is <i>Left Schur complement preconditioner with arms as local preconditioner,</i>
8	preconditioner type is <i>Right Schur complement preconditioner with ilu0 as local preconditioner,</i>
9	preconditioner type is <i>Right Schur complement preconditioner with ilut as local preconditioner,</i>
10	preconditioner type is <i>Right Schur complement preconditioner with iluk as local preconditioner,</i>
11	preconditioner type is <i>Right Schur complement preconditioner with arms as local preconditioner,</i>
12	preconditioner type is <i>sch_gilu0</i> , Schur complement preconditioner with global ilu0
13	preconditioner type is <i>SchurSymmetric GS preconditioner</i>

Table 11.7: Preconditionners in pARMS

<b>n= 471281</b>		<b>nnz=<math>13 \times 10^6</math></b>		<b>Te=571,29</b>
np	add(iluk)		schur(iluk)	
	nit	time	nit	time
4	230	637.57	21	557.8
8	240	364.12	22	302.25
16	247	212.07	24	167.5
32	261	111.16	25	81.5

Table 11.8: Convergence and time for solving linear system from example 11.4

n	matrix size
nnz	number of non null entries inside matrix
nit	number of iteration for convergence
time	Time for convergence
Te	Time for constructing finite element matrix
np	number of processor

Table 11.9: Legend of table 11.8

**Laplacian 3D solve with HIPS** Let us consider the 3D Laplacian example inside FreeFem++ package where after discretization we want to solve the linear equation with Hips. Example 11.5 is Laplacian3D using Hips as linear solver. We first load Hips solver at line 2. From line 4 to 15 we specify the parameters for the Hips solver and in line 46 of example 11.5 we set these parameters in the linear solver. In Table 11.10 results of running example 11.5 on Cluster Paradent of Grid5000 are reported. We can see in this running example the efficiency of parallelism.

**Example 11.5 (Laplacian3D.edp)** 1: `load "msh3"`

```

2: load "hips_FreeFem" // load library
3: int nn=10,iii;
4: int[int] iparm(14);
5: real[int] dparm(6);
6: for(iii=0;iii<14;iii++)iparm[iii]=-1;
7: for(iii=0;iii<6;iii++) dparm[iii]=-1;
8: iparm[0]=0; // use iterative solver
9: iparm[1]=1; // PCG as Krylov method
10:iparm[4]=0; // Matrix are symmetric
11:iparm[5]=1; // Pattern are also symmetric
12: iparm[9]=1; // Scale matrix
13:dparm[0]=1e-13; // Tolerance to convergence
14: dparm[1]=5e-4; // Threshold in ILUT
15: dparm[2]=5e-4; // Threshold for Schur preconditionner
16: mesh Th2=square(nn,nn);
17: fespace Vh2(Th2,P2);
18: Vh2 ux,uz,p2;
19: int[int] rup=[0,2], rdown=[0,1], rmid=[1,1,2,1,3,1,4,1];
20:real zmin=0,zmax=1;
21: mesh3 Th=buildlayers(Th2,nn,
    zbound=[zmin,zmax],
    reffacemid=rmid,
    reffaceup = rup,
    reffacelow = rdown);
22: savemesh(Th,"copie.mesh");
23: mesh3 Th3("copie.mesh");
24: fespace Vh(Th,P2);
25: func ue = 2*x*x + 3*y*y + 4*z*z + 5*x*y+6*x*z+1;
26: func uex= 4*x+ 5*y+6*z;
27: func uey= 6*y + 5*x;
28: func uez= 8*z +6*x;
29: func f= -18. ;
30: Vh uhe = ue; //
31: cout << " uhe min: " << uhe[].min << " max:" << uhe[].max << endl;
32: Vh u,v;

```



$n = 4 \times 10^6$	$nnz = 118 \times 10^6$	<b>Te=221.34</b>
np	nit	time
8	190	120.34
16	189	61.08
32	186	31.70
64	183	23.44

Table 11.10: Iterations and Timing of solving linear system from example 11.5

```

33: macro Grad3(u) [dx(u),dy(u),dz(u)]
34: varf va(u,v)= int3d(Th)(Grad3(v)' *Grad3(u))
    + int2d(Th,2)(u*v)
    - int3d(Th)(f*v)
    - int2d(Th,2) ( ue*v + (uex*N.x +uey*N.y +uez*N.z)*v )
    + on(1,u=ue);
35: real cpu=clock();
36: matrix Aa;
37: Aa=va(Vh,Vh);
38: varf l(unused,v)=int3d(Th)(f*v);
39: Vh F; F[]=va(0,Vh);
40: if(mpirank==0){
    cout << "Taille " << Aa.n << endl;
    cout << "Non zeros " << Aa.nbcoef << endl;
}
41: if(mpirank==0)
42:   cout << "CPU TIME FOR FORMING MATRIX = " << clock()-cpu << endl;
43:   set(Aa,solver=sparsesolver,dparams=dparm, lparams=iparm); // Set hips as linear
solver
44:   u[]=Aa^-1*F[];

```

Legend of table 11.10 are give in table 11.9.

### 11.3.3 Interfacing with HYPRE

**HYPRE** (*High Level Preconditioner*) is a suite of parallel preconditioner developed at Lawrence Livermore National Lab [?].

There are two main classes of preconditioners developed in HYPRE: AMG (Algebraic MultiGrid) and Parasails (Parallel Sparse Approximate Inverse).

Now, suppose we want to solve  $Ax = b$ . At the heart of AMG there is a series of progressively coarser(smaller) representations of the matrix  $A$ . Given an approximation  $\hat{x}$  to the solution  $x$ , consider solving the residual equation  $Ae = r$  to find the error  $e$ , where  $r = b - A\hat{x}$ . A fundamental principle of AMG is that it is an algebraically smooth error. To reduce the algebraically smooth errors further, they need to be represented by a smaller defect equation (coarse grid residual equation)  $A_c e_c = r_c$ , which is cheaper to solve. After solving this coarse equation, the solution is then interpolated in fine grid represented here by matrix  $A$ . The quality of AMG depends on the choice of coarsening and interpolating operators.

The *sparse approximate inverse* approximates the inverse of a matrix  $A$  by a sparse matrix  $M$ . A technical idea to construct matrix  $M$  is to minimize the Frobenius norm of the residual matrix  $I - MA$ . For more details on this preconditioner technics see [?].

HYPRE implement three Krylov subspace solvers: GMRES, PCG and BiCGStab.

Entries of <b>iparm</b>	Significations of each entries
iparm[0]	Strategy use for solving ( Iterative=0 or Hybrid=1 or Direct=2 ). Defaults values are : Iterative
iparm[1]	Krylov methods. If iparm[0]=0, give type of Krylov methods: 0 for GMRES, 1 for PCG
iparm[2]	Maximum of iterations in outer iteration: default value 1000
iparm[3]	Krylov subspace dimension in outer iteration: default value 40
iparm[4]	Symmetric(=0 for symmetric) and 1 for unsymmetric matrix: default value 1(unsymmetric matrix)
iparm[5]	Pattern of matrix are symmetric or not: default value 0
iparm[6]	Partition type of input matrix: default value 0
iparm[7]	Number of level that use the HIPS locally consistent fill-in: Default value 2
iparm[8]	Numbering in indices array will start at 0 or 1: Default value 0
iparm[9]	Scale matrix. Default value 1
iparm[10]	Reordering use inside subdomains for reducing fill-in: Only use for iterative. Default value 1
iparm[11]	Number of unknowns per node in the matrix non-zero pattern graph: Default value 1
iparm[12]	This value is used to set the number of time the normalization is applied to the matrix: Default 2.
iparm[13]	Level of informations printed during solving: Default 5.
iparm[14]	HIPS_DOMSIZE Subdomain size

Table 11.11: Significations of **lparams** corresponding to HIPS interface

dparm[0]	<i>HIPS_PREC</i> : Relative residual norm: Default=1e-9
dparm[1]	<i>HIPS_DROPTOL0</i> : Numerical threshold in ILUT for interior domain (important : set 0.0 in HYBRID: Default=0.005)
dparm[2]	<i>HIPS_DROPTOL1</i> : Numerical threshold in ILUT for Schur preconditioner: Default=0.005
dparm[3]	<i>HIPS_DROPTOLE</i> : Numerical threshold for coupling between the interior level and Schur: Default 0.005
dparm[4]	<i>HIPS_AMALG</i> : Numerical threshold for coupling between the interior level and Schur: Default=0.005
dparm[5]	<i>HIPS_DROPSCHUR</i> : Numerical threshold for coupling between the interior level and Schur: Default=0.005

Table 11.12: Significations of **dparams** corresponding to HIPS interface



```
43: set(Aa,solver=sparsesolver,dparams=dparm, lparams=iparm);
```

iparms[0]	Solver identification: 0: BiCGStab, 1: GMRES, 2: PCG. By <b>default=1</b>
iparms[1]	Preconditioner identification: 0: BOOMER AMG, 1: PILUT, 2: Parasails, 3: Schwartz <b>Default=0</b>
iparms[2]	Maximum of iteration: <b>Default=1000</b>
iparms[3]	Krylov subspace dim: <b>Default= 40</b>
iparms[4]	Solver print info level: <b>Default=2</b>
iparms[5]	Solver log : <b>Default=1</b>
iparms[6]	Solver stopping criteria only for BiCGStab : <b>Default=1</b>
dparams[0]	Tolerance for convergence : <i>Default = 1.0e - 11</i>

Table 11.13: Definitions of common entries of **iparms** and **dparams** vectors for every preconditioner in HYPRE

### 11.3.4 Conclusion

With the different runs presented here, we wanted to illustrate the gain in time when we increase the number of processors used for the simulations. We saw that in every case the time for the construction of the finite element matrix is constant. This is normal because until now this phase is sequential in **FreeFem++** . In contrast, phases for solving the linear system are parallel. We saw on several examples presented here that when we increase the number of processors, in general we decrease the time used for solving the linear systems. But this not true in every case. In several case, when we increase the number of processors the time to convergence also increases. There are two main reasons for this. First, the increase of processors can lead to the increase of volume of exchanged data across processors consequently increasing the time for solving the linear systems.

Furthermore, in decomposition domain type preconditioners, the number of processors generally corresponds to the number of sub domains. In subdomain methods, generally when we increase the number of subdomains we decrease convergence quality of the preconditioner. This can increase the time used for solving linear equations.

To end this, we should note that good use of the preconditioners interfaced in **FreeFem++** is empiric, because it is difficult to know what is a good preconditioner for some type of problems. Although, the efficiency of preconditioners sometimes depends on how its parameters are set. For this reason we advise the user to pay attention to the meaning of the parameters in the user guide of the iterative solvers interfaced in **FreeFem++** .

## 11.4 Domain decomposition

In the previous section, we saw that the phases to construct a matrix are sequential. One strategy to construct the matrix in parallel is to divide geometrically the domain into subdomains. In every subdomain we construct a local submatrix and after that we assemble every submatrix to form the global matrix.

We can use this technique to solve pde directly in domain  $\Omega$ . In this case, in every subdomains you have to define artificial boundary conditions to form consistent equations in every subdomains. After this, you solve equation in every subdomains and define a strategy to obtain the global solution.

In terms of parallel programming for **FreeFem++** , with MPI, this means that the user must be able to divide processors available for computation into subgroups of processors and also must be able to realize different type of communications in **FreeFem++** script. Here is a wrapper of some MPI functions.

iparms[7]	AMG interpolation type: <b>Default=6</b>
iparms[8]	Specifies the use of GSMG - geometrically smooth coarsening and interpolation: <b>Default=1</b>
iparms[9]	AMG coarsen type: <b>Default=6</b>
iparms[10]	Defines whether local or global measures are used: <b>Default=1</b>
iparms[11]	AMG cycle type: <b>Default=1</b>
iparms[12]	AMG Smoother type: <b>Default=1</b>
iparms[13]	AMG number of levels for smoothers: <b>Default=3</b>
iparms[14]	AMG number of sweeps for smoothers: <b>Default=2</b>
iparms[15]	Maximum number of multigrid levels: <b>Default=25</b>
iparms[16]	Defines which variant of the Schwartz method is used: 0: hybrid multiplicative Schwartz method (no overlap across processor boundaries) 1: hybrid additive Schwartz method (no overlap across processor boundaries) 2: additive Schwartz method 3: hybrid multiplicative Schwartz method (with overlap across processor boundaries) <b>Default=1</b>
iparms[17]	Size of the system of PDEs: <b>Default=1</b>
iparms[18]	Overlap for the Schwarz method: <b>Default=1</b>
iparms[19]	Type of domain used for the Schwarz method 0: each point is a domain 1: each node is a domain (only of interest in “systems” AMG) 2: each domain is generated by agglomeration (default)
dparms[1]	AMG strength threshold: <b>Default=0.25</b>
dparms[2]	Truncation factor for the interpolation: <b>Default=1e-2</b>
dparms[3]	Sets a parameter to modify the definition of strength for diagonal dominant portions of the matrix: <b>Default=0.9</b>
dparms[3]	Defines a smoothing parameter for the additive Schwartz method <b>Default=1.</b>

Table 11.14: Definitions of other entries of **iparms** and **dparms** if preconditioner is **BOOMER AMG**

iparms[7]	Row size in Parallel ILUT: <b>Default=1000</b>
iparms[8]	Set maximum number of iterations: <b>Default=30</b>
dparms[1]	Drop tolerance in Parallel ILUT: <b>Default=1e-5</b>

Table 11.15: Definitions of other entries of **iparms** and **dparms** if preconditioner is **PILUT**

iparms[7]	Number of levels in Parallel Sparse Approximate inverse: <b>Default=1</b>
iparms[8]	Symmetric parameter for the ParaSails preconditioner: 0: nonsymmetric and/or indefinite problem, and nonsymmetric preconditioner 1: SPD problem, and SPD (factored) preconditioner 2: nonsymmetric, definite problem, and SPD (factored) preconditioner <b>Default=0</b>
dparms[1]	Filters parameters: The filter parameter is used to drop small nonzeros in the preconditioner, to reduce the cost of applying the preconditioner: <b>Default=0.1</b>
dparms[2]	Threshold parameter: <b>Default=0.1</b>

Table 11.16: Definitions of other entries of **iparms** and **dparms** if preconditioner is **ParaSails**

iparms[7]	Defines which variant of the Schwartz method is used: 0: hybrid multiplicative Schwartz method (no overlap across processor boundaries) 1: hybrid additive Schwartz method (no overlap across processor boundaries) 2: additive Schwartz method 3: hybrid multiplicative Schwartz method (with overlap across processor boundaries) <b>Default=1</b>
iparms[8]	Overlap for the Schwartz method: <b>Default=1</b>
iparms[9]	Type of domain used for the Schwartz method 0: each point is a domain 1: each node is a domain (only of interest in “systems” AMG) 2: each domain is generated by agglomeration (default)

Table 11.17: Definitions of other entries of **iparms** and **dparms** if preconditioner is **Schwartz**

<b>n=4 × 10<sup>6</sup></b>	<b>nnz=13 × 10<sup>6</sup></b>	<b>Te=571,29</b>
np	AMG	
	nit	time
8	6	1491.83
16	5	708.49
32	4	296.22
64	4	145.64

Table 11.18: Convergence and time for solving linear system from example 11.4

### 11.4.1 Communicators and groups

#### Groups

**mpiGroup grpe(mpiGroup gp, *KN\_ < long >*):** Create *MPI\_Group* from existing group **gp** by given vector

#### Communicators

Communicators is an abstract MPI object which allows MPI user to communicate across group of processors. Communicators can be Intracommunicators (involves a single group) or Intercommunicators (involves two groups). When we not specify type of communicator it will be Intracommunicators

**mpiComm cc(mpiComm comm, mpiGroup gp):** Creates a new communicator. *comm* communicator(handle), *gp* group which is a subset of the group of *comm* (handle). Return new communicator

**mpiComm cc(mpiGroup gp):** Same as previous constructor but default *comm* here is *MPI\_COMM\_WORLD*.

**mpiComm cc(mpiComm comm, int color, int key):** Creates new communicators based on *colors* and *key*. This constructor is based on *MPI\_Comm\_split* routine of MPI.

**mpiComm cc(MPIrank p, int key):** Same constructor than the last one. Here *colors* and *comm* is defined in *MPIrank*. This constructor is based on *MPI\_Comm\_split* routine of MPI.

**Example 11.7 (commsplit.edp)**

```
1: int color=mpiRank(comm)%2;
2: mpiComm ccc(processor(color,comm),0);
3: mpiComm qpp(comm,);
4: mpiComm cp(cc,color,0);
```

**mpiComm cc(mpiComm comm, int high):** Creates an intracommunicator from an intercommunicator. *comm* intercommunicator, *high* Used to order the groups within *comm* (logical) when creating the new communicator. This constructor is based on *MPI\_Intercomm\_merge* routine of MPI.

**mpiComm cc(MPIrank p1, MPIrank p2, int tag):** This constructor creates an intercommunicator from two intracommunicators. *p1* defined local (intra)communicator and rank in local\_comm of leader (often 0) while *p2* defined remote communicator and rank in peer\_comm of remote leader (often 0). *tag* Message tag to use in constructing intercommunicator. This constructor is based on *MPI\_Intercomm\_create*.

**Example 11.8 (merge.edp)**

```
1: mpiComm comm,cc;
2: int color=mpiRank(comm)%2;
3: int rk=mpiRank(comm);
4: int size=mpiSize(comm);
4: cout << "Color values " << color << endl;
5: mpiComm ccc(processor((rk<size/2),comm),rk);
6: mpiComm cp(cc,color,0);
7: int rleader;
8: if (rk == 0) { rleader = size/2; }
9: else if (rk == size/2) { rleader = 0; }
10: else { rleader = 3; }
11: mpiComm qpp(processor(0,ccc),processor(rleader,comm),12345);
12: int aaa=mpiSize(ccc);
13: cout << "number of processor" << aaa << endl;
```

### 11.4.2 Process

In FreeFem++ we wrap MPI process by function call **processor** which create internal FreeFem++ object call **MPIrank**. This mean that do not use **MPIrank** in FreeFem++ script.

**processor(int rk)**: Keep process rank inside object **MPIrank**. Rank is inside **MPI\_COMM\_WORLD**.

**processor(int rk, mpiComm cc)** and **processor(mpiComm cc,int rk)** process rank inside communicator **cc**.

**processor(int rk, mpiComm cc)** and **processor(mpiComm cc,int rk)** process rank inside communicator **cc**.

**processorblock(int rk)** : This function is exactly the same than **processor(int rk)** but is use in case of blocking communication.

**processorblock(int rk, mpiComm cc)** : This function is exactly the same than **processor(int rk,mpiComm cc)** but use a synchronization point.

### 11.4.3 Points to Points communicators

In FreeFem++ you can call MPI points to points communications functions.

**Send(processor(int rk,mpiComm cc),Data D)** : Blocking send of *Data D* to processor of *rank rk* inside communicator *cc*. Note that *Data D* can be: *int, real,complex, int[int], real[int],complex[int], Mesh, Mesh3, Matrix*.

**Recv(processor(int rk,mpiComm cc),Data D)**: Receive *Data D* from process of *rank rk* in communicator *cc*. Note that *Data D* can be: *int, real,complex, int[int], real[int],complex[int], Mesh, Mesh3, Matrix* and should be the same type than corresponding send.

**Isend(processor(int rk,mpiComm cc),Data D)** : Non blocking send of *Data D* to processor of *rank rk* inside communicator *cc*. Note that *Data D* can be: *int, real,complex, int[int], real[int],complex[int], Mesh, Mesh3, Matrix*.

**Recv(processor(int rk,mpiComm cc),Data D)**: Receive corresponding to send.

### 11.4.4 Global operations

In FreeFem++ you can call MPI global communication functions.

**broadcast(processor(int rk,mpiComm cc),Data D)**: Process *rk* Broadcast *Data D* to all process inside communicator *cc*. Note that *Data D* can be: *int, real,complex, int[int], real[int],complex[int], Mesh, Mesh3, Matrix*.

**broadcast(processor(int rk),Data D)**: Process *rk* Broadcast *Data D* to all process inside **MPI\_COMM\_WORLD**. Note that *Data D* can be: *int, real,complex, int[int], real[int],complex[int], Mesh, Mesh3, Matrix*.

**mpiAlltoall(Data a,Data b)**: Sends *data a* from all to all processes. Receive buffer is *Data b*. This is done inside communicator **MPI\_COMM\_WORLD**.

**mpiAlltoall(Data a,Data b, mpiComm cc)**: Sends *data a* from all to all processes. Receive buffer is *Data b*. This is done inside communicator *cc*.

**mpiGather(Data a,Data b,processor(mpiComm,int rk)** : Gathers together values *Data a* from a group of processes. Process of *rank rk* get data on communicator *rk*. This function is like **MPI\_Gather**



**mpiAllgather(Data a,Data b)** : Gathers *Data a* from all processes and distribute it to all in *Data b*. This is done inside communicator `MPI_COMM_WORLD`. This function is like `MPI_Allgather`

**mpiAllgather(Data a,Data b, mpiComm cc)** : Gathers *Data a* from all processes and distribute it to all in *Data b*. This is done inside **communicator cc**. This function is like `MPI_Allgather`

**mpiScatter(Data a,Data b,processor(int rk, mpiComm cc))** : Sends **Data a** from one process with rank **rk** to all other processes in group represented by communicator *mpiComm cc*.

**mpiReduce(Data a,Data b,processor(int rk, mpiComm cc),MPI\_Op op)**, Reduces values *Data a* on all processes to a single value *Data b* on process of rank *rk* and communicator *cc*. Operation use in reduce is: *MPI\_Op op* which can be: *mpiMAX*, *mpiMIN*, *mpiSUM*, *mpiPROD*, *mpiLAND*, *mpiLOR*, *mpiLXOR*, *mpiBAND*, *mpiBXOR*, *mpiMAXLOC*, *mpiMINLOC*.

Note that, for all global operations, only `int[int]` and `real[int]` are data type take in account in `FreeFem++`. The following example present in details of Schwartz domain decomposition algorithm for solving Laplacian2d problem. In this example we use two level of parallelism to solve simple Laplacian2d in square domain. We have few number of subdomain and in every subdomain we use parallel sparse solver to solve local problem.

```

Example 11.9 (schwarz.edp) 1:load "hypr_FreeFem";           // Load Hypr solver
2:func bool AddLayers(mesh & Th,real[int] &ssd,int n,real[int] &unssd)
{
    // build a continuous function uussd (P1) :
    // ssd in the characteristics function on the input sub domain.
    // such that :
    // unssd = 1 when ssd =1;
    // add n layer of element (size of the overlap)
    // and unssd = 0 outside of this layer ...
    // -----

    fespace Vh(Th,P1);
    fespace Ph(Th,P0);
    Ph s;
    assert(ssd.n==Ph.ndof);
    assert(unssd.n==Vh.ndof);
    unssd=0;
    s[]= ssd;

    // plot(s,wait=1,fill=1);

    Vh u;
    varf vM(u,v)=int2d(Th,qforder=1)(u*v/area);
    matrix M=vM(Ph,Vh);

    for(int i=0;i<n;++i)
    {
        u[]= M*s[];
        // plot(u,wait=1);

        u = u>.1;
        // plot(u,wait=1);

        unssd+= u[];
        s[]= M'*u[];
        // '
        s = s >.1;
    }
    unssd /= (n);
    u[]=unssd;
}

```

```

    ssd=s[];
    return true;
}
3: mpiComm    myComm;                                // Create communicator with value MPI_COMM_WORLD

4: int membershipKey,rank,size;                        // Variables for manage communicators
5: rank=mpiRank(myComm); size=mpiSize(myComm);        // Rank of process and size of
communicator
6: bool withmetis=1, RAS=0;                            // Use or not metis for partitioning Mesh
7: int sizeoverlaps=5;                                // size off overlap
8: int withplot=1;
9: mesh Th=square(100,100);
10: int[int] chlab=[1,1 ,2,1 ,3,1 ,4,1 ];
11: Th=change(Th,refe=chlab);
12: int nn=2,mm=2, npart= nn*mm;
13: membershipKey = mpiRank(myComm)%npart; // Coloring for partitioning process group
14: mpiComm cc(processor(membershipKey,myComm),rank); // Create MPI communicator
according previous coloring
15: fespace Ph(Th,P0), fespace Vh(Th,P1);
16: Ph part;
17: Vh sun=0,unssd=0;
18: real[int] vsum=sun[], reducesum=sun[];            // Data use for control partitioning.
19: Ph xx=x,yy=y,nupp;
20: part = int(xx*nn)*mm + int(yy*mm);
21: if(withmetis)
{
    load "metis";
    int[int] nupart(Th.nt);
    metisdual(nupart,Th,npart);
    for(int i=0;i<nupart.n;++i)
        part[][i]=nupart[i];
}
22: if(withplot>1)
21: plot(part,fill=1,cmm="dual",wait=1);
22: mesh[int] aTh(npart);
23: mesh Thi=Th;
24: fespace Vhi(Thi,P1);
25: Vhi[int] au(npart),pun(npart);
26: matrix[int] Rih(npart), Dih(npart), aA(npart);
27: Vhi[int] auntgv(npart), rhsi(npart);
28: i=membershipKey;
    Ph suppi= abs(part-i)<0.1;
    AddLayers(Th,suppi[],sizeoverlaps,unssd[]);
    Thi=aTh[i]=trunc(Th,suppi>0,label=10,split=1);
    Rih[i]=interpolate(Vhi,Vh,inside=1);                // Vh -> Vhi
    if(RAS)
    {
        suppi= abs(part-i)<0.1;
        varf vSuppi(u,v)=int2d(Th,qforder=1)(suppi*v/area);
        unssd[] = vSuppi(0,Vh);
        unssd = unssd>0.;
        if(withplot>19)
            plot(unssd,wait=1);
    }
    pun[i][]=Rih[i]*unssd[];                                // this is global operation
    sun[] += Rih[i]*pun[i][];                            // also global operation like broadcast';

```

```

vsum=sun[];
if(withplot>9)
    plot(part,aTh[i],fill=1,wait=1);
// Add mpiReduce for sum all sun and pun local contribution.
29: mpiReduce(vsum, reducesum,processor(0,myComm),mpiSUM); // MPI global operation
MPI.Reduce on global communicator
30: broadcast(processor(0,myComm),reducesum); // Broadcast sum on process 0 to all
process
31: sun[]=reducesum;
32: plot(sun,wait=1);
33: i=membershipKey
34: Thi=aTh[i];
35: pun[i]= pun[i]/sun;
36: if(withplot>8) plot(pun[i],wait=1);
37: macro Grad(u) [dx(u),dy(u)] // EOM
38: sun=0;
39: i=membershipKey
    Thi=aTh[i];
    varf va(u,v) =
        int2d(Thi)(Grad(u)'*Grad(v)) // ')
        +on(1,u=1) + int2d(Th)(v)
        +on(10,u=0) ;
40: aA[i]=va(Vhi,Vhi);
41: set(aA[i],solver=sparseSolver,mpicomm=cc); // Set parameters for Solver Hypre.
mpicomm=cc means you not solve on global process but in group on of process define by cc
42: rhsi[i][]= va(0,Vhi);
43: Dih[i]=pun[i][];
44: real[int] un(Vhi.ndof);
45: un=1.;
46: real[int] ui=Dih[i]*un;
47: sun[] += Rih[i]'*ui; // ';
48: varf vaun(u,v) = on(10,u=1);
49: auntgv[i][]=vaun(0,Vhi); // store array of tgv on Gamma intern.
56: reducesum=0; vsum=sun;
57: mpiReduce(vsum, reducesum,processor(0,myComm),mpiSUM); // MPI global operation
MPI.Reduce on global communicator
58: broadcast(processor(0,myComm),reducesum); // Broadcast sum on process 0 to all
other process
59: sun[]=reducesum;
60: if(withplot>5)
61: plot(sun,fill=1,wait=1);
62: cout << sun[].max << " " << sun[].min<< endl;
63: assert( 1.-1e-9 <= sun[].min && 1.+1e-9 >= sun[].max);
64: int nitermax=1000;
{
    Vh un=0;
    for(int iter=0;iter<nitermax;++iter)
    {
        real err=0,rerr=0;
        Vh un1=0;
        i=membershipKey;
        Thi=aTh[i];
        real[int] ui=Rih[i]*un[]; // ';
    real[int] bi = ui .* auntgv[i][];
        bi = auntgv[i][] ? bi : rhsi[i][];
        ui=au[i][];

```

```

        ui= aA[i] ^-1 * bi;          // Solve local linear system on group of process
        represented by color membershipKey
        bi = ui-au[i][];
        err += bi'*bi;                //   ';
        au[i][]= ui;
        bi = Dih[i]*ui;              // Prolongation of current solution to obtain right hand
        un1[] += Rih[i]'*bi;         //   ';
    }
65: reducesum=0; vsum=un1[];
66: mpiReduce(vsum, reducesum,processor(0,myComm),mpiSUM);          // MPI global operation
    MPI Reduce on global communicator
67: broadcast(processor(0,myComm),reducesum);          // Broadcast sum on process 0 to all
    other process
68: un1[]=reducesum;
69: real residrela=0;
70: mpiReduce(err,residrela ,processor(0,myComm),mpiSUM);
71: broadcast(processor(0,myComm),residrela);
72: err=residrela; err= sqrt(err);
73: if(rank==0) cout << iter << " Err = " << err << endl;
74:     if(err<1e-5) break;
75:         un[]=un1[];
76:             if(withplot>2)
77:                 plot(au,dim=3,wait=0,cmm=" iter  "+iter,fill=1 );
78:     }
79: plot(un,wait=1,dim=3);
80: }

```

# Chapter 12

## Mesh Files

### 12.1 File mesh data structure

The mesh data structure, output of a mesh generation algorithm, refers to the geometric data structure and in some case to another mesh data structure.

In this case, the fields are

- MeshVersionFormatted 0
- Dimension (I) dim
- Vertices (I) NbOfVertices  
( (R)  $x_i^j$ ,  $j=1,\text{dim}$  ), (I)  $Ref\phi_i^v$ ,  $i=1,\text{NbOfVertices}$  )
- Edges (I) NbOfEdges  
( @@Vertex<sub>i</sub><sup>1</sup>, @@Vertex<sub>i</sub><sup>2</sup>, (I)  $Ref\phi_i^e$ ,  $i=1,\text{NbOfEdges}$  )
- Triangles (I) NbOfTriangles  
( ( @@Vertex<sub>i</sub><sup>j</sup>,  $j=1,3$  ), (I)  $Ref\phi_i^t$ ,  $i=1,\text{NbOfTriangles}$  )
- Quadrilaterals (I) NbOfQuadrilaterals  
( ( @@Vertex<sub>i</sub><sup>j</sup>,  $j=1,4$  ), (I)  $Ref\phi_i^t$ ,  $i=1,\text{NbOfQuadrilaterals}$  )
- Geometry  
(C\*) FileNameOfGeometricSupport
  - VertexOnGeometricVertex  
(I) NbOfVertexOnGeometricVertex  
( @@Vertex<sub>i</sub>, @@Vertex<sub>i</sub><sup>geo</sup>,  $i=1,\text{NbOfVertexOnGeometricVertex}$  )
  - EdgeOnGeometricEdge  
(I) NbOfEdgeOnGeometricEdge  
( @@Edge<sub>i</sub>, @@Edge<sub>i</sub><sup>geo</sup>,  $i=1,\text{NbOfEdgeOnGeometricEdge}$  )
- CrackedEdges (I) NbOfCrackedEdges  
( @@Edge<sub>i</sub><sup>1</sup>, @@Edge<sub>i</sub><sup>2</sup>,  $i=1,\text{NbOfCrackedEdges}$  )

When the current mesh refers to a previous mesh, we have in addition

- MeshSupportOfVertices  
(C\*) FileNameOfMeshSupport
  - VertexOnSupportVertex  
(I) NbOfVertexOnSupportVertex  
( @@Vertex<sub>i</sub>, @@Vertex<sub>i</sub><sup>supp</sup>, i=1,NbOfVertexOnSupportVertex )
  - VertexOnSupportEdge  
(I) NbOfVertexOnSupportEdge  
( @@Vertex<sub>i</sub>, @@Edge<sub>i</sub><sup>supp</sup>, (R) u<sub>i</sub><sup>supp</sup>, i=1,NbOfVertexOnSupportEdge )
  - VertexOnSupportTriangle  
(I) NbOfVertexOnSupportTriangle  
( @@Vertex<sub>i</sub>, @@Tria<sub>i</sub><sup>supp</sup>, (R) u<sub>i</sub><sup>supp</sup>, (R) v<sub>i</sub><sup>supp</sup>,  
i=1 ,NbOfVertexOnSupportTriangle )
  - VertexOnSupportQuadrilaterals  
(I) NbOfVertexOnSupportQuadrilaterals  
( @@Vertex<sub>i</sub>, @@Quad<sub>i</sub><sup>supp</sup>, (R) u<sub>i</sub><sup>supp</sup>, (R) v<sub>i</sub><sup>supp</sup>,  
i=1 ,NbOfVertexOnSupportQuadrilaterals )

## 12.2 bb File type for Store Solutions

The file is formatted such that:

2 nbsol nbv 2  
 $((U_{ij}, \forall i \in \{1, \dots, \text{nbsol}\}), \forall j \in \{1, \dots, \text{nbv}\})$   
 where

- nbsol is a integer equal to the number of solutions.
- nbv is a integer equal to the number of vertex .
- U<sub>ij</sub> is a real equal the value of the *i* solution at vertex *j* on the associated mesh background if read file, generated if write file.

## 12.3 BB File Type for Store Solutions

The file is formatted such that:

2 n typesol<sup>1</sup> ... typesol<sup>n</sup> nbv 2  
 $((U_{ij}^k, \forall i \in \{1, \dots, \text{typesol}^k\}), \forall k \in \{1, \dots, n\}) \forall j \in \{1, \dots, \text{nbv}\})$   
 where

- n is a integer equal to the number of solutions
- typesol<sup>k</sup>, type of the solution number *k*, is
  - typesol<sup>k</sup> = 1 the solution *k* is scalar (1 value per vertex)

- $\text{typesol}^k = 2$  the solution  $k$  is vectorial (2 values per unknown)
- $\text{typesol}^k = 3$  the solution  $k$  is a  $2 \times 2$  symmetric matrix (3 values per vertex)
- $\text{typesol}^k = 4$  the solution  $k$  is a  $2 \times 2$  matrix (4 values per vertex)
- $\text{nbv}$  is a integer equal to the number of vertices
- $U_{ij}^k$  is a real equal to the value of the component  $i$  of the solution  $k$  at vertex  $j$  on the associated mesh background if read file, generated if write file.

## 12.4 Metric File

A metric file can be of two types, isotropic or anisotropic.  
the isotropic file is such that

$\text{nbv}$  1

$h_i \quad \forall i \in \{1, \dots, \text{nbv}\}$

where

- $\text{nbv}$  is a integer equal to the number of vertices.
- $h_i$  is the wanted mesh size near the vertex  $i$  on background mesh, the metric is  $\mathcal{M}_i = h_i^{-2} Id$ , where  $Id$  is the identity matrix.

The metric anisotrope

$\text{nbv}$  3

$a11_i, a21_i, a22_i \quad \forall i \in \{1, \dots, \text{nbv}\}$

where

- $\text{nbv}$  is a integer equal to the number of vertices,
- $a11_i, a12_i, a22_i$  is metric  $\mathcal{M}_i = \begin{pmatrix} a11_i & a12_i \\ a12_i & a22_i \end{pmatrix}$  which define the wanted mesh size in a vicinity of the vertex  $i$  such that  $h$  in direction  $u \in \mathbb{R}^2$  is equal to  $|u| / \sqrt{u \cdot \mathcal{M}_i u}$ , where  $\cdot$  is the dot product in  $\mathbb{R}^2$ , and  $|\cdot|$  is the classical norm.

## 12.5 List of AM\_FMT, AMDBA Meshes

The mesh is only composed of triangles and can be defined with the help of the following two integers and four arrays:

$\text{nbt}$  is the number of triangles.

$\text{nbv}$  is the number of vertices.

$\text{nu}(1:3, 1:\text{nbt})$  is an integer array giving the three vertex numbers counterclockwise for each triangle.

$\text{c}(1:2, \text{nbv})$  is a real array giving the two coordinates of each vertex.

$\text{refs}(\text{nbv})$  is an integer array giving the reference numbers of the vertices.

$\text{reft}(\text{nbv})$  is an integer array giving the reference numbers of the triangles.

**AM\_FMT Files** In fortran the `am_fmt` files are read as follows:

```
open(1,file='xxx.am_fmt',form='formatted',status='old')
  read (1,*) nbv,nbt
  read (1,*) ((nu(i,j),i=1,3),j=1,nbt)
  read (1,*) ((c(i,j),i=1,2),j=1,nbv)
  read (1,*) ( reft(i),i=1,nbt)
  read (1,*) ( refs(i),i=1,nbv)
close(1)
```

**AM Files** In fortran the `am` files are read as follows:

```
open(1,file='xxx.am',form='unformatted',status='old')
  read (1,*) nbv,nbt
  read (1) ((nu(i,j),i=1,3),j=1,nbt),
& ((c(i,j),i=1,2),j=1,nbv),
& ( reft(i),i=1,nbt),
& ( refs(i),i=1,nbv)
close(1)
```

**AMDBA Files** In fortran the `amdba` files are read as follows:

```
open(1,file='xxx.amdba',form='formatted',status='old')
  read (1,*) nbv,nbt
  read (1,*) (k,(c(i,k),i=1,2),refs(k),j=1,nbv)
  read (1,*) (k,(nu(i,k),i=1,3),reft(k),j=1,nbt)
close(1)
```

**msh Files** First, we add the notions of boundary edges

`nbbe` is the number of boundary edge.

`nube(1:2,1:nbbe)` is an integer array giving the two vertex numbers

`refbe(1:nbbe)` is an integer array giving the two vertex numbers

In fortran the `msh` files are read as follows:

```
open(1,file='xxx.msh',form='formatted',status='old')
  read (1,*) nbv,nbt,nbbe
  read (1,*) ((c(i,k),i=1,2),refs(k),j=1,nbv)
  read (1,*) ((nu(i,k),i=1,3),reft(k),j=1,nbt)
  read (1,*) ((ne(i,k),i=1,2), refbe(k),j=1,nbbe)
close(1)
```



**ftq Files** In fortran the ftq files are read as follows:

```
open(1,file='xxx.ftq',form='formatted',status='old')
read (1,*) nbv,nbe,nbt,nbq
read (1,*) (k(j),(nu(i,j),i=1,k(j)),reft(j),j=1,nbe)
read (1,*) ((c(i,k),i=1,2),refs(k),j=1,nbv)
close(1)
```

where if  $k(j) = 3$  then the element  $j$  is a triangle and if  $k = 4$  the the element  $j$  is a quadrilateral.



# Chapter 13

## Addition of a new finite element

### 13.1 Some notations

For a function  $f$  taking value in  $\mathbb{R}^N$ ,  $N = 1, 2, \dots$ , we define the finite element approximation  $\Pi_h f$  of  $f$ . Let us denote the number of the degrees of freedom of the finite element by  $NbDoF$ . Then the  $i$ -th base  $\omega_i^K$  ( $i = 0, \dots, NbDoF - 1$ ) of the finite element space has the  $j$ -th component  $\omega_{ij}^K$  for  $j = 0, \dots, N - 1$ .

The operator  $\Pi_h$  is called the interpolator of the finite element. We have the identity  $\omega_i^K = \Pi_h \omega_i^K$ . Formally, the interpolator  $\Pi_h$  is constructed by the following formula:

$$\Pi_h f = \sum_{k=0}^{kPi-1} \alpha_k f_{j_k}(P_{p_k}) \omega_{i_k}^K \quad (13.1)$$

where  $P_p$  is a set of  $npPi$  points,

In the formula (13.1), the list  $p_k, j_k, i_k$  depend just on the type of finite element (not on the element), but the coefficient  $\alpha_k$  can be depending on the element.

Example 1: with the classical scalar Lagrange finite element, we have  $kPi = npPi = NbOfNode$  and

- $P_p$  is the point of the nodal points
- the  $\alpha_k = 1$ , because we take the value of the function at the point  $P_k$
- $p_k = k, j_k = k$  because we have one node per function.
- $j_k = 0$  because  $N = 1$

Example 2: The Raviart-Thomas finite element:

$$RT0_h = \{ \mathbf{v} \in H(div) / \forall K \in \mathcal{T}_h \quad \mathbf{v}|_K(x, y) = \left[ \frac{\alpha_K}{\beta_K} + \gamma_K \right] \begin{pmatrix} x \\ y \end{pmatrix} \} \quad (13.2)$$

The degrees of freedom are the flux through an edge  $e$  of the mesh, where the flux of the function  $\mathbf{f} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$  is  $\int_e \mathbf{f} \cdot \mathbf{n}_e$ ,  $\mathbf{n}_e$  is the unit normal of edge  $e$  (this implies a orientation of all the edges of the mesh, for example we can use the global numbering of the edge vertices and we just go to small to large number).

To compute this flux, we use a quadrature formula with one point, the middle point of the edge. Consider a triangle  $T$  with three vertices  $(\mathbf{a}, \mathbf{b}, \mathbf{c})$ . Let denote the vertices numbers by  $i_a, i_b, i_c$ , and define the three edge vectors  $\mathbf{e}^0, \mathbf{e}^1, \mathbf{e}^2$  by  $\text{sgn}(i_b - i_c)(\mathbf{b} - \mathbf{c})$ ,  $\text{sgn}(i_c - i_a)(\mathbf{c} - \mathbf{a})$ ,  $\text{sgn}(i_a - i_b)(\mathbf{a} - \mathbf{b})$ ,

The three basis functions are:

$$\omega_0^K = \frac{\text{sgn}(i_b - i_c)}{2|T|}(x - a), \quad \omega_1^K = \frac{\text{sgn}(i_c - i_a)}{2|T|}(x - b), \quad \omega_2^K = \frac{\text{sgn}(i_a - i_b)}{2|T|}(x - c), \quad (13.3)$$

where  $|T|$  is the area of the triangle  $T$ .

So we have  $N = 2$ ,  $kPi = 6$ ;  $npPi = 3$ ; and:

- $P_p = \left\{ \frac{\mathbf{b}+\mathbf{c}}{2}, \frac{\mathbf{a}+\mathbf{c}}{2}, \frac{\mathbf{b}+\mathbf{a}}{2} \right\}$
- $\alpha_0 = -\mathbf{e}_2^0, \alpha_1 = \mathbf{e}_1^0, \alpha_2 = -\mathbf{e}_2^1, \alpha_3 = \mathbf{e}_1^1, \alpha_4 = -\mathbf{e}_2^2, \alpha_5 = \mathbf{e}_1^2$  (effectively, the vector  $(-\mathbf{e}_2^m, \mathbf{e}_1^m)$  is orthogonal to the edge  $\mathbf{e}^m = (e_1^m, e_2^m)$  with a length equal to the side of the edge or equal to  $\int_{e^m} 1$ ).
- $i_k = \{0, 0, 1, 1, 2, 2\}$ ,
- $p_k = \{0, 0, 1, 1, 2, 2\}$ ,  $j_k = \{0, 1, 0, 1, 0, 1\}$ .

## 13.2 Which class to add?

Add file FE\_ADD.cpp in directory src/femlib for example first to initialize :

```
#include "error.hpp"
#include "rgraph.hpp"
using namespace std;
#include "RNM.hpp"
#include "fem.hpp"
#include "FESpace.hpp"
#include "AddNewFE.h"
```

```
namespace Fem2D {
```

Then add a class which derive for public TypeOfFE like:

```
class TypeOfFE_RTortho : public TypeOfFE { public:
    static int Data[]; // some numbers
    TypeOfFE_RTortho():
        TypeOfFE( 0+3+0, // nb degree of freedom on element
            2, // dimension N of vectorial FE (1 if scalar FE)
            Data, // the array data
            1, // nb of subdivision for plotting
            1, // nb of sub finite element (generaly 1)
            6, // number kPi of coef to build the interpolator (13.1)
            3, // number npPi of integration point to build interpolator
            0 // an array to store the coef  $\alpha_k$  to build interpolator
            // here this array is no constant so we have
            // to rebuilt for each element.
        )
    {
        const R2 Pt[] = { R2(0.5,0.5), R2(0.0,0.5), R2(0.5,0.0) }; // the set of Point in  $\hat{K}$ 

        for (int p=0, kk=0; p<3; p++) {
            P_Pi_h[p]=Pt[p];
            for (int j=0; j<2; j++)
                pij_alpha[kk++] = IPJ(p, p, j); // definition of  $i_k, p_k, j_k$  in (13.1)
        }

        void FB(const bool * watdd, const Mesh & Th, const Triangle & K,
            const R2 &PHat, RNMK_ & val) const;

        void Pi_h_alpha(const baseFElement & K, KN_<double> & v) const ;
    } ;
```

where the array data is form with the concatenation of five array of size NbDoF and one array of size N.

This array is:

```
int TypeOfFE_RTortho::Data[]={

    //      for each df 0,1,3 :
    3,4,5, //      the support of the node of the df
    0,0,0, //      the number of the df on the node
    0,1,2, //      the node of the df
    0,0,0, //      the df come from which FE (generally 0)
    0,1,2, //      which are de df on sub FE
    0,0 };          //      for each component j=0,N-1 it give the sub FE associated
```

where the support is a number 0, 1, 2 for vertex support, 3, 4, 5 for edge support, and finally 6 for element support.

The function to defined the function  $\omega_i^K$ , this function return the value of all the basics function or this derivatives in array val, computed at point PHat on the reference triangle corresponding to point R2  $P=K(\text{Phat})$ ; on the current triangle K.

The index  $i, j, k$  of the array  $val(i, j, k)$  corresponding to:

$i$  is basic function number on finite element  $i \in [0, NoF[$

$j$  is the value of component  $j \in [0, N[$

$k$  is the type of computed value  $f(P), dx(f)(P), dy(f)(P), \dots i \in [0, \text{last\_operatortype}[$ . Remark for optimization, this value is computed only if  $\text{whatd}[k]$  is true, and the numbering is defined with

```
enum operatortype { op_id=0,
    op_dx=1, op_dy=2,
    op_dxx=3, op_dyy=4,
    op_dyx=5, op_dxy=5,
    op_dz=6,
    op_dzz=7,
    op_dzx=8, op_dxz=8,
    op_dzy=9, op_dyz=9
};
const int last_operatortype=10;
```

The shape function :

```
void TypeOfFE_RTortho::FB(const bool *whatd, const Mesh & Th, const Triangle & K,
    const R2 & PHat, RNMK_ & val) const
{
    R2 P(K(PHat));
    R2 A(K[0]), B(K[1]), C(K[2]);
    R l0=1-P.x-P.y, l1=P.x, l2=P.y;
    assert(val.N() >=3);
    assert(val.M()==2 );
    val=0;
    R a=1./(2*K.area);
    R a0= K.EdgeOrientation(0) * a ;
    R a1= K.EdgeOrientation(1) * a ;
    R a2= K.EdgeOrientation(2) * a ;

    if (whatd[op_id])
        //      -----
        //      value of the function
```

```

{
    assert(val.K()>op_id);
    RN_ f0(val('.',0,0));
    RN_ f1(val('.',1,0));
    f1[0] = (P.x-A.x)*a0;
    f0[0] = -(P.y-A.y)*a0;

    f1[1] = (P.x-B.x)*a1;
    f0[1] = -(P.y-B.y)*a1;

    f1[2] = (P.x-C.x)*a2;
    f0[2] = -(P.y-C.y)*a2;
}

if (whatd[op_dx])
{
    assert(val.K()>op_dx);
    val(0,1,op_dx) = a0;
    val(1,1,op_dx) = a1;
    val(2,1,op_dx) = a2;
}
if (whatd[op_dy])
{
    assert(val.K()>op_dy);
    val(0,0,op_dy) = -a0;
    val(1,0,op_dy) = -a1;
    val(2,0,op_dy) = -a2;
}

for (int i= op_dy; i< last_operatortype ; i++)
    if (whatd[op_dx])
        assert(op_dy);
}

```

The function to defined the coefficient  $\alpha_k$ :

```

void TypeOfFE_RT::Pi_h_alpha(const baseFEElement & K,KN_<double> & v) const
{
    const Triangle & T(K.T);

    for (int i=0,k=0;i<3;i++)
    {
        R2 E(T.Edge(i));
        R signe = T.EdgeOrientation(i) ;
        v[k++] = signe*E.y;
        v[k++] = -signe*E.x;
    }
}

```

Now , we just need to add a new key work in FreeFem++, Two way, with static or dynamic link so at the end of the file, we add :

With dynamic link is very simple (see section C of appendix), just add before the end of FEM2d namespace add:

```
static TypeOfFE_RTortho The_TypeOfFE_RTortho; //
static AddNewFE("RT0Ortho", The_TypeOfFE_RTortho);
} // FEM2d namespace
```

Try with `"/load.link"` command in `examples++-load/` and see `BernardiRaugel.cpp` or `Morley.cpp` new finite element examples.

**Otherwise** with static link (for expert only), add

```
static TypeOfFE_RTortho The_TypeOfFE_RTortho; // let the 2 globals variables //
static ListOfTFE typefemRTortho("RT0Ortho", & The_TypeOfFE_RTortho); // ----- the name in freefem ----- //

// link with FreeFem++ do not work with static library .a
// FH so add a extern name to call in init_static_FE
// (see end of FESpace.cpp)
void init_FE_ADD() { };
// --- end ---
} // FEM2d namespace
```

To enforce in loading of this new finite element, we have to add the two new lines close to the end of files `src/femlib/FESpace.cpp` like:

```
void init_static_FE() // correct Problem of static library link with new make file
{ // list of other FE file.o
    extern void init_FE_P2h() ;
    init_FE_P2h() ;
    extern void init_FE_ADD() ; // new line 1
    init_FE_ADD(); // new line 2
}
```

and now you have to change the makefile.

First, create a file `FE_ADD.cpp` contening all this code, like in file `src/femlib/Element_P2h.cpp`, after modifier the `Makefile.am` by adding the name of your file to the variable `EXTRA_DIST` like:

```
# Makefile using Automake + Autoconf
# -----
# $Id$
```

```
# This is not compiled as a separate library because its
# interconnections with other libraries have not been solved.
```

```
EXTRA_DIST=BamgFreeFem.cpp BamgFreeFem.hpp CGNL.hpp CheckPtr.cpp \
ConjuguedGradientNL.cpp DOperator.hpp Drawing.cpp Element_P2h.cpp \
Element_P3.cpp Element_RT.cpp fem3.hpp fem.cpp fem.hpp FESpace.cpp \
FESpace.hpp FESpace-v0.cpp FQuadTree.cpp FQuadTree.hpp gibbs.cpp \
glutdraw.cpp gmres.hpp MatriceCreuse.hpp MatriceCreuse_tpl.hpp \
MeshPoint.hpp mortar.cpp mshptg.cpp QuadratureFormular.cpp \
QuadratureFormular.hpp RefCounter.hpp RNM.hpp RNM_opc.hpp RNM_op.hpp \
RNM_tpl.hpp FE_ADD.cpp
```

and do in the `freefem++` root directory

```
autoreconf
./reconfigure
make
```

For codewarrior compilation add the file in the project and remove the flag in panel PPC linker FreeFEM++ Setting Dead-strip Static Initialization Code Flag.



# Appendix A

## Table of Notations

Here mathematical expressions and corresponding FreeFem++ commands are explained.

### A.1 Generalities

$\delta_{ij}$  Kronecker delta (0 if  $i \neq j$ , 1 if  $i = j$  for integers  $i, j$ )

$\forall$  for all

$\exists$  there exist

**i.e.** that is

**PDE** partial differential equation (with boundary conditions)

$\emptyset$  the empty set

$\mathbb{N}$  the set of integers ( $a \in \mathbb{N} \Leftrightarrow \text{int } a$ ); “int” means *long integer* inside FreeFem++

$\mathbb{R}$  the set of real numbers ( $a \in \mathbb{R} \Leftrightarrow \text{real } a$ ); *double* inside FreeFem++

$\mathbb{C}$  the set of complex numbers ( $a \in \mathbb{C} \Leftrightarrow \text{complex } a$ ); *complex;double*

$\mathbb{R}^d$   $d$ -dimensional Euclidean space

### A.2 Sets, Mappings, Matrices, Vectors

Let  $E, F, G$  be three sets and  $A$  subset of  $E$ .

$\{x \in E \mid P\}$  the subset of  $E$  consisting of the elements possessing the property  $P$

$E \cup F$  the set of elements belonging to  $E$  or  $F$

$E \cap F$  the set of elements belonging to  $E$  and  $F$

$E \setminus A$  the set  $\{x \in E \mid x \notin A\}$

$E + F$   $E \cup F$  with  $E \cap F = \emptyset$

$E \times F$  the cartesian product of  $E$  and  $F$

$E^n$  the  $n$ -th power of  $E$  ( $E^2 = E \times E$ ,  $E^n = E \times E^{n-1}$ )

$f : E \rightarrow F$  the mapping from  $E$  into  $F$ , i.e.,  $E \ni x \mapsto f(x) \in F$

$I_E$  or  $I$  the identity mapping in  $E$ , i.e.,  $I(x) = x \quad \forall x \in E$

$f \circ g$  for  $f : F \rightarrow G$  and  $g : E \rightarrow F$ ,  $E \ni x \mapsto (f \circ g)(x) = f(g(x)) \in G$  (see Section ??)

$f|_A$  the restriction of  $f : E \rightarrow F$  to the subset  $A$  of  $E$

$\{a_k\}$  column vector with components  $a_k$

$(a_k)$  row vector with components  $a_k$

$(a_k)^T$  denotes the transpose of a matrix  $(a_k)$ , and is  $\{a_k\}$

$\{a_{ij}\}$  matrix with components  $a_{ij}$ , and  $(a_{ij})^T = (a_{ji})$

### A.3 Numbers

For two real numbers  $a, b$

$[a, b]$  is the interval  $\{x \in \mathbb{R} \mid a \leq x \leq b\}$

$]a, b]$  is the interval  $\{x \in \mathbb{R} \mid a < x \leq b\}$

$[a, b[$  is the interval  $\{x \in \mathbb{R} \mid a \leq x < b\}$

$]a, b[$  is the interval  $\{x \in \mathbb{R} \mid a < x < b\}$

### A.4 Differential Calculus

$\partial f / \partial x$  the partial derivative of  $f : \mathbb{R}^d \rightarrow \mathbb{R}$  with respect to  $x$  ( $\text{dx}(f)$ )

$\nabla f$  the gradient of  $f : \Omega \rightarrow \mathbb{R}$ , i.e.,  $\nabla f = (\partial f / \partial x, \partial f / \partial y)$

**div** $f$  or  $\nabla \cdot f$  the divergence of  $f : \Omega \rightarrow \mathbb{R}^d$ , i.e.,  $\text{div } f = \partial f_1 / \partial x + \partial f_2 / \partial y$

$\Delta f$  the Laplacian of  $f : \Omega \rightarrow \mathbb{R}$ , i.e.,  $\Delta f = \partial^2 f / \partial x^2 + \partial^2 f / \partial y^2$

## A.5 Meshes

$\Omega$  usually denotes a domain on which PDE is defined

$\Gamma$  denotes the boundary of  $\Omega$ , i.e.,  $\Gamma = \partial\Omega$  (keyword **border**, see Section 5.1.2)

$\mathcal{T}_h$  the triangulation of  $\Omega$ , i.e., the set of triangles  $T_k$ , where  $h$  stands for mesh size (keyword **mesh**, **buildmesh**, see Section 5)

$n_t$  the number of triangles in  $\mathcal{T}_h$  (get by **Th.nt**, see “mesh.edp”)

$\Omega_h$  denotes the approximated domain  $\Omega_h = \cup_{k=1}^{n_t} T_k$  of  $\Omega$ . If  $\Omega$  is polygonal domain, then it will be  $\Omega = \Omega_h$

$\Gamma_h$  the boundary of  $\Omega_h$

$n_v$  the number of vertices in  $\mathcal{T}_h$  (get by **Th.nv**)

$[q^i q^j]$  the segment connecting  $q^i$  and  $q^j$

$q^{k_1}, q^{k_2}, q^{k_3}$  the vertices of a triangle  $T_k$  with anti-clock direction (get the coordinate of  $q^{k_j}$  by  $(\text{Th}[\mathbf{k}-1][\mathbf{j}-1].\mathbf{x}, \text{Th}[\mathbf{k}-1][\mathbf{j}-1].\mathbf{y}))$

$I_\Omega$  the set  $\{i \in \mathbb{N} \mid q^i \notin \Gamma_h\}$

## A.6 Finite Element Spaces

$L^2(\Omega)$  the set  $\left\{ w(x, y) \mid \int_{\Omega} |w(x, y)|^2 dx dy < \infty \right\}$

$$\text{norm: } \|w\|_{0,\Omega} = \left( \int_{\Omega} |w(x, y)|^2 dx dy \right)^{1/2}$$

$$\text{scalar product: } (v, w) = \int_{\Omega} vw$$

$H^1(\Omega)$  the set  $\left\{ w \in L^2(\Omega) \mid \int_{\Omega} (|\partial w / \partial x|^2 + |\partial w / \partial y|^2) dx dy < \infty \right\}$

$$\text{norm: } \|w\|_{1,\Omega} = \left( \|w\|_{0,\Omega}^2 + \|\nabla w\|_{0,\Omega}^2 \right)^{1/2}$$

$H^m(\Omega)$  the set  $\left\{ w \in L^2(\Omega) \mid \int_{\Omega} \frac{\partial^{|\alpha|} w}{\partial x^{\alpha_1} \partial y^{\alpha_2}} \in L^2(\Omega) \quad \forall \alpha = (\alpha_1, \alpha_2) \in \mathbb{N}^2, |\alpha| = \alpha_1 + \alpha_2 \right\}$

$$\text{scalar product: } (v, w)_{1,\Omega} = \sum_{|\alpha| \leq m} \int_{\Omega} D^{\alpha} v D^{\alpha} w$$

$H_0^1(\Omega)$  the set  $\{w \in H^1(\Omega) \mid w = 0 \text{ on } \Gamma\}$

$L^2(\Omega)^2$  denotes  $L^2(\Omega) \times L^2(\Omega)$ , and also  $H^1(\Omega)^2 = H^1(\Omega) \times H^1(\Omega)$

$V_h$  denotes the finite element space created by “`fespace Vh(Th,*)`” in FreeFem++ (see Section 6 for “\*”)

$\Pi_h f$  the projection of the function  $f$  into  $V_h$  (“`func f=x^2*y^3; Vh v = f;`” means  $v = \Pi_h f$ )

$\{v\}$  for FE-function  $v$  in  $V_h$  means the column vector  $(v_1, \dots, v_M)^T$  if  $v = v_1\phi_1 + \dots + v_M\phi_M$ , which is shown by “`fespace Vh(Th,P2); Vh v; cout << v[] << endl;`”

# Appendix B

## Grammar

### B.1 The bison grammar

```
start:  input ENDOFFILE;

input:  instructions ;

instructions: instruction
          | instructions instruction ;

list_of_id_args:
    | id
    | id '=' no_comma_expr
    | FESPACE id
    | type_of_dcl id
    | type_of_dcl '&' id
    | '[' list_of_id_args ']'
    | list_of_id_args ',' id
    | list_of_id_args ',' '[' list_of_id_args ']'
    | list_of_id_args ',' id '=' no_comma_expr
    | list_of_id_args ',' FESPACE id
    | list_of_id_args ',' type_of_dcl id
    | list_of_id_args ',' type_of_dcl '&' id ;

list_of_id1: id
            | list_of_id1 ',' id ;

id: ID | FESPACE ;

list_of_dcls:  ID
              | ID '=' no_comma_expr
              | ID '(' parameters_list ')'
              | list_of_dcls ',' list_of_dcls ;

parameters_list:
    no_set_expr
    | FESPACE ID
    | ID '=' no_set_expr
```

```

    | parameters_list ',' no_set_expr
    | parameters_list ',' id '=' no_set_expr ;

type_of_dcl:    TYPE
               | TYPE '[' TYPE ']' ;

ID_space:
    ID
    | ID '[' no_set_expr ']'
    | ID '=' no_set_expr
    | '[' list_of_id1 ']'
    | '[' list_of_id1 ']' '[' no_set_expr ']'
    | '[' list_of_id1 ']' '=' no_set_expr ;

ID_array_space:
    ID '(' no_set_expr ')'
    | '[' list_of_id1 ']' '(' no_set_expr ')' ;

fespace: FESPACE ;

spaceIDa :    ID_array_space
           |    spaceIDa ',' ID_array_space ;

spaceIDb :    ID_space
           |    spaceIDb ',' ID_space ;

spaceIDs :    fespace                spaceIDb
           |    fespace '[' TYPE ']' spaceIDa ;

fespace_def: ID '(' parameters_list ')' ;

fespace_def_list: fespace_def
                 | fespace_def_list ',' fespace_def ;

declaration:  type_of_dcl list_of_dcls ';'
              | 'fespace' fespace_def_list ';'
              | spaceIDs ';'
              | FUNCTION ID '=' Expr ';'
              | FUNCTION type_of_dcl ID '(' list_of_id_args ')' '{' instructions'}'
              | FUNCTION ID '(' list_of_id_args ')' '=' no_comma_expr ';' ;

begin: '{' ;
end:   '}' ;

for_loop: 'for' ;
while_loop: 'while' ;

instruction:  ';'
            | 'include' STRING
            | 'load'  STRING
            | Expr ';'
            | declaration
            | for_loop '(' Expr ';' Expr ';' Expr ')' instruction
            | while_loop '(' Expr ')' instruction
            | 'if' '(' Expr ')' instruction

```

```

| 'if' '(' Expr ')' instruction ELSE instruction
| begin instructions end
| 'border' ID border_expr
| 'border' ID '[' array ']' ';'
| 'break' ';'
| 'continue' ';'
| 'return' Expr ';' ;

```

```
bornes: '(' ID '=' Expr ',' Expr ')';
```

```
border_expr: bornes instruction ;
```

```
Expr: no_comma_expr
| Expr ',' Expr ;
```

```
unop: '-'
| '+'
| '!'
| '++'
| '--' ;
```

```
no_comma_expr:
    no_set_expr
| no_set_expr '=' no_comma_expr
| no_set_expr '+=' no_comma_expr
| no_set_expr '-=' no_comma_expr
| no_set_expr '*=' no_comma_expr
| no_set_expr '/=' no_comma_expr ;
```

```
no_set_expr:
    no_ternary_expr
| no_ternary_expr '?' no_set_expr ':' no_set_expr ;
```

```
no_ternary_expr:
    unary_expr
| no_ternary_expr '*' no_ternary_expr
| no_ternary_expr '.' no_ternary_expr
| no_ternary_expr './' no_ternary_expr
| no_ternary_expr '/' no_ternary_expr
| no_ternary_expr '%' no_ternary_expr
| no_ternary_expr '+' no_ternary_expr
| no_ternary_expr '-' no_ternary_expr
| no_ternary_expr '<<' no_ternary_expr
| no_ternary_expr '>>' no_ternary_expr
| no_ternary_expr '&' no_ternary_expr
| no_ternary_expr '&&' no_ternary_expr
| no_ternary_expr '|' no_ternary_expr
| no_ternary_expr '||' no_ternary_expr
| no_ternary_expr '<' no_ternary_expr
| no_ternary_expr '<=' no_ternary_expr
| no_ternary_expr '>' no_ternary_expr
| no_ternary_expr '>=' no_ternary_expr
```

```

        | no_ternary_expr '==' no_ternary_expr
        | no_ternary_expr '!=' no_ternary_expr ;

sub_script_expr:
    no_set_expr
|   ':'
|   no_set_expr ':' no_set_expr
|   no_set_expr ':' no_set_expr ':' no_set_expr ;

```

```

parameters:
    |   no_set_expr
    |   FESPACE
    |   id '=' no_set_expr
    |   sub_script_expr
    |   parameters ',' FESPACE
    |   parameters ',' no_set_expr
    |   parameters ',' id '=' no_set_expr ;

```

```

array:   no_comma_expr
        | array ',' no_comma_expr ;

```

```

unary_expr:
    pow_expr
|   unop pow_expr %prec UNARY ;

```

```

pow_expr: primary
|   primary '^' unary_expr
|   primary '_' unary_expr
|   primary '`' ;

```

// transpose

```

primary:
    ID
|   LNUM
|   DNUM
|   CNUM
|   STRING
|   primary '(' parameters ')'
|   primary '[' Expr ']'
|   primary '[' ']'
|   primary '.' ID
|   primary '++'
|   primary '--'
|   TYPE '(' Expr ')' ;
|   '(' Expr ')'
|   '[' array ']' ;

```



## B.2 The Types of the languages, and cast

### B.3 All the operators

```

- CG, type :<TypeSolveMat>
- Cholesky, type :<TypeSolveMat>
- Crout, type :<TypeSolveMat>
- GMRES, type :<TypeSolveMat>
- LU, type :<TypeSolveMat>
- LinearCG, type :<Polymorphic> operator() :
  ( <long> : <Polymorphic>, <KN<double> *>, <KN<double> *> )

- N, type :<Fem2D::R3>
- NoUseOfWait, type :<bool *>
- P, type :<Fem2D::R3>
- P0, type :<Fem2D::TypeOfFE>
- P1, type :<Fem2D::TypeOfFE>
- P1nc, type :<Fem2D::TypeOfFE>
- P2, type :<Fem2D::TypeOfFE>
- RT0, type :<Fem2D::TypeOfFE>
- RTmodif, type :<Fem2D::TypeOfFE>
- abs, type :<Polymorphic> operator() :
  ( <double> : <double> )

- acos, type :<Polymorphic> operator() :
  ( <double> : <double> )

- acosh, type :<Polymorphic> operator() :
  ( <double> : <double> )

- adaptmesh, type :<Polymorphic> operator() :
  ( <Fem2D::Mesh> : <Fem2D::Mesh>... )

- append, type :<std::ios_base::openmode>
- asin, type :<Polymorphic> operator() :
  ( <double> : <double> )

- asinh, type :<Polymorphic> operator() :
  ( <double> : <double> )

- atan, type :<Polymorphic> operator() :
  ( <double> : <double> )
  ( <double> : <double>, <double> )

- atan2, type :<Polymorphic> operator() :
  ( <double> : <double>, <double> )

- atanh, type :<Polymorphic> operator() :
  ( <double> : <double> )

```

```

- buildmesh, type :<Polymorphic> operator() :
  (   <Fem2D::Mesh> :   <E_BorderN> )

- buildmeshborder, type :<Polymorphic> operator() :
  (   <Fem2D::Mesh> :   <E_BorderN> )

- cin, type :<istream>
- clock, type :<Polymorphic>
  (   <double> :   )

- conj, type :<Polymorphic> operator() :
  (   <complex> :   <complex> )

- convect, type :<Polymorphic> operator() :
  (   <double> :   <E_Array>, <double>, <double> )

- cos, type :<Polymorphic> operator() :
  (   <double> :   <double> )
  (   <complex> :   <complex> )

- cosh, type :<Polymorphic> operator() :
  (   <double> :   <double> )
  (   <complex> :   <complex> )

- cout, type :<ostream>
- dumptable, type :<Polymorphic> operator() :
  (   <ostream> :   <ostream> )

- dx, type :<Polymorphic> operator() :
  (   <LinearComb<MDroit, C_F0>> :   <LinearComb<MDroit, C_F0>> )
  (   <double> :   <std::pair<FEbase<double> *, int>> )
  (   <LinearComb<MGauche, C_F0>> :   <LinearComb<MGauche, C_F0>> )

- dy, type :<Polymorphic> operator() :
  (   <LinearComb<MDroit, C_F0>> :   <LinearComb<MDroit, C_F0>> )
  (   <double> :   <std::pair<FEbase<double> *, int>> )
  (   <LinearComb<MGauche, C_F0>> :   <LinearComb<MGauche, C_F0>> )

- endl, type :<char>
- exec, type :<Polymorphic> operator() :
  (   <long> :   <string> )

- exit, type :<Polymorphic> operator() :
  (   <long> :   <long> )

- exp, type :<Polymorphic> operator() :
  (   <double> :   <double> )
  (   <complex> :   <complex> )

```

```

- false, type :<bool>
- imag, type :<Polymorphic> operator() :
  ( <double> : <complex> )

- int1d, type :<Polymorphic> operator() :
  ( <CDomainOfIntegration> : <Fem2D::Mesh>... )

- int2d, type :<Polymorphic> operator() :
  ( <CDomainOfIntegration> : <Fem2D::Mesh>... )

- intalldges, type :<Polymorphic>
operator( :
  ( <CDomainOfIntegration> : <Fem2D::Mesh>... )

- jump, type :<Polymorphic>
operator( :
  ( <LinearComb<MDroit, C_F0>> : <LinearComb<MDroit, C_F0>> )
  ( <double> : <double> )
  ( <complex> : <complex> )
  ( <LinearComb<MGauche, C_F0>> : <LinearComb<MGauche, C_F0>> )

- label, type :<long *>
- log, type :<Polymorphic> operator() :
  ( <double> : <double> )
  ( <complex> : <complex> )

- log10, type :<Polymorphic> operator() :
  ( <double> : <double> )

- max, type :<Polymorphic> operator() :
  ( <double> : <double>, <double> )
  ( <long> : <long>, <long> )

- mean, type :<Polymorphic>
operator( :
  ( <double> : <double> )
  ( <complex> : <complex> )

- min, type :<Polymorphic> operator() :
  ( <double> : <double>, <double> )
  ( <long> : <long>, <long> )

- movemesh, type :<Polymorphic> operator() :
  ( <Fem2D::Mesh> : <Fem2D::Mesh>, <E_Array>... )

- norm, type :<Polymorphic>
operator( :
  ( <double> : <std::complex<double>> )

- nuTriangle, type :<long>

```

```

- nuEdge, type :<long>
- on, type :<Polymorphic> operator() :
  ( <BC_set<double>> : <long>... )

- otherside, type :<Polymorphic>
operator( :
  ( <LinearComb<MDroit, C_F0>> : <LinearComb<MDroit, C_F0>> )
  ( <LinearComb<MGauche, C_F0>> : <LinearComb<MGauche, C_F0>> )

- pi, type :<double>
- plot, type :<Polymorphic> operator() :
  ( <long> : ... )

- pow, type :<Polymorphic> operator() :
  ( <double> : <double>, <double> )
  ( <complex> : <complex>, <complex> )

- qf1pE, type :<Fem2D::QuadratureFormular1d>
- qf1pT, type :<Fem2D::QuadratureFormular>
- qf1pTlump, type :<Fem2D::QuadratureFormular>
- qf2pE, type :<Fem2D::QuadratureFormular1d>
- qf2pT, type :<Fem2D::QuadratureFormular>
- qf2pT4P1, type :<Fem2D::QuadratureFormular>
- qf3pE, type :<Fem2D::QuadratureFormular1d>
- qf5pT, type :<Fem2D::QuadratureFormular>

- readmesh, type :<Polymorphic> operator() :
  ( <Fem2D::Mesh> : <string> )

- real, type :<Polymorphic> operator() :
  ( <double> : <complex> )

- region, type :<long *>
- savemesh, type :<Polymorphic> operator() :
  ( <Fem2D::Mesh> : <Fem2D::Mesh>, <string>... )

- sin, type :<Polymorphic> operator() :
  ( <double> : <double> )
  ( <complex> : <complex> )

- sinh, type :<Polymorphic> operator() :
  ( <double> : <double> )
  ( <complex> : <complex> )

- sqrt, type :<Polymorphic> operator() :
  ( <double> : <double> )
  ( <complex> : <complex> )

- square, type :<Polymorphic> operator() :
  ( <Fem2D::Mesh> : <long>, <long> )

```

```
(    <Fem2D::Mesh> :    <long>, <long>, <E_Array> )

- tan,  type :<Polymorphic>  operator() :
  (    <double> :    <double> )

- true,  type :<bool>
- trunc,  type :<Polymorphic>  operator() :
  (    <Fem2D::Mesh> :    <Fem2D::Mesh>, <bool> )

- verbosity,  type :<long *>
- wait,  type :<bool *>
- x,  type :<double *>
- y,  type :<double *>
- z,  type :<double *>
```



# Appendix C

## Dynamical link

Now, it's possible to add built-in fonctionnalites in FreeFem++ under the three environnements Linux, Windows and MacOS X 10.3 or newer. It is agood idea to, first try the example `load.edp` in directory `example++-load`.

You will need to install a c++ compiler (generally g++/gcc compiler) to compile your function.

**Windows** Install the cygwin environnement or the mingw

**MacOs** Install the developer tools xcode on the apple DVD

**Linux/Unix** Install the correct compiler (gcc for instance)

Now, assume that you are in a shell window (a cygwin window under Windows) in the directory `example++-load`. Remark that in the sub directory `include` they are all the FreeFem++ include file to make the link with FreeFem++.

**Note C.1** *If you try to load dynamically a file with command `load "xxx"`*

- *Under unix (Linux or MacOS), the file `xxx.so` twill be loaded so it must be either in the search directory of routine `dlopen` (see the environment variable `$LD_LIBRARY_PATH` or in the current directory, and the suffix `".so"` or the prefix `"/"` is automatically added.*
- *Under Windows, The file `xxx.dll` will be loaded so it must be in the `loadLibrary` search directory which includes the directory of the application,*

**The compilation of your module:** the script `ff-c++` compiles and makes the link with FreeFem++, but be careful, the script has no way to known if you try to compile for a pure Windows environment or for a cygwin environment so to build the load module under cygwin you must add the `-cygwin` parameter.

### C.1 A first example `myfunction.cpp`

The following defines a new function call `myfunction` with no parameter, but using the `x, y` current value.

```
#include <iostream>
#include <cfloat>
```

```

using namespace std;
#include "error.hpp"
#include "AFunction.hpp"
#include "rgraph.hpp"
#include "RNM.hpp"
#include "fem.hpp"
#include "FESpace.hpp"
#include "MeshPoint.hpp"

using namespace Fem2D;
double myfunction(Stack stack)
{
    // to get FreeFem++ data
    MeshPoint &mp= *MeshPointStack(stack); // the struct to get x,y, normal , value
    double x= mp.P.x; // get the current x value
    double y= mp.P.y; // get the current y value
    // cout << "x = " << x << " y=" << y << endl;
    return sin(x)*cos(y);
}

```

Now the Problem is to build the link with FreeFem++, to do that we need two classes, one to call the function myfunction

All FreeFem++ evaluable expression must be a struct/class C++ which derive from E\_F0. By default this expression does not depend of the mesh position, but if they derive from E\_F0mps the expression depends of the mesh position, and for more details see [12].

```

// A class build the link with FreeFem++
// generally this class are already in AFunction.hpp
// but unfortunately, I have no simple function with no parameter
// in FreeFem++ depending of the mesh,

template<class R>
class OneOperator0s : public OneOperator {

    // the class to defined a evaluated a new function
    // It must devive from E_F0 if it is mesh independent
    // or from E_F0mps if it is mesh dependent

    class E_F0_F :public E_F0mps { public:
        typedef R (*func)(Stack stack) ;
        func f; // the pointeur to the fnction myfunction
        E_F0_F(func ff) : f(ff) {}

        // the operator evaluation in FreeFem++
        AnyType operator()(Stack stack) const {return SetAny<R>( f(stack)) ;}

    };

    typedef R (*func)(Stack ) ;
    func f;
public:
    // the function which build the FreeFem++ byte code
    E_F0 * code(const basicAC_F0 & ) const { return new E_F0_F(f);}
    // the constructor to say ff is a function without parameter
    // and returning a R
    OneOperator0s(func ff): OneOperator(map_type[typeid(R).name()],f(ff){}
};

```

To finish we must add this new function in FreeFem++ table , to do that include :



```

class Init { public: Init(); };

Init init;

Init::Init(){
    Global.Add("myfunction", "(" , new OneOperator0s<double>(myfunction));
}

```

It will be called automatically at load module time.

To compile and link, use the ff-c++ script :

```

% ff-c++ myfunction.cpp
g++ -c -g -Iinclude myfunction.cpp
g++ -bundle -undefined dynamic_lookup -g myfunction.o -o ./myfunction.dylib

```

To, try the simple example under Linux or MacOS, do

```

% FreeFem++-nw load.edp
-- FreeFem++ v 1.4800028 (date Tue Oct  4 11:56:46 CEST 2005)
file : load.edp
Load: lg_fem lg_mesh eigenvalue  UMFPACK
  1 :                                     //  Example of dynamic function load
  2 :                                     //  -----
  3 :                                     //  Id : freefem + +doc.tex, v1.1102010/06/0411 : 27 : 24hechtExp
  4 :
  5 :  load "myfunction"

load: myfunction
load: dlopen(/myfunction) = 0xb01cc0

  6 :  mesh Th=square(5,5);
  7 :  fespace Vh(Th,P1);
  8 :  Vh uh=myfunction();                                     //  warning do not forget ()
  9 :  cout << uh[].min << " " << uh[].max << endl;
 10 :  sizestack + 1024 =1240 ( 216 )

-- square mesh : nb vertices  =36 ,  nb triangles = 50 ,  nb boundary edges 20
Nb of edges on Mortars  = 0
Nb of edges on Boundary = 20, neb = 20
Nb Of Nodes = 36
Nb of DF = 36
0 0.841471
times: compile 0.05s, execution -3.46945e-18s
CodeAlloc : nb ptr 1394, size :71524
Bien: On a fini Normalement

```

Under Windows, launch FreeFem++ with the mouse (or ctrl O) on the example.

## C.2 Example: Discrete Fast Fourier Transform

This will add FFT to FreeFem++, taken from <http://www.fftw.org/>. To download and install under download/include just go in download/fftw and trymake.

The 1D dfft (fast discret fourier transform) for a simple array  $f$  of size  $n$  is defined by the following formula

$$\text{dfft}(f, \varepsilon)_k = \sum_{j=0}^{n-1} f_j e^{\varepsilon 2\pi i k j / n}$$

The 2D DFFT for an array of size  $N = n \times m$  is

$$\text{dfft}(f, m, \varepsilon)_{k+nl} = \sum_{j'=0}^{m-1} \sum_{j=0}^{n-1} f_{i+nj} e^{\varepsilon 2\pi i (kj/n + l'j'/m)}$$

Remark: the value  $n$  is given by  $\text{size}(f)/m$ , and the numbering is row-major order.

So the classical discrete DFFT is  $\hat{f} = \text{dfft}(f, -1)/\sqrt{n}$  and the reverse dFFT  $f = \text{dfft}(\hat{f}, 1)/\sqrt{n}$

Remark: the 2D Laplace operator is

$$f(x, y) = 1/\sqrt{N} \sum_{j'=0}^{m-1} \sum_{j=0}^{n-1} \hat{f}_{i+nj} e^{\varepsilon 2\pi i (xj+yj')}$$

and we have

$$f_{k+nl} = f(k/n, l/m)$$

So

$$\widehat{\Delta f_{kl}} = -((2\pi)^2((\tilde{k})^2 + (\tilde{l})^2))\widehat{f_{kl}}$$

where  $\tilde{k} = k$  if  $k \leq n/2$  else  $\tilde{k} = k - n$  and  $\tilde{l} = l$  if  $l \leq m/2$  else  $\tilde{l} = l - m$ .

And to have a real function we need all modes to be symmetric around zero, so  $n$  and  $m$  must be odd.

### Compile to build a new library

```
% ff-c++ dfft.cpp ../download/install/lib/libfftw3.a -I../download/install/include
export MACOSX_DEPLOYMENT_TARGET=10.3
g++ -c -Iinclude -I../download/install/include dfft.cpp
g++ -bundle -undefined dynamic_lookup dfft.o -o ../dfft.dylib ../download/install/lib/libfftw3.a
```

To test ,

```
-- FreeFem++ v 1.4800028 (date Mon Oct 10 16:53:28 EEST 2005)
file : dfft.edp
Load: lg_fem cadna lg_mesh eigenvalue  UMFPACK
 1 :                                     //      Example of dynamic function load
 2 :                                     //      -----
 3 :                                     //      Id : freefem + +doc.tex, v1.1102010/06/0411 : 27 : 24hechtExp
 4 :                                     //      Discret Fast Fourier Transform
 5 :                                     //      -----
 6 : load "dfft" load: init dfft

load: dlopen(dfft.dylib) = 0x2b0c700
```

```

7 :
8 : int nx=32,ny=16,N=nx*ny;
9 : // warning the Fourier space is not exactly the unite square due to periodic
conditions
10 : mesh Th=square(nx-1,ny-1,[(nx-1)*x/nx,(ny-1)*y/ny]);
11 : // warring the numbering is of the vertices (x,y) is
12 : // given by i = x/nx + nx * y/ny
13 :
14 : fespace Vh(Th,P1);
15 :
16 : func f1 = cos(2*x*2*pi)*cos(3*y*2*pi);
17 : Vh<complex> u=f1,v;
18 : Vh w=f1;
19 :
20 :
21 : Vh ur,ui;
22 : // in dfft the matrix n,m is in row-major order ann array n,m is
23 : // store j + m* i ( the transpose of the square numbering )
24 : v[]=dfft(u[],ny,-1);
25 : u[]=dfft(v[],ny,+1);
26 : u[] /= complex(N);
27 : v = f1-u;
28 : cout << " diff = "<< v[].max << " " << v[].min << endl;
29 : assert( norm(v[].max) < 1e-10 && norm(v[].min) < 1e-10) ;
30 : // ----- a more hard example ----
31 : // Lapacien en FFT
32 : // -Δu = f with biperiodic condition
33 : func f = cos(3*2*pi*x)*cos(2*2*pi*y); //
34 : func ue = +(1./(square(2*pi)*13.))*cos(3*2*pi*x)*cos(2*2*pi*y); //
35 : Vh<complex> ff = f;
36 : Vh<complex> fhat;
37 : fhat[] = dfft(ff[],ny,-1);
38 :
39 : Vh<complex> wij;
40 : // warning in fact we take mode between -nx/2, nx/2 and -ny/2,ny/2
41 : // thank to the operator ? :
42 : wij = square(2.*pi)*(square(( x<0.5?x*nx:(x-1)*nx))
+ square((y<0.5?y*ny:(y-1)*ny)));
43 : wij[][0] = 1e-5; // to remove div / 0
44 : fhat[] = fhat[]./ wij[]; //
45 : u[]=dfft(fhat[],ny,1);
46 : u[] /= complex(N);
47 : ur = real(u); // the solution
48 : w = real(ue); // the exact solution
49 : plot(w,ur,value=1 ,cmm=" ue ", wait=1);
50 : w[] -= ur[]; // array sub
51 : real err= abs(w[].max)+abs(w[].min) ;
52 : cout << " err = " << err << endl;
53 : assert( err < 1e-6);
54 : sizestack + 1024 =3544 ( 2520 )

```

```

-----CheckPtr:-----init execution ----- NbUndelPtr 2815 Alloc: 111320 NbPtr 6368
-- square mesh : nb vertices =512 , nb triangles = 930 , nb boundary edges 92
Nb of edges on Mortars = 0
Nb of edges on Boundary = 92, neb = 92

```

```

Nb Of Nodes = 512
Nb of DF = 512
0x2d383d8 -1 16 512 n: 16 m:32
dfft 0x402bc08 = 0x4028208 n = 16 32 sign = -1
--- --- ---0x2d3ae08 1 16 512 n: 16 m:32
dfft 0x4028208 = 0x402bc08 n = 16 32 sign = 1
--- --- --- diff = (8.88178e-16,3.5651e-16) (-6.66134e-16,-3.38216e-16)
0x2d3cfb8 -1 16 512 n: 16 m:32
dfft 0x402de08 = 0x402bc08 n = 16 32 sign = -1
--- --- ---0x2d37ff8 1 16 512 n: 16 m:32
dfft 0x4028208 = 0x402de08 n = 16 32 sign = 1
--- --- --- err = 3.6104e-12
times: compile 0.13s, execution 2.05s
-----CheckPtr:-----end execution -- ----- NbUndelPtr 2815 Alloc: 111320 NbPtr 26950
CodeAlloc : nb ptr 1693, size :76084
Bien: On a fini Normalement
      CheckPtr:Nb of undelete pointer is 2748 last 114
      CheckPtr:Max Memory used      228.531 kbytes Memory undelete 105020

```

### C.3 Load Module for Dervieux' P0-P1 Finite Volume Method

the associated edp file is `examples++-load/convect_dervieux.edp`

```

// ----- Implementation of P1-P0 FVM-FEM -----
// ----- Id : freefem + +doc.tex,v1.1102010/06/0411 : 27 : 24hechtExp -----
// compile and link with ff-c++ mat.dervieux.cpp (i.e. the file name without .cpp)
#include <iostream>
#include <cfloat>
#include <cmath>
using namespace std;
#include "error.hpp"
#include "AFunction.hpp"
#include "rgraph.hpp"
#include "RNM.hpp"

// remove problem of include
#undef HAVE_LIBUMFPACK
#undef HAVE_CADNA
#include "MatriceCreuse_tpl.hpp"
#include "MeshPoint.hpp"
#include "lgfem.hpp"
#include "lgsolver.hpp"
#include "problem.hpp"

class MatrixUpWind0 : public E_F0mps { public:
    typedef Matrice_Creuse<R> * Result;
    Expression emat,expTh,expc,expu1,expu2;
    MatrixUpWind0(const basicAC_F0 & args)
    {
        args.SetNameParam();
        emat =args[0];
        expTh= to<pmesh>(args[1]);
        expc = CastTo<double>(args[2]);
        // the matrix expression
        // a the expression to get the mesh
        // the expression to get c (must be a double)

```

```

//      a array expression [ a, b]
const E_Array * a= dynamic_cast<const E_Array*>((Expression) args[3]);
if (a->size() != 2) CompileError("syntax:  MatrixUpWind0(Th,rhi,[u1,u2])");
int err =0;
expu1= CastTo<double>((*a)[0]);      //      fist exp of the array (must be a double)
expu2= CastTo<double>((*a)[1]);      //      second exp of the array (must be a double)
}

~MatrixUpWind0(){
}

static ArrayOfaType  typeargs()
{ return  ArrayOfaType(atype<Matrice_Creuse<R>*>(),
    atype<pmesh>(),atype<double>(),atype<E_Array>());}
static  E_F0 * f(const basicAC_F0 & args){ return new MatrixUpWind0(args);}

AnyType operator()(Stack s) const ;

};

int  fvmP1P0(double q[3][2], double u[2],double c[3], double a[3][3], double where[3]
)
{
    //      computes matrix a on a triangle for the Dervieux
    FVM
    for(int i=0;i<3;i++) for(int j=0;j<3;j++) a[i][j]=0;

    for(int i=0;i<3;i++){
        int ip = (i+1)%3; ipp =(ip+1)%3;
        double unL =-((q[ip][1]+q[i][1]-2*q[ipp][1])*u[0]
            -(q[ip][0]+q[i][0]-2*q[ipp][0])*u[1])/6;
        if(unL>0) { a[i][i] += unL; a[ip][i]-=unL;}
        else{ a[i][ip] += unL; a[ip][ip]-=unL;}
        if(where[i]&&where[ip]){
            //      this is a boundary edge
            unL=((q[ip][1]-q[i][1])*u[0] -(q[ip][0]-q[i][0])*u[1])/2;
            if(unL>0) { a[i][i]+=unL; a[ip][ip]+=unL;}
        }
    }
    return 1;
}

//      the evaluation routine
AnyType MatrixUpWind0::operator()(Stack stack) const
{
    Matrice_Creuse<R> * sparse_mat =GetAny<Matrice_Creuse<R>*> ((*emat)(stack));
    MatriceMorse<R> * amorse =0;
    MeshPoint *mp(MeshPointStack(stack)) , mps=*mp;
    Mesh * pTh = GetAny<pmesh> ((*expTh)(stack));
    ffassert(pTh);
    Mesh & Th (*pTh);
    {
        map< pair<int,int>, R> Aij;
        KN<double> cc(Th.nv);
        double infini=DBL_MAX;
        cc=infini;
        for (int it=0;it<Th.nt;it++)
            for (int iv=0;iv<3;iv++)

```

```

{
    int i=Th(it,iv);
    if ( cc[i]==infini) { // if nuset the set
        mp->setP(&Th,it,iv);
        cc[i]=GetAny<double>((*expc)(stack));
    }
}

for (int k=0;k<Th.nt;k++)
{
    const Triangle & K(Th[k]);
    const Vertex & A(K[0]), &B(K[1]),&C(K[2]);
    R2 Pt(1./3.,1./3.);
    R u[2];
    MeshPointStack(stack)->set(Th,K(Pt),Pt,K,K.lab);
    u[0] = GetAny< R>( (*expu1)(stack) ) ;
    u[1] = GetAny< R>( (*expu2)(stack) ) ;

    int ii[3] ={ Th(A), Th(B),Th(C)};
    double q[3][2]= { { A.x,A.y} ,{B.x,B.y},{C.x,C.y} } ; // coordinates of 3
    vertices (input)
    double c[3]={cc[ii[0]],cc[ii[1]],cc[ii[2]]};
    double a[3][3], where[3]={A.lab,B.lab,C.lab};
    if (fvmP1P0(q,u,c,a,where) )
    {
        for (int i=0;i<3;i++)
            for (int j=0;j<3;j++)
                if (fabs(a[i][j]) >= 1e-30)
                    { Aij[make_pair(ii[i],ii[j])]+=a[i][j];
                    }
    }
}
amorse= new MatriceMorse<R>(Th.nv,Th.nv,Aij,false);
}
sparse_mat->pUh=0;
sparse_mat->pVh=0;
sparse_mat->A.master(amorse);
sparse_mat->typemat=(amorse->n == amorse->m) ? TypeSolveMat(TypeSolveMat::GMRES) : TypeSolveMat(Ty
// none square matrice (morse)

*mp=mps;

if(verbosity>3) { cout << " End Build MatrixUpWind : " << endl;}

return sparse_mat;
}

class Init { public:
    Init();
};
Init init;
Init::Init()
{
    cout << " load: init Mat Chacon " << endl;
    Global.Add("MatUpWind0",("(", new OneOperatorCode<MatrixUpWind0 >( ));
}

```

## C.4 More on Adding a new finite element

First read the section 13 of the appendix, we add two new finite elements examples in the directory `examples++-load`.

**The Bernardi-Raugel Element** The Bernardi-Raugel finite element is meant to solve the Navier Stokes equations in  $u, p$  formulation; the velocity space  $P_K^{br}$  is minimal to prove the inf-sup condition with piecewise constant pressure by triangle. The finite element space  $V_h$  is

$$V_h = \{u \in H^1(\Omega)^2; \quad \forall K \in T_h, u|_K \in P_K^{br}\}$$

where

$$P_K^{br} = \text{span}\{\lambda_i^K e_k\}_{i=1,2,3, k=1,2} \cup \{\lambda_i^K \lambda_{i+1}^K n_{i+2}^K\}_{i=1,2,3}$$

with notation  $4 = 1, 5 = 2$  and where  $\lambda_i^K$  are the barycentric coordinates of the triangle  $K$ ,  $(e_k)_{k=1,2}$  the canonical basis of  $\mathbb{R}^2$  and  $n_k^K$  the outer normal of triangle  $K$  opposite to vertex  $k$ .

```
// The P2BR finite element : the Bernadi Raugel Finite Element
// F. Hecht, decembre 2005
// -----
// See Bernardi, C., Raugel, G.: Analysis of some finite elements for the Stokes
// problem. Math. Comp. 44, 71-79 (1985).
// It is a 2d coupled FE
// the Polynomial space is  $P_1^2 + 3$  normals bubbles edges function ( $P_2$ )
// the degree of freedom is 6 values at of the 2 componants at the 3 vertices
// and the 3 flux on the 3 edges
// So 9 degrees of freedom and  $N= 2$ .

// ----- related files:
// to check and validate : testFE.edp
// to get a real example : MSP2BRP0.edp
// -----
```

```
#include "error.hpp"
#include "AFunction.hpp"
#include "rgraph.hpp"
using namespace std;
#include "RNM.hpp"
#include "fem.hpp"
#include "FESpace.hpp"
#include "AddNewFE.h"
```

```
namespace Fem2D {

class TypeOfFE_P2BRLagrange : public TypeOfFE { public:
    static int Data[];

    TypeOfFE_P2BRLagrange(): TypeOfFE(6+3+0,
        2,
        Data,
        4,
        1,
```

```

        6+3*(2+2),          //    nb coef to build interpolation
        9,                 //    np point to build interpolation
        0)
    {
    ....                    //    to long see the source
    }
    void FB(const bool * whatd, const Mesh & Th,const Triangle & K,const R2 &P, RNMK_ & val)
const;
    void TypeOfFE_P2BRLagrange::Pi_h_alpha(const baseFEelement & K,KN_<double> & v) const;
    } ;

    //    on what nu df on node node of df

    int TypeOfFE_P2BRLagrange::Data[]={
        0,0, 1,1, 2,2, 3,4,5,
        0,1, 0,1, 0,1, 0,0,0,
        0,0, 1,1, 2,2, 3,4,5,
        0,0, 0,0, 0,0, 0,0,0,
        0,1, 2,3, 4,5, 6,7,8,
        0,0
    };

    void TypeOfFE_P2BRLagrange::Pi_h_alpha(const baseFEelement & K,KN_<double> & v) const
    {
        const Triangle & T(K.T);
        int k=0;

        //    coef pour les 3 sommets fois le 2 composantes

        for (int i=0;i<6;i++)
            v[k++]=1;

        //    integration sur les aretes

        for (int i=0;i<3;i++)
        {

            R2 N(T.Edge(i).perp());
N    *= T.EdgeOrientation(i)*0.5 ;
            v[k++]= N.x;
            v[k++]= N.y;
            v[k++]= N.x;
            v[k++]= N.y;
        }
    }

    void TypeOfFE_P2BRLagrange::FB(const bool * whatd,const Mesh & ,const Triangle & K,const
R2 & P,RNMK_ & val) const
    {
    ....                    //    to long see the source
    }

    //    ---- cooking to add the finite elemet to freefem table -----
    //    a static variable to def the finite element

    static TypeOfFE_P2BRLagrange P2LagrangeP2BR;

    //    now adding FE in FreeFem++ table

    static AddNewFE P2BR("P2BR",&P2LagrangeP2BR);

    //    --- end cooking
    //    end FEM2d namespace
}

```



A way to check the finite element

```
load "BernadiRaugel"

// a macro the compute numerical derivative
macro DD(f,hx,hy) ( (f(x1+hx,y1+hy)-f(x1-hx,y1-hy))/(2*(hx+hy))) //
mesh Th=square(1,1,[10*(x+y/3),10*(y-x/3)]);

real x1=0.7,y1=0.9, h=1e-7;
int it1=Th(x1,y1).nuTriangle;

fespace Vh(Th,P2BR);

Vh [a1,a2],[b1,b2],[c1,c2];

for (int i=0;i<Vh.ndofK;++i)
cout << i << " " << Vh(0,i) << endl;
for (int i=0;i<Vh.ndofK;++i)
{
  a1[]=0;
  int j=Vh(it1,i);
  a1[][j]=1;
  plot([a1,a2], wait=1); // a bascis functions

  [b1,b2]=[a1,a2]; // do the interpolation

  c1[] = a1[] - b1[];

  cout << " -----" << i << " " << c1[].max << " " << c1[].min << endl;
  cout << " a = " << a1[] << endl;
  cout << " b = " << b1[] << endl;
  assert(c1[].max < 1e-9 && c1[].min > -1e-9); // check if the interpolation is
correct

// check the derivative and numerical derivative

cout << " dx(a1)(x1,y1) = " << dx(a1)(x1,y1) << " == " << DD(a1,h,0) << endl;
assert( abs(dx(a1)(x1,y1)-DD(a1,h,0) ) < 1e-5);
assert( abs(dx(a2)(x1,y1)-DD(a2,h,0) ) < 1e-5);
assert( abs(dy(a1)(x1,y1)-DD(a1,0,h) ) < 1e-5);
assert( abs(dy(a2)(x1,y1)-DD(a2,0,h) ) < 1e-5);
}
```

A real example using this finite element, just a small modification of the NSP2P1.edp examples, just the bebeginning is change to

```
load "BernadiRaugel"

real s0=clock();
mesh Th=square(10,10);
fespace Vh2(Th,P2BR);
fespace Vh(Th,P0);
Vh2 [u1,u2],[up1,up2];
Vh2 [v1,v2];
```

And the plot instruction is also changed because the pressure is constant, and we cannot plot isovalues of piecewise constant functions.

**The Morley Element** See the example `bilapMorley.edp`.

## C.5 Add a new sparse solver

Warning the sparse solver interface as been completely rewritten in version 3.2 , so the section is obsolete, the example in are correct/

Only a fast sketch of the code is given here; for details see the `.cpp` code from `SuperLU.cpp` or `NewSolve.cpp`.

First the include files:

```
#include <iostream>
using namespace std;

#include "rgraph.hpp"
#include "error.hpp"
#include "AFunction.hpp"

// #include "lex.hpp"

#include "MatriceCreuse_tpl.hpp"
#include "slu_ddefs.h"
#include "slu_zdefs.h"
```

A small template driver to unified the double and Complex version.

```
template <class R> struct SuperLUDriver
{
};

template <> struct SuperLUDriver<double>
{
    .... double version
};

template <> struct SuperLUDriver<Complex>
{
    .... Complex version
};
```

To get Matrix value, we have just to remark that the Morse Matrice the storage, is the SLU\_NR format is the compressed row storage, this is the transpose of the compressed column storage.

So if `AA` is a `MatriceMorse` you have with SuperLU notation.

```
n=AA.n;
m=AA.m;
nnz=AA.nbcoef;
a=AA.a;
```

```

asub=AA.cl;
xa=AA.lg;
options.Trans = TRANS;

Dtype_t R_SLU = SuperLUDriver<R>::R_SLU_T();
Create_CompCol_Matrix(&A, m, n, nnz, a, asub, xa, SLU_NC, R_SLU, SLU_GE);

```

To get vector information, to solve the linear solver  $x = A^{-1}b$

```

void Solver(const MatriceMorse<R> &AA,KN_<R> &x,const KN_<R> &b) const
{
....
Create_Dense_Matrix(&B, m, 1, b, m, SLU_DN, R_SLU, SLU_GE);
Create_Dense_Matrix(&X, m, 1, x, m, SLU_DN, R_SLU, SLU_GE);
....
}

```

The two BuildSolverSuperLU function, to change the default sparse solver variable  
DefSparseSolver<double>::solver

```

MatriceMorse<double>::VirtualSolver *
BuildSolverSuperLU(DCL_ARG_SPARSE_SOLVER(double,A))
{
    if(verbosity>9)
        cout << " BuildSolverSuperLU<double>" << endl;
    return new SolveSuperLU<double>(*A,ds.strategy,ds.tgv,ds.epsilon,ds.tol_pivot,ds.tol_pivot_sym,d
}

MatriceMorse<Complex>::VirtualSolver *
BuildSolverSuperLU(DCL_ARG_SPARSE_SOLVER(Complex,A))
{
    if(verbosity>9)
        cout << " BuildSolverSuperLU<Complex>" << endl;
    return new SolveSuperLU<Complex>(*A,ds.strategy,ds.tgv,ds.epsilon,ds.tol_pivot,ds.tol_pivot_sym,d
}

```

The link to FreeFem++

```

class Init { public:
    Init();
};

```

To set the 2 default sparse solver double and complex:

```

DefSparseSolver<double>::SparseMatSolver SparseMatSolver_R ; ;
DefSparseSolver<Complex>::SparseMatSolver SparseMatSolver_C;

```

To save the default solver type

```

TypeSolveMat::TSolveMat TypeSolveMatdefaultvalue=TypeSolveMat::defaultvalue;

```

To reset to the default solver, call this function:

```

bool SetDefault()
{
    if(verbosity>1)
    cout << " SetDefault sparse to default" << endl;
    DefSparseSolver<double>::solver =SparseMatSolver_R;
    DefSparseSolver<Complex>::solver =SparseMatSolver_C;
    TypeSolveMat::defaultvalue =TypeSolveMat::SparseSolver;
}

```

To set the default solver to superLU, call this function:

```

bool SetSuperLU()
{
    if(verbosity>1)
    cout << " SetDefault sparse solver to SuperLU" << endl;
    DefSparseSolver<double>::solver =BuildSolverSuperLU;
    DefSparseSolver<Complex>::solver =BuildSolverSuperLU;
    TypeSolveMat::defaultvalue =TypeSolveMatdefaultvalue;
}

```

To add new function/name defaultsolver,defaulttoSuperLUin freefem++, and set the default solver to the new solver., just do:

```

Init init;
Init::Init()
{

    SparseMatSolver_R= DefSparseSolver<double>::solver;
    SparseMatSolver_C= DefSparseSolver<Complex>::solver;

    if(verbosity>1)
        cout << "\n Add: SuperLU,  defaultsolver defaultsolverSuperLU" << endl;
    TypeSolveMat::defaultvalue=TypeSolveMat::SparseSolver;
    DefSparseSolver<double>::solver =BuildSolverSuperLU;
    DefSparseSolver<Complex>::solver =BuildSolverSuperLU;
    // test if the name "defaultsolver" exist in freefem++
    if(! Global.Find("defaultsolver").NotNull() )
        Global.Add("defaultsolver", "(" ,new OneOperator0<bool>(SetDefault));
    Global.Add("defaulttoSuperLU", "(" ,new OneOperator0<bool>(SetSuperLU));
}

```

To compile superlu.cpp, just do:

1. download the SuperLu 3.0 package and do

```

curl  http://crd.lbl.gov/~xiaoye/SuperLU/superlu_3.0.tar.gz  -o superlu_3.0.ta
tar xvfz superlu_3.0.tar.gz
go SuperLU_3.0 directory
$EDITOR make.inc
make

```

2. In directoy include do to have a correct version of SuperLu header due to mistake in case of inclusion of double and Complex version in the same file.

```
tar xvfz ../SuperLU_3.0-include-ff.tar.gz
```

I will give a correct one to compile with freefm++.

To compile the freefem++ load file of SuperLu with freefem do: some find like :

```
ff-c++ SuperLU.cpp -L$HOME/work/LinearSolver/SuperLU_3.0/ -lsuperlu_3.0
```

And to test the simple example:

A example:

```
load "SuperLU"
verbosity=2;
for(int i=0;i<3;++i)
{
  //   if i == 0 then SuperLu solver
  //   i == 1 then GMRES solver
  //   i == 2 then Default solver
  {
    matrix A =
      [[ 0, 1, 0, 10],
       [ 0, 0, 2, 0],
       [ 0, 0, 0, 3],
       [ 4,0 , 0, 0]];
    real[int] xx = [ 4,1,2,3], x(4), b(4);
    b = A*xx;
    cout << b << " " << xx << endl;
    set(A,solver=sparsesolver);
    x = A^-1*b;
    cout << x << endl;
  }

  {
    matrix<complex> A =
      [[ 0, 1i, 0, 10],
       [ 0 , 0, 2i, 0],
       [ 0, 0, 0, 3i],
       [ 4i,0 , 0, 0]];
    complex[int] xx = [ 4i,1i,2i,3i], x(4), b(4);
    b = A*xx;
    cout << b << " " << xx << endl;
    set(A,solver=sparsesolver);
    x = A^-1*b;
    cout << x << endl;
  }
  if(i==0)defaulttoGMRES();
  if(i==1)defaultsolver();
}
```

To Test do for exemple:

```
FreeFem++ SuperLu.edp
```



# FreeFem++ LGPL License

This is The FreeFem++ software. Programs in it were maintained by

- Frédéric hecht <Frederic.Hecht@upmc.fr>
- Jacques Morice <morice@ann.jussieu.fr>

All its programs except files the coming from COOOL software (files in directory src/Algo) and the file mt19937ar.cpp which may be redistributed under the terms of the GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables. The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy. This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange. If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along



with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

#### NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

# Appendix D

## Keywords

### Main Keywords

adaptmesh  
Cmatrix  
R3  
bool  
border  
break  
buildmesh  
catch  
cin  
complex  
continue  
cout  
element  
else  
end  
fespace  
for  
func  
if  
ifstream  
include  
int  
intalledge  
load  
macro  
matrix  
mesh  
movemesh  
ofstream  
plot  
problem  
real  
return  
savemesh  
solve  
string  
try  
throw  
vertex  
varf

while

### Second category of Keywords

int1d  
int2d  
on  
square

### Third category of Keywords

dx  
dy  
convect  
jump  
mean

### Fourth category of Keywords

wait  
ps  
solver  
CG  
LU  
UMFPACK  
factorize  
init  
endl

### Other Reserved Words

x, y, z, pi, i,  
sin, cos, tan, atan, asin, acos,  
cotan, sinh, cosh, tanh, cotanh,  
exp, log, log10, sqrt  
abs, max, min,



# Bibliography

- [1] R. B. LEHOUCQ, D. C. SORESENSEN, AND C. YANG *ARPACK Users' Guide: Solution of Large-Scale Eigenvalue Problems with Implicitly Restarted Arnoldi Methods* SIAM, ISBN 0-89871-407-9  
// <http://www.caam.rice.edu/software/ARPACK/>
- [2] I. BABBUŠKA, Error bounds for finite element method, *Numer. Math.* 16, 322-333.
- [3] Y. ACHDOU AND O. PIRONNEAU, *Computational Methods for Option Pricing*. SIAM monograph (2005).
- [4] D. BERNARDI, F. HECHT, K. OHTSUKA, O. PIRONNEAU, *freefem+ documentation*, on the web at <ftp://www.freefem.org/freefemplus>.
- [5] D. BERNARDI, F. HECHT, O. PIRONNEAU, C. PRUD'HOMME, *freefem documentation*, on the web at <http://www.freefem.fr/freefem>
- [6] T.A. DAVIS: Algorithm 8xx: UMFPACK V4.1, an unsymmetric-pattern multifrontal method TOMS, 2003 (submitted for publication) <http://www.cise.ufl.edu/research/sparse/umfpack>
- [7] P.L. GEORGE, *Automatic triangulation*, Wiley 1996.
- [8] F. HECHT, Outils et algorithmes pour la méthode des éléments finis, HdR, Université Pierre et Marie Curie, France, 1992
- [9] F. HECHT, The mesh adapting software: bamg. INRIA report 1998.
- [10] A. PERRONNET ET. AL. Library Modulef, INRIA, <http://www.inria-rocq/modulef>
- [11] A. ERN AND J.-L. GUERMOND, Discontinuous Galerkin methods for Friedrichs' symmetric systems and Second-order PDEs, *SIAM J. Numer. Anal.*, (2005). See also: *Theory and Practice of Finite Elements*, vol. 159 of Applied Mathematical Sciences, Springer-Verlag, New York, NY, 2004.
- [12] F. HECHT. C++ Tools to construct our user-level language. Vol 36, N°, 2002 pp 809-836, *Modél. math et Anal Numér.*
- [13] J.L. LIONS, O. PIRONNEAU: Parallel Algorithms for boundary value problems, *Note CRAS*. Dec 1998. Also : Superpositions for composite domains (to appear)
- [14] B. LUCQUIN, O. PIRONNEAU: *Introduction to Scientific Computing* Wiley 1998.
- [15] I. DANAILA, F. HECHT, AND O. PIRONNEAU. *Simulation numérique en C++*. Dunod, Paris, 2003.

- [16] J. NEČAS, L. HLAVÁČEK, Mathematical theory of elastic and elasto-plastic bodies: An introduction, Elsevier, 1981.
- [17] K. OHTSUKA, O. PIRONNEAU AND F. HECHT: Theoretical and Numerical analysis of energy release rate in 2D fracture, *INFORMATION* **3** (2000), 303–315.
- [18] F. PREPARATA, M. SHAMOS *Computational Geometry* Springer series in Computer sciences, 1984.
- [19] R. RANNACHER: On Chorin's projection method for the incompressible Navier-Stokes equations, in "Navier-Stokes Equations: Theory and Numerical Methods" (R. Rautmann, et al., eds.), Proc. Oberwolfach Conf., August 19-23, 1991, Springer, 1992
- [20] J.E. ROBERTS AND THOMAS J.-M: Mixed and Hybrid Methods, Handbook of Numerical Analysis, Vol.II, North-Holland, 1993
- [21] J.L. STEGER: The Chimera method of flow simulation, Workshop on applied CFD, Univ of Tennessee Space Institute, August 1991.
- [22] M. TABATA: Numerical solutions of partial differential equations II (in Japanese), Iwanami Applied Math., 1994
- [23] F. THOMASSET: Implementation of finite element methods of Navier-Stokes Equations, Springer-Verlag, 1981
- [24] N. WIRTH: *Algorithms + Data Structures = Programs*, Prentice Hall, 1976
- [25] BISON The GNU compiler-compiler documentation (on the web).
- [26] B. STROUSTRUP, The C++ , programming language, Third edition, Addison-Wesley 1997.
- [27] L. DENG, WENCES GOUVEIA, COOOL: a package of tools for writing optimization code and solving optimization problems, <http://coool.mines.edu>
- [28] B. RIVIERE, M. WHEELER, V. GIRAULT, A priori error estimates for finite element methods based on discontinuous approximation spaces for elliptic problems. *SIAM J. Numer. Anal.* **39** (2001), no. 3, 902–931 (electronic).
- [29] R. GLOWINSKI AND O. PIRONNEAU, Numerical methods for the Stokes problem, Chapter 13 of *Energy Methods in Finite Element Analysis*, R.Glowinski, E.Y. Rodin, O.C. Zienkiewicz eds., J.Wiley & Sons, Chichester, UK, 1979, pp. 243-264.
- [30] R. GLOWINSKI, *Numerical Methods for Nonlinear Variational Problems*, Springer-Verlag, New York, NY, 1984.
- [31] R. GLOWINSKI, Finite Element Methods for Incompressible Viscous Flow. In *Handbook of Numerical Analysis*, Vol. IX, P.G. Ciarlet and J.L. Lions, eds., North-Holland, Amsterdam, 2003, pp.3-1176.
- [32] C. HORGAN, G. SACCOMANDI, Constitutive Models for Compressible Nonlinearly Elastic Materials with Limiting Chain Extensibility, *Journal of Elasticity*, Volume 77, Number 2, November 2004, pp. 123-138(16).



- [33] KAZUFUMI ITO, AND KARL KUNISCH, Semi smooth newton methods for variational inequalities of the first kind , M2AN, vol 37, N<sup>o</sup>, 2003, pp 41-62.
- [34] R.W. OGDEN, Non-Linear Elastic Deformations, Dover, 1984.
- [35] P.A. RAVIART, J.M. THOMAS, Introduction à l'analyse numérique des équations aux dérivées partielles, Masson, 1983.
- [36] HANG SI, *TetGen Users' Guide: A quality Tetrahedral Mesh Generator and Three-Dimensional Delaunay Triangulator* // <http://tetgen.berlios.de>
- [37] J.R. SHEWCHUK, *Tetrahedral Mesh Generation by Delaunay Refinement* Proceeding of the Fourteenth Annual Symposium on Computational Geometry (Minneapolis, Minnesota), pp 86–95, 1998.
- [38] M. A. TAYLOR, B. A. WINGATE , L. P. BOS, Several new quadrature formulas for polynomial integration in the triangle , Report-no: SAND2005-0034J, <http://xyz.lanl.gov/format/math.NA/0501496>
- [39] P. WILLMOTT, S. HOWISON, J. DEWYNNE : A student introduction to mathematical finance, Cambridge University Press (1995).
- [40] P. FREY, A fully automatic adaptive isotropic surface remeshing procedure. INRIA RT-0252, 2001.

# Index

- <<, 78
  - matrix, 74
- >>, 78
- .\*, 72
- .\*, 159
- ./, 72
- =, 150
- ?:, 58
- [], 16, 148, 226
- , 55
- ', 72
- 3d
  - beam-3d.edp, 195
  - periodic, 184
- time dependent, 28
- accuracy, 19
- acos, 61
- acosh, 61
- adaptation, 98, 115, 137
- adaptmesh, 38, 49, 98, 101
  - abserror=, 101
  - cutoff=, 102
  - err=, 101
  - errg=, 101
  - hmax=, 101
  - hmin=, 101
  - inquire=, 102
  - isMetric=, 102
  - iso=, 101
  - keepbackvertices=, 102
  - maxsubdiv=, 102
  - metric=, 102
  - nbjacobian=, 101
  - nbsmooth=, 101
  - nbvx=, 101
  - nomeshgeneration=, 102
  - omega=, 101
  - periodic=, 102
  - powerin=, 102
  - ratio=, 101
  - rescaling=, 102
  - splitin2, 102
  - splitpbedge=, 102
  - uniform, 102
  - verbosity=, 102
- alphanumeric, 55
- append, 78
- area, 58
- area coordinate, 156
- argument, 60
- ARGV, 79
- array, 56, 64, 76, 158
  - .11, 67
  - .12, 68
  - .linfty, 68
  - .max, 68
  - .min, 68
  - .sum, 68
  - ::, 65
  - ?:, 65
  - = + - \* / .\* ./ += -= /= \*= , 67
  - column, 70
  - dot product, 68
  - FE function, 76
  - fespace, 142
  - im, 65, 66
  - line, 70
  - max, 65
  - mesh, 245
  - min, 65, 76
  - quantile, 68
  - re, 65, 66
  - renumbering, 69
  - resize, 65
  - sort, 65
  - sum, 65
  - varf, 161

- asin, 61
- asinh, 61
- assert(), 58
- atan, 61
- atanh, 61
- axisymmetric, 28
- backward Euler method, 205
- barycentric coordinates, 13
- bessel, 62
- BFGS, 174
- block matrix, 71
- bool, 56
- border, 86, 87
- boundary condition, 159
- break, 77
- broadcast, 245
- bubble, 146
- buildmesh
  - fixeborder, 88
  - fixeborder=1, 184
  - nbvx=, 88
- catch, 81
- Cauchy, 53
- ceil, 61
- CG, 153
- change, 110
- Characteristics-Galerkin, 33
- checkmovemesh, 96
- Cholesky, 153, 173
- cin, 58, 78
- column, 70
- compatibility condition, 152
- compiler, 55
- Complex, 56
- complex, 46, 60, 73
- Complex geometry,, 30
- concatenation, 100
- cone, 120
- connectivity, 163
- continue, 77
- convect, 34, 215, 218
- cos, 61
- cosh, 61
- cout, 58, 78
- Crout, 153
- cube, 119
- de Moivre's formula, 60
- default, 78
- degree of freedom, 13
- DFFT, 310
- diag, 73, 221
- diagonal matrix, 73
- Dirichlet, 19, 25, 53, 151
- discontinuous functions, 231
- Discontinuous-Galerkin, 33
- displacement vector, 193
- divide
  - term to term, 72
- domain decomposition, 223, 225
- dot product, 72, 76
- dumptable, 58
- Edge03d, **141**
- EigenValue, 202
  - ivalue=, 201
  - maxit=, 201
  - ncv=, 201
  - nev=, 201
  - rawvector=, 201
  - sigma=, 201
  - sym=, 201
  - tol=, 201
  - value=, 201
  - vector=, 201
- eigenvalue problems, 26
- elements, 13, 14
- emptymesh, 95
- endl, 78
- erf, 62
- erfc, 62
- exception, 81
- exec, 58, 169, 170
- exp, 61
- expression optimization, 161
- external C++ function, 37
- factorize=, 173
- false, 56, 58
- FE function
  - [], **148**
  - complex, 46, 64, 73
  - n, **148**

- value, 148
- FE space, 141, 142
- FE-function, 63, 141, 142
- FEspace
  - (int ,int ), 163
  - ndof, 163
  - nt, 163
- fespace, 139
  - Edge03d, 141
  - P0, 140
  - P1, 140
  - P13d, 140
  - P1b, 140
  - P1b3d, 140
  - P1dc, 140
  - P1nc, 141
  - P2, 140
  - P2dc, 140
  - periodic=, 153, 182
  - RT0, 141
- ffmedit, 169
- FFT, 310
- file
  - am, 283, 284
  - am\_fmt, 90, 283, 284
  - amdba, 283, 284
  - bang, 90, 281
  - data base, 281
  - ftq, 285
  - mesh, 90
  - msh, 284
  - nopo, 90
- finite element space, 139
- Finite Volume Methods, 36
- fixed, 78
- floor, 61
- fluid, 214
- for, 77
- Fourier, 28
- func, 57
- function
  - tables, 94
- functions, 61
- gamma, 62
- geometry input , 24
- GMRES, 153
- gnuplot, 169
- graphics packages, 19
- hat function, 13
- Helmholtz, 46
- hTriangle, 57, 189
- ifstream, 78
- ill posed problems, 26
- im, 65, 66
- imag, 60
- include, 8, 79, 217
- includepath, 8
- init, 36
- init=, 153
- initial condition, 53
- inside=, 163
- int1d, 154
- int2d, 154
- int3d, 154
- intalledges, 154, 189
- interpolate, 161
  - inside=, 163
  - op=, 163
  - t=, 163
- interpolation, 150
- Irecv, 245
- Isend, 245
- isotropic, 193
- jump, 189
- label, 57, 85, 86
- label on the boundaries, 25
- label=, 103
- lagrangian, 97
- Laplace operator, 19
- lenEdge, 57, 189
- level line, 35
- line, 70
- linearCG
  - eps=, 171
  - nbiter=, 171
  - precon=, 171
  - veps=, 171
- LinearGMRES
  - eps=, 171
  - nbiter=, 171

- precon=, 171
- veps=, 171
- load, 8
- loadpath, 8
- log, 61
- log10, 61
- LU, 153
- macro, 35, 80, 237
  - parameter, 80
  - quote, 252
  - quoting, 80, 81
  - with parameter, 40
  - without parameter, 35
- mass lumping, 37
- matrix, 15, 57, 173
  - =, 218
  - array, 70
  - block, 71
  - complex, 73
  - constant, 71
  - diag, 73, 221
  - factorize=, 200
  - interpolate, 161
  - renumbering, 70, 72
  - resize, 72, 73
  - set, 71
  - solver=, 218
  - stiffness matrix, 15
  - varf, 71, 160
    - eps=, 160
    - precon=, 160
    - solver=, 160
    - solver=factorize, 160
    - tg=, 160
    - tolpivot =, 160
- max, 65
- maximum, 58
- medit, 169, 170
- membrane, 19
- mesh, 57
  - (), 91
  - +, 110
  - [], 91
  - 3point bending, 109
  - adaptation, 38, 49, 98
  - beam, 104
  - Bezier curve, 106
  - Cardioid, 105
  - Cassini Egg, 106
  - change, 110
  - connectivity, 91
  - NACA0012, 105
  - regular, 98
  - Section of Engine, 107
  - Smiling face, 108
  - U-shape channel, 107
  - uniform, 102, 103
  - V-shape cut, 108
- mesh adaptation, 37
- min, 65, 76
- minimum, 58
- mixed, 28
- mixed Dirichlet Neumann, 19
- modulus, 60
- movemesh, 96
- mpiAllgather, 245
- mpiAllReduce, 245
- mpiAlltoall, 245
- mpiAnySource, 243
- mpiBarrier, 244
- mpiBXOR, 243
- mpiCom, 243
- mpiCommWorld, 243
- mpiGather, 245
- mpiGroup, 243
- mpiLAND, 243
- mpiLOR, 243
- mpiLXOR, 243
- mpiMAX, 243
- mpiMIN, 243
- mpiPROD, 243
- mpiRank, 244
- mpirank, 243
- mpiReduce, 245
- mpiReduceScatter, 245
- mpiRequest, 243
- mpiScatter, 245
- mpiSize, 244
- mpisize, 243
- mpiSUM, 243
- mpiUndefined, 243
- mpiWait, 244
- mpiWtick, 244

- mpiWtime, 244
- multi-physics system, 30
- multiple meshes, 30
- N, 57, 155
- n, 148
- Navier-Stokes, 215, 217
- ndof, 163
- ndofK, 163
- Neumann, 53, 155
- Newton, 174, 200
- NLCG, 173
  - eps=, 171
  - nbiter=, 171
  - veps=, 171
- nodes, 13
- non-homogeneous Dirichlet, 19
- nonlinear, 30
- nonlinear problem, 28
- normal, 35, 155
- noshowbase, 78
- noshowpos, 78
- nt, 163
- nTonEdge, 35, 58
- nuEdge, 57
- number of degrees of freedom, 163
- number of element, 163
- nuTriangle, 57
- ofstream, 78
  - append, 78
- on, 155
  - intersection, 217
  - scalar, 155
- optimize=, 161
- outer product, 70, 72
- P, 57
- P0, **140**
- P1, **140**
- P1b, **140**
- P1dc, **140**
- P1nc, **141**
- P2, **140**
- P2dc, **140**
- parabolic, 28
- periodic, 139, 153, 182
  - 3d, 184
- pi, 58
- plot
  - aspectratio =, 166
  - nbiso =, 166
  - bb=, 166
  - border, 88
  - boundary =, 166
  - bw=, 166
  - cmm=, 166
  - coef=, 166
  - cut, 166
  - dim=, 166
  - grey=, 166
  - hsv=, 166
  - mesh, 88
  - nbarrow=, 166
  - ps=, 166
  - value=, 166
  - varrow=, 166
  - viso=, 166
- point
  - region, 91
  - triangle, 91
- pow, 61
- precision, 78
- precon=, 154, 160, 218
- problem, 36, 57, 151
  - eps=, 153
  - init=, 153
  - precon=, 154
  - solver=, 153
  - strategy =, 154, 160
  - tgV=, 154
  - tolpivot =, 154
  - tolpivotsym =, 154, 160
- processor, 244, 245
- processorblock, 244
- product
  - Hermitian dot, 72
  - dot, 72, 76
  - outer, 72
  - term to term, 72
- qforder=, 218
- quadrature: qf5pT, 157
- quadrature: qfV5, 158
- quadrature:default, 158

- quadrature:qf1pE, 156
- quadrature:qf1pElump, 156
- quadrature:qf1pT, 157
- quadrature:qf1pTlump, 157
- quadrature:qf2pE, 156
- quadrature:qf2pT, 157
- quadrature:qf2pT4P1, 157
- quadrature:qf3pE, 156
- quadrature:qf7pT, 157
- quadrature:qfe=, 157, 158
- quadrature:qforder=, 157, 158
- quadrature:qft=, 157, 158
- quadrature:qfV, 157
- quadrature:qfV1, 158
- quadrature:qfV1lump, 158
- quadrature:qfV2, 158
- quantile, 69
- radiation, 30
- rand, 62
- randinit, 62
- randint31, 62
- randint32, 62
- random, 62
- re, 65, 66
- read files, 90
- readmesh, 89, 111
- real, 56, 60
- region, 57, 91, 231
- region indicator, 30
- renumbering, 69
- resize, 65, 73
- Reusable matrices, 216
- rint, 61
- Robin, 28, 151, 155
- RT0, **141**
- savemesh, 89, 111
- schwarz, 245
- scientific, 78
- sec:Plot, 165
- Secv, 245
- Send, 245
- set, 36
  - matrix, 71
- showbase, 78
- showpos, 78
- shurr, 223, 225
- sin, 61
- singularity, 100
- sinh, 61
- solve, 57, 151
  - eps=, 153
  - init=, 153
  - linear system, 72
  - precon=, 154
  - solver=, 153
  - strategy=, 154, 160
  - tgV=, 15, 154
  - tolpivot=, 154
  - tolpivotsym=, 154, 160
- solver=, 173
  - CG, 100, 153
  - Cholesky, 153
  - Crout, 153
  - GMRES, 153
  - LU, 153
  - sparsesolver, 153
  - UMFPACK, 153
- sort, 65, 143
- sparsesolver, 153
- split=, 103
- square, 189
  - flags=, 86
  - label=, 86
  - region=, 86
- Stokes, 214
- stokes, 211
- stop test, 153
  - absolue, 218
- strain tensor, 193
- streamlines, 215
- stress tensor, 193
- string, 56
- subdomains, 230
- sum, 65
- tan, 61
- Taylor-Hood, 216
- tetgconvexhull, 115
- tetgtransfo, 115
- transpose, 72, 76, 300
- triangle
  - [], 91

- area, 91
  - label, 91
  - region, 91
- triangulate, 94
- triangulation files, as well as read and write, 24
- true, 56, 58
- trunc, 103
  - label=, 103
  - split=, 103
- try, 81
- tutorial
  - LaplaceRT.edp, 188
  - adapt.edp, 100
  - adaptindicatorP2.edp, 188
  - AdaptResidualErrorIndicator.edp, 190
  - aTutorial.edp, 176
  - beam.edp, 194
  - BlackSchol.edp, 211
  - convect.edp, 209
  - fluidStruct.edp, 227
  - freeboundary.edp, 234
  - movemesh.edp, 97
  - NSUzawaCahouetChabart.edp, 217
  - periodic.edp, 182
  - periodic4.edp, 182
  - periodic4bis.edp, 184
  - readmesh.edp, 90
  - Schwarz-gc.edp, 225
  - Schwarz-no-overlap.edp, 224
  - Schwarz-overlap.edp, 222
  - StokesUzawa.edp, 216
- tutorial
  - VI.edp, 220
- type of finite element, 140
- UMFPACK, 153
- upwinding, 33
- varf, 15, 57, 154, 158, 218
  - array, 160
  - matrix, 160
  - optimize=, 161
- variable, 55
- variational formulation, 20
- veps=, 173
- verbosity, 5, 8
- vertex
  - label, 91
  - x, 91
  - y, 91
- viso, 35
- volume, 58
- weak form, 20
- while, 77
- write files, 90
- x, 57
- y, 57
- z, 57





## Book Description

Fruit of a long maturing process freefem, in its last avatar, `FreeFem++`, is a high level integrated development environment (IDE) for partial differential equations (PDE). It is the ideal tool for teaching the finite element method but it is also perfect for research to quickly test new ideas or multi-physics and complex applications.

`FreeFem++` has an advanced automatic mesh generator, capable of a posteriori mesh adaptation; it has a general purpose elliptic solver interfaced with fast algorithms such as the multi-frontal method UMFPACK. Hyperbolic and parabolic problems are solved by iterative algorithms prescribed by the user with the high level language of `FreeFem++`. It has several triangular finite elements, including discontinuous elements. Finally everything is there in `FreeFem++` to prepare research quality reports: color display online with zooming and other features and postscript printouts.

This book is ideal for students at Master level, for researchers at any level and for engineers also in financial mathematics.

## Editorial Reviews

"... Impossible to put the book down, suspense right up to the last page..."

A. TANH, Siam Chronicle.

"... The chapter on discontinuous fems is so hilarious ..."

B. GALERKINE, Российской академии наук .