

globus authz

2.2

Generated by Doxygen 1.8.1.1

Thu Jul 19 2012 21:39:24

Contents

1 Module Index	1
1.1 Modules	1
2 Module Documentation	1
2.1 GSI Authorization API	1
2.1.1 Detailed Description	2
2.1.2 Function Documentation	2
2.2 GSI Credential Constants	4
2.2.1 Detailed Description	4
2.2.2 Enumeration Type Documentation	4

1 Module Index

1.1 Modules

Here is a list of all modules:

GSI Authorization API	1
GSI Credential Constants	4

2 Module Documentation

2.1 GSI Authorization API

Initialize Handle

- `globus_result_t globus_gsi_authz_handle_init (globus_gsi_authz_handle_t *handle, const char *service_name, const gss_ctx_id_t context, globus_gsi_authz_cb_t callback, void *callback_arg)`

Authorization decision made here

- `globus_result_t globus_gsi_authorize (globus_gsi_authz_handle_t handle, const void *action, const void *object, globus_gsi_authz_cb_t callback, void *callback_arg)`

Destroy Handle

- `globus_result_t globus_gsi_authz_handle_destroy (globus_gsi_authz_handle_t handle, globus_gsi_authz_cb_t callback, void *callback_arg)`

Query for authorization identity

- `globus_result_t globus_gsi_authz_get_authorization_identity (globus_gsi_authz_handle_t handle, char **identity_ptr, globus_gsi_authz_cb_t callback, void *callback_arg)`

2.1.1 Detailed Description

2.1.2 Function Documentation

2.1.2.1 `globus_result_t globus_gsi_authz_handle_init (globus_gsi_authz_handle_t * handle, const char * service_name, const gss_ctx_id_t context, globus_gsi_authz_cb_t callback, void * callback_arg)`

Initializes a handle.

Parameters

<i>handle</i>	Pointer to the handle that is to be initialized
<i>service_name</i>	Service to authorize access to
<i>context</i>	Security context used to contact the service
<i>callback</i>	Callback function to call when authz handle init completes
<i>callback_arg</i>	Argument to callback function

Returns

GLOBUS_SUCCESS if successful A Globus error object on failure:

2.1.2.2 `globus_result_t globus_gsi_authorize (globus_gsi_authz_handle_t handle, const void * action, const void * object, globus_gsi_authz_cb_t callback, void * callback_arg)`

Authorization decision made here.

Parameters

<i>handle</i>	Pointer to the handle that is to be initialized
<i>action</i>	Action to authorize
<i>object</i>	Object that the action pertains to.
<i>callback</i>	Callback function to call when authorization completes
<i>callback_arg</i>	Argument to callback function

Returns

GLOBUS_SUCCESS if successful A Globus error object on failure:

2.1.2.3 `globus_result_t globus_gsi_authz_handle_destroy (globus_gsi_authz_handle_t handle, globus_gsi_authz_cb_t callback, void * callback_arg)`

Destroy a Globus GSI authz handle.

Parameters

<i>handle</i>	The handle that is to be destroyed
<i>callback</i>	Callback function to call when handle is destroyed
<i>callback_arg</i>	Argument to callback function

Returns

GLOBUS_SUCCESS

2.1.2.4 `globus_result_t globus_gsi_authz_get_authorization_identity (globus_gsi_authz_handle_t handle, char ** identity_ptr, globus_gsi_authz_cb_t callback, void * callback_arg)`

Query for authorization identity.

Parameters

<i>handle</i>	The handle that is to be used for the identity check.
<i>identity_ptr</i>	The authorization identity determined by the authorization handle. This is must be freed by the caller. If the value is NULL (and this function returned GLOBUS_SUCCESS), the caller should use the authenticated identity.
<i>callback</i>	Callback function to call when identity is determined.
<i>callback_arg</i>	Argument to callback function.

Returns

GLOBUS_SUCCESS

2.2 GSI Credential Constants

Enumerations

- enum `globus_gsi_authz_error_t`{
 GLOBUS_GSI_AUTHZ_ERROR_SUCCESS = 0,
 GLOBUS_GSI_AUTHZ_ERROR_ERRNO = 1,
 GLOBUS_GSI_AUTHZ_ERROR_BAD_PARAMETER = 2,
 GLOBUS_GSI_AUTHZ_ERROR_CALLOUT = 3 }

2.2.1 Detailed Description

2.2.2 Enumeration Type Documentation

2.2.2.1 enum `globus_gsi_authz_error_t`

GSI Authz Error codes.

Enumerator:

- `GLOBUS_GSI_AUTHZ_ERROR_SUCCESS`** Success.
- `GLOBUS_GSI_AUTHZ_ERROR_ERRNO`** Error with system call.
- `GLOBUS_GSI_AUTHZ_ERROR_BAD_PARAMETER`** Invalid parameter.
- `GLOBUS_GSI_AUTHZ_ERROR_CALLOUT`** Callout returned an error.

Index

GLOBUS_GSI_AUTHZ_ERROR_BAD_PARAMETER
 GSI Credential Constants, 4

GLOBUS_GSI_AUTHZ_ERROR_CALLOUT
 GSI Credential Constants, 4

GLOBUS_GSI_AUTHZ_ERROR_ERRNO
 GSI Credential Constants, 4

GLOBUS_GSI_AUTHZ_ERROR_SUCCESS
 GSI Credential Constants, 4

GSI Authorization API, 1

- globus_gsi_authorize, 2
- globus_gsi_authz_get_authorization_identity, 2
- globus_gsi_authz_handle_destroy, 2
- globus_gsi_authz_handle_init, 1

GSI Credential Constants, 4

- GLOBUS_GSI_AUTHZ_ERROR_BAD_PARAMETER, 4
- GLOBUS_GSI_AUTHZ_ERROR_CALLOUT, 4
- GLOBUS_GSI_AUTHZ_ERROR_ERRNO, 4
- GLOBUS_GSI_AUTHZ_ERROR_SUCCESS, 4
- globus_gsi_authz_error_t, 4

globus_gsi_authorize
 GSI Authorization API, 2

globus_gsi_authz_error_t
 GSI Credential Constants, 4

globus_gsi_authz_get_authorization_identity
 GSI Authorization API, 2

globus_gsi_authz_handle_destroy
 GSI Authorization API, 2

globus_gsi_authz_handle_init
 GSI Authorization API, 1